

BX GitHub Repositories

Manual for Shop Operators

Purpose of this guide

This guide describes how to set up the BX GitHub Repositories module for production use.

After completing these steps, your shop can:

- access its own GitHub repositories,
- retrieve release ZIP files,
- store ZIP files in the shop folder download,
- and use only the repositories approved for that specific shop.

Result after setup

The following three values must be configured successfully:

1. GitHub App ID
2. Installation ID
3. Private Key (PEM)

Additionally:

- The connection test in the module is successful.
- Repositories of the installation can be loaded and selected.

Prerequisites

1. A GitHub account with permission to create and install a GitHub App.
2. Admin access to the shop.
3. Write permissions for the shop folder download.
4. Access to the repositories that will be synchronized.

Step 1: Create the GitHub App

1. In GitHub, click your profile icon in the top right corner.
2. Open Settings.
3. Open Developer settings in the left menu.
4. Select GitHub Apps.
5. Click New GitHub App.
6. Enter a unique name, for example shopname-release-sync.
7. Enter the Homepage URL (for example, your shop URL).
8. Set a Callback URL only if user login via GitHub is required.
9. If webhooks are not needed: disable webhooks.

10. Set minimal permissions:
 - Repository permission Metadata: Read-only
 - Repository permission Contents: Read-only

11. Define where the app can be installed.

12. Save the app.

Note: Grant as few permissions as possible (least privilege).

Step 2: Install the GitHub App

1. Open `Install App` in your GitHub App settings.
2. Select the target account or organization.
3. Set repository access to `Selected repositories`.
4. Select only the repositories your shop should use.
5. Confirm the installation.

Important: This selection determines which repositories the shop can technically access.

Step 3: Retrieve the App ID

1. Open the GitHub App settings.
2. Copy the `App ID`.
3. Save this value.

Step 4: Retrieve the Installation ID

1. Open the app installation view.
2. Read the installation ID from the URL or from the installation details.
3. Save this value.

Example: if the URL contains `.../settings/installations/12345678`, then `12345678` is the Installation ID.

Step 5: Generate the private key (PEM)

1. In the GitHub App configuration, open `Private keys`.
2. Click `Generate a private key`.
3. Store the downloaded PEM file securely.
4. Keep the PEM file ready for module configuration.

Important:

- Never send private keys by email.
 - Never post private keys in tickets or chats.
 - If you suspect a leak, generate a new key immediately and revoke the old one.
-

Step 6: Enter data in the shop module

1. Open the BX GitHub Repositories module in the shop admin.
2. Fill in: GitHub App ID, Installation ID, upload Private Key (PEM).
3. Run Test connection.
4. On success, click Save settings.

Step 7: Load repository list and set selection

1. After a successful connection test, load the repository list.
2. Select the required repositories and save the selection.
3. Download repositories.

Import target: ZIP files are stored in the shop folder download.

Important: Each repository must have at least one version tag (for example v2.0.5).

```
git tag -a v2.0.5 -m "BX Products Video v2.0.5"  
git push origin v2.0.5
```

Typical errors and solutions

Error 401 / 403 during connection test

Possible cause: values do not match, app not installed, or permissions too restrictive.

Solution: verify values, installation, and permissions.

Repository list is empty

Possible cause: no repositories enabled in the installation, or wrong account/organization selected.

Solution: check Selected repositories and grant required repositories.

ZIP import does not work

Possible cause: release asset pattern mismatch or missing write permissions in download.

Solution: verify asset naming, folder permissions, and retry.

Security checklist before go-live

1. Only minimal permissions are enabled.
2. Installation is set to Selected repositories.
3. No sensitive data is stored in logs in plain text.
4. Private key is stored securely.
5. Test run is successful.
6. Download file is correctly written to download.
7. Scheduled task execution is enabled.

Maintenance and rotation

1. Rotate private keys regularly.
2. Remove repositories no longer needed from the installation.

3. Run the connection test again after permission changes.
4. Review error logs regularly.