

1. View the 12 month prescription history for Joseph song. Display the customer name, drug name, date of pickup and strength.

$(Person) \leftarrow \sigma_{customerFirst='Joseph' \wedge customerLast='song'}(Customer)$

- Filters out the customer relation for only customers who have the name 'joseph song'

$(Last12months) \leftarrow \sigma_{prescription.prescDate \geq 3-2-21 \wedge Person.customerId = prescription.customerId}(prescription \times Person)$

- Filters out any prescriptions older than a year under Joseph songs records.

$(A) \leftarrow \sigma_{Last12months.prescriptionId = prescriptionDrug.prescriptionId}(prescriptionDrug \times Last12months)$

- Makes a new relation with the multivalued 'prescriptionDrug' relation.

$(B) \leftarrow \sigma_{Drug.drugId = A.drugId}(A \times drug)$

- Cartesian product to add drug attributes/columns that correspond to josephs prescriptions.

$(pickupDate) \leftarrow \sigma_{pickup.customerId = B.customerId}(B \times pickup)$

- Another cartesian product to add DateOfPickup column to the final answer.

$(Answer) \leftarrow \pi_{customerFirst, drugName, DateOfPickup, drugStrength}(pickupDate)$

2. Identify prescriptions available for pickup now at the CVS in 'Francis Lewis Blvd, Queens, NY 11357' for Sandra lee. Display the customer name, drug and strength.

$(Person) \leftarrow \sigma_{customerFirst='Sandra' \wedge customerLast='lee'}(Customer)$

- Creates a new relation for only Sandra lee.

$(Today) \leftarrow \sigma_{Person.customerId = prescription.customerId}(prescription \times Person)$

- Filters all prescriptions that belong to Sandra.

$(pickupToday) \leftarrow \sigma_{Today.customerId = pickup.customerId \wedge pickup.dateOfPickup = 3-2-22}(Today \times pickup)$

- Creates new columns with pickup attributes and filters all prescriptions that need to be picked up on 3-2-22.

$(whichStore) \leftarrow \sigma_{store.storeId = pickupToday.storeId \wedge store.storeZip = '11357' \wedge store.storeStreet = 'Francis Lewis Blvd'}(store \times pickupToday)$

- Creates new columns with store attributes for Sandras prescriptions available at the designated CVS

$(Presc) \leftarrow \sigma_{prescriptionDrug.prescriptionId = whichStore.prescriptionId}(prescriptionDrug \times whichStore)$

- Creates a new cartesian product with the multivalued 'prescriptionDrug' relation.

$(DrugsPickup) \leftarrow \sigma_{Presc.drugId = drug.drugId}(Presc \times drug)$

- Creates a new cartesian product to add drug attributes/columns that correspond to each prescription.

$(Answer) \leftarrow \pi_{customerFirst, customerLast, drugName, drugStrength}(DrugsPickup)$

3. Identify prescriptions that require refilling for Andrew keblish. Display the drug name, number of remaining refills and doctor.

$(Person) \leftarrow \sigma_{customerFirst='Andrew' \wedge customerLast='keblish'}(Customer)$

- Creates a new relation for Andrew keblish.

$(A) \leftarrow \sigma_{Person.customerId = prescription.customerId}(Person \times prescription)$

- Selects all prescriptions for Andrew keblish.

$(allPresc) \leftarrow \sigma_{A.prescriptionId = prescriptionDrug.prescriptionId}(A \times prescriptionDrug)$

- Creates new relation with the multivalued 'prescriptionDrug' relation.

$(refills) \leftarrow \sigma_{allPresc.prescriptionId = prescReqs.prescriptionId \wedge prescReqs.refills > 0}(allPresc \times prescReqs)$

- Creates new relation with the multivalued 'prescReqs' relation. We disclude any prescription that doesnt need refills.

$(DrugsPickup) \leftarrow \sigma_{refills.drugId = drug.drugId} (refills \times drug)$

- Makes a new cartesian product of all the drugs that each prescription prescribes.

$(customerDoc) \leftarrow \sigma_{doctor.doctorId = DrugsPickup.doctorId} (DrugsPickup \times doctor)$

- Cross products the doctor relation to add the doctor columns for the final answer.

$(Answer) \leftarrow \pi_{drugName, drugRefills, doctorFirst, doctorLast} (customerDoc)$

4. Identify drugs not sold in the last month at CVS location flushing 11354. Display the drug name, quantity.

$(theStore) \leftarrow \sigma_{store.storeZip = '11354' \wedge store.storeCity = 'flushing'} (store)$

- Locates the correct address of the store to narrow down searching.

$(Sold) \leftarrow \sigma_{theStore.prescriptionId = prescription.prescriptionId \wedge prescription.prescDate \geq 2-2-22} (theStore \times prescription)$

- Finds the prescriptions in the store from the last month.

$(thePrescriptions) \leftarrow \sigma_{Sold.prescriptionId = prescriptionDrug.prescriptionId} (Sold \times prescriptionDrug)$

- Since each prescription can include multiple drugs, we join this relation with the prescriptionDrug relation.

$(theDrugs) \leftarrow \sigma_{thePrescriptions.drugId = drug.drugId} (thePrescriptions \times drug)$

- Adds all the drug attributes.

$(notSold) \leftarrow \pi_{drugId} (drug) - \pi_{drugId} (theDrugs)$

- Subtracts all the drugs sold this month from the (available) drugs.

$(display) \leftarrow \sigma_{drug.drugId = notSold.drugId} (drug \times notSold)$

- This will add drug attributes

$(amount) \leftarrow \sigma_{display.storeId = storeStock.storeId} (display \times storeStock)$

- This will allow us to count the quantity with an aggregate function.

$\rho_{answer}(Drug\ name, \ quantity)_{drugName} \Join_{count\ drugId} (amount)$

5. Identify customers without a drug purchase in the last year. Display the customer name, address, email and phone.

$(purchased) \leftarrow \sigma_{prescription.prescDate \geq 3-2-21} (prescription)$

- This will filter all the prescription in all of CVS's databases who have purchased something in the last year.

$(notPurchased) \leftarrow \pi_{customerId} (customer) - \pi_{customerId} (purchased)$

- This will find the complement by subtracting the customerIds.

$(display) \leftarrow \sigma_{notPurchased.customerId = customer.customerId} (notPurchased \times customer)$

- This will add customer columns to appropriate Ids.

$(Answer) \leftarrow \pi_{customerFirst, customerLast, customerStreet, customerCity, customerZip, customerEmail, customerPhone} (display)$

6. Identify drugs with low inventory now at CVS 886, flushing. Display the drug name, manufacturer, drug id, store and quantity.

$(theStore) \leftarrow \sigma_{store.storeName = 'CVS 886' \wedge store.storeCity = 'flushing'} (store)$

- Locates the correct address of the store to narrow down searching.

$(inventory) \leftarrow \sigma_{theStore.storeId = storeStock.storeId} (theStore \times storeStock)$

- We find the available stock at the CVS 886, flushing.

$(atts) \leftarrow \sigma_{inventory.drugId = drug.drugId} (inventory \times drug)$

- We join the drug relation with our stores stock.

$(Answer) \leftarrow \rho_{answer}(drugName, drugManufacturer, drugId, storeName, quantity)_{drugName, drugManufacturer, drugId, storeName} \Join_{count\ drugId} (atts)$

- We count all the drugs in our specific store.

$(finalAns) \leftarrow \pi_{drugName, drugManufacturer, drugId, storeName, quantity}(\sigma_{quantity < 5}(Answer))$

7. Identify drugs that will expire this week at CVS bayside, 11355. Display the drug name, manufacturer, drug id, store and quantity.

$(theStore) \leftarrow \sigma_{store.storeZip = '11355' \wedge store.city = 'bayside'}(store)$

- Locates the correct address of the store to narrow down searching.

$(inventory) \leftarrow \sigma_{theStore.storeId = storeStock.storeId}(theStore \times storeStock)$

- We find the available stock at the CVS 886, flushing.

$(expiring) \leftarrow \sigma_{inventory.drugId = drug.drugId \wedge drug.drugExpDate \leq 3-9-22}(inventory \times drug)$

- We select all drugs expiring this week.

$\rho_{answer}(drugName, drugManufacturer, drugId, storeName, quantity)_{drugName, drugManufacturer, drugId, storeName} \Join_{count\ drugId} (expiring)$

8. Identify customers with allergies to current medication. Display the customer name, drug name, strength and quantity.

$(people) \leftarrow \sigma_{customerAllergies.customerId = customer.customerId}(customerAllergies \times customer)$

- Cartesian product with the customerAllergies relation to only find customers with allergies to current medication.

$(allergies) \leftarrow \sigma_{drugInteractions.drugInteractionId = people.drugInteractionId}(people \times drugInteractions)$

- Add the drug interactions relation with people who have allergies.

$(peopleDrugs) \leftarrow \sigma_{allergies.drugId = drug.drugId}(allergies \times drug)$

- Add the drug relation.

$(stock) \leftarrow \sigma_{storeStock.drugId = peopleDrugs.drugId}(peopleDrugs \times storeStock)$

- Find the stock of the drug in from stores available.

$\rho_{answer}(customerFirst, customerLast, drugName, drugStrength, quantity)_{customerFirst, customerLast, drugName, drugStrength} \Join_{count\ drugId} (stock)$

9. Identify products sold today at CVS 285, NY, 11498. Display the customer name, drug name, strength, cost and store.

$(theStore) \leftarrow \sigma_{store.storeZip = '11498' \wedge store.storeState = 'NY' \wedge store.storeName = '285'}(store)$

- Locates the correct address of the store to narrow down searching.

$(presc) \leftarrow \sigma_{prescription.prescriptionId = theStore.prescriptionId \wedge prescription.prescDate = 3-2-22}(prescription \times theStore)$

- Finds prescriptions sold at the store today.

$(customerPresc) \leftarrow \sigma_{presc.customerId = customer.customerId}(presc \times customer)$

- Adds the customer attributes.

$(thePresc) \leftarrow \sigma_{customerPresc.prescriptionId = prescriptionDrug.prescriptionId}(customerPresc \times prescriptionDrug)$

- Finds all drugs sold by each prescription.

$(theDrugs) \leftarrow \sigma_{presc.drugId = drug.drugId}(thePresc \times drug)$

- Adds the drug columns/attributes.

$(Answer) \leftarrow \pi_{customerFirst, customerLast, drugName, drugStrength, drugPrice, storeName}(theDrugs)$

10. Identify total revenue and [drug] by neighborhood. Display 3 columns: neighborhood, total prescriptions and total sales.

$(allStores) \leftarrow \sigma_{store.prescriptionId = prescription.prescriptionId}(store \times prescription)$

- Find all prescriptions from all stores.

$(allPresc) \leftarrow \sigma_{allStores.prescriptionId = prescriptionDrug.prescriptionId}(allStores \times prescriptionDrug)$

- Find all drugs that match to each prescription.

$(allDrugs) \leftarrow \sigma_{allPresc.drugId = drug.drugId} (allPresc \times drug)$

- We need this step to obtain the drugPrice attribute which we will need to use an aggregate function on in the answer.

$(Answer) \leftarrow \rho_{answer}(Neighborhood, total\ prescriptions, total\ sales) \text{ storeZip } \mathcal{I}_{count\ prescriptionId, sum\ drugPrice}(allDrugs)$

11. Identify the number of active customers in your neighborhood. Display 1 row with the number of active customers.

$(people) \leftarrow \sigma_{customerZip = '11354'} (customer)$

- My zipcode is 11354 and thats how I searched my area.

$(active) \leftarrow \sigma_{prescription.customerId = people.customerId \wedge prescription.prescDate \geq 3-2-21} (people \times prescription)$

- Kept only the people who have purchased a drug in the last year.

$(Answer) \leftarrow \mathcal{I}_{count\ customerId}(active)$

12. Identify the number of prescriptions by doctor. Display 3 columns: doctor name, number of prescriptions and total sales.

$(presc) \leftarrow \sigma_{prescription.prescriptionId = prescriptionDrug.prescriptionId} (prescription \times prescriptionDrug)$

- Find all prescriptions and its prescribed drugs.

$(prescDrugs) \leftarrow \sigma_{presc.drugId = drug.drugId} (presc \times drug)$

- Join the drug relation so we can sum the drugPrice attribute in the answer.

$(prescDoc) \leftarrow \sigma_{prescDrugs.doctorId = doctor.doctorId} (prescDrugs \times doctor)$

- Join the doctor relation so we can group the aggregate function by the doctor name attributes.

$(Answer) \leftarrow \rho_{answer}(first\ name, last\ name, total\ prescriptions, total\ sales) \text{ doctorFirst, doctorLast } \mathcal{I}_{count\ prescriptionId, sum\ drugPrice}(prescDoc)$