

—★★★—
Patented

Incombustible alternative cleaning agent
[Determined as non-dangerous goods]

BCS-5000



Replacing TCE / 1,2-DCP toxic agents
Replacing NPBr reproduction-toxicity
/ Special control substance

Occupational Safety
and Health Act

Chemical Substances
Control Act

Safety Control of
Hazardous Substances Act

Not Applicable



Purpose of product

Cleaning metal-working fluid



Automobile parts

Cleaning PCB flux



Electric/electronic parts

Cleaning grease and inhibited oil



Mobile phone parts

Cleaning drawing oil and rolling oil



Metal-processing parts

Other oil (preliminary test)



Other alloys (preliminary test)

Category	BCS-5000	TCE	NPBr	1,2-DCP
Specific gravity	1.485	1.464	1.354	1.156
Distillation range(°C)	92~110	85~88	70~72	90~95
Flash point(°C)	>250	>250	69	16
Moisture content(%)	0.058	<0.1	<0.1	<0.1
Evaporation residue (%)	0.0013	<0.01	<0.01	<0.01

Product specifications : Drum (250kg), Pail 20L (23kg), CAN 18L (23kg)

Deposition & ultrasonic cleaning

Temperature(°C):60~70°C
Time(sec):60~120
Frequency(kHz):25~40

Rinsing


Temperature(°C)
:Room temperature
Time(sec):60~120

Vapor degreasing & Drying


Temperature(°C)
:105~110°C
Time(sec):60~120

3~5-bath Ultrasonic & Vapor degreasing cleaning system


[Drawing oil / SUS Tube]



[Punching oil / Nickel Silver]



[Cutting oil / Brass]



[Abrasive / Copper]

