

# **Software Testing, Quality Assurance & Maintenance—Lecture 9**

Patrick Lam  
University of Waterloo

February 2, 2026

## Part I

# Intro: Grammar-Based Fuzzing

# Types of Fuzzing

Goal: generate many test cases automatically.

Mutation-based fuzzing: generate new inputs automatically, by modifying known inputs.

**Grammar-based fuzzing**: generate new inputs automatically, using a grammar.

## Example: Regular expression

`^4[0-9]{12}(:[0-9]{3})?.$`

Uses:

- check if a number is valid
- **generate** numbers of the right shape

But: also must satisfy checksum rules!

# Checksum rules for credit card numbers

Luhn algorithm:

- calculate a checksum from all-but-last digits;  
the last digit must match the checksum.

Can't specify checksum rules as regexp or context-free grammars.

## Example (standard): expressions

### Context-free grammars (CFGs):

```
<start>      ::= <expr>
<expr>       ::= <term> + <expr> | <term> - <expr> | <term>
<term>       ::= <term> * <factor> | <term> / <factor>
               | <factor>
<factor>     ::= +<factor> | -<factor> | (<expr>) | <integer>
               | <integer>.<integer>
<integer>    ::= <digit><integer> | <digit>
<digit>     ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9
```

Can also recognize and generate strings for CFGs.

# Generating from grammars

What we're doing in this lecture:  
generating (trees and) strings  
from grammars.

These are more interesting than random  
sequences of characters;  
they test behaviour beyond input validation.

Aim: create grammars that specify all legal  
inputs.

Other uses: configs, APIs, GUIs, etc.

## Part II

# Generating from CFGs

AUCKLAND GRAMMAR SCHOOL



# Expressiveness

```
1 <!DOCTYPE html>
2 <html lang="en" dir="ltr">
3 <head>
4 <meta charset="utf-8">
5 <meta name="generator" content="Piwigo (aka PWG), see piwigo.org">
6
7
8 <meta name="description" content="Home">
9
10 <title>plan gallery</title>
11 <link rel="shortcut icon" type="image/x-icon" href="themes/default/icon/favicon.ico">
12
13 <link rel="start" title="Home" href="/" >
14 <link rel="search" title="Search" href="search.php" >
15
16
17 <link rel="canonical" href="/">
18
19
20 <!--[if lt IE 7]>
21 <link rel="stylesheet" type="text/css" href="themes/default/fix-ie5-ie6.css">
22 <![endif]-->
23 <!--[if IE 7]>
24 <link rel="stylesheet" type="text/css" href="themes/default/fix-ie7.css">
25 <![endif]-->
26
27
28 <!--[if lt IE 8]>
29 <link rel="stylesheet" type="text/css" href="themes/elegant/fix-ie7.css">
30 <![endif]-->
31
32
33 <!-- BEGIN get_combined -->
34 <link rel="stylesheet" type="text/css" href="_data/combined/lylcc4n.css">
35
36
37 <!-- END get_combined -->
38
39 <!--[if lt IE 7]>
40 <script type="text/javascript" src="themes/default/js/pngfix.js"></script>
```

Regexps can't count (so no HTML parsers).  
CFGs can't implement Luhn algorithm.

# Generating Inputs

How to generate inputs from this grammar?

`<start> ::= <digit><digit>`

`<digit> ::= 0 | 1 | 2 | 3 | 4`  
`| 5 | 6 | 7 | 8 | 9`

(Could be expressed as a regexp).

# Generating Inputs: double-digits

- `<start>`  $\rightarrow$  `<digit><digit>`
- visit first `<digit>`, have 10 choices;  
choose randomly, say 1;  
replace `<digit>` by 1.
- visit second `<digit>`,  
choose say 7 randomly;  
replace `<digit>` by 7.
- generated input: 17

# Generating Inputs: back to expr

```
<start>      ::= <expr>
<expr>       ::= <term> + <expr> | <term> - <expr> | <term>
<term>       ::= <term> * <factor> | <term> / <factor>
               | <factor>
<factor>     ::= +<factor> | -<factor> | (<expr>) | <integer>
               | <integer>.<integer>
<integer>    ::= <digit><integer> | <digit>
<digit>     ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9
```

# Generating Inputs: `expr`

- `<start> → <expr>`
- visit `<expr>`; three `<expr>` alternatives, randomly choose `<term> + <expr>`, replace `<expr>` by our choice.
- visit `<term>`; also three `<term>` alternatives, randomly choose `<factor>`.
- visit `<factor>`; randomly choose `<integer>` of the 5 alternatives.
- visit `<integer>`; randomly choose `<digit>`;
- visit `<digit>`; randomly choose terminal 4 and generate it.
- continue with next nonterminal `expr ...`

Could generate, for instance, `4 + 22 * 5.3`, or many other expressions.

# Coding Things Up: Grammars in Python

Just use Python data structures.

Grammar = mapping from an alternative's LHS to its RHS.

Here is a single-production grammar.

```
DIGIT_GRAMMAR = {  
    "<start>":  
        ["0", "1", "2", "3", "4", "5", "6", "7", "8", "9"]  
}
```

Nonterminals in `<brackets>`.

All else taken as terminals.

# Python Type Hint for Grammars

```
from typing import Dict, List
type Expansion = str
type Grammar = Dict[str, List[Expansion]]
```

# Expression Grammar in Python

```
EXPR_GRAMMAR: Grammar = {  
    "<start>":  
        ["<expr>"],  
    "<expr>":  
        ["<term> + <expr>", "<term> - <expr>", "<term>"],  
    "<term>":  
        ["<factor> * <term>",  
         "<factor> / <term>", "<factor>"],  
    "<factor>":  
        ["+<factor>", "-<factor>",  
         "(<expr>)",  
         "<integer>.<integer>", "<integer>"],  
    "<integer>":  
        ["<digit><integer>", "<digit>"],  
    "<digit>":  
        ["0", "1", "2", "3", "4", "5", "6", "7", "8", "9"]  
}
```



# Playing with Grammars

```
>>> EXPR_GRAMMAR["<digit>"]  
['0', '1', '2', '3', '4', '5', '6', '7', '8', '9']  
>>> "<integer>" in EXPR_GRAMMAR  
True
```

# Conventions and Helpers

Must always have start symbol `<start>`:

```
START_SYMBOL = "<start>"
```

Non-terminals always in `<brackets>`:

```
import re
RE_NONTERMINAL = re.compile(r'(<[^<> ]*>)' )
def nonterminals(expansion):
    if isinstance(expansion, tuple):
        # can be a tuple, use first element
        expansion = expansion[0]

    return RE_NONTERMINAL.findall(expansion)

def is_nonterminal(s):
    return RE_NONTERMINAL.match(s)
```

# Using these Utilities

```
>>> nonterminals("<term> * <factor>")
["<term>", "<factor>"]
>>> is_nonterminal("<symbol-1>")
<re.Match object; span=(0, 10), match='<symbol-1>'>
>>> is_nonterminal("<symbol-1")
>>>
```

# A Simple Grammar Fuzzer

```
def simple_grammar_fuzzer(grammar: Grammar,  
                           start_symbol: str = START_SYMBOL,  
                           max_nonterminals: int = 10,  
                           max_expansion_trials: int = 100,  
                           log: bool = False) -> str:  
    """Produce a string from 'grammar'.  
    'start_symbol': use a start symbol other than '<start>' (  
                    default).  
    'max_nonterminals': the maximum number of nonterminals  
                        still left for expansion  
    'max_expansion_trials': maximum # of attempts to produce a  
                            string  
    'log': print expansion progress if True"""
```

# It's all strings: implementation

```
term = start_symbol
expansion_trials = 0
while len(nonterminals(term)) > 0:
    symbol_to_expand = random.choice(nonterminals(term))
    expansions = grammar[symbol_to_expand]
    expansion = random.choice(expansions)
    new_term = term.replace(symbol_to_expand, expansion, 1)

    if len(nonterminals(new_term)) < max_nonterminals:
        term = new_term
        expansion_trials = 0
    else:
        expansion_trials += 1
        if expansion_trials >= max_expansion_trials:
            raise ExpansionError("Cannot expand " + repr(term))

return term
```

# Comments on Simple Grammar Fuzzer

- takes a string, finds a nonterminal, replaces with an alternative.
- it's all string replacement.
- tree manipulations would be better; stay tuned.
- there are some limits to help w/termination.

# Grammar: CGI

```
CGI_GRAMMAR: Grammar = {
    "<start>":
        ["<string>"],
    "<string>":
        ["<letter>", "<letter><string>"],
    "<letter>":
        ["<plus>", "<percent>", "<other>"],
    "<plus>":
        ["+"],
    "<percent>":
        ["%<hexdigit><hexdigit>"],
    "<hexdigit>":
        ["0", "1", "2", "3", "4", "5", "6", "7",
         "8", "9", "a", "b", "c", "d", "e", "f"],
    "<other>": # Actually, could be _all_ letters
        ["0", "1", "2", "3", "4", "5", "a", "b", "c", "d", "e",
         "-", "_"],
}
```

# Generating CGI strings

```
>>> for i in range(10):  
...     print(simple_grammar_fuzzer(grammar=CGI_GRAMMAR,  
                                     max_nonterminals=10))  
  
...  
%e5  
+  
+3  
_1a  
e+  
%625%ee  
%db%df%5d  
+44  
%4b  
+%b8+2
```



# Grammar: URL

```
URL_GRAMMAR: Grammar = {  
    "<start>": ["<url>"],  
    "<url>": ["<scheme>://<authority><path><query>"],  
    "<scheme>": ["http", "https", "ftp", "ftps"],  
    "<authority>":  
        ["<host>", "<host>:<port>",  
         "<userinfo>@<host>", "<userinfo>@<host>:<port>"],  
    "<host>": # Just a few  
        ["patricklam.ca", "www.google.com", "fuzzingbook.com"],  
    "<port>": ["80", "8080", "<nat>"],  
    "<nat>": ["<digit>", "<digit><digit>"],  
    "<digit>":  
        ["0", "1", "2", "3", "4", "5", "6", "7", "8", "9"],  
    "<userinfo>": # Just one  
        ["user:password"],  
    "<path>": # Just a few  
        ["", "/", "/<id>"],  
    "<id>": ["abc", "def", "x<digit><digit>"],  
    "<query>": ["", "?<params>"],  
    "<params>": ["<param>", "<param>&<params>"],  
    "<param>": ["<id>=<id>", "<id>=<nat>"],  
}
```

# Generating URLs

```
>>> for i in range(10):  
...     print(simple_grammar_fuzzer(grammar=URL_GRAMMAR,  
                                     max_nonterminals=10))  
  
...  
https://user:password@www.google.com/abc  
http://user:password@fuzzingbook.com/  
http://user:password@patricklam.ca/def?x97=60  
ftp://user:password@fuzzingbook.com/x60?abc=def  
https://patricklam.ca/?x84=31&x95=x12  
ftp://www.google.com:1/abc  
ftp://user:password@fuzzingbook.com:80/x40?def=6&x12=abc  
ftp://user:password@www.google.com  
http://user:password@fuzzingbook.com/def?x35=1  
ftp://user:password@www.google.com/abc
```

This isn't all URLs, but we do get better coverage of our chosen subset.  
Other examples possible, e.g. book titles (see *Fuzzing Book*).

# On Validity

If you have a grammar,  
you can generate strings belonging to the grammar  
(as we've seen).

These strings, by definition, always satisfy the grammar.

They may not be valid inputs to a program.

- e.g. port number between 1024 and 2048;
- e.g. checksum digit satisfies Luhn's algorithm.

Can attach constraints to grammars to generate more-valid inputs, or weight some alternatives more heavily (not discussed today).

# Grammars & Mutation Seeds

So far: only produce syntactically valid inputs.

What about *invalid* inputs?

One answer: **mutation**.

Our `MutationFuzzer` accepts seeds to start from.

# Generating CGI strings

```
number_of_seeds = 10
seeds = [
    simple_grammar_fuzzer(
        grammar=URL_GRAMMAR,
        max_nonterminals=10) for i in range(number_of_seeds) ]
seeds
m = MutationFuzzer(seeds)
[m.fuzz() for i in range(20) ]
```

Use the grammar fuzzer to produce seeds,  
then the mutation fuzzer to mutate them.

# EBNF

Extended Backus-Naur form; is syntactic sugar:

- `<symbol>?`: `<symbol>` can occur 0 or 1 times;
- `<symbol>+`: `<symbol>` can occur 1 or more times;
- `<symbol>*`: `<symbol>` can occur 0 or more times;
- parentheses can be used with these shortcuts, e.g.  
`(<s1><s2>)+`

Instead of

```
"<identifier>": ["<idchar>", "<identifier><idchar>"],
```

just write

```
"<identifier>": ["<idchar>+"],
```

Function `convert_ebnf_grammar()` (in  
code/L09/ebnf.py) translates EBNF to BNF.

## Opts (for future expansion)

```
"<expr>":  
    [("<term> + <expr>", opts(min_depth=10)),  
     ("<term> - <expr>", opts(max_depth=2)),  
      "<term>"]
```

and there are functions like `opts()`,  
`exp_string()`, `exp_opt()`, `exp_opts()`,  
`set_opts()` in `code/L09/opts.py`.

# Grammar Utilities

found in `code/L09/grammars.py`:

`trim_grammar()`: remove unneeded expansions;

`is_valid_grammar()`: validity checks, e.g. no unreachable symbols, etc



# Applications of Grammars in Testing

- Earliest known: Burkhardt, 1967: “Generating test programs from syntax.”
- CSmith: grammar-based fuzzing; they work hard to only generate valid C programs; pseudo-oracle comparing GCC and LLVM.
- EMI: fuzz dead code, observe mis-compilations.
- LangFuzz: grammar-based fuzzing on test suites.
- Grammarinator: open-source grammar fuzzer in Python.
- Domato: fuzzes Document Object Model inputs.