

How to enable Role-Based Strategy Plugin


The Role-Based Strategy plugin is used when access rights and privileges need to be assigned to different users based on their role in Jenkins. For example, developers should only have access to development jobs, whereas testers should have access to testing jobs. This document can be divided into the following four sections:

1. Installing Role-Based Authorization Plugin
2. Creating users
3. Managing and assigning roles to users
4. Creating jobs and verifying roles

Installing Role-Based Authorization Plug-in

First, we need to have a Role-Based Authorization Plug-in installed. Now, let's take a look at the various steps involved.

1. Select the **Manage Jenkins** option.



2. Then, select the **Manage Plugins** option.

System Configuration



Configure System

Configure global settings and paths.



Global Tool Configuration

Configure tools, their locations and automatic installers.



Manage Plugins

Add, remove, disable or enable plugins that can extend the functionality of Jenkins.


There are updates available



Manage Nodes and Clouds

Add, remove, control and monitor the various nodes that Jenkins runs jobs on.

3. Click on the **Available** tab.
4. Next, search for the **Role-Based Authorization Strategy** option.
5. Select it and click on the **Install without restart** option as shown in the screenshot given below.



The screenshot shows the Jenkins Manage Plugins interface. A search bar at the top contains the text "Role". The "Available" tab is selected. A table lists available plugins. The "Role-based Authorization Strategy" plugin is selected with a checkbox. Below the table, the "Install without restart" button is highlighted.

Install	Name	Version	Released
<input checked="" type="checkbox"/>	Role-based Authorization Strategy Security Authentication and User Management Enables user authorization using a Role-Based strategy. Roles can be defined globally or for particular jobs or nodes selected by regular expressions.	3.1.1	14 days ago
<input type="checkbox"/>	CloudBees AWS Credentials aws Allows storing Amazon IAM credentials within the Jenkins Credentials API. Store Amazon IAM access keys (AWSAccessKeyId and AWSSecretKey) within the Jenkins Credentials API. Also support IAM Roles and IAM MFA Token.	1.28.1	17 days ago


Buttons at the bottom: **Install without restart**, **Download now and install after restart**, **Check now**. Update information obtained: 47 min ago.

6. Once it is installed, go back to the **Jenkins Dashboard**.

Creating users

Now, we will create some users before assigning them to various roles. Let's take a look at the different steps involved here.

1. Select **the Manage Jenkins** option as shown in the screenshot attached below.



2. Then, click on **Manage Users**.

Security



Configure Global Security

Secure Jenkins; define who is allowed to access/use the system.



Manage Credentials

Configure credentials



Configure Credential Providers

Configure the credential providers and types



Manage Users

Create/delete/modify users that can log in to this Jenkins

3. Click on the **Create User** option from the left side of the window.



Back to Dashboard



Manage Jenkins



Create User

4. The first user that we are creating is **Developer**.
5. So, provide all the details and then click on **Create User**.

Create User

Username:

Password:

Confirm password:

Full name:

E-mail address:

[Create User](#)

6. Similarly, create one more user named **Tester**.

Create User

Username:

Password:

Confirm password:

Full name:









E-mail address:

[Create User](#)

7. Next, you can see that we have three users created as shown in the screenshot attached below.

Users


These users can log into Jenkins. This is a sub set of [this list](#), which also contains auto-created users who really just made some commits on some projects and have no direct Jenkins access.

User ID	Name	
 admin	admin	
 Developer	Developer	 
 Tester	Tester	 

Managing and assigning roles to users


Now, we will create different roles and assign our users to them. You will learn about the various steps involved here.

1. Now, navigate to the Jenkins dashboard and click on the **Manage Jenkins** option as shown below.



2. Next, select the **Configure Global Security** option.

Security



3. Then, in **Authorization**, select the **Role-Based Strategy** option.
4. Click on **Apply** and then **Save**.

Authorization

- ☐ Anyone can do anything
- ☐ Legacy mode
- ☐ Logged-in users can do anything
- ☐ Matrix-based security
- ☐ Project-based Matrix Authorization Strategy
- ☒ Role-Based Strategy

Markup Formatter

Markup Formatter



- Now, navigate to the **Manage Jenkins** page and select the **Manage And Assign Roles** option.

Security



Configure Global Security
Secure Jenkins; define who is allowed to access/use the system.



Manage Credentials
Configure credentials



Configure Credential Providers
Configure the credential providers and types



Manage and Assign Roles
Handle permissions by creating roles and assigning them to users/groups




Manage Users
Create/delete/modify users that can log in to this Jenkins

- Select the **Manage Roles** option from here.



Manage and Assign Roles



Assign Roles
Assign Roles





Role Strategy Macros
Provides info about macro usage and available macros

- First, we need to add **Global roles**.

8. Enter the role to add. Here, we are creating one more role named **ProjectMember**. Click on the **Add** option.
9. Next, select the access privileges that you want to provide for the role by checking the correct boxes.

Global roles

Role	Overall		Credentials					Agent							Job					
	Administer	Read	Create	Delete	ManageDomains	Update	View	Build	Configure	Connect	Create	Delete	Disconnect	Provision	Build	Cancel	Configure	Create	Delete	Discover
 admin	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
 ProjectMember	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

10. Similarly, more roles can be added.
11. Now, we need to provide **Project roles**.
12. Here, we are creating one role named **Developer** with the pattern **'Prog.*'** that is specified.
13. Now, check all the boxes for these roles as shown in the figure given below.

Item roles																						
Role	Pattern	Credentials					Job							Run			SCM			Lockable Resources		
		Create	Delete	ManageDomains	Update	View	Build	Cancel	Configure	Create	Delete	Discover	Move	Read	Workspace	Delete	Replay	Update	Tag	Reserve	Unlock	View
Developer	"Prog.*"	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Role to add

Pattern

Add

14. Similarly, we have created one more role named **Tester** with the pattern **'Test.*'**.

Item roles																						
Role	Pattern	Credentials					Job							Run			SCM			Lockable Resources		
		Create	Delete	ManageDomains	Update	View	Build	Cancel	Configure	Create	Delete	Discover	Move	Read	Workspace	Delete	Replay	Update	Tag	Reserve	Unlock	View
Developer	"Prog.*"	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Tester	"Test.*"	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Role to add

Pattern

Add

15. After that, click on **Apply** and then on **Save**.
16. Now, navigate to the **Manage Jenkins** page and select the **Manage and Assign Roles** option.
17. Select the **Assign Roles** option here.



Manage and Assign Roles



Manage Roles

Manage Roles



Assign Roles

Assign Roles




Role Strategy Macros

Provides info about macro usage and available macros

18. Now, we need to add the users in the **Global role** that we created earlier to assign them roles.
19. Enter the **user to add** and click on **Add** option. Here we are adding the user **Developer**.
20. Next, assign the user to the correct role as shown in the screenshot given below. Similarly, we can add other users.

Assign Roles

Global roles

User/group	ProjectMember	admin
 admin	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Anonymous	<input type="checkbox"/>	<input type="checkbox"/>
Developer	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tester	<input checked="" type="checkbox"/>	<input type="checkbox"/>

- Now, we need to add users in the **Item** roles.
- Enter the **user to add** and then click on the **Add** option as shown below.
- Now, assign them to the correct group as shown below.
- Similarly, we can add other users here.

Item roles

User/group	Developer	Tester
Anonymous	<input type="checkbox"/>	<input type="checkbox"/>
Developer	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tester	<input type="checkbox"/>	<input checked="" type="checkbox"/>

- Then, click on **Apply** and then **Save**.







Creating jobs and verifying roles

Now, let's create some jobs and check whether our roles are working as per the pattern.

Now, we will take a look at the steps involved here.

- Create two jobs named **TestProject** and **Program1**.




[add description](#)

All +						
S	W	Name ↓	Last Success	Last Failure	Last Duration	
		Program1	N/A	N/A	N/A	
		TestProject	N/A	N/A	N/A	

Icon: [S](#) [M](#) [L](#)

[Legend](#)
[Atom feed for all](#)
[Atom feed for failures](#)
[Atom feed for just latest builds](#)




- Now, log out and then log in as **Developer**.
- You will notice that only the job **Program1** is visible to us, as we have specified that developers can access only the jobs starting with “**Prog.***”

All						
S	W	Name ↓	Last Success	Last Failure	Last Duration	
		Program1	N/A	N/A	N/A	

Icon: [S](#) [M](#) [L](#)

[Legend](#)
[Atom feed for all](#)
[Atom feed for failures](#)
[Atom feed for just latest builds](#)

- Log out and log in as **Tester**.
- This time you will only see the TestProject job, as we have specified that the tester can only view the job starting with “**Test.***”
- The tester can only create and build jobs starting with **Test**.

All						
S	W	Name ↓	Last Success	Last Failure	Last Duration	
		TestProject	N/A	N/A	N/A	

Icon: [S](#) [M](#) [L](#)

[Legend](#)
[Atom feed for all](#)
[Atom feed for failures](#)
[Atom feed for just latest builds](#)

- Finally, click on **Build Now** to view the Console Output.

Console Output

Started by user **Tester_1**

Running as SYSTEM

Building in workspace /var/lib/jenkins/workspace/TestProject

Finished: SUCCESS