

Algorithms: Applications of BFS

Suppose we have a graph $G = (V, E)$. A given graph could have few edges, or lots of edges, or anything in between. Let's think about the range of possible relationships between V and E .

- 1 The smallest possible value of $|E|$ is _____.

- 2 $|E|$ is $O(\quad)$ because _____.

- 3 When G is a tree, $|E|$ is $\Theta(\quad)$ because _____.

Now, recall from last class that we showed breadth-first search (BFS) can be implemented to run in $\Theta(|V| + |E|)$ time.

- 4 In terms of Θ , how fast does BFS run, as a function of $|V|$, when G is a tree?

- 5 How fast does BFS run, as a function of $|V|$, when G is very dense, *i.e.* it contains some constant fraction (say, half) of all possible edges?


A first application of BFS

- 6 Describe an algorithm to find the connected components of a graph G .

Input: a graph $G = (V, E)$

Output: a set of sets of vertices, $\text{Set}\langle\text{Set}\langle\text{Vertex}\rangle\rangle$, where each set contains the vertices in some (maximal) connected component. That is, all the vertices within each set should be connected; no vertex should be connected to vertices in any other set; and every vertex in V should be contained in exactly one of the sets.

For example, given the graph below, the algorithm should return $\{\{D, E, F\}, \{C, B, A\}, \{G\}, \{H\}\}$.




Describe your algorithm (using informal prose or pseudocode) and analyze its asymptotic running time.



A second application of BFS

Model 1: Directed graphs



- 7 What is the difference between directed graphs and the (undirected) graphs we saw on a previous activity?
- 8 The previous activity defined graphs as consisting of a set V of vertices and a set E of edges, where each edge is a set of two vertices. How would you modify this definition to allow for directed graphs?
- 9 For each of the following graph terms/concepts, say whether you think its definition needs to be modified for directed graphs; if so, say what the new definition should be.
- 1 *vertex*
 - 2 *degree*
 - 3 *path*
 - 4 *cycle*
- 10 What (if anything) about our implementation of BFS needs to be modified for BFS to work sensibly on directed graphs?



Definition 1. A directed graph $G = (V, E)$ is *strongly connected* if for any two vertices $u, v \in V$ there is a (directed) path from u to v , and also from v to u .

- 11 Describe a brute force algorithm for determining whether a given directed graph G is strongly connected.
- 12 Analyze the running time of your algorithm. Express your answer using Θ .

Model 2: Reverse graphs and strong connectivity

Definition 2. Given a directed graph G , its *reverse graph* G^{rev} is the graph with the same vertices and edges, except with all the edges reversed.

Theorem 3. A directed graph $G = (V, E)$ is strongly connected if and only if given any $s \in V$,

- all vertices are reachable from s in G , and
- all vertices are reachable from s in G^{rev} .

- 13 Based on the above theorem, describe an algorithm to determine whether a given directed graph $G = (V, E)$ is strongly connected, and analyze its running time.



- 14 Can you give an informal, intuitive explanation why the theorem is true? (*Hint*: if all vertices are reachable from s in G^{rev} , what does it tell us about G ?)

