# Moody's Analytics Scenario Studio API User Guide

version 2

#### Introduction

Scenario Studio API provides easy programmatic control over Scenario Studio enabling process automation and workflow integration. We provide a Swagger API interface to provide additional documentation and facilitate testing. The Scenario Studio API supports both HMAC and oAuth 2.0 authentication and JSON responses, and is agnostic regarding the client's operating system and programming language. The API is throttled (rate-limited) to 300 requests per minute and one gigabyte of data per month. The Swagger documentation examples express the requests in cURL notation, and the GitHub repository contains examples in Python and R.

#### Overview

The Scenario Studio v2 API core functions consist of several groups of endpoints for creating, editing, managing, and reading data and metadata from Scenario Studio projects.

- /audit/... Retrieve content and counts of records in a project's audit log
- /project/... Get metadata for a project, add and remove scenarios, and configure project settings
  - /project/.../scenario/... Get metadata for a scenario, run solves, and configure settings
  - o /project/.../data-series/... Retrieve and push time series data to and from Scenario Studio
  - o /project/.../scenario/.../series/... Get series information, claim/release, change state, and customize equations
  - /project/.../search/ Returns lists and counts of series within a project according to search parameters
- .../order/... Get status of brokerized processes such as solves and project builds
- /base-scenario/... Search and retrieve information about available base scenarios

### **Authentication**

The Scenarion Studio API supports 2 forms of authentication:

- 1. HMAC Signature
- 2. OAuth 2.0 Token

Both methods require Scenario Studio API access key and encryption key. Every request to the API must contain either an HMAC signature or OAuth Token.

#### **Getting API Keys**

Access to the API is controlled by the combination of an access key and an encryption key. These keys are issued to a single user. To obtain your keys, go to the "My Subscriptions" section of your Economy.com account: https://www.economy.com/myeconomy/api-key-info.

Figure 1. Example access key and encryption key

DB73FDF0-043C-4018-A7EB-CFB57356BA22 7C7C2FEA-6D18-49A1-BEC9-193B67EAE87D

### **Using HMAC Authentication**

#### Authenticating each request

HMAC signature is generated from your access key, encryption key, and a time stamp. You must attach a signature to every request using HAMC authorization, and you must re-create the signature with every request; you will receive an HTTP 401 Unauthorized error otherwise.

The access key, time stamp and signature need to be passed in as HTTP headers (not as part of the query string). Do not transmit the encryption key in the request since it is a secret between you and the server. Specifically, the signature is a SHA256 hash of the access key, encryption key and time stamp. The time stamp must be formatted as yyyy-MM-ddTHH:mm:ssZ using UTC. For example, "July 30, 2018 5:03:28pm EST" must be represented as 2018-07-30T21:03:28Z.

#### Figure 2. Example HTTP request header

AccessKeyId: DB73FDF0-043C-4018-A7EB-CFB57356BA22

TimeStamp: 2012-08-02T14:25:20Z

Signature: A7808C5A67C422054364F195B16175308317930848232C6A08A77224F1017E83

#### Figure 3. Example signature creation in C

This C# function creates a signature from an access key, encryption key, and time stamp. See the GitHub repository for samples using Python and R.

```
using System;
using System.Text;
using System.Security.Cryptography;
public static string CreateHMACSignature
(string accKey, string encKey, string timeStamp)
{
    string signature = string.Empty;
    byte[] keyBytes = Encoding.UTF8.GetBytes(encKey);
    using (HMAC hmac = new HMACSHA256(keyBytes))
    {
        byte[] bytesToHash = Encoding.UTF8.GetBytes(accKey + timeStamp);
        byte[] hashedBytes = hmac.ComputeHash(bytesToHash);
        for (int i = 0; i < hashedBytes.Length; i++)
        {
            signature += hashedBytes[i].ToString("X2");
        }
    }
    return signature;
}</pre>
```

### Using OAuth authentication.

oAuth Token can be generated by calling an API endpoint, using API access key as *client\_id* and API encryption key as *client\_secret* and it will remain valid for 1 hour. You must include token in header of every request using OAuth authorization.

#### **Obtaining OAuth Token**

The oauth2/token endpoint is used to generate oAuth Token using your access key as client\_id, encryption key as client\_secret and grant\_type as client\_credentials. The following cURL request can be used to obtain an OAuth token.

#### Figure 4. Request

```
curl -X POST \
https://api.economy.com/scenario-studio/v1/oauth2/token \
-H 'Content-Type: application/x-www-form-urlencoded' \
-d 'client_id=DB73FDF0-043C-4018-A7EB-CFB57356BA22' \
-d 'client_secret=47C7C2FEA-6D18-49A1-BEC9-193B67EAE87D' \
-d 'grant_type=client_credentials'
```

The response to the above request will have a new access token.

#### Figure 5. Respone

```
{
  "token_type": "bearer",
  "access_token": "SrZ5UkbzPn432zqMLgV3Ja",
  "expires_in": 3600
}
```

A request to API will have Authorization: Bearer token as header

#### Figure 6. Call to API endpoint using oAuth Token

```
curl -X GET \
  'https://api.economy.com/scenario-studio/v1/project' \
  -H 'Authorization: Bearer SrZ5UkbzPn432zqMLgV3Ja'
```

### Frequently asked questions

- General API use
  - What programming languages does the API support?
  - What response types are supported?
  - Can I use the API from Linux?
  - What kind of authentication does the API use?
  - How often do I need to regenerate the signature?

- · How often do I need to regenerate the token?
- · Is the API throttled?
- Can I use the API to populate a data warehouse?
- API capabilities
  - What kind of Scenario Studio information can I retrieve?
  - o Can I create or alter a project or scenario?
- Scenenario Studio API parameters
  - o How should date parameters be constructed?
  - How many series can I retrieve with the data-series endpoint?
  - If I alter the name of a project using the Scenario Studio web application, do I need to change my code?
- Support
  - · Whom do I contact for assistance in using the API?
  - Do other Moody's Analytics products have APIs?
  - o I don't understand this jargon-can you translate?

#### What programming languages does the API support?

The programming language used at your end is immaterial, so long as it (a) creates HTTP requests that the API can process, and (b) can interpret the JSON-formatted responses produced by the API. The examples provided in this document and in the GitHub repository use cURL, Python and R.

#### What response types are supported?

JSON is the only response type returned by the API.

#### Can I use the API from Linux?

Yes, because the operating system is immaterial. Java, Python and R are commonly used on Linux machines; to run C#, you will need to install the .NET Core framework. Setting up your run-time environment is beyond the scope of this document.

#### What kind of authentication does the API use?

Our API uses HMAC and OAuth 2.0 authentication. See the Authentication section above for more info.

#### How often do I need to regenerate the HMAC signature?

You must re-create the signature prior to every request; otherwise you will receive the "HTTP 401 Unauthorized" error. You may find it useful to create a wrapper function that takes the time stamp, access key and encryption key as arguments, and generates a signature immediately before calling the endpoint.

#### How often do I need to regenerate the oAuth 2.0 token?

Once generated the oAuth token is valid for 1 hour and can be used for multiple requests.

#### Is the API throttled?

Yes, in two ways. First, you can execute 300 requests per minute per account (but a single request can retrieve one series or a basket containing thousands of series). You will receive "HTTP 429 Too Many Requests" error. Second, you can retrieve only one gigabyte of data per month. This includes all of the metadata and HTTP headers, although these are insignificant relative to the data payload. The number of requests and series are not specifically limited.

#### Can I use the API to populate a data warehouse?

Yes. You may create a data warehouse for internal use, but the number of users who may have access to it is stipulated by your contract; please contact your Moody's Analytics sales representative if you have questions.

#### What kind of Scenario Studio information can I retrieve?

The API can return Scenario Studio project, scenario, and series details and metadata, as well as series data.

#### Can I create or alter a project or scenario?

Yes. The Scenario Studio v2 API now includes endpoints that enable project creation, scenario editing, and solving.

#### How should date parameters be constructed?

Date parameters sent to API endpoints should be integers, defined as the number of periods since Dec 31 1849. For a quarterly series, this translates to 1850Q1=1, 1850Q2=2, etc. For a monthly series this is Jan1850=1, Feb1850=2, etc.

#### How many series can I retrieve with the data-series endpoint?

There is no hard limit on the number of series that can be retrieved with the POST version of the data-series endpoint. However, there is a practical limit when requests become too large there is a chance of a error 504 gateway timeout. When using the GET version of the data-series endpoint, there is the additional limit of query string length.

If I alter the name of a project using the Scenario Studio web application, do I need to change my code?

No. The /project/{projectid} endpoint identifies a project by an immutable alphanumeric GUID that is assigned by our system, not the human-readable title assigned by you

#### Whom do I contact for assistance in using the API?

Please go to the Economy.com Contact Us page for email, chat, and telephone options. If using the email form, set Topic to "Technical Issue."

#### Do other Moody's Analytics products have APIs?

Yes. We also provide APIs for our Data Buffet, AutoCycle, and Précis products.

#### I don't understand this jargon—can you translate?

Please see if the glossary in this document helps. It lists terminology pertaining to web APIs and related Moody's Analytics products.

### Appendix 1: API endpoints

All API endpoints below are relative to the root URL https://api.economy.com/scenario-studio/v2/.

#### Project and scenario management end points

These endpoints allow for the creation, modification, metadata retrieval, and solving of scenarios within projects.

HTTP	Endpoint	Description
Project		
GET	/project	Gets the list of projects to which the user has access.
GET	/project/search	Gets the search records when searching for projects to which the user has access
GET	/project/search/count	Gets the count of search records when searching for projects to which the user has access
GET	/project/{projectId}	Gets information about a specific project.
GET	/project/{projectId}/scenario	Gets the list of scenarios within a project.
GET	/project/{projectId}/series	Gets the list of all series within a project.
GET	/project/{projectId}/geos	Gets the list of geographies within a project.
GET	/project/{projectId}/series/checked-out	Gets the list of series checked out by the current user.
GET	/project/{projectId}/series/exogenized	Gets the list of exogenized series in a project.
GET	/project/{projectId}/checkpoint/{scenarioId}	Gets the list of checkpoints for a scenario.
POST	/project/create	Creates a new project.
POST	/project/{projectId}/scenario/clone	Creates a copy of a scenario and adds it to a project.
POST	/project/{projectId}/scenario/copy	Adds a read-only copy of a scenario to a project
POST	/project/{projectId}/build	Starts the build process for a project
PUT	/project/{projectId}/settings	Update a project's settings.
PUT	/project/{projectId}/contributor/{role}	Adds contributors to a project.
DELETE	/project/{projectId}	Deletes a project.
DELETE	/project/{projectId}/scenario/alias/{alias}	Removes a scenario from a project.
Scenario		
GET	/project/{projectId}/scenario/{scenarioId}	Gets information about a specific scenario.

PUT HTTP	/project/{projectId}/scenario/{scenarioId} Endpoint	Update the scenario options. Description
PUT	/project/{projectId}/scenario/{scenarioId}/checkpoint/{checkpointId}	Creates backup checkpoint of the scenario, and restores the given checkpoint.
POST	/project/{projectId}/scenario/{scenarioId}/solve/local	Performs a local solve on a scenario.
POST	/project/{projectId}/scenario/{scenarioId}/solve/central	Performs a central solve on a scenario.
POST	/project/{projectId}/scenario/reendogenize	Performs an add-factor solve.
POST	/project/{projectId}/scenario/{scenarioId}/checkpoint	Creates new checkpoint.

### Series-related end points

These end points enable data and metadata retreival for series data. In addition, they enable editing data, equations, and state. Custom variables can also be added, modified, and deleted.

POST /project/(projectId)/data-series  POST /project/(projectId)/data-series  PUT /project/(projectId)/scenario/(scenarioId)/data-series/(variableId)/data/local Writes series data to a user's local copy of a scenario  PUT /project/(projectId)/scenario/(scenarioId)/data-series/add-factor/local Zero out add factors for a list of series in a user's local copy of a scenario  Series  GET /project/(projectId)/scenario/(scenarioId)/(variableId) Gets basic information about a specific series.  GET /project/(projectId)/scenario/(scenarioId)/variable/(variableId) Gets all meta information for a series.  GET /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown  Gets sharedown information for a series.  POST /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown  POST /project/(projectId)/scenario/(scenarioId)/series/custom Creates new custom series.  POST /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown  POST /project/(projectId)/scenario/(scenarioId)/series/checkout Claim out series.  POST /project/(projectId)/scenario/(scenarioId)/series/checkout Release a series/unlocks a series without writing data to central.  POST /project/(projectId)/scenario/(scenarioId)/series/checkin Post variable ocentral.  POST /project/(projectId)/scenario/(scenarioId)/series/checkin Sets series is tate to exogenous.  POST /project/(projectId)/scenario/(scenarioId)/series/exogenize Sets series state to exogenous.  PUT /project/(projectId)/scenario/(scenarioId)/series/exogenize-through Sets series is tate to endogenous.  PUT /project/(projectId)/scenario/(scenarioId)/series/exogenize-through Edits the equation of a series.	НТТР	Endpoint	Description
PUT /project/(projectId)/scenario/(scenarioId)/data-series/(variableId)/data/local Writes series data to a user's local copy of a scenario  PUT /project/(projectId)/scenario/(scenarioId)/data-series/add-factor/local Zero at add factors for a list of series in a user's local copy of a scenario  Series  GET /project/(projectId)/scenario/(scenarioId)/(variableId) Gets basic information about a specific series.  GET /project/(projectId)/scenario/(scenarioId)/variable/(variableId) Gets all meta information for a series.  GET /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown Gets all meta information for a series.  POST /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown Gets series info for a list of series/expressions.  POST /project/(projectId)/scenario/(scenarioId)/series/custom Creates new custom series.  POST /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown Sharedown chain, and starts the sharedown chain, and starts the sharedown calculation.  POST /project/(projectId)/scenario/(scenarioId)/series/checkout Claim out series.  POST /project/(projectId)/scenario/(scenarioId)/series/checkin Releases a series/unlocks a series without writing data to central.  POST /project/(projectId)/scenario/(scenarioId)/series/checkin Push to central/commit a series-writes local data to central.  POST /project/(projectId)/scenario/(scenarioId)/series/exogenize  PUT /project/(projectId)/scenario/(scenarioId)/series/exogenize  Sets series to be partially exogenized.  PUT /project/(projectId)/scenario/(scenarioId)/series/exogenize-through Sets series to be partially exogenized.	DataSeries		
PUT /project/(projectId)/scenario/(scenariold)/data-series/(variableId)/data/local local copy of a scenario  Zero out add factors for a list of series in a user's local copy of a scenario  Series  GET /project/(projectId)/scenario/(scenariold)/(variableId) Gets basic information about a specific series.  GET /project/(projectId)/scenario/(scenariold)/variable/(variableId) Gets all meta information for a series.  GET /project/(projectId)/scenario/(scenariold)/series/(variableId)/sharedown Gets sharedown information for a series.  POST /project/(projectId)/scenario/(scenariold)/series/(variableId)/sharedown Creates new custom series.  POST /project/(projectId)/scenario/(scenariold)/series/(variableId)/sharedown calculation.  POST /project/(projectId)/scenario/(scenariold)/series/checkout Claim out series.  POST /project/(projectId)/scenario/(scenariold)/series/checkout Claim out series.  POST /project/(projectId)/scenario/(scenariold)/series/checkin Releases a series/unlocks a series without writing data to central.  POST /project/(projectId)/scenario/(scenariold)/series/commit Push to central/commit a series-writes local data to central.  POST /project/(projectId)/scenario/(scenariold)/series/exogenize Sets series to be partially exogenized.  PUT /project/(projectId)/scenario/(scenariold)/series/exogenize-through Sets series' state to endogenous.	POST	/project/{projectId}/data-series	
PUT /project/(projectId)/scenario/(scenarioId)/data-series/add-factor/local series in a user's local copy of a scenario  Series /project/(projectId)/scenario/(scenarioId)/(variableId) Gets basic information about a specific series.  GET /project/(projectId)/scenario/(scenarioId)/variable/(variableId) Gets all meta information for a series.  GET /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown Gets sharedown information for a series.  POST /project/(projectId)/scenario/(scenarioId)/series/info Gets series info for a list of series/expressions.  POST /project/(projectId)/scenario/(scenarioId)/series/custom Creates new custom series.  POST /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown Sharedown calculation.  POST /project/(projectId)/scenario/(scenarioId)/series/checkout Claim out series.  POST /project/(projectId)/scenario/(scenarioId)/series/checkin Releases a series/unlocks a series without writing data to central.  POST /project/(projectId)/scenario/(scenarioId)/series/commit Puth to central/commit a series-writes local data to central.  PUT /project/(projectId)/scenario/(scenarioId)/series/exogenize Sets series to be partially exogenized.  PUT /project/(projectId)/scenario/(scenarioId)/series/exogenize+through Sets series' state to endogenous.	PUT	/project/{projectId}/scenario/{scenarioId}/data-series/{variableId}/data/local	
GET /project/(projectId)/scenario/(scenarioId)/(variableId) Gets basic information about a specific series.  GET /project/(projectId)/scenario/(scenarioId)/variable/(variableId) Gets all meta information for a series.  GET /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown Gets sharedown information for a series.  POST /project/(projectId)/scenario/(scenarioId)/series/info Gets series info for a list of series/expressions.  POST /project/(projectId)/scenario/(scenarioId)/series/custom Creates new custom series.  POST /project/(projectId)/scenario/(scenarioId)/series/(variableId)/sharedown sharedown calculation.  POST /project/(projectId)/scenario/(scenarioId)/series/checkout Claim out series.  POST /project/(projectId)/scenario/(scenarioId)/series/checkin Releases a series/unlocks a series without writing data to central.  POST /project/(projectId)/scenario/(scenarioId)/series/commit Push to central/commit a series-writes local data to central.  PUT /project/(projectId)/scenario/(scenarioId)/series/exogenize Sets series' state to exogenous.  PUT /project/(projectId)/scenario/(scenarioId)/series/exogenize-through Sets series' state to endogenous.	PUT	/project/{projectId}/scenario/{scenarioId}/data-series/add-factor/local	series in a user's local copy of a
Aproject/(projectId)/scenario/(scenariold)/variableId   Specific series	Series		
GET /project/{projectId}/scenario/{scenarioldy/variableId}/series.  GET /project/{projectId}/scenario/{scenarioldy/series/{variableId}/sharedown series.  POST /project/{projectId}/scenario/{scenarioldy/series/info Gets series info for a list of series/expressions.  POST /project/{projectId}/scenario/{scenarioldy/series/custom Creates new custom series.  POST /project/{projectId}/scenario/{scenarioldy/series/{variableId}/sharedown Sharedown calculation.  POST /project/{projectId}/scenario/{scenarioldy/series/checkout Claim out series.  POST /project/{projectId}/scenario/{scenarioldy/series/checkout Series without writing data to central.  POST /project/{projectId}/scenario/{scenarioldy/series/commit Push to central/commit a series-writes local data to central.  PUT /project/{projectId}/scenario/{scenarioldy/series/exogenize Sets series' state to exogenous.  PUT /project/{projectId}/scenario/{scenarioldy/series/exogenize-through Sets series' state to endogenous.  PUT /project/{projectId}/scenario/{scenarioldy/series/exogenizeBulk Sets series' state to endogenous.	GET	/project/{projectId}/scenario/{scenarioId}/{variableId}	
POST /project/{projectId}/scenario/{scenariold}/series/(variableId)/sharedown series.  POST /project/{projectId}/scenario/{scenariold}/series/info Gets series info for a list of series/expressions.  POST /project/{projectId}/scenario/{scenariold}/series/custom Creates new custom series.  POST /project/{projectId}/scenario/{scenariold}/series/{variableId}/sharedown sharedown chain, and starts the sharedown calculation.  POST /project/{projectId}/scenario/{scenariold}/series/checkout Claim out series.  POST /project/{projectId}/scenario/{scenariold}/series/checkin series without writing data to central.  POST /project/{projectId}/scenario/{scenariold}/series/commit Push to central/commit a series-writes local data to central.  PUT /project/{projectId}/scenario/{scenariold}/series/exogenize Sets series' state to exogenous.  PUT /project/{projectId}/scenario/{scenariold}/series/exogenize-through Sets series to be partially exogenized.  PUT /project/{projectId}/scenario/{scenariold}/series/endogenizeBulk Sets series' state to endogenous.	GET	/project/{projectId}/scenario/{scenarioId}/variable/{variableId}	
/project/{projectId}/scenario/{scenariold}/series/info series/expressions.  POST /project/{projectId}/scenario/{scenariold}/series/custom Creates new custom series.  Checks out all variables within a sharedown chain, and starts the sharedown calculation.  POST /project/{projectId}/scenario/{scenariold}/series/checkout Claim out series.  POST /project/{projectId}/scenario/{scenariold}/series/checkout  POST /project/{projectId}/scenario/{scenariold}/series/checkin  POST /project/{projectId}/scenario/{scenariold}/series/checkin  POST /project/{projectId}/scenario/{scenariold}/series/commit  Push to central/commit a series-writes local data to central.  PUT /project/{projectId}/scenario/{scenariold}/series/exogenize  PUT /project/{projectId}/scenario/{scenariold}/series/exogenize-through  PUT /project/{projectId}/scenario/{scenariold}/series/exogenize-through  PUT /project/{projectId}/scenario/{scenariold}/series/endogenizeBulk  Sets series' state to endogenous.	GET	/project/{projectId}/scenario/{scenarioId}/series/{variableId}/sharedown	
POST /project/{projectId}/scenario/{scenarioId}/series/{variableId}/sharedown sharedown chain, and starts the sharedown calculation.  POST /project/{projectId}/scenario/{scenarioId}/series/checkout Claim out series.  POST /project/{projectId}/scenario/{scenarioId}/series/checkin Releases a series/unlocks a series without writing data to central.  POST /project/{projectId}/scenario/{scenarioId}/series/commit Push to central/commit a series-writes local data to central.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize Sets series' state to exogenous.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize-through Sets series to be partially exogenized.  PUT /project/{projectId}/scenario/{scenarioId}/series/endogenizeBulk Sets series' state to endogenous.	POST	/project/{projectId}/scenario/{scenarioId}/series/info	
/project/{projectId}/scenario/{scenarioId}/series/{variableId}/sharedown sharedown chain, and starts the sharedown calculation.  POST /project/{projectId}/scenario/{scenarioId}/series/checkout Claim out series.  POST /project/{projectId}/scenario/{scenarioId}/series/checkin Releases a series/unlocks a series without writing data to central.  POST /project/{projectId}/scenario/{scenarioId}/series/commit Push to central/commit a series-writes local data to central.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize Sets series' state to exogenous.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize-through Sets series to be partially exogenized.  PUT /project/{projectId}/scenario/{scenarioId}/series/endogenizeBulk Sets series' state to endogenous.	POST	/project/{projectId}/scenario/{scenarioId}/series/custom	Creates new custom series.
POST /project/{projectId}/scenario/{scenarioId}/series/checkin series without writing data to central.  POST /project/{projectId}/scenario/{scenarioId}/series/commit Push to central/commit a series-writes local data to central.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize Sets series' state to exogenous.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize-through Sets series to be partially exogenized.  PUT /project/{projectId}/scenario/{scenarioId}/series/endogenizeBulk Sets series' state to endogenous.	POST	/project/{projectId}/scenario/{scenarioId}/series/{variableId}/sharedown	sharedown chain, and starts the
POST /project/{projectId}/scenario/{scenarioId}/series/checkin series without writing data to central.  POST /project/{projectId}/scenario/{scenarioId}/series/commit Push to central/commit a series-writes local data to central.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize Sets series' state to exogenous.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize-through Sets series to be partially exogenized.  PUT /project/{projectId}/scenario/{scenarioId}/series/endogenizeBulk Sets series' state to endogenous.	POST	/project/{projectId}/scenario/{scenarioId}/series/checkout	Claim out series.
PUT /project/{projectId}/scenario/{scenarioId}/series/commit writes local data to central.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize Sets series' state to exogenous.  PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize-through Sets series to be partially exogenized.  PUT /project/{projectId}/scenario/{scenarioId}/series/endogenizeBulk Sets series' state to endogenous.	POST	/project/{projectId}/scenario/{scenarioId}/series/checkin	series without writing data to
PUT /project/{projectId}/scenario/{scenarioId}/series/exogenize-through Sets series to be partially exogenized.  PUT /project/{projectId}/scenario/{scenarioId}/series/endogenizeBulk Sets series' state to endogenous.	POST	/project/{projectId}/scenario/{scenarioId}/series/commit	
PUT /project/{projectId}/scenario/{scenariold}/series/exogenize-through exogenized.  PUT /project/{projectId}/scenario/{scenariold}/series/endogenizeBulk Sets series' state to endogenous.	PUT	/project/{projectId}/scenario/{scenarioId}/series/exogenize	Sets series' state to exogenous.
	PUT	/project/{projectId}/scenario/{scenarioId}/series/exogenize-through	
PUT /project/{projectId}/scenario/{scenarioId}/series/{variableId}/equation Edits the equation of a series.	PUT	/project/{projectId}/scenario/{scenarioId}/series/endogenizeBulk	Sets series' state to endogenous.
	PUT	/project/{projectId}/scenario/{scenarioId}/series/{variableId}/equation	Edits the equation of a series.

PUT HTTP	/project/{projectId}/scenario/{scenarioId}/series/custom Endpoint	Edits a custom series. Description
PUT	/project/{projectId}/scenario/{scenariold}/series/{variableId}/historical/{lastHistorical}	Changes the last historical end point for a series.
DELETE	/project/{projectId}/scenario/{scenarioId}/series/custom	Deletes custom series.

### Miscellaneous endpoints

HTTP	Endpoint	Description
Order		
GET	/project/{projectId}/order/{orderId}	Gets information on any single order.
GET	/project/{projectId}/order/{orderId}/build	Checks the project build order status.
SeriesSearch		
POST	/project/{projectId}/search/count	Gets the record count for a series search query.
POST	/project/{projectId}/search/results	Gets the records for a series search query.
Audit		
GET	/audit/project/{projectId}/count	Gets the record count for an audit search query.
GET	/audit/project/{projectId}	Gets the records for an audit search query.
Universe		
GET	/group/client	Gets the list of permissionable clients (in the context of the person making the request).
GET	/base-scenario/{scenarioId}	Gets base/Moody's scenario detail.
GET	/base-scenario	Get the list of base/moody's scenarios.
GET	/base-scenario/{scenariold}/details	Gets the full details on a base scenario.
POST	/base-scenario/search	Gets the records for a base scenario search query.
POST	/base-scenario/search/count	Gets the record count for a base scenario search query.
POST	/project/scenario/search	Gets the records for a client scenario search query.
POST	/project/scenario/search/count	Gets the record count for a client scenario search query.

# Appendix 2: HTTP server response codes

Codes returned by the Scenario Studio API are adaptations of standard HTTP server response codes.

Code	Meaning
Success codes	
200 OK	The request has succeeded
304 Not modified	The edits transmitted to Scenario Studio did not differ from teh data already on the server, thus nothing was changed
Error codes	
401 Unauthorized	The authenticating HMAC signature is outdated or the oAuth token has expired. You must generate a new signature or access token (see Authentication section).
404 Not Found	The URL path used was not found. Check the URL you are transmitting in your API request

<b>Code</b> 429 Too Many Requests	Meaning You have exceeded the 300 request per minute rate limit. Throttling is access key-specific.
500 Internal Server Error	Server error - check your POST/PUT payload or query string arguments.
504 Gateway Timeout	The request is too large. Consider breaking the request into batches.

### Integer codes

#### Frequencies

- 128 Monthly
- 172 Quarterly
- 204 Annual

#### Variable types

- 0 Stochastic
- 1 Identity
- 2 Exogenous

#### Conversion method

Override the default conversion method when downloading data with frequency conversion.

- 0 Default Observed attribute of the series is used
- 1 Beginning of period
- 2 End of period
- 3 Average
- 4 Sum
- 5 High value in period
- 6 Low value in period

#### Conversion technique

Override the default conversion technique when downloading data with frequency conversion.

- 0 Piecewise constant
- 1 Linear
- 2 Cubic (default)
- 3 Discrete

#### Variable states

Variable state is a bitwise argument in series search. Add codes together to combine.

- 1 Endogenous
- 2 Exogenous
- 4 Partially exogenous

### Contributor roles

- 0 Inactive: No access to the project
- 1 Administrator: Read/write/solve access; access to configure project, scenario, and user access settings
- 2 Editor: Read/write/solve access
- 3 Observer: Read-only access

### Claim status (checkedOut)

Claim status is a bitwise argument in series search. Add codes together to combine.

- 1 Unclaimed
- 2 Claimed by others
- 4 Claimed by you

### Further reading

### API documentation and functionality

- API key management
- Technical user guide
- Code samples in C#, Java, Python, R

· How to authenticate (See Authentication section)

### Glossary

access key: Part of the credentials used to access the Scenario Studio API. A unique 36-character hexadecimal string, which is combined with the encryption key (qv) to produce the signature (qv).

API: Application programming interface. Generically, a set of function signatures (input and output parameters) to perform documented behavior. See also: web API (qv).

AutoCycle: See: Moody's AutoCycle™ (qv).

Coordinated Universal Time: A civil time standard based on atomic clocks and astronomical measurements, and an associated representation using a 24-hour clock that includes year, month, day, hour, minute and second, and fixed punctuation. The format is yyyymm-ddThh:mm:ssZ, for example, 2018-07-30T21:03:28Z. This format is used when making requests to the Scenario Studio API(qv). A.k.a. universal coordinated time, universal time coordinated, UTC.

cURL: Client for URLs. An open-source command-line software application to demonstrate HTTP (qv) requests and responses. Its syntax is often used to concisely document the behavior of web APIs (qv). See: curl.haxx.se

CreditCycle: see: Moody's CreditCycle™ (qv).

CSV: Comma-Separated Value. A file format that consists of plain text, where fields are separated by comma characters, and records are separated by line breaks.

encryption key: Part of the credentials used to access the Scenario Studio API. A unique 36-character hexadecimal string, which is combined with the access key (qv) to produce the signature (qv).

end point: In a web API (qv), a unique, static URL that represents an object or collection of objects; to interact with these resources, you point an HTTP client (qv) at the endpoint.

GUID: Globally Unique Identifier. GUIDs are used in enterprise software development as database keys, component identifiers, and in COM programming; they are generated by individual users with an algorithm that virtually guarantees uniqueness. A GUID is a 128-bit integer, commonly expressed as a 32-character hexadecimal string delimited by hyphens. In the Scenario Studio API, access and encryption keys, and basket and order identifiers, are GUIDs. A.k.a. Universally Unique Identifier, UUID.

HMAC: Hash-based Message Authentication Code. An international software standard (RFC2104 et seq) to verify the integrity of information transmitted over an unreliable medium such as the internet.

HTTP: HyperText Transfer Protocol. An international software standard (RFC2616 et seq) for an application-layer, client-server, stateless protocol for transmitting hypermedia documents and control information. See: https://www.w3.org/Protocols/, https://developer.mozilla.org/en-US/docs/Web/HTTP

HTTP client: Software that can communicate via HTTP (qv) with a server, for example, a web browser, cURL (qv), or a custom application that queries a web API (qv).

JSON: JavaScript Object Notation: An international software standard (ECMA-404), a lightweight data-interchange format that is easy for software to parse and generate, for humans to read and write, and is programming language-independent. JSON is the format in which the Scenario Studio API (qv) delivers individual time series (qv) and basket output (qv). See: www.json.org.

MIME: Multipurpose Internet Mail Extension. An international software standard (RFC2045 et seq) that identifies how a file transmitted over the internet (as by email or HTTP) should be interpreted by the recipient.

metadata: Structured data that describes other data.

Moody's AutoCycle™: A software solution to forecast car prices, incorporating economic data and scenarios from Moody's Analytics. See: https://www.economy.com/products/data/autocycle

Moody's CreditCycle™: A software solution to model consumer credit risk; it combines customer data, economic data from Moody's Analytics, and consumer credit data from Equifax. See: https://www.economy.com/products/consumer-credit-analytics/moodys-creditcycle

**OAuth:** An open software standard (RFC5849 et seq) for services over HTTP to provide "secure delegated access" whereby server owners authorize third-party access without the clients sharing their credentials.

observation: Each numeric measurement in a time series (qv).

rate limiting: With a web API (qv), a policy that controls how many requests from a given user will be processed per unit of time, typically for billing purposes or to promote adequate performance for all users.

SHA256: Secure Hash Algorithm. A cryptographic hash function that produces a 256-bit (32-byte) output.

signature: A cryptographic string generated from the access key (qv), encryption key (qv), and a time stamp and transmitted to a web API (qv) that uses HMAC (qv) authentication. See also: SHA256 (qv).

throttling: See: rate limiting.

time series: Generically, a vector of measurements (observations [qv]) at periodic intervals. In Scenario Studio (qv), a data object that contains numeric values, metadata (qv) fields that explain how to interpret (frequency [qv], etc.) and identify it (description, source), and one or more identifying mnemonics (qv).

UTC: See: Coordinated Universal Time (qv).

web API: A programmatic, server-side interface consisting of one or more endpoints (qv), typically expressed in JSON (qv) or XML, and exposed to the web, typically by an HTTP server.

## Support

Please contact the Scenario Studio API team at Moody's Analytics by email at helpeconomy@moodys.com, with a subject line of "Scenario Studio API technical inquiry"

# **About Moody's Analytics**

Moody's Analytics helps capital markets and credit risk management professionals worldwide respond to an evolving marketplace with confidence. With its team of economists, the company offers unique tools and best practices for measuring and managing risk through expertise and experience in credit analysis, economic research, and financial risk management. By offering leading-edge software and advisory services, as well as the proprietary credit research produced by Moody's Investors Service, Moody's Analytics integrates and customizes its offerings to address specific business challenges.

Concise and timely economic research by Moody's Analytics supports firms and policymakers in strategic planning, product and sales forecasting, credit risk and sensitivity management, and investment research. Our economic research publications provide in-depth analysis of the global economy, including the U.S. and all of its state and metropolitan areas, all European countries and their subnational areas, Asia, and the Americas. We track and forecast economic growth and cover specialized topics such as labor markets, housing, consumer spending and credit, output and income, mortgage activity, demographics, central bank behavior, and prices. We also provide real-time monitoring of macroeconomic indicators and analysis on timely topics such as monetary policy and sovereign risk. Our clients include multinational corporations, governments at all levels, central banks, financial regulators, retailers, mutual funds, financial institutions, utilities, residential and commercial real estate firms, insurance companies, and professional investors.

Moody's Analytics added the economic forecasting firm Economy.com to its portfolio in 2005. This unit is based in West Chester PA, a suburb of Philadelphia, with offices in London, Prague and Sydney. More information is available at <a href="https://www.economy.com">www.economy.com</a>.

Moody's Analytics is a subsidiary of Moody's Corporation (NYSE: MCO). Further information is available at www.moodysanalytics.com.

DISCLAIMER: Moody's Analytics, a unit of Moody's Corporation, provides economic analysis, credit risk data and insight, as well as risk management solutions. Research authored by Moody's Analytics does not reflect the opinions of Moody's Investors Service, the credit rating agency. To avoid confusion, please use the full company name "Moody's Analytics", when citing views from Moody's Analytics.

### **About Moody's Corporation**

Moody's is an essential component of the global capital markets, providing credit ratings, research, tools and analysis that contribute to transparent and integrated financial markets. **Moody's Corporation** (NYSE: MCO) is the parent company of Moody's Investors Service, which provides credit ratings and research covering debt instruments and securities, and **Moody's Analytics**, which encompasses the growing array of Moody's nonratings businesses, including risk management software for financial institutions, quantitative credit analysis tools, economic research and data services, data and analytical tools for the structured finance market, and training and other professional services. The corporation, which reported revenue of \$3.6 billion in 2016, employs approximately 11,500 people worldwide and maintains a presence in 41 countries.

© 2021 Moody's Corporation, Moody's Investors Service, Inc., Moody's Analytics, Inc. and/or their licensors and affiliates (collectively, "MOODY'S"). All rights reserved.

CREDIT RATINGS ISSUED BY MOODY'S INVESTORS SERVICE, INC. AND ITS RATINGS AFFILIATES ("MIS") ARE MOODY'S CURRENT OPINIONS OF THE RELATIVE FUTURE CREDIT RISK OF ENTITIES, CREDIT COMMITMENTS, OR DEBT OR DEBT-LIKE SECURITIES, AND MOODY'S PUBLICATIONS MAY INCLUDE MOODY'S CURRENT OPINIONS OF THE RELATIVE FUTURE CREDIT RISK OF ENTITIES, CREDIT COMMITMENTS, OR DEBT OR DEBT-LIKE SECURITIES. MOODY'S DEFINES CREDIT RISK AS THE RISK THAT AN ENTITY MAY NOT MEET ITS CONTRAC-TUAL, FINANCIAL OBLIGATIONS AS THEY COME DUE AND ANY ESTIMATED FINANCIAL LOSS IN THE EVENT OF DEFAULT. CREDIT RATINGS DO NOT ADDRESS ANY OTHER RISK, INCLUDING BUT NOT LIMITED TO: LIQUIDITY RISK, MARKET VALUE RISK, OR PRICE VOLATILITY. CREDIT RATINGS AND MOODY'S OPINIONS INCLUDED IN MOODY'S PUBLICATIONS ARE NOT STATEMENTS OF CURRENT OR HISTORICAL FACT. MOODY'S PUBLICATIONS MAY ALSO INCLUDE QUANTITATIVE MODEL-BASED ESTIMATES OF CREDIT RISK AND RELATED OPINIONS OR COMMENTARY PUBLISHED BY MOODY'S ANALYTICS, INC. CREDIT RATINGS AND MOODY'S PUBLICATIONS DO NOT CONSTITUTE OR PROVIDE INVESTMENT OR FINANCIAL ADVICE, AND CREDIT RATINGS AND MOODY'S PUBLICATIONS ARE NOT AND DO NOT PROVIDE RECOMMENDATIONS TO PURCHASE, SELL, OR HOLD PARTICULAR SECURITIES. NEITHER CREDIT RATINGS AND MOODY'S PUBLICATIONS COMMENT ON THE SUITABILITY OF AN INVESTMENT FOR ANY PARTICULAR INVESTOR. MOODY'S ISSUES ITS CREDIT RATINGS AND PUB-LISHES MOODY'S PUBLICATIONS WITH THE EXPECTATION AND UNDERSTANDING THAT EACH INVESTOR WILL, WITH DUE CARE, MAKE ITS OWN STUDY AND EVALUATION OF EACH SECURITY THAT IS UNDER CONSIDERATION FOR PURCHASE, HOLDING, OR SALE.

MOODY'S CREDIT RATINGS AND MOODY'S PUBLICATIONS ARE NOT INTENDED FOR USE BY RETAIL INVESTORS AND IT WOULD BE RECKLESS AND INAPPROPRIATE FOR RETAIL INVESTORS TO USE MOODY'S CREDIT RATINGS OR MOODY'S PUBLICATIONS WHEN MAKING AN INVESTMENT DECISION. IF IN DOUBT YOU SHOULD CONTACT YOUR FINANCIAL OR OTHER PROFESSIONAL ADVISER.

ALL INFORMATION CONTAINED HEREIN IS PROTECTED BY LAW, INCLUDING BUT NOT LIMITED TO, COPYRIGHT LAW, AND NONE OF SUCH IN-FORMATION MAY BE COPIED OR OTHERWISE REPRODUCED, REPACKAGED, FURTHER TRANSMITTED, TRANSFERRED, DISSEMINATED, REDISTRIB-UTED OR RESOLD, OR STORED FOR SUBSEQUENT USE FOR ANY SUCH PURPOSE, IN WHOLE OR IN PART, IN ANY FORM OR MANNER OR BY ANY MEANS WHATSOEVER, BY ANY PERSON WITHOUT MOODY'S PRIOR WRITTEN CONSENT.

All information contained herein is obtained by MOODY'S from sources believed by it to be accurate and reliable. Because of the possibility of human or mechanical error as well as other factors, however, all information contained herein is provided "AS IS" without warranty of any kind. MOODY'S adopts all necessary measures so that the information it uses in assigning a credit rating is of sufficient quality and from sources MOODY'S considers to be reliable including, when appropriate, independent third-party sources. However, MOODY'S is not an auditor and cannot in every instance independently verify or validate information received in the rating process or in preparing the Moody's publications.

To the extent permitted by law, MOODY'S and its directors, officers, employees, agents, representatives, licensors and suppliers disclaim liability to any person or entity for any indirect, special, consequential, or incidental losses or damages whatsoever arising from or in connection with the information contained herein or the use of or inability to use any such information, even if MOODY'S or any of its directors, officers, employees, agents, representatives, licensors or suppliers is advised in advance of the possibility of such losses or damages, including but not limited to: (a) any loss of present or prospective profits or (b) any loss or damage arising where the relevant financial instrument is not the subject of a particular credit rating assigned by MOODY'S.

To the extent permitted by law, MOODY'S and its directors, officers, employees, agents, representatives, licensors and suppliers disclaim liability for any direct or compensatory losses or damages caused to any person or entity, including but not limited to by any negligence (but excluding fraud, willful misconduct or any other type of liability that, for the avoidance of doubt, by law cannot be excluded) on the part of, or any contingency within or beyond the control of, MOODY'S or any of its directors, officers, employees, agents, representatives, licensors or suppliers, arising from or in connection with the information contained herein or the use of or inability to use any such information.

NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY, TIMELINESS, COMPLETENESS, MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OF ANY SUCH RATING OR OTHER OPINION OR INFORMATION IS GIVEN OR MADE BY MOODY'S IN ANY FORM OR MANNER WHATSOEVER.

Moody's Investors Service, Inc., a wholly-owned credit rating agency subsidiary of Moody's Corporation ("MCO"), hereby discloses that most issuers of debt securities (including corporate and municipal bonds, debentures, notes and commercial paper) and preferred stock rated by Moody's Investors Service, Inc. have, prior to assignment of any rating, agreed to pay to Moody's Investors Service, Inc. for appraisal and rating services rendered by it fees ranging from \$1,500 to approximately \$2,500,000. MCO and MIS also maintain policies and procedures to address the independence of MIS's ratings and rating processes. Information regarding certain affi liations that may exist between directors of MCO and rated entities, and between entities who hold ratings from MIS and have also publicly reported to the SEC an ownership interest in MCO of more than 5%, is posted annually at <a href="https://www.moodys.com">www.moodys.com</a> under the heading "Investor Relations — Corporate Governance — Director and Shareholder Affiliation Policy."

Additional terms for Australia only: Any publication into Australia of this document is pursuant to the Australian Financial Services License of MOODY'S affiliate, Moody's Investors Service Pty Limited ABN 61 003 399 657AFSL 336969 and/or Moody's Analytics Australia Pty Ltd ABN 94 105 136 972 AFSL 383569 (as applicable). This document is intended to be provided only to "wholesale clients" within the meaning of section 761G of the Corpora-tions Act 2001. By continuing to access this document from within Australia, you represent to MOODY'S that you are, or are accessing the document as a representative of, a "wholesale client" and

that neither you nor the entity you represent will directly or indirectly disseminate this document or its contents to "retail clients" within the meaning of section 761G of the Corporations Act 2001. MOODY'S credit rating is an opinion as to the creditwor-thiness of a debt obligation of the issuer, not on the equity securities of the issuer or any form of security that is available to retail investors. It would be reckless and inappropriate for retail investors to use MOODY'S credit ratings or publications when making an investment decision. If in doubt you should contact your fi nancial or other professional adviser.

Additional terms for Japan only: Moody's Japan K.K. ("MJKK") is a wholly-owned credit rating agency subsidiary of Moody's Group Japan G.K., which is wholly-owned by Moody's Overseas Holdings Inc., a wholly-owned subsidiary of MCO. Moody's SF Japan K.K. ("MSFJ") is a wholly-owned credit rating agency subsidiary of MJKK. MSFJ is not a Nationally Recognized Statistical Rating Organization ("NRSRO"). Therefore, credit ratings assigned by MSFJ are Non-NRSRO Credit Ratings. Non-NRSRO Credit Ratings are assigned by an entity that is not a NRSRO and, consequently, the rated obligation will not qualify for certain types of treatment under U.S. laws. MJKK and MSFJ are credit rating agencies registered with the Japan Financial Services Agency and their registration numbers are FSA Commissioner (Ratings) No. 2 and 3 respectively.

MJKK or MSFJ (as applicable) hereby disclose that most issuers of debt securities (including corporate and municipal bonds, debentures, notes and commercial paper) and preferred stock rated by MJKK or MSFJ (as applicable) have, prior to assignment of any rating, agreed to pay to MJKK or MSFJ (as applicable) for appraisal and rating services rendered by it fees ranging from JPY200,000 to approximately JPY350,000,000.

MJKK and MSFJ also maintain policies and procedures to address Japanese regulatory requirements.