

BIS-SpecAI: Benchmark Evaluation & Accuracy Report

Empirical Validation across 22 Ground-Truth Procurement Queries: Recall@1, Recall@5, MRR, and Obsolescence Detection

1. Executive Evaluation Summary

To empirically validate recommendation precision and recall, the BIS-SpecAI engine was evaluated against an automated test suite comprising **22 ground-truth procurement queries**. The test suite spans five essential domains: Electrical, Civil, Mechanical, Safety/PPE, and Renewable Energy.

Evaluation Metric	Benchmark Score	Benchmark Target	Evaluation Significance
Recall@1 (Top Rank Precision)	95.45% (21/22)	> 85%	Probability that the top-ranked recommendation is the exact primary standard
Recall@5 (Candidate Coverage)	100.00% (22/22)	> 90%	Probability that the applicable standard is in the top-5 candidate pool
Mean Reciprocal Rank (MRR)	0.9773	> 0.8500	Measures ranking position quality (1.0 = perfect top-1 ranking across all queries)
Outdated Version Detection	100.00% (2/2)	100%	Accuracy in detecting superseded references (IS 325, IS 8112) and mapping replacements
Normative Reference Discovery	100.00% (22/22)	> 95%	Consistency in discovering mandatory testing and safety cross-references
Average Pipeline Latency	1.9 ms / query	< 100 ms	Fast end-to-end execution time enabling real-time portal integration

2. Sector Breakdown & Ground-Truth Test Cases

Sector	Sample Procurement Specification	Expected Standard	Retrieved Rank & Score
Electrical	15 kW three phase induction motor, 415 V, 50 Hz with efficiency and IP protection	IS 12615:2018	Rank #1 (82.4%)
Electrical	Outdoor oil immersed distribution transformer 500 kVA 11 kV / 433 V BEE Star	IS 1180 (Part 1):2014	Rank #1 (85.4%)
Civil	Plain and reinforced concrete code of practice for design of M30 grade RCC beam	IS 456:2000	Rank #1 (83.9%)
Civil	Fly ash based Portland Pozzolana Cement PPC for marine jetty construction	IS 1489 (Part 1):2015	Rank #1 (81.7%)
Safety/PPE	Industrial safety helmet with high impact resistance and 1000V electrical protection	IS 2925:2024	Rank #1 (81.0%)

Safety/PPE	Safety footwear with 200 Joules steel toe cap and oil resistant sole for factory personnel	IS 15298 (Part 2):2016	Rank #1 (77.1%)
Mechanical	High density polyethylene HDPE pipes PE 100 PN 10 for drinking water distribution	IS 4984:2016	Rank #1 (79.6%)
Solar	Crystalline silicon solar photovoltaic modules design qualification utility solar farm	IS 14286:2010 / IEC 61215	Rank #1 (77.2%)
Audit Test	Procurement of electric motor as per legacy standard IS 325:1996 for water pump	IS 12615:2018 (Replacement)	Rank #1 (77.3%) + Alert

EVALUATION CONCLUSION

Achieving 100% Recall@5 and an MRR of 0.9773 confirms that the hybrid BM25 + dense semantic retrieval pipeline provides an exceptionally accurate and dependable engine for Indian Standards recommendation in public procurement.