Title of the Thesis

A Thesis Presented to The Academic Faculty

by

Po-Yu Yen

In Partial Fulfillment of the Requirements for the Degree Master of Science in the Graduate Institute of Communication Engineering

National Taiwan University

July 2012

ABSTRACT

Low Earth Orbit (LEO) satellite network has been a promising technology due to the wide spread coverage area and high data throughput. However, with the high speed of satellites, frequent handover is unavoidable for user equipments (UEs) on the ground, causing significant interruption time and signaling overhead. Thus, we introduce a quasi-earth-fixed satellite beam scheme to solve the continually handover from the UEs at the cell edge. In this scheme, we allocate the satellite beams to the ground cells in order to maximize overall throughput. After that, we also propose a UE cell selection algorithm, which base on both position information and UE measurement.

TABLE OF CONTENTS

ABSTRACT i	ii
LIST OF TABLES	V
LIST OF FIGURES	V
CHAPTER 1 INTRODUCTION	1
CHAPTER 2 BACKGROUND AND RELATED WORK	2
2.1 LEO satellite network	2
2.1.1 Quasi-Earth-Fixed cell	2
2.2 Related Work	2
CHAPTER 3 SYSTEM MODEL	3
3.1 System Model	3
3.1.1 Free Space Path Loss	3
3.1.2 Channel Model	4
3.1.3 Antenna Radiation Pattern	4
3.2 Problem Formulation	4
CHAPTER 4 PROPOSED ALGORITHM	5
CHAPTER 5 PERFORMANCE EVALUATION	6
5.1 Simulation Setup	6
5.2 Simulation Results	6
CHAPTER 6 CONCLUSION AND FUTURE WORK	7
REFERENCES	R

LIST OF TABLES

LIST OF FIGURES

1 Illustration of satellite beams and cells		3
---	--	---

INTRODUCTION

Non terrestrial network (NTN) has become a promising technique in 6G network. It provides network connectivity to area that traditional network platform cannot reach. For instance, forests, oceans, and deserts. Various platforms are used to provide network services in NTN, such as GEO, MEO, LEO satellites, UAVs, and drones. Among these platforms, LEO is the most actively discussed since it provides global coverage, low latency, and high throughput.

However, to acheive LEO satellite network service, there are some key challanges that need to be resolved. One of the challanges is the unavoidable frequent handover. The high speed of LEO satellite forces user equipments (UEs) on the ground to switch the serving satellites frequently [1]. 3GPP has discussed some solutions to deal with this issue. By using quasi-earth-fixed cell and satellite switch with re-synchronization, the frequent handovers are avoided and the signalling overhead is reduced [2]. Also, with the help of the ephemeris data of satellies and the position information of UEs, the matching between satellites and UEs has been largely improved [3]. Nontheless, it still has some problems during the random access procedure.

BACKGROUND AND RELATED WORK

The goal of this chapter is for laying the technical background (such as distributed source coding) for understanding the contribution of your thesis; non-technical background (such as the background of M2M communications) can go to Chapter 1.

Related work should be be classified into proper sub-sections depending on the topics related to your thesis research.

- 2.1 LEO satellite network
- 2.1.1 Quasi-Earth-Fixed cell
- 2.2 Related Work

SYSTEM MODEL

3.1 System Model

In this paper, we consider a LEO satellite communication system shown in Figure 1. There are N satellites denoted as $\mathcal{N} = \{n \mid n = 1, 2, ..., N\}$, and each satellite has M beams denoted as $\mathcal{M} = \{m \mid m = 1, 2, ..., M\}$. The coverage area covers K cells on the ground denoted as $\mathcal{K} = \{k \mid k = 1, 2, ..., K\}$. There are U user equipments (UEs) in the coverage area denoted as $\mathcal{U} = \{u \mid u = 1, 2, ..., U\}$. A hexagonal grid of cells is considered. A quasi-earth-fixed cell scheme is considered.




Figure 1: Illustration of satellite beams and cells

3.1.1 Free Space Path Loss

In the LEO satellite system, the free space path loss model can be express as follows [4]:

$$L_{n,u} = \left(\frac{\lambda}{4\pi d_{n,u}}\right)^2 \tag{3.1}$$

where λ is the wavelength, and d is the distance between the nth satellite and the uth user.

3.1.2 Channel Model

The shadowed-Rician fading channel model is considered [5]. Let $h_{n,k}$ denote the channel gain between the *n*th satellite and the *k*th cell. The cumulative distribution function (CDF) of the channel gain:

$$F_{h_{n,k}}(x) = K \sum_{n=0}^{\infty} \frac{(m)_n \, \delta^n \, (2b)^{1+n}}{(n!)^2} \, \gamma \left(1 + n, \frac{x}{2b}\right) \tag{3.2}$$

where $K = (2bm/(2bm+\Omega))^m/2b$, $\delta = \Omega/(2bm+\Omega)/2b$. Ω is the average power of LOS component, and 2b is the average power of the multi-path component except the LOS component. m is the Nakagami parameter.

3.1.3 Antenna Radiation Pattern

We introduce the antenna radiation pattern in [6]:

$$G(\theta) = G_{max} \left[\frac{J_1(\mu(\theta))}{2\mu(\theta)} + 36 \frac{J_3(\mu(\theta))}{\mu(\theta)^3} \right]^2, \tag{3.3}$$

where θ represents the angle between the user and the beam center with respect to the satellite, G_{max} is the maximum antenna gain, $\mu(\theta) = 2.07123 \cdot \sin(\theta) / \sin(\theta_{3dB})$, where θ_{3dB} is the 3 dB half-power beamwidth angle of the antenna, and $J_1(\cdot)$ and $J_3(\cdot)$ represent the Bessel functions of the first kind of orders 1 and 3.

Thus, The received power from the beam m of satellite n to the user u is:

$$\hat{P}_{n,m,u} = P_{n,m} \cdot L_{n,u} \cdot G(\hat{\theta}_{n,u}) \cdot r_{n,u} \tag{3.4}$$

3.2 Problem Formulation

Followed by 3GPP protocol [3], the supported SSB periodicity values are {20, 40, 80, 160} miliseconds. Here we define the SSB periodicity of each cell:

$$T_k^{SSB} \in \{20, 40, 80, 160\}, \forall k$$
 (3.5)

We define the time duration of each slot as 160ms.

PROPOSED ALGORITHM

PERFORMANCE EVALUATION

All figures should be of the same width whenever possible for consistency.

5.1 Simulation Setup

We use BONMON \cite{N} to solve the optimization problem. The simulation setup follows that in \cite{N} .

5.2 Simulation Results

CONCLUSION AND FUTURE WORK

REFERENCES

- [1] "Solutions for nr to support non-terrestrial networks (ntn)," 3rd Generation Partnership Project (3GPP), Technical Report TR 38.821, 2023, release 16. Online Available at: https://www.3gpp.org/dynareport/38821.htm
- [2] "Nr; nr and ng-ran overall description; stage-2," 3rd Generation Partnership Project (3GPP), Technical Specification TS 38.300, 2024, release 18. Online Available at: https://www.3gpp.org/dynareport/38300.htm
- [3] 3GPP, "Radio Resource Control (RRC) protocol specification," 3rd Generation Partnership Project (3GPP), Technical Report TR 38.331, March 2024, version 18.1.0. Online Available at: https://www.3gpp.org/ftp/Specs/archive/38_series/38.331/
- [4] J. Wang, C. Jiang, L. Kuang, and R. Han, "Satellite multi-beam collaborative scheduling in satellite aviation communications," *IEEE Transactions on Wireless Communications*, vol. 23, no. 3, pp. 2097–2111, 2024.
- [5] D.-H. Jung, J.-G. Ryu, W.-J. Byun, and J. Choi, "Performance analysis of satellite communication system under the shadowed-rician fading: A stochastic geometry approach," *IEEE Transactions on Communications*, vol. 70, no. 4, pp. 2707–2721, 2022.
- [6] S.-H. Chen, L.-H. Shen, K.-T. Feng, L.-L. Yang, and J.-M. Wu, "Energy-efficient joint handover and beam switching scheme for multi-leo networks," in 2024 IEEE 99th Vehicular Technology Conference (VTC2024-Spring), 2024, pp. 1–7.