HTML Attribute Reference

The table below lists all HTML attributes and what elements they can be used within:

	Attribute	Belongs to	**Description**
1.	accept	<input>	Specifies the types of files that the server accepts (only for type="file")
2.	accept-charset	<form>	Specifies the character encodings that are to be used for the form submission
3.	accesskey	Global Attributes	Specifies a shortcut key to activate/focus an element
4.	action	<form>	Specifies where to send the form-data when a form is submitted
5.	align	Not supported in HTML 5.	Specifies the alignment according to surrounding elements. Use CSS instead
6.	alt	<area>, <img>, <input>	Specifies an alternate text when the original element fails to display

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

7.	async	<script>	Specifies that the script is executed asynchronously (only for external scripts)
8.	autocomplete	<form>, <input>	Specifies whether the <form> or the <input> element should have autocomplete enabled
9.	autofocus	<button>, <input>, <select>, <textarea>	Specifies that the element should automatically get focus when the page loads
10.	autoplay	<audio>, <video>	Specifies that the audio/video will start playing as soon as it is ready
11.	bgcolor	Not supported in HTML 5.	Specifies the background color of an element. Use CSS instead
12.	border	Not supported in HTML 5.	Specifies the width of the border of an element. Use CSS instead
13.	charset	<meta>, <script>	Specifies the character encoding
14.	checked	<input>	Specifies that an <input> element should be pre-selected when the page loads (for

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

			type="checkbox" or type="radio")
15.	cite	<blockquote>, <del>, <ins>, <q>	Specifies a URL which explains the quote/deleted/inserted text
16.	class	Global Attributes	Specifies one or more classnames for an element (refers to a class in a style sheet)
17.	color	Not supported in HTML 5.	Specifies the text color of an element. Use CSS instead
18.	cols	<textarea>	Specifies the visible width of a text area
19.	colspan	<td>, <th>	Specifies the number of columns a table cell should span
20.	content	<meta>	Gives the value associated with the http-equiv or name attribute
21.	contenteditable	Global Attributes	Specifies whether the content of an element is editable or not
22.	controls	<audio>, <video>	Specifies that audio/video controls should be displayed

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

			(such as a play/pause button etc)
23.	coords	<area>	Specifies the coordinates of the area
24.	data	<object>	Specifies the URL of the resource to be used by the object
25.	data-*	Global Attributes	Used to store custom data private to the page or application
26.	datetime	<del>, <ins>, <time>	Specifies the date and time
27.	default	<track>	Specifies that the track is to be enabled if the user's preferences do not indicate that another track would be more appropriate
28.	defer	<script>	Specifies that the script is executed when the page has finished parsing (only for external scripts)
29.	dir	Global Attributes	Specifies the text direction for the content in an element

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

30.	dirname	<input>, <textarea>	Specifies that the text direction will be submitted
31.	disabled	<button>, <fieldset>, <input>,<optgroup>, <option>, <select>, <textarea>	Specifies that the specified element/group of elements should be disabled
32.	download	<a>, <area>	Specifies that the target will be downloaded when a user clicks on the hyperlink
33.	draggable	Global Attributes	Specifies whether an element is draggable or not
34.	enctype	<form>	Specifies how the form-data should be encoded when submitting it to the server (only for method="post")
35.	enterkeyhint	Global Attributes	Specifies the text of the enter-key on a virtual keybord
36.	for	<label>, <output>	Specifies which form element(s) a label/calculation is bound to
37.	form	<button>, <fieldset>, <input>,<label>, <meter>, <object>,	Specifies the name of the form the element belongs to

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

		<output>, <select>, <textarea>	
38.	formaction	<button>, <input>	Specifies where to send the form-data when a form is submitted. Only for type="submit"
39.	headers	<td>, <th>	Specifies one or more headers cells a cell is related to
40.	height	<canvas>, <embed>, <iframe>,<img>,<input> ,<object>, <video>	Specifies the height of the element
41.	hidden	Global Attributes	Specifies that an element is not yet, or is no longer, relevant
42.	high	<meter>	Specifies the range that is considered to be a high value
43.	href	<a>, <area>, <base>, <link>	Specifies the URL of the page the link goes to
44.	hreflang	<a>, <area>, <link>	Specifies the language of the linked document

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

45.	http-equiv	<meta>	Provides an HTTP header for the information/value of the content attribute
46.	id	Global Attributes	Specifies a unique id for an element
47.	inert	Global Attributes	Specifies that the browser should ignore this section
48.	inputmode	Global Attributes	Specifies the mode of a virtual keyboard
49.	ismap	<img>	Specifies an image as a server-side image map
50.	kind	<track>	Specifies the kind of text track
51.	label	<track>, <option>, <optgroup>	Specifies the title of the text track
52.	lang	Global Attributes	Specifies the language of the element's content

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

53.	list	<input>	Refers to a <datalist> element that contains pre-defined options for an <input> element
54.	loop	<audio>, <video>	Specifies that the audio/video will start over again, every time it is finished
55.	low	<meter>	Specifies the range that is considered to be a low value
56.	max	<input>, <meter>, <progress>	Specifies the maximum value
57.	maxlength	<input>, <textarea>	Specifies the maximum number of characters allowed in an element
58.	media	<a>, <area>, <link>, <source>, <style>	Specifies what media/device the linked document is optimized for
59.	method	<form>	Specifies the HTTP method to use when sending form-data
60.	min	<input>, <meter>	Specifies a minimum value

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

61.	multiple	<input>, <select>	Specifies that a user can enter more than one value
62.	muted	<video>, <audio>	Specifies that the audio output of the video should be muted
63.	name	<button>,<fieldset>, <form>,<iframe>, <input>,<map>,<meta>, <object>,<output>, <param>, <select>, <textarea>	Specifies the name of the element
64.	novalidate	<form>	Specifies that the form should not be validated when submitted
65.	onabort	<audio>, <embed>, <img>, <object>, <video>	Script to be run on abort
66.	onafterprint	<body>	Script to be run after the document is printed
67.	onbeforeprint	<body>	Script to be run before the document is printed

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

68.	onbeforeunload	<body>	Script to be run when the document is about to be unloaded
69.	onblur	All visible elements.	Script to be run when the element loses focus
70.	oncanplay	<audio>, <embed>, <object>, <video>	Script to be run when a file is ready to start playing (when it has buffered enough to begin)
71.	oncanplaythrough	<audio>, <video>	Script to be run when a file can be played all the way to the end without pausing for buffering
72.	onchange	All visible elements.	Script to be run when the value of the element is changed
73.	onclick	All visible elements.	Script to be run when the element is being clicked
74.	oncontextmenu	All visible elements.	Script to be run when a context menu is triggered
75.	oncopy	All visible elements.	Script to be run when the content of the element is being copied

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

76.	oncuechange	<track>	Script to be run when the cue changes in a <track> element
77.	oncut	All visible elements.	Script to be run when the content of the element is being cut
78.	ondblclick	All visible elements.	Script to be run when the element is being double-clicked
79.	ondrag	All visible elements.	Script to be run when the element is being dragged
80.	ondragend	All visible elements.	Script to be run at the end of a drag operation
81.	ondragenter	All visible elements.	Script to be run when an element has been dragged to a valid drop target
82.	ondragleave	All visible elements.	Script to be run when an element leaves a valid drop target
83.	ondragover	All visible elements.	Script to be run when an element is being dragged over a valid drop target

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

84.	ondragstart	All visible elements.	Script to be run at the start of a drag operation
85.	ondrop	All visible elements.	Script to be run when dragged element is being dropped
86.	ondurationchange	<audio>, <video>	Script to be run when the length of the media changes
87.	onemptied	<audio>, <video>	Script to be run when something bad happens and the file is suddenly unavailable (like unexpectedly disconnects)
88.	onended	<audio>, <video>	Script to be run when the media has reach the end (a useful event for messages like "thanks for listening")
89.	onerror	<audio>, <body>, <embed>, <img>, <object>, <script>, <style>, <video>	Script to be run when an error occurs
90.	onfocus	All visible elements.	Script to be run when the element gets focus

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

91.	onhashchange	<body>	Script to be run when there has been changes to the anchor part of the a URL
92.	oninput	All visible elements.	Script to be run when the element gets user input
93.	oninvalid	All visible elements.	Script to be run when the element is invalid
94.	onkeydown	All visible elements.	Script to be run when a user is pressing a key
95.	onkeypress	All visible elements.	Script to be run when a user presses a key
96.	onkeyup	All visible elements.	Script to be run when a user releases a key
97.	onload	<body>,<iframe>,<img> ,<input>,<link>,<script>, <style>	Script to be run when the element is finished loading
98.	onloadeddata	<audio>, <video>	Script to be run when media data is loaded

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

99.	onloadedmetadata	<audio>, <video>	Script to be run when meta data (like dimensions and duration) are loaded
100.	onloadstart	<audio>, <video>	Script to be run just as the file begins to load before anything is actually loaded
101.	onmousedown	All visible elements.	Script to be run when a mouse button is pressed down on an element
102.	onmousemove	All visible elements.	Script to be run as long as the mouse pointer is moving over an element
103.	onmouseout	All visible elements.	Script to be run when a mouse pointer moves out of an element
104.	onmouseover	All visible elements.	Script to be run when a mouse pointer moves over an element
105.	onmouseup	All visible elements.	Script to be run when a mouse button is released over an element

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

106.	onmousewheel	All visible elements.	Script to be run when a mouse wheel is being scrolled over an element
107.	onoffline	<body>	Script to be run when the browser starts to work offline
108.	ononline	<body>	Script to be run when the browser starts to work online
109.	onpagehide	<body>	Script to be run when a user navigates away from a page
110.	onpageshow	<body>	Script to be run when a user navigates to a page
111.	onpaste	All visible elements.	Script to be run when the user pastes some content in an element
112.	onpause	<audio>, <video>	Script to be run when the media is paused either by the user or programmatically
113.	onplay	<audio>, <video>	Script to be run when the media has started playing

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

114.	onplaying	<audio>, <video>	Script to be run when the media has started playing
115.	onpopstate	<body>	Script to be run when the window's history changes.
116.	onprogress	<audio>, <video>	Script to be run when the browser is in the process of getting the media data
117.	onratechange	<audio>, <video>	Script to be run each time the playback rate changes (like when a user switches to a slow motion or fast forward mode).
118.	onreset	<form>	Script to be run when a reset button in a form is clicked.
119.	onresize	<body>	Script to be run when the browser window is being resized.
120.	onscroll	All visible elements.	Script to be run when an element's scrollbar is being scrolled
121.	onsearch	<input>	Script to be run when the user writes something in a search field (for <input type="search">)

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

122.	onseeked	<audio>, <video>	Script to be run when the seeking attribute is set to false indicating that seeking has ended
123.	onseeking	<audio>, <video>	Script to be run when the seeking attribute is set to true indicating that seeking is active
124.	onselect	All visible elements.	Script to be run when the element gets selected
125.	onstalled	<audio>, <video>	Script to be run when the browser is unable to fetch the media data for whatever reason
126.	onstorage	<body>	Script to be run when a Web Storage area is updated
127.	onsubmit	<form>	Script to be run when a form is submitted
128.	onsuspend	<audio>, <video>	Script to be run when fetching the media data is stopped before it is completely loaded for whatever reason
129.	ontimeupdate	<audio>, <video>	Script to be run when the playing position has changed (like when

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

			the user fast forwards to a different point in the media)
130.	ontoggle	<details>	Script to be run when the user opens or closes the <details> element
131.	onunload	<body>	Script to be run when a page has unloaded (or the browser window has been closed)
132.	onvolumechange	<audio>, <video>	Script to be run each time the volume of a video/audio has been changed
133.	onwaiting	<audio>, <video>	Script to be run when the media has paused but is expected to resume (like when the media pauses to buffer more data)
134.	onwheel	All visible elements.	Script to be run when the mouse wheel rolls up or down over an element
135.	open	<details>	Specifies that the details should be visible (open) to the user
136.	optimum	<meter>	Specifies what value is the optimal value for the gauge

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

137.	pattern	<input>	Specifies a regular expression that an <input> element's value is checked against
138.	placeholder	<input>, <textarea>	Specifies a short hint that describes the expected value of the element
139.	popover	Global Attributes	Specifies a popover element
140.	popovertarget	<button>, <input>	Specifies which popover element to invokde
141.	popovertargetaction	<button>, <input>	Specifies what happens to the popover element when the button is clicked
142.	poster	<video>	Specifies an image to be shown while the video is downloading, or until the user hits the play button
143.	preload	<audio>, <video>	Specifies if and how the author thinks the audio/video should be loaded when the page loads
144.	readonly	<input>, <textarea>	Specifies that the element is read-only

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

145.	rel	<a>, <area>, <form>, <link>	Specifies the relationship between the current document and the linked document
146.	required	<input>, <select>, <textarea>	Specifies that the element must be filled out before submitting the form
147.	reversed		Specifies that the list order should be descending (9,8,7...)
148.	rows	<textarea>	Specifies the visible number of lines in a text area
149.	rowspan	<td>, <th>	Specifies the number of rows a table cell should span
150.	sandbox	<iframe>	Enables an extra set of restrictions for the content in an <iframe>
151.	scope	<th>	Specifies whether a header cell is a header for a column, row, or group of columns or rows
152.	selected	<option>	Specifies that an option should be pre-selected when the page loads

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

153.	shape	<area>	Specifies the shape of the area
154.	size	<input>, <select>	Specifies the width, in characters (for <input>) or specifies the number of visible options (for <select>)
155.	sizes	<img>, <link>, <source>	Specifies the size of the linked resource
156.	span	<col>, <colgroup>	Specifies the number of columns to span
157.	spellcheck	Global Attributes	Specifies whether the element is to have its spelling and grammar checked or not
158.	src	<audio>, <embed>, <iframe>,<img>,<input> ,<script>, <source>, <track>, <video>	Specifies the URL of the media file
159.	srcdoc	<iframe>	Specifies the HTML content of the page to show in the <iframe>

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

160.	srclang	<track>	Specifies the language of the track text data (required if kind="subtitles")
161.	srcset	<img>, <source>	Specifies the URL of the image to use in different situations
162.	start		Specifies the start value of an ordered list
163.	step	<input>	Specifies the legal number intervals for an input field
164.	style	Global Attributes	Specifies an inline CSS style for an element
165.	tabindex	Global Attributes	Specifies the tabbing order of an element
166.	target	<a>, <area>, <base>, <form>	Specifies the target for where to open the linked document or where to submit the form
167.	title	Global Attributes	Specifies extra information about an element

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50

168.	translate	Global Attributes	Specifies whether the content of an element should be translated or not
169.	type	<a>,<button>, <embed> ,<input>,<link>,<menu> ,<object>, <script>, <source>, <style>	Specifies the type of element
170.	usemap	<img>, <object>	Specifies an image as a client-side image map
171.	value	<button>, <input>, , <option>, <meter>, <progress>, <param>	Specifies the value of the element
172.	width	<canvas>, <embed>, <iframe>,<img>,<input> ,<object>, <video>	Specifies the width of the element
173.	wrap	<textarea>	Specifies how the text in a text area is to be wrapped when submitted in a form

Email id : alokmauryaofficial9936@gmail.com
Instagram : @AlokMaurya_up50