

Something about Microtransit Simulation

Hayden Atchley^a, Gregory Macfarlane^a

^a*Civil and Construction Engineering Department, 430 Engineering Building, Provo, Utah 84602*

Abstract

This paper has to do with simulating microtransit and determining whether it makes sense to deploy microtransit in other areas in the Wasatch Front.

Keywords: Microtransit Passive Data Location Choice

1. Question

In November of 2019, the Utah Transit Authority (UTA) began a partnership with Via Transportation, a private mobility company (Robertson et al., 2020). Under this partnership, UTA has supplemented its fixed-route services with on-demand shuttles hailed through a mobile application. So-called “microtransit” offerings of this kind have the potential to efficiently extend UTA services into low-density areas and function as first- and last-mile services for the regular fixed-route rail and bus network. The current microtransit service is currently only operating in southern Salt Lake County (Utah Transit Authority, 2021). UTA is interested in examining if there are other areas where similar services can be effectively deployed. In September 2020, UTA released a report detailing a possible expansion of microtransit services to other areas in Utah following the UTA on Demand pilot program (Robertson et al., 2020). 19 zones were identified between Brigham City and Santaquin as areas that could potentially benefit from microtransit services. Ridership was estimated based on number of residents and number of workers employed within each zone, as well as a mode share score that VIA developed based on their internal demand model.

We seek however to provide UTA and the Utah Department of Transportation (UDOT) with a microsimulation model they can use as a template to examine future similar projects. We want to know how the results of such a model would compare to those of UTA’s September 2020 report. Though UTA’s own report made no definitive recommendations regarding expansion of microtransit services, it may be useful in calibrating our simulation. We also seek to use our results (possibly in conjunction with those of UTA’s report) to make recommendations to UTA and UDOT regarding expansion of microtransit services.

2. Methods

We used the Behavior, Energy, Autonomy, and Mobility (BEAM) model to run and calibrate our simulations. This model is being developed by Lawrence Berkeley National Laboratory and the UC Berkeley Institute for Transportation Studies, and is an extension to the MATSim (Multi-Agent Transportation Simulation) model. BEAM is an agent-based simulation that allows agents to dynamically adjust their plans, including mode choice, depending on the current state of the mobility simulation (The BEAM Team, 2017). The version of the BEAM code we used is available at *<insert commit ID or other reference to the code>*.

We identified *<some number of>* potential areas to expand ridehail services to, and created BEAM scenarios incorporating each of these areas. We also created a base scenario for the current system. We ran

Email addresses: satchley@byu.edu (Hayden Atchley), gregmacfarlane@byu.edu (Gregory Macfarlane)

each scenario with the same parameters, and for 15 iterations each.¹ BEAM outputs an `events` file, which we then used to perform our analysis.

We compared the different scenarios on several metrics, including weekday ridership, utilization (passengers/hour/vehicle), wait time, and travel time. We also compared the base scenario to the results of UTA’s September 2020 report (Robertson et al., 2020). The results of that report used many qualitative metrics, but some quantitative metrics of interest were average ridership, wait time, and utilization. These results of the report are presented in 1 below.

Table 1: UTA On Demand Report Findings

Month	Avg wkday ridership	Utilization	Avg wait time
DEC	224.00	1.33	9.00
JAN	334.00	2.00	11.00
FEB	392.00	2.31	12.00
MAR	316.00	1.88	11.00
APR	275.00	1.52	10.00
MAY	105.00	0.67	8.00
JUN	162.00	1.10	9.00
JUL	155.00	1.10	9.00
AUG	193.00	1.50	12.00
SEP	214.00	1.60	12.00
OCT	200.00	1.70	13.00
NOV	169.00	1.70	13.00
Average	228.25	1.53	10.75
Average Jan–Mar	347.33	2.06	11.33

3. Findings

The metrics we calculated for each of the scenarios are given in ??.

Scenario	Total Ridership	Ride Hail Trips	Percent of RH Trips	Average Wait Time (min)
South SL County only	1006	930	1.16	
South SLC with Airport	1395	1328	1.66	
South SLC/Airport/Sandy	2796	2473	3.08	
South SLC/Airport/West Jordan	2620	2353	2.93	

[1] "Utilization is calculated as passengers per hour per vehicle"

We also compared some of these metrics to the UDOT report. We used the average from January through March. These results are given in ??.

Scenario	Total Ridership	Average Wait Time (minutes)	Utilization ^a
South SL County only	1006.00	5.82	4.14
UDOT Report	347.33	11.33	2.06

^a Utilization is calculated as passengers per hour per vehicle

¹BEAM runs several iterations, and allows some percentage of agents to replan their activities and/or transportation modes between each iteration.

Acknowledgements

I would like to thank some people

References

Robertson, J., Callison, E., and Taylor, R. (2020). Utah Transit Authority Microtransit Planning Project. Technical report.
The BEAM Team (2017). BEAM Documentation.
Utah Transit Authority (2021). UTA On Demand.