One-dimensional turbulence (ODT): computationally efficient modeling and simulation of turbulent flows

Victoria B. Stephens, David O. Lignell*

Chemical Engineering Department, Brigham Young University, Provo, UT 84602, USA

Abstract

Write this last. About 100 words.

Keywords: turbulence, reacting flows, one-dimensional turbulence

Code Metadata

Nr.	Code metadata description	Please fill in this column
C1	Current code version	1.0
C2	Permanent link to code/repository used for this code version	*github.com/BYUignite/ODT*
C3	Code Ocean compute capsule	N/A
C4	Legal Code License	MIT
C5	Code versioning system used	Git
C6	Software code languages, tools, and services used	C++, Python 3.x, Yaml,
C7	Compilation requirements, operating environments & dependencies	CMake 3.12+, Cantera, Git, Doxygen (optional)
C8	If available Link to developer documentation/manual	N/A
C9	Support email for questions	davidlignellbyu.edu

Table 1: Code metadata (mandatory)

1. Motivation and significance

Turbulent flows characterize the vast majority of fluid flows in practical engineering applications, and simulations of turbulent flows provide re-

*Corresponding author.
Email address: davidlignell@byu.edu (David O. Lignell)

searchers with valuable insights into complex systems, particularly reacting turbulent flows such as combustion processes. Turbulence is a complex phemonenon that affects the full range of a flow's length and time scales. As a result, resolving the entire flow field by numerically solving the Navier-Stokes equations of fluid flow, as is done in direct numerical simulations (DNS), requires substantial computational resources. DNS is a powerful research tool, but its high computational cost makes it intractable for simulating most practical engineering flows. In order to achieve numerical solutions to practical flow problems, researchers can use alternative frameworks that model turbulence rather than resolving it directly.

Large-eddy simulations (LES) address the problem of wide-ranging length and time scales by combining direct resolution of grid-scale quantities, as in DNS, with subgrid modeling of smaller turbulence structures. The more complex the flow, the more modeling is required; for example, a jet flame simulation might require subgrid modeling for the combustion chemistry, radiative heat transfer, or soot chemistry in addition to turbulence structures, all of which form a tightly coupled system in which each model interacts heavily with the others. While subgrid modeling makes LES more computationally affordable than DNS, it can introduce empiricism into simulations, which can lead to inaccurate results. Additionally, unresolved quantities are often parameterized in state space with empirical relationships or assumed distributions that lack universal applicability. LES is a valuable simulation tool, but its approach to turbulence modeling can introduce unwanted empiricism and make errors difficult to isolate and quantify.

The one-dimensional turbulence model (ODT) functionally reverses the LES approach, modeling large-scale turbulent advection and directly resolving small-scale flow structures, simulating the full range of length and time scales in a single dimension. Because large-scale structures are much easier to study and model than small-scale structures, ODT mitigates or sidesteps many of the subgrid modeling issues that complicate LES. Previous studies show that ODT can attain accuracy comparable to DNS at a fraction of the computational cost [1, 2], making it an attractive tool for simulating turbulent flows. Because the ODT model is one-dimensional, it is limited to homogeneous or boundary-layer flows, such as jets, wakes, and mixing layers; these types of flows, however, are common in nature and central to turbulence research. ODT's computational efficiency and resolution of a full range of scales make it a valuable tool that complements experimental studies and other simulation tools like DNS and LES.

Early applications of ODT focused on homogenous turbulence, wakes, and mixing layers [3, 4, 5]. Later extension to variable-density flows and a spatial downstream coordinate system facilitated its growth and application to more

complex flows, including combustion in jet flames [6, 7, 8, 9, 10, 11, 12, 13], counterflow flames [14], wall fires [15], and sooting flames [1, 16, 17, 18, 19], as well as other particle flows [20, 21, 22, 23]. ODT has also served to complement LES through subgrid modeling studies [24, 25, 26] and has been applied to various other flow configurations such as double-diffusive interfaces [27], Rayleigh-Taylor mixing [28], and stratified turbulence [29]. Most recently, the ODT code was extended to include cylindrical and spherical coordinate systems [30, 31, 32].

During the recent implementation of the cylindrical and spherical model formulations, the ODT code was drastically overhauled and reorganized, resulting in its current configuration. The ODT code presented here is a pared down version of the development code, representing the fundamental aspects of the ODT model and its most reliable functions. The example cases in Section 3 are a representative sample of the ODT code's capabilities as it is presented here. Future releases will expand this code's functionality with additional features currently in development.

2. Software description

2.1. Model description

The ODT model is described in detail in the literature [3, 5, 33, 30, 34]; only a brief explanation will be given here. In ODT, turbulent advection is modeled with stochastic processes called eddy events, which punctuate the solution of unsteady, one-dimensional transport equations for mass, momentum, and enthalpy. The ODT code uses a Lagrangian finite-volume formulation for diffusive advancement in which mass stays constant within each grid cell while cell volumes increase or decrease according to cell dilation via an adaptive mesh refinement [34].

Transport equations for mass, momentum, and enthalpy in the temporal formulation of ODT take the following generic form, derived from the Reynolds Transport Theorem [35] for a given scalar quantity per unit mass β:

$$\frac{\mathrm{d}\beta}{\mathrm{d}t} = -\frac{j_{\beta,e}A_{x,e} - j_{\beta,w}A_{x,w}}{\rho V} + \frac{S_\beta}{\rho V}. \tag{1}$$

Here, j_β is the diffusion flux of scalar β across the cell face area A_x where the subscripts e and w refer to the "east" and "west" faces of the grid cell, respectively. S_β is the Lagrangian source term derived from the conservation law for β, ρ represents mass density, and V represents cell volume. In practice, we refer to the left hand term on the right side of Equation 1 as the "mixing term" and the right hand term on the right side of Equation 1 as the "source term". The generic transport equation differs slightly in the spatial

formulation of ODT, but its form is the same, so we omit it here for brevity. The system of ordinary differential equations (ODEs) that results is well behaved at all grid points and in all geometries in their finite-volume forms. For details on transport equation derivation and use in both the temporal and spatial formulations of ODT, see Lignell et al. [30].

Eddy events occur as a Poisson process in accordance with their eddy rates, where a given eddy event of size l and location x_0 has an eddy timescale t and an associated eddy rate $1/t$. Three user-defined ODT parameters control the eddy event process: the eddy rate parameter C scales the rate of occurrence of the eddies; the viscous penalty parameter Z suppresses small eddies; and the large eddy suppression parameter β constrains eddies such that they do not reach over the elapsed simulation time. Sampled eddies that do not fit the defined parameters are rejected and not applied to the domain.

Eddy events modify domain variables using triplet maps, as illustrated for a cylindrical domain in Figure 1. For a region of eddy size l, the domain is copied to create three map images; the three images are then placed back to back with the middle image inverted to maintain continuity, and the composite is reapplied to the domain. This process applies to all transported variables on the domain. Applied properly, the triplet map increases scalar gradients and decreases length scales consistent with the application of turbulent eddies in real flows, conserves all quantities and their statistical moments, and maintains continuity in property profiles. Subsequent eddies in the same region will result in a cascade of scales, and eddy rates depend on eddy size and the local kinetic energy such that they follow turbulent cascade scaling laws.

Eddy events occur concurrently with diffusive advancement via solution of the system of unsteady one-dimensional transport equations. In this way, the ODT code marches in time or space until it reaches its end point. Due to the stochastic nature of eddy events, each ODT simulation, or realization, is different, even when it is provided with the same input parameters. In order to obtain statistically stable data for a given set of parameters, we run many realizations with the same input parameters and time-average them. This is done via post-processing tools, which are provided in the ODT package.

2.2. Software Architecture

The ODT package consists primarily of an object-oriented C++ code responsible for running flow simulation cases and generating data. The package also contains auxiliary data processing and visualization tools, written mostly in Python. The post-processing tools are case-specific but will be addressed in Section 2.3.



Figure 1: Schematic diagram of a cylindrical triplet map, adapted from [30]. Before the triplet map, the domain contains three grid cells of equal volume, while after the triplet map has been applied, the domain contains nine cells. The nine final cells are labeled according to the cells from which they originated and shaded to indicate that three map images were combined to create the final composite.



Figure 2: Basic structure of the ODT code. For clarity and brevity, this diagram makes two major assumptions: first, that diffusion advancement in the `micromixer` uses an explicit solution method; and second, that the eddy event sampled by the `eddy` object passes all rejection tests before being applied to the domain.

Figure 2 illustrates the ODT code's most important objects and structural features. User inputs are provided to the executable in YAML [36] format via `input.yaml`; the location of the specific `input.yaml` file to be used is determined by the case name and case type specified in the run script. The `main` function defines storage for the main objects, but, once created, the `domain` object is responsible for object initialization as well as variable initialization and storage via a case-specific `domaincase` object.

Three primary objects handle the code's main functions: the `solver`, `micromixer`, and `eddy` objects. The `solver` coordinates the ODT solution process, marching along the simulation time and invoking diffusive advancement and eddy events when appropriate. The `micromixer` handles diffusive advancement by setting step sizes, interacting with the transported domain variables, and solving the system of ODEs defined by Equation 1 (or its equivalent in the spatial formulation). The `micromixer` includes three solution methods that can be specified in `input.yaml`, each appropriate for various case types: a first-order explicit Euler method (pictured in Figure 2); a first-order semi-implicit method that uses CVODE [37] to advance coupled ODEs in individual grid cells, integrated sequentially; and a second-order Strang splitting method [38] good for treating stiff chemistry. In reacting flow cases, chemical kinetics are handled by Cantera [39], which uses transported variable values—enthalpy and gas species composition, for instance—to specify local scalar values such as gas temperature or density, which can affect flow properties. The `micromixer` is also the code's primary point of interaction with the `mesher` object (not pictured in Figure 2), which manages the adaptive grid functions. Finally, the `eddy` object manages eddy event selection and implementation, which proceeds as described in Section 2.1.

2.3. Workflow

This section outlines the process a user would go through in order to successfully build the ODT code and run a simulation. For more details, please see the package documentation. ODT is a standalone, self-contained package, and users interact with its files primarily via the command line rather than a graphical interface.

Within the main download package, several directories organize the ODT package. The `source`, `build`, and `run` directories contain the ODT source code, compilation tools, and run scripts, respectively. The `input` directory contains subdirectories corresponding to several possible case types, each populated with an appropriate input files. The `data` directory, initially empty, holds the raw data files and runtime information generated by ODT, as well as post-processed data files generated from within the `post` directory.

Finally, the `doc` directory contains documentation optionally generated by Doxygen [40] during the build process.

2.3.1. Building ODT

The ODT build process is relatively automated through CMake. First, navigate to the `build` directory and edit the CMake configuration file. Note that the user must specify which chemical mechanism to compile with before building the code. In order to run simulations with different chemical mechanisms, the code must be recompiled, including the CMake configuration files, between simulations, whereas this is not required when other variables are changed. This is a known inconsistency that will be changed in future code releases. The CMake configuration file also specifies Cantera's location and must be changed to reflect the local installation location. Once the settings are correct, the user runs CMake to apply these changes.

YAML is required in order to process input files. If it has not yet been installed, it is built and installed at this point. For convenience, the ODT package includes the appropriate files and automates this process. YAML need only be installed once for a given instance of the ODT package. Rebuilding the ODT code with CMake does not affect the YAML installation.

Once CMake and YAML have been prepared, the user can build the ODT code with the appropriate `make` command. There is no associated `install` command that needs to be run. The most common errors that occur during the build process concern incorrect file paths or incomplete installation of precursor packages. See the build documentation for troubleshooting help.

Once the code is built, the user may optionally build a local copy of the documentation via Doxygen, which must be previously installed. This step is not required in order to run the ODT code. As an alternative, documentation can be accessed via `README` files within the code or at the code repository wiki.

2.3.2. Input files

User-modified input files are located within the `input` directory, which contains subdirectories that correspond to various case types that can be run with ODT. At minimum, a case's subdirectory contains an `input.yaml` file, but may contain other files or subfolders. ODT has the capability to restart a simulation from a specified time or state. To use this function, a raw data file at the required state must be copied to the input case directory and renamed `restart.dat`. For an example, please see the `jetFlame/flameD` case. Note that the user must also change the `Lrestart` parameter within the `input.yaml` file in order to use the restart feature. Input case directories may also contain subdirectories with supplemental information or input file

Section	Description
`params`*	General parameters, including simulation length, domain size, and ODT parameters (C, Z, β_{LES})
`radParams`	Radiation parameters; only relevant to reacting flow cases (i.e. jet flames)
`streamProps`	Stream properties; used when there are two or more separate streams (i.e. non-premixed jets)
`bcCond`*	Boundary conditions for velocity and temperature (where required)
`initParams`	Case-specific initialization parameters, usually flow geometry and stream velocities
`dumpTimes`*	List of simulation time steps at which to output data files

Table 2: Common sections present in `input.yaml` files. Sections marked with a * should be present in every `input.yaml` file regardless of case type. Sections usually appear in this order, but this is not required.

examples; only the `input.yaml` file located in the base case input directory is used in a simulation.

The `input` directory also contains the `gas_mechanisms` subdirectory, which contains chemical mechanism files in XML format that can be used in reacting flow cases. For cases in which a chemical mechanism is not required, the `not_used.xml` mechanism file is specified in the appropriate `input.yaml` file in place of other mechanisms. Note that the chemical mechanism chosen for the case and specified in the input file must match the mechanism specified in the Cmake configuration file during the ODT build process.

Input files contain simulation parameters in a human-readable format parsed by YAML. Not all of the parameters in an input file may be used in a given simulation. An overview of possible ODT parameters will be covered here, but does not represent all the possibilities or functions of ODT; please see the associated documentation for more information. Input files are divided into sections, several of which are common to all `input.yaml` files; these are summarized in Table 2. Details about individual parameters, including usage and typical values, are covered in the documentation.

Prior to running a simulation, the user must select and modify the appropriate `input.yaml` file to reflect the desired conditions. The default values already present in the input files represent general parameters that may be used to run a successful simulation of that case type.

2.3.3. Running ODT

DETAILS GO HERE

3. Example Cases

3.1. Pipe Flow

First, we present an incompressible pipe flow simulation using the temporal, cylindrical ODT formulation. Results for three different friction Reynolds numbers (Re_τ = 550, 1000, 2000) are compared to DNS results from El Khoury et al. [41] (Re_τ = 550, 1000) and Chin et al. [42] (Re_τ = 2000) for a pipe diameter of $D = 2.0$ m and flow density of 1.0 kg·m^{-3}. Friction velocity values of 1 m·s^{-1} ($Re_\tau = 550, 1000$) and 2 m·s^{-1} ($Re_\tau = 2000$) were assumed and used to calculate the mean pressure gradient driving the flow. Using initial conditions with uniform velocity profiles, simulations were run until a state of developed flow was achieved, at which point data were gathered until statistical convergence for the root mean square (RMS) velocity difference from the mean profiles occurred.

The simulations were performed with ODT parameters $C = 5$ and $Z = 350$ for the temporal ODT formulation. The values of C and Z were adjusted to give good agreement of the ODT results compared to the DNS. Schmidt et al. [25] showed that higher Z results in the buffer-layer being located further from the wall, and increasing C results in a lower slope of the mean streamwise velocity in the log-layer.

RESULTS AND PLOTS GO HERE

3.2. Non-reacting Jet

Here, we present ODT simulation results for a non-reacting round, turbulent jet compared to the experimental data of Hussein et al. [43]. The jet consists of air issuing into air through a 1 in (0.0254 m) diameter duct with a uniform exit velocity of 56.2 m·s^{-1} and a reported Reynolds number of 95,500. The ODT simulations use this diameter and velocity with a kinematic viscosity of $1.534 \cdot 10^{-5}$ m^{2}s^{-1}, resulting in a Reynolds number of 93,056. The initial velocity profile in the ODT simulations is a modified top-hat profile in which a hyperbolic tangent function of width $\delta = 0.1$D is used on either side of the jet to smooth the transition between the jet and the free stream. In the spatial formulation of ODT, the streamwise velocity must be positive everywhere on the line, so a small minimum velocity of $v_{min} = 0.1$m·s^{-1} is specified and added across the entire velocity profile.

ODT simulations were performed with parameters $C = 5.25$, $\beta_{LES} = 3.5$, and $Z = 400$. The value of Z is the same as the spatial simulations in [15], and the values of C and β_{LES} were adjusted to give good agreement with the experimental data. Note the close agreement of the C and Z parameters here to the optimal values used for the pipe flow simulations ($C = 5$ and $Z = 350$). This illustrates a level of robustness in the ODT parameters

and suggests that intermediate values could be successfully applied in both configurations.

1024 independent ODT realizations were performed and results were ensemble averaged. All quantities are normalized consistent with jet similarity scaling. Downstream locations are normalized by the jet diameter D, and radial locations are normalized by $(y - y_0)$, where y is the downstream location and $y_0 = 4D$ is the virtual origin used in [43].

RESULTS AND PLOTS GO HERE

3.3. Jet Flame

ODT is uniquely suited for reacting flow simulations. Here, we present illustrative ODT simulation results of a round, turbulent jet flame based on and compared to the experimental DLR-A flame of Meier et al. [44]. This canonical flame configuration has been used extensively to study and validate turbulent combustion models [45, 46, 47, 48, 49, 50].

The DLR-A fuel stream is mixture of 22.1% CH_4, 33.2% H_2, and 44.7% N_2 (by volume) that issues into dry air via a nozzle with an inner diameter of 8 mm at a mean exit velocity of 42.2 $\mathrm{m{\cdot}s^{-1}}$. The coflow air stream issues from a concentric nozzle 140 mm in diameter at a velocity of 0.3 $\mathrm{m{\cdot}s^{-1}}$. The reported jet Reynolds number is 15,200.

Previous ODT studies of turbulent jet flames have used the temporal planar formulation, but the spatial cylindrical formulation developed recently [30] more closely matches the experimental configuration. This simulation uses the experimentally reported velocity profiles and jet dimensions. In the non-reacting case, a small minimum velocity was added uniformly to the velocity profile; no such addition is required here because of the slow-moving coflow air stream that issues alongside the reacting jet. The fuel was diluted with N_2 in the experimental flame to minimize radiative heat losses, and radiation is ignored in the simulation. This flame has a low Reynolds number, and the combustion chemistry proceeds quickly. The ODT simulation transports the chemical species O_2, N_2, CH_4, H_2, H_2O, and CO_2. We assume that reactions proceed to the products of complete combustion and apply simple, fast reaction rates according to the following chemical equations:

$$CH_4 + 2O_2 \rightarrow CO_2 + 2H_2O, \tag{2}$$

$$H_2 + \frac{1}{2}O_2 \rightarrow H_2O. \tag{3}$$

These assumptions are not reasonable for the DLR-A flame, but they allow us to illustrate ODT in a reacting jet configuration with variable properties

and heat release, which is the primary purpose of this example case. More complex combustion reaction mechanisms are available within the source code and can be accessed by changing the appropriate input file parameter.

This simulation uses ODT parameters $C = 20$, $\beta_{LES} = 17$, and $Z = 400$. The values of C and β_{LES} were adjusted to give good agreement with the experimental data, and the value of Z is the same as it was for the non-reacting jet in Section 3.2. 1024 independent flow realizations were performed in parallel and the results ensemble averaged. Downstream distance y and radial position r are normalized by the jet diameter D.

RESULTS AND PLOTS GO HERE

4. Impact

Questions to answer in this section (from SoftwareX template)

1. How can new research questions be pursued with this software?
    - possibility of parametric studies (much harder with DNS/LES/RANS)
    - study of late-flame soot and radiation interactions, soot emissions as smoke
    - comparative radiation model studies?
2. How does the software improve pursuit of existing research questions?
    - late-flame behavior becomes easier to study
    - validation of LES subgrid models
    - soot stuff, especially late in the flame (because soot moves slowly compared to gas species and therefore short simulation times like in DNS aren't enough to study it effectively)
3. How does the software change the daily practice of its users?
    - cases take hours or days rather than weeks using supercomputer resources
    - test cases can be run on local computers (unlike something like DNS) and as background tasks without disrupting other tasks
    - ODT as a tool complements other approaches, can cover blind spots and be used in validation
4. How widespread is the software? Who uses it? (Within and outside of intended research area and/or group.)
    - BYU group
    - JCH at Sandia

- Chalmers group in Sweden (Marco Fistler, etc.)
- German university group (Heiko Schmidt, Juan Media, Marten Klein, etc.)
- TO DO: find other groups who have used or currently use ODT

5. How is the software used in commercial settings (if any)? Has it led to creation of spin-off companies?
   - No commercial use (I think).

5. Conclusion

Write this part next to last

6. Conflict of Interest

We wish to confirm that there are no known conflicts of interest associated with this publication and there has been no significant financial support for this work that could have influenced its outcome.

Acknowledgements

This work was supported in part by the National Science Foundation under Grant No. CBET-1403403.

References

[1] D. O. Lignell, G. C. Fredline, A. D. Lewis, Comparison of one-dimensional turbulence and direct numerical simulations of soot formation and transport in a nonpremixed ethylene jet flame 35 (2) (2015) 1199–1206. doi:10.1016/j.proci.2014.05.046.

[2] A. W. Abboud, C. Schulz, T. Saad, S. T. Smith, D. D. Harris, D. O. Lignell, A numerical comparison of precipitating turbulent flows between large-eddy simulation and one-dimensional turbulence 61 (10) (2015) 3185–3197. doi:10.1002/aic.14870.

[3] A. R. Kerstein, One-dimensional turbulence: model formulation and application to homogeneous turbulence, shear flows, and buoyant stratified flows 392 (1999) 277–334. doi:10.1017/S0022112099005376.

[4] A. R. Kerstein, T. D. Dreeben, Prediction of turbulent free shear flow statistics using a simple stochastic model 12 (2) (2000) 418–424. doi:10.1063/1.870319.

[5] A. R. Kerstein, W. T. Ashurst, S. Wunsch, V. Nilsen, One-dimensional turbulence: vector formulation and application to free shear flows 447 (2001) 85–109. doi:10.1017/S0022112001005778.

[6] T. Echekki, A. R. Kerstein, T. D. Dreeben, J.-Y. Chen, 'one-dimensional turbulence' simulation of turbulent jet diffusion flames: model formulation and illustrative applications 125 (3) (2001) 1083–1105. doi:10.1016/S0010-2180(01)00228-0.

[7] J. C. Hewson, A. R. Kerstein, Stochastic simulation of transport and chemical kinetics in turbulent $co/h_2/n_2$ flames 5 (4) (2001) 669–697. doi:10.1088/1364-7830/5/4/309.

[8] J. C. Hewson, A. R. Kerstein, Local extinction and reignition in nonpremixed turbulent $co/h_2/n_2$ jet flames 174 (5-6) (2002) 35–66. doi:10.1080/713713031.

[9] D. O. Lignell, D. S. Rappleye, One-dimensional-turbulence simulation of flame extinction and reignition in planar ethylene jet flames 159 (9) (2012) 2930–2943. doi:10.1016/j.combustflame.2012.03.018.

[10] N. Punati, J. C. Sutherland, A. R. Kerstein, E. R. Hawkes, J. H. Chen, An evaluation of the one-dimensional turbulence model: Comparison with direct numerical simulations of co/h_2 jets with extinction and reignition 33 (1) (2011) 1515–1522. doi:10.1016/j.proci.2010.06.127.

[11] A. Abdelsamie, D. O. Lignell, D. Thévenin, Comparison between odt and dns for ignition occurrence in turbulent premixed jet combustion: safety-relevant applications 231 (10) (2017) 1709–1735. doi:10.1515/zpch-2016-0902.

[12] D. O. Lignell, V. B. Lansinger, A. R. Kerstein, A cylindrical formulation of the one-dimensional turbulence (odt) model for turbulent jet flames, in: AIChE Annual Meeting 2017, American Institute of Chemical Engineers, 2017.

[13] B. Goshayeshi, J. C. Sutherland, Prediction of oxy-coal flame stand-off using high-fidelity thermochemical models and the one-dimensional turbulence model 35 (3) (2015) 2829–2837. doi:10.1016/j.proci.2014.07.003.

[14] Z. Jozefik, A. R. Kerstein, H. Schmidt, S. Lyra, H. Kolla, J. H. Chen, One-dimensional turbulence modeling of a turbulent counterflow flame with comparison to dns 162 (8) (2015) 2999–3015. doi:10.1016/j.combustflame.2015.05.010.

[15] E. I. Monson, D. O. Lignell, M. A. Finney, C. Werner, Z. Jozefik, A. R. Kerstein, R. S. Hintze, Simulation of ethylene wall fires using the spatially-evolving one-dimensional turbulence model 52 (1) (2016) 167–196. doi:10.1007/s10694-014-0441-2.

[16] J. C. Hewson, A. J. Ricks, S. R. Tieszen, A. R. Kerstein, R. O. Fox, Conditional-moment closure with differential diffusion for soot evolution in fire, in: Center for Turbulence Research, Proceedings of the Summer Program 2006, Stanford University, 2006.

[17] J. C. Hewson, A. J. Ricks, S. R. Tieszen, A. R. Kerstein, R. O. Fox, On the transport of soot relative to a flame: modeling differential diffusion for soot evolution in fire, in: H. Bockhorn, A. D'Anna, A. F. Sarofim, H. Wang (Eds.), Combustion Generated Fine Carbonaceous Particles, KIT Scientific Publishing, 2009, pp. 571–588.

[18] D. O. Lignell, J. C. Hewson, One-dimensional turbulence simulation: overview and application to soot formation in nonpremixed flames, in: SIAM Conference on Computational Science and Engineering, 2015.

[19] A. J. Ricks, J. C. Hewson, A. R. Kerstein, J. P. Gore, S. R. Tieszen, W. T. Ashurst, A spatially developing one-dimensional turbulence (odt) study of soot and enthalpy evolution in meter-scale buoyant turbulent flames 182 (1) (2010) 60–101. doi:10.1080/00102200903297003.

[20] G. Sun, J. C. Hewson, D. O. Lignell, Evaluation of stochastic particle dispersion modeling in turbulent round jets 89 (2017) 108–122. doi:10.1016/j.ijmultiphaseflow.2016.10.005.

[21] J. R. Schmidt, J. O. L. Wendt, A. R. Kerstein, Non-equilibrium wall deposition of inertial particles in turbulent flow 137 (2) (2009) 233–257. doi:10.1007/s10955-009-9844-8.

[22] G. Sun, D. O. Lignell, J. C. Hewson, C. R. Gin, Particle dispersion in homogeneous turbulence using the one-dimensional turbulence model 26 (10) (2014) 103301. doi:10.1063/1.4896555.

[23] M. Fistler, D. O. Lignell, A. R. Kerstein, M. Oevermann, Numerical studies of turbulent particle-laden jets using spatial approach of one-dimensional turbulence, in: ILASS-Europe 28th Conference on Liquid Atomization and Spray Systems, 2017.

[24] S. Cao, T. Echekki, A low-dimensional stochastic closure model for combustion large-eddy simulation 9. doi:10.1080/14685240701790714.

[25] R. C. Schmidt, A. R. Kerstein, S. Wunsch, V. Nilsen, Near-wall les closure based on one-dimensional turbulence modeling 186 (1) (2003) 317–355. doi:10.1016/S0021-9991(03)00071-8.

[26] R. C. Schmidt, A. R. Kerstein, R. McDermott, Odtles: A multi-scale model for 3d turbulent flow based on one-dimensional turbulence modeling 199 (13-16) (2010) 865–880. doi:10.1016/j.cma.2008.05.028.

[27] E. Gonzalez-Juez, A. R. Kerstein, D. O. Lignell, Fluxes across double-diffusive interfaces: a one-dimensional-turbulence study 677 (2011) 218–254. doi:10.1017/jfm.2011.78.

[28] E. Gonzalez-Juez, A. R. Kerstein, D. O. Lignell, Reactive rayleigh–taylor turbulent mixing: a one-dimensional-turbulence study 107 (5) (2013) 506–525. doi:10.1080/03091929.2012.736504.

[29] S. Wunsch, A. R. Kerstein, A model for layer formation in stably stratified turbulence 13 (3) (2001) 702–712. doi:10.1063/1.1344182.

[30] D. O. Lignell, V. B. Lansinger, J. Medina, M. Klein, A. R. Kerstein, H. Schmidt, M. Fistler, M. Oevermann, One-dimensional turbulence modeling for cylindrical and spherical flows: model formulation and application 32 (4) (2018) 495–520. doi:10.1007/s00162-018-0465-1.

[31] M. Klein, D. O. Lignell, H. Schmidt, Map-based modeling of turbulent convection: Application of the one-dimensional turbulence model to planar and spherical geometries, in: International Conference on Rayleigh-Benard Turbulence, 2018.

[32] M. Klein, D. O. Lignell, H. Schmidt, Stochastic modeling of temperature and velocity statistics in spherical-shell convection, in: EGU Conference on Recent developments in Geophysical Fluid Dynamics, 2019.

[33] W. T. Ashurst, A. R. Kerstein, One-dimensional turbulence: Variable-density formulation and application to mixing layers 17 (2). doi:10.1063/1.1847413.

[34] D. O. Lignell, A. R. Kerstein, G. Sun, E. I. Monson, Mesh adaption for efficient multiscale implementation of one-dimensional turbulence 27 (3-4) (2013) 273–295. doi:10.1007/s00162-012-0267-9.

[35] Y. A. Çengel, J. M. Cimbala, Fluid Mechanics, 2nd Edition, Çengel series in engineering thermal-fluid sciences, McGraw-Hill Higher Education, 2010.

[36] J. Beder, yaml-cpp v0.6.3 (2008).
URL https://github.com/jbeder/yaml-cpp/

[37] A. C. Hindmarsh, R. Serban, D. R. Reynolds, CVODE, https://computing.llnl.gov/sites/default/files/public/cv_guide.pdf (2020).
URL https://computing.llnl.gov/projects/sundials/cvode

[38] G. Strang, On the construction and comparison of difference schemes 5 (3) (1968) 506–517. doi:10.1137/0705041.

[39] D. G. Goodwin, R. L. Speth, H. K. Moffat, B. W. Weber, Cantera (2018). doi:10.5281/zenodo.1174508.
URL https://cantera.org/

[40] D. van Heesch, Doxygen (2018).
URL https://www.doxygen.nl/

[41] G. K. El Khoury, P. Schlatter, A. Noorani, P. F. Fischer, G. Brethouwer, A. V. Johansson, Direct numerical simulation of turbulent pipe flow at moderately high reynolds numbers 91 (3) (2013) 475–495. doi:10.1007/s10494-013-9482-8.

[42] C. Chin, J. P. Monty, A. Ooi, Reynolds number effects in dns of pipe flow and comparison with channels and boundary layers 45 (2014) 33–40. doi:10.1016/j.ijheatfluidflow.2013.11.007.

[43] H. J. Hussein, S. P. Capp, W. K. George, Velocity measurements in a high-reynolds-number, momentum-conserving, axisymmetric, turbulent jet 258 (1994) 31–75. doi:10.1017/S002211209400323X.

[44] W. Meier, R. S. Barlow, Y.-L. Chen, J.-Y. Chen, Raman/Rayleigh/LIF measurements in a turbulent $CH_4/H_2/N_2$ jet diffusion flame: experimental techniques and turbulence–chemistry interaction 123 (3) (2000) 326–343. doi:10.1016/S0010-2180(00)00171-1.
URL https://tnfworkshop.org/data-archives/simplejet/dlrflames/

[45] H. Pitsch, Unsteady flamelet modeling of differential diffusion in turbulent jet diffusion flames 123 (3) (2000) 358–374. doi:10.1016/S0010-2180(00)00135-8.

[46] R. P. Lindstedt, H. Ozarovsky, Joint scalar transported pdf modeling of nonpiloted turbulent diffusion flames 143 (4) (2005) 471–490. doi:10.1016/j.combustflame.2005.08.030.

[47] H. Wang, S. B. Pope, Large eddy simulation/probability density function modeling of a turbulent $ch_4/h_2/n_2$ jet flame 33 (1) (2011) 1319–1330. doi:10.1016/j.proci.2010.08.004.

[48] M. Fairweather, R. M. Woolley, First-order conditional moment closure modeling of turbulent, nonpremixed methane flames 138 (1-2) (2004) 3–19. doi:10.1016/j.combustflame.2004.03.001.

[49] K. W. Lee, D. H. Choi, Prediction of no in turbulent diffusion flames using eulerian particle flamelet model 12 (5) (2008) 905–927. doi:10.1080/13647830802094351.

[50] K. W. Lee, D. H. Choi, Analysis of no formation in high temperature diluted air combustion in a coaxial jet flame using an unsteady flamelet model 52 (5-6) (2009) 1412–1420. doi:10.1016/j.ijheatmasstransfer.2008.08.015.

Current executable software version

Ancillary data table required for sub version of the executable software: (x.1, x.2 etc.) kindly replace examples in right column with the correct information about your executables, and leave the left column as it is.

Nr.	(Executable) software metadata description	Please fill in this column
S1	Current software version	2.1
S2	Permanent link to executables of this version	For example: *https* : *//github.com/combogenomics/DuctApe/releases/tag/DuctApe* − 0.16.4
S3	Legal Software License	MIT
S4	Computing platforms/Operating Systems	Linux, OS X, Microsoft Windows
S5	Installation requirements & dependencies	CMake 3.12+, Cantera, Git, Doxygen (optional)
S6	If available, link to user manual - if formally published include a reference to the publication in the reference list	For example: *http* : *//mozart.github.io/documentation/*
S7	Support email for questions	davidlignell@byu.edu

Table 3: Software metadata (optional)