

please translate the python code into rust.

python

🔗 折叠 运行 复制

```
class Solution:
    def is_prime(self, n: int) -> bool:
        if n == 1:
            return False
        if n <= 3:
            return True
        if n % 2 == 0 or n % 3 == 0:
            return False
        for i in range(5, int(n ** 0.5) + 1, 6):
            if n % i == 0 or n % (i + 2) == 0:
                return False
        return True

    def sumOfLargestPrimes(self, s: str) -> int:
        primes = []
        for i in range(len(s)):
            for j in range(i, len(s)):
                v = int(s[i:j + 1])
                if self.is_prime(v):
                    primes.append(v)
        primes.sort(reverse=True)
        res, prev, cnt = 0, -1, 0
        for v in primes:
            if v != prev:
                prev = v
                res += v
                cnt += 1
            if cnt == 3:
                break
        return res
```

HKGAI-V1 | Free

- -- Free credit: 8.0; Paid credit: 0.0 --

rust

🔗 折叠 复制

```
impl Solution {
```

```

fn is_prime(n: i32) -> bool {
    if n == 1 {
        return false;
    }
    if n <= 3 {
        return true;
    }
    if n % 2 == 0 || n % 3 == 0 {
        return false;
    }
    let mut i = 5;
    while i * i <= n {
        if n % i == 0 || n % (i + 2) == 0 {
            return false;
        }
        i += 6;
    }
    true
}

```

```

pub fn sum_of_largest_primes(s: String) -> i32 {
    let mut primes = Vec::new();
    let len = s.len();
    for i in 0..len {
        for j in i..len {
            let v = s[i..j].parse::<i32>().unwrap();
            if Self::is_prime(v) {
                primes.push(v);
            }
        }
    }
    primes.sort_by(|a, b| b.cmp(a));
    let mut res = 0;
    let mut prev = -1;
    let mut cnt = 0;
    for &v in primes.iter() {
        if v != prev {
            prev = v;
            res += v;
            cnt += 1;
        }
    }
    res
}

```

```

        if cnt == 3 {
            break;
        }
    }
}
res
}
}

```

There is an run time error: Line 27: Char 49: called `Result::unwrap()` on an `Err` value: `ParseIntError { kind: PosOverflow }` (solution.rs)

HKGAI-V1 | Free

- -- Free credit: 8.0; Paid credit: 0.0 --

The error occurs because the input string `s` can contain numbers that are too large to fit into an `i32`. To fix this, we can use `i64` instead of `i32` to handle larger numbers. Here's the corrected Rust code:

rust

折叠复制

```

impl Solution {
    fn is_prime(n: i64) -> bool {
        if n == 1 {
            return false;
        }
        if n <= 3 {
            return true;
        }
        if n % 2 == 0 || n % 3 == 0 {
            return false;
        }
        let mut i = 5;
        while i * i <= n {
            if n % i == 0 || n % (i + 2) == 0 {
                return false;
            }
            i += 6;
        }
        true
    }
}

```

```

}

pub fn sum_of_largest_primes(s: String) -> i64 {
    let mut primes = Vec::new();
    let len = s.len();
    for i in 0..len {
        for j in i..len {
            let v = s[i..j].parse::<i64>().unwrap();
            if Self::is_prime(v) {
                primes.push(v);
            }
        }
    }
    primes.sort_by(|a, b| b.cmp(a));
    let mut res = 0;
    let mut prev = -1;
    let mut cnt = 0;
    for &v in primes.iter() {
        if v != prev {
            prev = v;
            res += v;
            cnt += 1;
            if cnt == 3 {
                break;
            }
        }
    }
    res
}
}

```