

Lab4 main

Database Explorer

- postgres@localhost
 - keys 2
 - indexes 2
 - checks 1
 - baggage
 - baggage_check
 - boarding_pass
 - booking
 - columns 8
 - booking_id integer
 - passenger_id integer
 - booking_platform varchar
 - created_at date
 - update_at date
 - status varchar(50)
 - price numeric(7,2)
 - discount numeric
 - keys 2
 - foreign keys 1
 - indexes 2

del_pass_book.sql reschedule.sql reprice.sql defence.sql test.sql

```
4
5 ✓ select booking.price, f.flight_id from booking
6 join public.booking_flight bf 1<->1.m on booking.booking_id = bf.booking_id
7 join public.flights f 1.m<->1: on bf.flight_id = f.flight_id
8 where f.flight_id = 31;
9
10 ✓ update booking
11 set price = 5000
12 from flights
13 where flight_id = 31;
14
15 ✓ select booking.price, f.flight_id from booking
16 join public.booking_flight bf 1<->1.m on booking.booking_id = bf.booking_id
17 join public.flights f 1.m<->1: on bf.flight_id = f.flight_id
18 where f.flight_id = 31;
19
20
21 ✓ commit;
22
23
```

Services

Output Result 8-3 Result 8-5

price	flight_id
5000.00	31
5000.00	31

2 rows

Lab9 > reprice.sql

Lab4 main

Database Explorer

- postgres@localhost
 - lab3 3
 - information_schema
 - pg_catalog
 - public
 - tables 10
 - airline
 - columns 6
 - keys 2
 - indexes 2
 - checks 1
 - airport
 - columns 7
 - airport_id integer
 - airport_name varchar(50)
 - country varchar(50)
 - state varchar(50)
 - city varchar(50)
 - created_at date

del_pass_book.sql reschedule.sql defence.sql test.sql

```
1 ✓ begin;
2
3 ✓ select flights.flight_id, flights.scheduled_departure from flights
4 where flight_id = 42;
5
6 ✓ update flights
7 set scheduled_departure = '2023-01-01'
8 where flight_id = 42;
9
10 ✓ select flights.flight_id, flights.scheduled_departure from flights
11 where flight_id = 42;
12
13 ✓ commit;
14
15
```

Services

Output lab3.public.flights lab3.public.flights 2

flight_id	scheduled_departure
42	2023-01-01

1 row

Lab9 > reschedule.sql

Lab4 main

Database Explorer

- postgres@localhost
 - keys 2
 - indexes 2
 - checks 1
 - baggage
 - baggage_check
 - boarding_pass
 - booking
 - columns 8
 - booking_id integer
 - passenger_id integer
 - booking_platform varchar
 - created_at date
 - update_at date
 - status varchar(50)
 - price numeric(7,2)
 - discount numeric
 - keys 2
 - foreign keys 1
 - indexes 2

del_pass_book.sql reschedule.sql reprice.sql defence.sql test.sql

```
4 select booking.price, f.flight_id from booking
5 join public.booking_flight bf 1<->1.m on booking.booking_id = bf.booking_id
6 join public.flights f 1.m<->1: on bf.flight_id = f.flight_id
7 where f.flight_id = 31;
8
9
10 update booking
11 set price = 5000
12 from flights
13 where flight_id = 31;
14
15
16 select booking.price, f.flight_id from booking
17 join public.booking_flight bf 1<->1.m on booking.booking_id = bf.booking_id
18 join public.flights f 1.m<->1: on bf.flight_id = f.flight_id
19 where f.flight_id = 31;
20
21 commit;
22
23
```

Services

Output Result 8-3 Result 8-5

price	flight_id
5000.00	31
5000.00	31

2 rows

Lab9 > reprice.sql

Lab4 main

Database Explorer

- postgres@localhost
 - update_at date
 - keys 2
 - foreign keys 3
 - indexes 7
 - checks 1
 - passengers
 - columns 10
 - passenger_id integer
 - first_name varchar(50)
 - last_name varchar(50)
 - date_of_birth date
 - gender varchar(50)
 - country_of_citizenship varchar(50)
 - country_of_residence varchar(50)
 - passport_number varchar(50)
 - created_at date
 - update_at date
 - keys 1
 - indexes 1

del_pass_book.sql upd_pass.sql reschedule.sql reprice.sql defence.sql test.sql

```
5 add constraint booking_passenger_id_fkey
6 on update cascade
7 on delete cascade ;
8
9
10
11 begin;
12
13 select passengers.first_name from passengers
14 where passenger_id = 101;
15
16 update passengers
17 set first_name = 'Nikita'
18 where passenger_id = 101;
19
20 select passengers.first_name from passengers
21 where passenger_id = 101;
22
23 commit;
24
25
26
```

Services

Output lab3.public.passengers lab3.public.passengers 2

first_name
Nikita

1 row

Lab9 > upd_pass.sql

Lab4 main

Database Explorer

- postgres@localhost
 - baggage_check
 - boarding_pass
 - booking
 - columns 8
 - booking_id integer
 - passenger_id integer
 - booking_platform varchar
 - created_at date
 - update_at date
 - status varchar(50)
 - price numeric(7,2)
 - discount numeric
 - keys 2
 - foreign keys 1
 - indexes 2
 - checks 3
 - booking_flight
 - columns 5
 - keys 2

del_pass_book.sql

```
1 begin;
2
3 insert into passengers (passenger_id, first_name, last_name, date_of_birth, gender, country_of_citizenship,
4 values ( passenger_id 553, first_name 'Nikita', last_name 'Lee', date_of_birth '2006-01-01' , gender 'Male', cou
5
6 insert into booking (booking_id ,passenger_id, booking_platform, price)
7 values (
8 booking_id 567,
9 passenger_id 553,
10 booking_platform 'Online',
11 price 5500
12 );
13
14 select passengers.first_name, b.booking_id from passengers
15 join public.booking b 1<=>1.n: on passengers.passenger_id = b.passenger_id;
16
17 commit;
```

new_pass.sql

reschedule.sql

reprice.sql

defence...

Files

- Lab8 ~/Desktop/University/Dt
- Lab9 ~/Desktop/University/Dt
 - del_pass_book.sql [postgres@localhost]
 - new_pass.sql [postgres@localhost]
 - reprice.sql [postgres@localhost]
 - reschedule.sql [postgres@localhost]
 - test.sql [postgres@localhost]
 - upd_pass.sql [postgres@localhost]
- Scratches and Consoles

Services

Output Result 12-4

first_name	booking_id
Nikita	567
Glynis	17
Glenna	1
Xerxes	2
Danella	3
Fedora	4

Lab9 > new_pass.sql 1:1 (574 chars, 16 line breaks) LF UTF-8 4 spaces

Lab4 main

Database Explorer

- postgres@localhost
 - baggage_check
 - boarding_pass
 - booking
 - columns 8
 - booking_id integer
 - passenger_id integer
 - booking_platform varchar
 - created_at date
 - update_at date
 - status varchar(50)
 - price numeric(7,2)
 - discount numeric
 - keys 2
 - foreign keys 1
 - indexes 2
 - checks 3
 - booking_flight
 - columns 5
 - keys 2

del_pass_book.sql

upd_pass.sql

new_pass.sql

upd_price_flight.sql

reschedule.sql

Files

- Lab8 ~/Desktop/University/Dt
- Lab9 ~/Desktop/University/Dt
 - del_pass_book.sql [postgres@localhost]
 - new_pass.sql [postgres@localhost]
 - reprice.sql [postgres@localhost]
 - reschedule.sql [postgres@localhost]
 - test.sql [postgres@localhost]
 - upd_pass.sql [postgres@localhost]
 - upd_price_flight.sql [postgres@localhost]
- Scratches and Consoles

Services

Output Result 6-2 Result 6-4

flight_id	price
31	5500.00
31	5500.00

Lab9 > upd_price_flight.sql 1:1 (591 chars, 19 line breaks) LF UTF-8 4 spaces

Lab4 main

Database Explorer

- postgres@localhost
 - baggage_check
 - boarding_pass
 - booking
 - columns 8
 - booking_id integer
 - passenger_id integer
 - booking_platform varchar
 - created_at date
 - update_at date
 - status varchar(50)
 - price numeric(7,2)
 - discount numeric
 - keys 2
 - foreign keys 1
 - indexes 2
 - checks 3
 - booking_flight
 - columns 5
 - keys 2

```
1 begin;
2
3 select baggage.baggage_id, baggage.weight_in_kg from baggage
4 where baggage_id = 13;
5
6 update baggage
7 set weight_in_kg = 5.5
8 where baggage_id = 13;
9
10 select baggage.baggage_id, baggage.weight_in_kg from baggage
11 where baggage_id = 13;
12
13 commit;
```

Services

Output

baggage_id	weight_in_kg
13	5.50

1 row

Lab9 > upd_bag_wg.sql 13:8 (247 chars, 12 line breaks) LF UTF-8 4 spaces

Lab4 main

Database Explorer

- postgres@localhost
 - city varchar(50)
 - created_at date
 - update_at date
 - keys 2
 - indexes 2
 - checks 1
 - baggage
 - baggage_check
 - boarding_pass
 - booking
 - columns 8
 - booking_id integer
 - passenger_id integer
 - booking_platform varchar
 - created_at date
 - update_at date
 - status varchar(50)
 - price numeric(7,2)

```
5 select passengers.first_name, passengers.last_name, b.price from passengers
6 join public.booking b 1<->1.n: on passengers.passenger_id = b.passenger_id
7 where passengers.passenger_id = 13;
8
9 update booking
10 set price = price * 0.9
11 from passengers
12 where passengers.passenger_id = 13;
13
14 select passengers.first_name, passengers.last_name, b.price from passengers
15 join public.booking b 1<->1.n: on passengers.passenger_id = b.passenger_id
16 where passengers.passenger_id = 13;
17
18 commit;
19
20 select passengers.first_name, passengers.last_name, b.price from passengers
21 join public.booking b 1<->1.n: on passengers.passenger_id = b.passenger_id
22 where passengers.passenger_id = 13;
23
```

Services

Output

first_name	last_name	price
Domenic	Błaszczak	4950.00

1 row

Lab9 > set_disc.sql 17:1 (669 chars, 22 line breaks) LF UTF-8 4 spaces

Lab4main

Database Explorer

postgres@localhost

city varchar(50)

created_at date

update_at date

keys 2

indexes 2

checks 1

baggage

baggage_check

boarding_pass

booking

columns 8

booking_id integer

passenger_id integer

booking_platform varchar

created_at date

update_at date

status varchar(50)

price numeric(7,2)

1 ✓

2 ✓

3 ✓

4 ✓

5 ✓

6 ✓

7 ✓

8 ✓

9 ✓

10 ✓

11 ✓

12 ✓

13 ✓

14 ✓

15 ✓

begin;

select b.booking_id, bf.flight_id from booking b

join public.booking_flight bf on b.booking_id = bf.booking_id

where flight_id = 33;

update booking_flight bf

set flight_id = 77

where bf.flight_id = 33;

select b.booking_id, bf.flight_id from booking b

join public.booking_flight bf on b.booking_id = bf.booking_id

where flight_id = 77;

commit;

Files

Lab8

Lab9

del_pass_book.sql

new_pass.sql

old_to_new_f.sql

reprice.sql

reschedule.sql

set_disc.sql

test.sql

upd_bag_wg.sql

upd_pass.sql

upd_price_flight.sql

Scratches and Consoles

Services

Output

Result 2-2

Result 2-4

1 row

5:21 (353 chars, 14 line breaks) LF UTF-8 4 spaces