

Entangled Basis Finite Element Method PDE solver for Quantum Computer

Abhijatmedhi Chotrattanapituk

Quantum Measurement Group, MIT, Cambridge, MA, USA

Department of Electrical Engineering and Computer Science, MIT, Cambridge, MA, USA

(Dated: October 10, 2023)

1. FINITE ELEMENT METHOD (FEM)

2. TENSOR NETWORK (TN)

3. TARGET EQUATION

In this work, we will focus on a class of analytic partial differential equation (A-PDE) of a function of time and space, $u(t, q)$ with q be spatial vector, that is linear in time (LTA-PDE). This PDE can be written in the form

$$D_t u + h(t, q, u, D_q u, D_q^2 u, \dots) = 0, \quad (3.1)$$

where D_t is time derivative, D_q is space derivative, and h is an analytic function which can be written as

$$h(t, q, u, D_q u, D_q^2 u, \dots) = \sum_{p_t, p_q, p_0, \dots} h_{p_t, p_q, p_0, \dots} t^{p_t} q^{p_q} u^{p_0} (D_q u)^{p_1} (D_q^2 u)^{p_2} \dots \quad (3.2)$$

Notice that $h_{p_t, p_q, p_0, \dots}$ is a rank $\prod_{r=0} (r \cdot p_r)$ tensors.

4. FEM REPRESENTATION OF LTA-PDE

5. TENSOR OPTIMIZATION

6. MATRIX PRODUCT STATE (MPS) REPRESENTATION

7. IMPLEMENTATION