

Maintenance checks report

| Checklist name | Year |
|-------------------------------|------|
| Preventive Maintenance Year 7 | 7 |

| Site | Turbine serial number | Order number |
|----------|-------------------------|---------------|
| | | |
| Language | Revision date checklist | Approval date |
| en-US | 10/15/2024 | |

Siemens Gamesa Renewable Energy S.A. Parque Tecnológico de Bizkaia, Edificio 222, 48170, Zamudio, Vizcaya, Spain
+34 944 03 73 52 – info@siemensgamesa.com – www.siemensgamesa.com

1. Tools

| Tools | | | | |
|-------|---|-------------------------------------|----------------|---------|
| Group | # | Name | Calibration ID | Remarks |
| 1 | 1 | Hioki BT3554 (Dummy-Adw018) | | |
| | 2 | STAHLWILLE 130-650Nm (Dummy-Adw015) | | |
| | 3 | STAHLWILLE 80-400Nm (Dummy-Adw016) | | |

2. Check details

2.1. Checks from the maintenance plan

| ECN | | | | |
|------------------------------------|--|---------|-------|--------|
| | | | | |
| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 1 | ATD000233.0: Rotor blade 1 - Oil level pitch gear - Inspection | | | |
| 2 | ATD000233.1: Rotor blade 2 - Oil level pitch gear - Inspection | | | |
| 3 | ATD000233.2: Rotor blade 3 - Oil level pitch gear - Inspection | | | |
| 4 | ATD000234.0: Rotor blade 1 - Pitch gear - Oil sample Barcode number on bottle | | | |
| 5 | ATD000234.1: Rotor blade 2 - Pitch gear - Oil sample Barcode number on bottle | | | |
| 6 | ATD000234.2: Rotor blade 3 - Pitch gear - Oil sample Barcode number on bottle | | | |
| 7 | ATD000236.0: Rotor blade 1 - Position indicators of the limit switches - Inspection | | | |
| 8 | ATD000236.1: Rotor blade 1 - Activation plate bolts of the limit switches - Test | | | |
| 9 | ATD000236.2: Rotor blade 1 - Support and joint elements of the limit switches - Inspection | | | |
| 10 | ATD000236.3: Rotor blade 2 - Position indicators of the limit switches - Inspection | | | |
| 11 | ATD000236.4: Rotor blade 2 - Activation plate bolts of the limit switches - Test | | | |
| 12 | ATD000236.5: Rotor blade 2 - Support and joint elements of the limit switches - Inspection | | | |
| 13 | ATD000236.6: Rotor blade 3 - Position indicators of the limit switches - Inspection | | | |
| 14 | ATD000236.7: Rotor blade 3 - Activation plate bolts of the limit switches - Test | | | |
| 15 | ATD000236.8: Rotor blade 3 - Support and joint elements of the limit switches - Inspection | | | |
| 16 | ATD000241.0: Rotor blade 1 - Blade bearing, pos. A - Grease sample Barcode number on bottle | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 17 | ATD000241.1: Rotor blade 1 - Blade bearing, pos. B - Grease sample Barcode number on bottle | | | |
| 18 | ATD000241.2: Rotor blade 1 - Blade bearing, pos. C - Grease sample Barcode number on bottle | | | |
| 19 | ATD000241.3: Rotor blade 2 - Blade bearing, pos. A - Grease sample Barcode number on bottle | | | |
| 20 | ATD000241.4: Rotor blade 2 - Blade bearing, pos. B - Grease sample Barcode number on bottle | | | |
| 21 | ATD000241.5: Rotor blade 2 - Blade bearing, pos. C - Grease sample Barcode number on bottle | | | |
| 22 | ATD000241.6: Rotor blade 3 - Blade bearing, pos. A - Grease sample Barcode number on bottle | | | |
| 23 | ATD000241.7: Rotor blade 3 - Blade bearing, pos. B - Grease sample Barcode number on bottle | | | |
| 24 | ATD000241.8: Rotor blade 3 - Blade bearing, pos. C - Grease sample Barcode number on bottle | | | |
| 25 | ATD000242.00: Rotor system - Lubricant collector bottles - Inspection | | | |
| 26 | ATD000242.01: Rotor blade 1 - Lubricant collector bottles - Inspection and replace if level >50% Amount of replaced bottles | | | |
| 27 | ATD000242.02: Rotor blade 2 - Lubricant collector bottles - Inspection and replace if level >50% Amount of replaced bottles | | | |
| 28 | ATD000242.03: Rotor blade 3 - Lubricant collector bottles - Inspection and replace if level >50% Amount of replaced bottles | | | |
| 29 | ATD000243.0: Rotor blade 1 - External condition of the pitch cabinet - Inspection | | | |
| 30 | ATD000243.10: Rotor blade 1 - Wires and connectors of pitch drive converter and power supplies 26T1 and 26T5 - Inspection | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|--|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 31 | ATD000243.11: Rotor blade 1 - Cabinet door closing clamp and general condition - Inspection | | | |
| 32 | ATD000243.12: Rotor blade 1 - Cabinet doors closed smoothly - Inspection | | | |
| 33 | ATD000243.13: Rotor blade 2 - Wires and connectors of pitch drive converter and power supplies 26T1 and 26T5 - Inspection | | | |
| 34 | ATD000243.14: Rotor blade 2 - Cabinet door closing clamp and general condition - Inspection | | | |
| 35 | ATD000243.15: Rotor blade 3 - Wires and connectors of pitch drive converter and power supplies 26T1 and 26T5 - Inspection | | | |
| 36 | ATD000243.16: Rotor blade 3 - Cabinet door closing clamp and general condition - Inspection | | | |
| 37 | ATD000243.17: Rotor blade 2 - Cabinet doors closed smoothly - Inspection | | | |
| 38 | ATD000243.18: Rotor blade 3 - Cabinet doors closed smoothly - Inspection | | | |
| 39 | ATD000243.1: Rotor blade 2 - External condition of the pitch cabinet - Inspection | | | |
| 40 | ATD000243.2: Rotor blade 3 - External condition of the pitch cabinet - Inspection | | | |
| 41 | ATD000243.3: Rotor blade 1 - Pitch drive converter, battery charger (leds), batteries, terminal connections of the batteries, connections of the cables to batteries, chopper resistor, starting resistor and grounding - Inspection | | | |
| 42 | ATD000243.4: Rotor blade 2 - Pitch drive converter, battery charger (leds), batteries, terminal connections of the batteries, connections of the cables to batteries, chopper resistor, starting resistor and grounding - Inspection | | | |
| 43 | ATD000243.5: Rotor blade 3 - Pitch drive converter, battery charger (leds), batteries, terminal connections of the batteries, connections of the cables to batteries, chopper resistor, starting resistor and grounding - Inspection | | | |
| 44 | ATD000243.6: Rotor blade 1 - Battery cabinet temperature - Measure Battery cabinet 1 temperature <div>°C</div> | | | |
| 45 | ATD000243.7: Rotor blade 2 - Battery cabinet temperature - Measure Battery cabinet 2 temperature <div>°C</div> | | | |
| 46 | ATD000243.8: Rotor blade 3 - Battery cabinet temperature - Measure Battery cabinet 3 temperature <div>°C</div> | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 47 | <div>ATD000243.9-1: Rotor blade 1 - Voltage and impedance of the batteries (exFO-S_0384) - Measure</div> <div>New batteries? Yes <input type="checkbox"/> No <input type="checkbox"/></div> <div>BSI (Battery Set Identifier), optional</div> <div></div> <div>Temperature measured by Hioki <input type="text"/> °C</div> <div>1G1 / 1.1 voltage <input type="text"/> V</div> <div>1G2 / 1.2 voltage <input type="text"/> V</div> <div>1G3 / 1.3 voltage <input type="text"/> V</div> <div>1G4 / 2.1 voltage <input type="text"/> V</div> <div>1G5 / 2.2 voltage <input type="text"/> V</div> <div>1G6 / 2.3 voltage <input type="text"/> V</div> <div>1G7 / 3.1 voltage <input type="text"/> V</div> <div>1G8 / 3.2 voltage <input type="text"/> V</div> <div>1G9 / 3.3 voltage <input type="text"/> V</div> <div>1G10 / 4.1 voltage <input type="text"/> V</div> <div>1G11 / 4.2 voltage <input type="text"/> V</div> <div>1G12 / 4.3 voltage <input type="text"/> V</div> <div>1G13 / 5.1 voltage <input type="text"/> V</div> <div>1G14 / 5.2 voltage <input type="text"/> V</div> <div>1G15 / 5.3 voltage <input type="text"/> V</div> <div>1G16 / 6.1 voltage <input type="text"/> V</div> <div>1G17 / 6.2 voltage <input type="text"/> V</div> <div>1G18 / 6.3 voltage <input type="text"/> V</div> <div>1G19 / 7.1 voltage <input type="text"/> V</div> | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|----------------------|---------|-------|--------|
| Location: | | | | |
| | 1G20 / 7.2 voltage | V | | |
| | 1G21 / 7.3 voltage | V | | |
| | 1G22 / 8.1 voltage | V | | |
| | 1G23 / 8.2 voltage | V | | |
| | 1G24 / 8.3 voltage | V | | |
| | 1G25 / voltage | V | | |
| | 1G26 / voltage | V | | |
| | 1G27 / voltage | V | | |
| | 1G28 / voltage | V | | |
| | 1G29 / voltage | V | | |
| | 1G30 / voltage | V | | |
| | 1G1 / 1.1 impedance | mΩ | | |
| | 1G2 / 1.2 impedance | mΩ | | |
| | 1G3 / 1.3 impedance | mΩ | | |
| | 1G4 / 2.1 impedance | mΩ | | |
| | 1G5 / 2.2 impedance | mΩ | | |
| | 1G6 / 2.3 impedance | mΩ | | |
| | 1G7 / 3.1 impedance | mΩ | | |
| | 1G8 / 3.2 impedance | mΩ | | |
| | 1G9 / 3.3 impedance | mΩ | | |
| | 1G10 / 4.1 impedance | mΩ | | |
| | 1G11 / 4.2 impedance | mΩ | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|----------------------|--|-------|--------|
| Location: | | | | |
| | 1G12 / 4.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G13 / 5.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G14 / 5.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G15 / 5.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G16 / 6.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G17 / 6.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G18 / 6.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G19 / 7.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G20 / 7.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G21 / 7.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G22 / 8.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G23 / 8.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G24 / 8.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G25 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G26 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G27 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G28 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G29 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G30 / impedance | <input type="text" value="mΩ"/> | | |
| | Leakages | Yes <input type="checkbox"/> No <input type="checkbox"/> | | |
| | Cracks | Yes <input type="checkbox"/> No <input type="checkbox"/> | | |
| | Bulks | Yes <input type="checkbox"/> No <input type="checkbox"/> | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 48 | <p>ATD000243.9-2: Rotor blade 2 - Voltage and impedance of the batteries (exFO-S_0384) - Measure</p> <p>New batteries? Yes <input type="checkbox"/> No <input type="checkbox"/></p> <p>BSI (Battery Set Identifier), optional <input type="text"/></p> <p>Temperature measured by Hioki <input type="text"/> °C</p> <p>1G1 / 1.1 voltage <input type="text"/> V</p> <p>1G2 / 1.2 voltage <input type="text"/> V</p> <p>1G3 / 1.3 voltage <input type="text"/> V</p> <p>1G4 / 2.1 voltage <input type="text"/> V</p> <p>1G5 / 2.2 voltage <input type="text"/> V</p> <p>1G6 / 2.3 voltage <input type="text"/> V</p> <p>1G7 / 3.1 voltage <input type="text"/> V</p> <p>1G8 / 3.2 voltage <input type="text"/> V</p> <p>1G9 / 3.3 voltage <input type="text"/> V</p> <p>1G10 / 4.1 voltage <input type="text"/> V</p> <p>1G11 / 4.2 voltage <input type="text"/> V</p> <p>1G12 / 4.3 voltage <input type="text"/> V</p> <p>1G13 / 5.1 voltage <input type="text"/> V</p> <p>1G14 / 5.2 voltage <input type="text"/> V</p> <p>1G15 / 5.3 voltage <input type="text"/> V</p> <p>1G16 / 6.1 voltage <input type="text"/> V</p> <p>1G17 / 6.2 voltage <input type="text"/> V</p> <p>1G18 / 6.3 voltage <input type="text"/> V</p> <p>1G19 / 7.1 voltage <input type="text"/> V</p> | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|----------------------|---------|-------|--------|
| Location: | | | | |
| | 1G20 / 7.2 voltage | V | | |
| | 1G21 / 7.3 voltage | V | | |
| | 1G22 / 8.1 voltage | V | | |
| | 1G23 / 8.2 voltage | V | | |
| | 1G24 / 8.3 voltage | V | | |
| | 1G25 / voltage | V | | |
| | 1G26 / voltage | V | | |
| | 1G27 / voltage | V | | |
| | 1G28 / voltage | V | | |
| | 1G29 / voltage | V | | |
| | 1G30 / voltage | V | | |
| | 1G1 / 1.1 impedance | mΩ | | |
| | 1G2 / 1.2 impedance | mΩ | | |
| | 1G3 / 1.3 impedance | mΩ | | |
| | 1G4 / 2.1 impedance | mΩ | | |
| | 1G5 / 2.2 impedance | mΩ | | |
| | 1G6 / 2.3 impedance | mΩ | | |
| | 1G7 / 3.1 impedance | mΩ | | |
| | 1G8 / 3.2 impedance | mΩ | | |
| | 1G9 / 3.3 impedance | mΩ | | |
| | 1G10 / 4.1 impedance | mΩ | | |
| | 1G11 / 4.2 impedance | mΩ | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|----------------------|--|-------|--------|
| Location: | | | | |
| | 1G12 / 4.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G13 / 5.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G14 / 5.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G15 / 5.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G16 / 6.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G17 / 6.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G18 / 6.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G19 / 7.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G20 / 7.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G21 / 7.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G22 / 8.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G23 / 8.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G24 / 8.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G25 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G26 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G27 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G28 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G29 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G30 / impedance | <input type="text" value="mΩ"/> | | |
| | Leakages | Yes <input type="checkbox"/> No <input type="checkbox"/> | | |
| | Cracks | Yes <input type="checkbox"/> No <input type="checkbox"/> | | |
| | Bulks | Yes <input type="checkbox"/> No <input type="checkbox"/> | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 49 | <p>ATD000243.9-3: Rotor blade 3 - Voltage and impedance of the batteries (exFO-S_0384) - Measure</p> <p>New batteries? Yes <input type="checkbox"/> No <input type="checkbox"/></p> <p>BSI (Battery Set Identifier), optional <input type="text"/></p> <p>Temperature measured by Hioki <input type="text"/> °C</p> <p>1G1 / 1.1 voltage <input type="text"/> V</p> <p>1G2 / 1.2 voltage <input type="text"/> V</p> <p>1G3 / 1.3 voltage <input type="text"/> V</p> <p>1G4 / 2.1 voltage <input type="text"/> V</p> <p>1G5 / 2.2 voltage <input type="text"/> V</p> <p>1G6 / 2.3 voltage <input type="text"/> V</p> <p>1G7 / 3.1 voltage <input type="text"/> V</p> <p>1G8 / 3.2 voltage <input type="text"/> V</p> <p>1G9 / 3.3 voltage <input type="text"/> V</p> <p>1G10 / 4.1 voltage <input type="text"/> V</p> <p>1G11 / 4.2 voltage <input type="text"/> V</p> <p>1G12 / 4.3 voltage <input type="text"/> V</p> <p>1G13 / 5.1 voltage <input type="text"/> V</p> <p>1G14 / 5.2 voltage <input type="text"/> V</p> <p>1G15 / 5.3 voltage <input type="text"/> V</p> <p>1G16 / 6.1 voltage <input type="text"/> V</p> <p>1G17 / 6.2 voltage <input type="text"/> V</p> <p>1G18 / 6.3 voltage <input type="text"/> V</p> <p>1G19 / 7.1 voltage <input type="text"/> V</p> | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|----------------------|---------|-------|--------|
| Location: | | | | |
| | 1G20 / 7.2 voltage | V | | |
| | 1G21 / 7.3 voltage | V | | |
| | 1G22 / 8.1 voltage | V | | |
| | 1G23 / 8.2 voltage | V | | |
| | 1G24 / 8.3 voltage | V | | |
| | 1G25 / voltage | V | | |
| | 1G26 / voltage | V | | |
| | 1G27 / voltage | V | | |
| | 1G28 / voltage | V | | |
| | 1G29 / voltage | V | | |
| | 1G30 / voltage | V | | |
| | 1G1 / 1.1 impedance | mΩ | | |
| | 1G2 / 1.2 impedance | mΩ | | |
| | 1G3 / 1.3 impedance | mΩ | | |
| | 1G4 / 2.1 impedance | mΩ | | |
| | 1G5 / 2.2 impedance | mΩ | | |
| | 1G6 / 2.3 impedance | mΩ | | |
| | 1G7 / 3.1 impedance | mΩ | | |
| | 1G8 / 3.2 impedance | mΩ | | |
| | 1G9 / 3.3 impedance | mΩ | | |
| | 1G10 / 4.1 impedance | mΩ | | |
| | 1G11 / 4.2 impedance | mΩ | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|--|-------|--------|
| Location: | | | | |
| | 1G12 / 4.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G13 / 5.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G14 / 5.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G15 / 5.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G16 / 6.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G17 / 6.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G18 / 6.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G19 / 7.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G20 / 7.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G21 / 7.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G22 / 8.1 impedance | <input type="text" value="mΩ"/> | | |
| | 1G23 / 8.2 impedance | <input type="text" value="mΩ"/> | | |
| | 1G24 / 8.3 impedance | <input type="text" value="mΩ"/> | | |
| | 1G25 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G26 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G27 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G28 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G29 / impedance | <input type="text" value="mΩ"/> | | |
| | 1G30 / impedance | <input type="text" value="mΩ"/> | | |
| | Leakages | Yes <input type="checkbox"/> No <input type="checkbox"/> | | |
| | Cracks | Yes <input type="checkbox"/> No <input type="checkbox"/> | | |
| | Bulks | Yes <input type="checkbox"/> No <input type="checkbox"/> | | |
| 50 | ATD000277.0: Yaw system - Yaw gear A - Oil sample | | | |
| | Barcode number on bottle | <input type="text"/> | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|---|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 51 | ATD000277.10: Yaw system - Yaw gear F - Oil sample Barcode number on bottle <input type="text"/> | | | |
| 52 | ATD000277.12: Yaw system - Yaw gear G - Oil sample Barcode number on bottle <input type="text"/> | | | |
| 53 | ATD000277.14: Yaw system - Yaw gear H - Oil sample Barcode number on bottle <input type="text"/> | | | |
| 54 | ATD000277.2: Yaw system - Yaw gear B - Oil sample Barcode number on bottle <input type="text"/> | | | |
| 55 | ATD000277.4: Yaw system - Yaw gear C - Oil sample Barcode number on bottle <input type="text"/> | | | |
| 56 | ATD000277.6: Yaw system - Yaw gear D - Oil sample Barcode number on bottle <input type="text"/> | | | |
| 57 | ATD000277.8: Yaw system - Yaw gear E - Oil sample Barcode number on bottle <input type="text"/> | | | |
| 58 | ATD000278.0: Yaw system - Yaw gear A oil level - Measure Yaw gear A oil level before refill/drain <input type="text"/> mm Yaw gear A oil level in range? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 59 | ATD000278.1: Yaw system - Yaw gear B oil level - Measure Yaw gear B oil level before refill/drain <input type="text"/> mm Yaw gear B oil level in range? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 60 | <p>ATD000278.2: Yaw system - Yaw gear C oil level - Measure</p> <p>Yaw gear C oil level before refill/drain <input type="text"/> mm</p> <p>Yaw gear C oil level in range?</p> <p>1 <input type="text"/> Yes, it was as needed</p> <p>2 <input type="text"/> Yes, after refill</p> <p>3 <input type="text"/> No, has to be refilled next visit (Case created)</p> | | | |
| 61 | <p>ATD000278.3: Yaw system - Yaw gear D oil level - Measure</p> <p>Yaw gear D oil level before refill/drain <input type="text"/> mm</p> <p>Yaw gear D oil level in range?</p> <p>1 <input type="text"/> Yes, it was as needed</p> <p>2 <input type="text"/> Yes, after refill</p> <p>3 <input type="text"/> No, has to be refilled next visit (Case created)</p> | | | |
| 62 | <p>ATD000278.4: Yaw system - Yaw gear E oil level - Measure</p> <p>Yaw gear E oil level before refill/drain <input type="text"/> mm</p> <p>Yaw gear E oil level in range?</p> <p>1 <input type="text"/> Yes, it was as needed</p> <p>2 <input type="text"/> Yes, after refill</p> <p>3 <input type="text"/> No, has to be refilled next visit (Case created)</p> | | | |
| 63 | <p>ATD000278.5: Yaw system - Yaw gear F oil level - Measure</p> <p>Yaw gear F oil level before refill/drain <input type="text"/> mm</p> <p>Yaw gear F oil level in range?</p> <p>1 <input type="text"/> Yes, it was as needed</p> <p>2 <input type="text"/> Yes, after refill</p> <p>3 <input type="text"/> No, has to be refilled next visit (Case created)</p> | | | |

| # | Measuring points | Remarks | Tools | Status |
|------------------------------------|---|---------|-------|--------|
| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
| Location: | | | | |
| 64 | ATD000278.6: Yaw system - Yaw gear G oil level - Measure Yaw gear G oil level before refill/drain <input type="text"/> mm Yaw gear G oil level in range? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 65 | ATD000278.7: Yaw system - Yaw gear H oil level - Measure Yaw gear H oil level before refill/drain <input type="text"/> mm Yaw gear H oil level in range? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 66 | ATD000280.00: Rotor lock - Engagement holes - Inspection | | | |
| 67 | ATD000280.01: Rotor lock - Cylinders - Inspection | | | |
| 68 | ATD000280.02: Rotor lock - Pins - Inspection | | | |
| 69 | ATD000280.03: Rotor lock - Pins engaged - Inspection | | | |
| 70 | ATD000282.1: Rotor lock - Cylinders and hydraulic hoses - Inspection | | | |
| 71 | ATD000282.2: Rotor lock - Sensor cables - Inspection | | | |
| 72 | ATD000283.0: Rotor brake - Callipers and drainage circuits - Inspection | | | |
| 73 | ATD000285.0: Rotor brake - Callipers - Test | | | |
| 74 | ATD000285.1: Rotor brake - Brake pads - Inspection | | | |
| 75 | ATD000286.0: Oil supply system - HG01, pos. 190.1 - Oil sample Barcode number on bottle <input type="text"/> | | | |
| 76 | ATD000297.0: Rotor brake - Rotor brake disk (360°) - Inspection | | | |
| 77 | ATD000297.1: Rotor brake - Brake disk (360°) wear - Inspection | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|---|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 78 | ATD000308.0: Yaw system - Gear grease collection tray - Inspection | | | |
| 79 | ATD000308.1: Yaw system - Bearing grease collection tray - Inspection | | | |
| 80 | ATD000309.0: Rotor brake - Drainage pipes - Inspection | | | |
| 81 | ATD000309.1: Rotor brake - Oil presence inside the drainage pipes - Inspection | | | |
| 82 | ATD000311.0: Wind turbine system - Emergency stop button at NC300 - Test | | | |
| 83 | ATD000311.1: Wind turbine system - Emergency stop button at NC320 - Test | | | |
| 84 | ATD000311.2: Wind turbine system - Emergency stop button at TBC300 - Test | | | |
| 85 | ATD000311.3: Wind turbine system - Emergency stop button at TBC00 - Test | | | |
| 86 | ATD000311.4: Wind turbine system - Emergency stop button at TBC202 - Test | | | |
| 87 | ATD000311.5: Wind turbine system - Emergency stop button at converter - Test | | | |
| 88 | ATD000311.7: Wind turbine system - Emergency stop button at TBC200 - Test | | | |
| 89 | ATD000313.0: Outer platform - Cooler platform - Inspection | | | |
| 90 | ATD000319.0: Tower - Ground meshes between TP and S3 - Inspection | | | |
| 91 | ATD000319.1: Tower - Ground meshes between S3 and S2 - Inspection | | | |
| 92 | ATD000319.2: Tower - Ground meshes between S2 and S1 - Inspection | | | |
| 93 | ATD000334.0: Platform 7 - All bolts (450 Nm) of the union between the lateral supports and the tower - Retighten and fill screw protocol | | | |
| 94 | ATD000334.2: Platform 7 - Accessible bolts (250 Nm), from the lift hatchway, of the lower bolted joints between the supports and the platform - Retighten and fill screw protocol | | | |
| 95 | ATD000334.4: Platform 7 - Rest of the lower bolted joints between the supports and the platform - Inspection and fill screw protocol | | | |
| 96 | ATD000334.5: Platform 6 - All bolts (450 Nm) of the union between the lateral supports and the tower - Retighten and fill screw protocol | | | |
| 97 | ATD000334.7: Platform 6 - Accessible bolts (250 Nm), from the lift hatchway, of the lower bolted joints between the supports and the platform - Retighten and fill screw protocol | | | |
| 98 | ATD000334.9: Platform 6 - Rest of the lower bolted joints between the supports and the platform - Inspection and fill screw protocol | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|--|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 99 | ATD000335.0: Oil supply system - Magnets - Inspection | | | |
| 100 | ATD000339.00: Oil supply system - Whole structure - Inspection | | | |
| 101 | ATD000341.0: Oil supply system - Oil level - Measure Oil level <input type="text"/> I Number of running pumps <input type="text"/> | | | |
| 102 | ATD000342.0: Yaw system - Trays - Inspection | | | |
| 103 | ATD000342.1: Yaw system - Trays - Clean | | | |
| 104 | ATD000355.0: Rotor brake - Hydraulic components of calliper 1 and 2 (right side) - Inspection | | | |
| 105 | ATD000355.15: Rotor brake - Seals around the callipers - Inspection | | | |
| 106 | ATD000355.1: Rotor brake - Hydraulic components of calliper 5 and 6 (left side) - Inspection | | | |
| 107 | ATD000355.2: Rotor brake - Hydraulic components of calliper 3 and 4 (upper side) - Inspection | | | |
| 108 | ATD000355.3: Rotor brake - Mechanical components of calliper 1 and 2 (right side) - Inspection | | | |
| 109 | ATD000355.4: Rotor brake - Mechanical components of calliper 5 and 6 (left side) - Inspection | | | |
| 110 | ATD000355.5: Rotor brake - Mechanical components of calliper 3 and 4 (upper side) - Inspection | | | |
| 111 | ATD000355.6: Rotor brake - Hoses and fittings of calliper 1 and 2 (right side) - Inspection | | | |
| 112 | ATD000355.7: Rotor brake - Hoses and fittings of calliper 5 and 6 (left side) - Inspection | | | |
| 113 | ATD000355.8: Rotor brake - Hoses and fittings of calliper 3 and 4 (upper side) - Inspection | | | |
| 114 | ATD000357.0: Rotor bearing - Seals - Inspection | | | |
| 115 | ATD000359.0: Hydraulic system - Hoses and fittings - Inspection | | | |
| 116 | ATD000359.1 : Hydraulic system - Mechanical components - Inspection | | | |
| 117 | ATD000359.2 : Hydraulic system - All components - Inspection | | | |
| 118 | ATD000360.0: Hydraulic system - Hydraulic tank - Oil sample Barcode number on bottle <input type="text"/> | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 119 | ATD000361.0: Hydraulic system - Tank breather filter - Replace | | | |
| 120 | ATD000361.1: Hydraulic system - Pressure filters - Replace | | | |
| 121 | ATD000361.2: Hydraulic system - Return line filter - Replace | | | |
| 122 | ATD000362.0: Hydraulic system - Oil level - Inspection Oil level (before refill) <input type="text" value="I"/> Oil level in range? 1 <input type="text" value="Yes, it was as needed"/> 2 <input type="text" value="Yes, after refill"/> 3 <input type="text" value="No, has to be refilled next visit (Case created)"/> | | | |
| 123 | ATD000394.0: Generator cooling system - All pipelines, compensator, heat exchange and other components of both cooling units - Inspection | | | |
| 124 | ATD000394.1: Generator cooling system - All pumps, compensators, pipelines and other components of the midsection - Inspection | | | |
| 125 | ATD000394.2: Generator cooling system - All pipelines around generator - Inspection | | | |
| 126 | ATD000394.3: Generator cooling system - All pipelines around cellar - Inspection | | | |
| 127 | ATD000395.0: Installation system - TBC300 - Inspection | | | |
| 128 | ATD000395.1: Installation system - TBC202 - Inspection | | | |
| 129 | ATD000395.2: Installation system - TBC201 - Inspection | | | |
| 130 | ATD000395.3: Installation system - TBC200 - Inspection | | | |
| 131 | ATD000395.4: Installation system - TBC00 - Inspection | | | |
| 132 | ATD000395.5: Installation system - TBC200 switch drives for -20Q2M1, -21Q2M1 and -24Q2M1 - Inspection | | | |
| 133 | ATD000398.0: Installation system - NC300 - Inspection | | | |
| 134 | ATD000398.1: NC300 - Electrical components and cable glands - Inspection | | | |
| 135 | ATD000398.2: Installation system - NC320 - Inspection | | | |
| 136 | ATD000398.3: NC320 - Electrical components and cable glands - Inspection | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 137 | ATD000401.0: Helicopter platform - Beacon 1 - Inspection | | | |
| 138 | ATD000401.1: Helicopter platform - Beacon 2 - Inspection | | | |
| 139 | ATD000401.2: Helicopter platform - Beacon 1 - Test | | | |
| 140 | ATD000401.3: Helicopter platform - Beacon 2 - Test | | | |
| 141 | ATD000405.0: Hydraulic accumulator - Rotor lock 570.1 - Measure Nitrogen pressures before refill <input type="text"/> bar Nitrogen pressures at 50 ±2.5 bar? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 142 | ATD000405.10: Hydraulic accumulator - Yaw brake 740.4 - Measure Nitrogen pressures before refill <input type="text"/> bar Nitrogen pressures at 120 ±2.5 bar? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 143 | ATD000405.12: Hydraulic accumulator - Rotor brake 920.1 - Measure Nitrogen pressures before refill <input type="text"/> bar Nitrogen pressures at 90 ±2.5 bar? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 144 | ATD000405.14: Hydraulic accumulator - Rotor brake 920.2 - Measure Nitrogen pressures before refill <input type="text"/> bar Nitrogen pressures at 90 ±2.5 bar? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 145 | ATD000405.16: Hydraulic accumulator - O-ring and connections - Inspection | | | |
| 146 | ATD000405.17: Hydraulic accumulator - Accumulator's body and connections - Inspection | | | |
| 147 | ATD000405.2: Hydraulic accumulator - Rotor lock 570.2 - Measure Nitrogen pressures before refill <input type="text"/> bar Nitrogen pressures at 50 ±2.5 bar? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 148 | ATD000405.4: Hydraulic accumulator - Yaw brake 740.1 - Measure Nitrogen pressures before refill <input type="text"/> bar Nitrogen pressures at 120 ±2.5 bar? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 149 | ATD000405.6: Hydraulic accumulator - Yaw brake 740.2 - Measure Nitrogen pressures before refill <input type="text"/> bar Nitrogen pressures at 120 ±2.5 bar? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 150 | ATD000405.8: Hydraulic accumulator - Yaw brake 740.3 - Measure Nitrogen pressures before refill <input type="text"/> bar Nitrogen pressures at 120 ±2.5 bar? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 151 | ATD000425.0: NC300 - Bolts - Inspection | | | |
| 152 | ATD000425.1: NC320 - Bolts - Inspection | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 153 | ATD000426.0: TBC300 - Bolts - Inspection | | | |
| 154 | ATD000426.1: TBC202 - Bolts - Inspection | | | |
| 155 | ATD000426.2: TBC201 - Bolts - Inspection | | | |
| 156 | ATD000426.3: TBC200 - Bolts - Inspection | | | |
| 157 | ATD000426.4: TBC00 - Bolts - Inspection | | | |
| 158 | ATD000428.0: Ventilation system - Compensator between P1 & P2 - Inspection | | | |
| 159 | ATD000428.1: Ventilation system - Compensator on P3 - Inspection | | | |
| 160 | ATD000428.2: Ventilation system - Compensators (3) on P4 - Inspection | | | |
| 161 | ATD000428.3: Ventilation system - Compensator on P5 - Inspection | | | |
| 162 | ATD000429.0: Ventilation system - Motor 1 - Auditory inspection | | | |
| 163 | ATD000429.1: Ventilation system - Motor 2 - Auditory inspection | | | |
| 164 | ATD000429.2: Ventilation system - Air intake humidity - Measure Air intake humidity <input type="text"/> % | | | |
| 165 | ATD000429.3: Ventilation system - Differential pressure - Inspection Differential pressure <input type="text"/> Pa | | | |
| 166 | ATD000443.0: Equipotential bonding systems - Yaw slip ring carbon brush 1 (mechanical part) - Inspection | | | |
| 167 | ATD000443.1: Equipotential bonding systems - Yaw slip ring carbon brush 2 (mechanical part) - Inspection | | | |
| 168 | ATD000443.2: Equipotential bonding systems - Yaw slip ring carbon brush (mechanical part) 3 - Inspection | | | |
| 169 | ATD000443.3: Equipotential bonding systems - Yaw slip ring carbon brush 1 - Inspection and measure Carbon brush 1 length <input type="text"/> mm | | | |
| 170 | ATD000443.4: Equipotential bonding systems - Yaw slip ring carbon brush 2 - Inspection and measure Carbon brush 2 length <input type="text"/> mm | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 171 | ATD000443.5: Equipotential bonding systems - Yaw slip ring carbon brush 3 - Inspection and measure Carbon brush 3 length mm | | | |
| 172 | ATD000445.0: Equipotential bonding systems - Heli deck handrail - Inspection | | | |
| 173 | ATD000445.1: Equipotential bonding systems - Nacelle grounding straps - Inspection | | | |
| 174 | ATD000445.2: Equipotential bonding systems - Upper nacelle lightning rods - Inspection | | | |
| 175 | ATD000445.3: Equipotential bonding systems - Lateral nacelle lightning rods - Inspection | | | |
| 176 | ATD000445.4: Equipotential bonding systems - Lower nacelle lightning rods - Inspection | | | |
| 177 | ATD000445.5: Equipotential bonding systems - Nacelle back side lightning rods - Inspection | | | |
| 178 | ATD000445.6: Equipotential bonding systems - Cellar platform lightning rods - Inspection | | | |
| 179 | ATD000445.7: Equipotential bonding systems - Grounding strap bolted connection - Inspection | | | |
| 180 | ATD000446.0: UPS - Surge arresters - Inspection | | | |
| 181 | ATD000446.2: Rotor blade 1 - VAL-MS 320/3+1/FM surge arrester of the pitch cabinet - Inspection | | | |
| 182 | ATD000446.3: Rotor blade 1 - PT 3-PB-ST surge arresters (x2) of the pitch cabinet - Inspection | | | |
| 183 | ATD000488.0: Rotor blade 1 - Bearing central lubrication system and elements - Inspection | | | |
| 184 | ATD000488.10: Rotor blade 3 - Bearing central lubrication pinion is greased - Inspection | | | |
| 185 | ATD000488.11: Rotor blade 3 - Bearing pinions area of work is greased - Inspection | | | |
| 186 | ATD000488.12: Blade bearing - Centralized lubrication system - Auditory inspection | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 187 | <p>ATD000488.1: Rotor blade 1 - Grease tank for the blade bearing - Refill and reset strokes, if necessary</p> <p>Grease level before refill <input type="text"/> %</p> <p>Grease level in range?</p> <p>1 <input type="text"/> Yes, it was as needed</p> <p>2 <input type="text"/> Yes, after refill</p> <p>3 <input type="text"/> No, has to be refilled next visit (Case created)</p> | | | |
| 188 | ATD000488.3: Rotor blade 1 - Bearing central lubrication pinion is greased - Inspection | | | |
| 189 | ATD000488.4: Rotor blade 1 - Bearing pinions area of work is greased - Inspection | | | |
| 190 | ATD000488.5: Rotor blade 2 - Bearing central lubrication system and elements - Inspection | | | |
| 191 | <p>ATD000488.6: Rotor blade 2 - Grease tank for the blade bearing - Refill and reset strokes, if necessary</p> <p>Grease level before refill <input type="text"/> %</p> <p>Grease level in range?</p> <p>1 <input type="text"/> Yes, it was as needed</p> <p>2 <input type="text"/> Yes, after refill</p> <p>3 <input type="text"/> No, has to be refilled next visit (Case created)</p> | | | |
| 192 | ATD000488.8: Rotor blade 2 - Bearing central lubrication pinion is greased - Inspection | | | |
| 193 | ATD000488.9: Rotor blade 2 - Bearing pinions area of work is greased - Inspection | | | |
| 194 | ATD000493.0: Rotor system - Fan pitch converter 1 - Inspection | | | |
| 195 | ATD000493.1: Rotor system - Fan pitch converter 2 - Inspection | | | |
| 196 | ATD000493.2: Rotor system - Fan pitch converter 3 - Inspection | | | |
| 197 | ATD000497.00: Offline oil bypass - Filter cartridge - Replace | | | |
| 198 | ATD000498.0: Lightning current measurement system - Antennas and fixations - Inspection | | | |
| 199 | ATD000498.1: Lightning current measurement system - Control box - Inspection | | | |
| 200 | ATD000498.2: Lightning current measurement system - Lightning sensor system - Test | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|---|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 201 | ATD000521.0: Converter - External coolers - Inspection | | | |
| 202 | ATD000521.2: Converter - Fans of the external coolers - Test | | | |
| 203 | ATD000523.0: Air treatment system - Pocket filters - Inspection | | | |
| 204 | ATD000523.1: Air treatment system - Cassette filters - Inspection | | | |
| 205 | ATD000551.0: Yaw system - Thickness of brake pad 1 - Measure Thickness of Svendborg brake pad 1 <input type="text"/> mm Thickness of Stromag brake pad 1 1 <input type="text"/> Green 2 <input type="text"/> Yellow 3 <input type="text"/> Red | | | |
| 206 | ATD000551.10: Yaw system - Thickness of brake pad 11 - Measure Thickness of Svendborg brake pad 11 <input type="text"/> mm Thickness of Stromag brake pad 11 1 <input type="text"/> Green 2 <input type="text"/> Yellow 3 <input type="text"/> Red | | | |
| 207 | ATD000551.11: Yaw system - Thickness of brake pad 12 - Measure Thickness of Svendborg brake pad 12 <input type="text"/> mm Thickness of Stromag brake pad 12 1 <input type="text"/> Green 2 <input type="text"/> Yellow 3 <input type="text"/> Red | | | |
| 208 | ATD000551.12: Yaw system - Thickness of brake pad 13 - Measure Thickness of Svendborg brake pad 13 <input type="text"/> mm Thickness of Stromag brake pad 13 1 <input type="text"/> Green 2 <input type="text"/> Yellow 3 <input type="text"/> Red | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|--|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 209 | <p>ATD000551.13: Yaw system - Thickness of brake pad 14 - Measure</p> <p>Thickness of Svendborg brake pad 14 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 14</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 210 | <p>ATD000551.14: Yaw system - Thickness of brake pad 15 - Measure</p> <p>Thickness of Svendborg brake pad 15 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 15</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 211 | <p>ATD000551.15: Yaw system - Thickness of brake pad 16 - Measure</p> <p>Thickness of Svendborg brake pad 16 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 16</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 212 | <p>ATD000551.16: Yaw system - Thickness of brake pad 17 - Measure</p> <p>Thickness of Svendborg brake pad 17 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 17</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 213 | <p>ATD000551.17: Yaw system - Thickness of brake pad 18 - Measure</p> <p>Thickness of Svendborg brake pad 18 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 18</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 214 | <p>ATD000551.1: Yaw system - Thickness of brake pad 2 - Measure</p> <p>Thickness of Svendborg brake pad 2 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 2</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 215 | <p>ATD000551.2: Yaw system - Thickness of brake pad 3 - Measure</p> <p>Thickness of Svendborg brake pad 3 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 3</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 216 | <p>ATD000551.3: Yaw system - Thickness of brake pad 4 - Measure</p> <p>Thickness of Svendborg brake pad 4 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 4</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 217 | <p>ATD000551.4: Yaw system - Thickness of brake pad 5 - Measure</p> <p>Thickness of Svendborg brake pad 5 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 5</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 218 | <p>ATD000551.5: Yaw system - Thickness of brake pad 6 - Measure</p> <p>Thickness of Svendborg brake pad 6 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 6</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 219 | <p>ATD000551.6: Yaw system - Thickness of brake pad 7 - Measure</p> <p>Thickness of Svendborg brake pad 7 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 7</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 220 | <p>ATD000551.7: Yaw system - Thickness of brake pad 8 - Measure</p> <p>Thickness of Svendborg brake pad 8 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 8</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 221 | <p>ATD000551.8: Yaw system - Thickness of brake pad 9 - Measure</p> <p>Thickness of Svendborg brake pad 9 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 9</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 222 | <p>ATD000551.9: Yaw system - Thickness of brake pad 10 - Measure</p> <p>Thickness of Svendborg brake pad 10 <input type="text"/> mm</p> <p>Thickness of Stromag brake pad 10</p> <p>1 <input type="text"/> Green</p> <p>2 <input type="text"/> Yellow</p> <p>3 <input type="text"/> Red</p> | | | |
| 223 | <p>ATD000556.0: Hydraulic system - Valve 500 (Rotor lock applied) - Check pressure at MB</p> <p>Pressure at MB <input type="text"/> bar</p> | | | |
| 224 | <p>ATD000556.1: Hydraulic system - Valve 490 (Rotor unlocked) - Check pressure at MA</p> <p>Pressure at MA <input type="text"/> bar</p> | | | |
| 225 | <p>ATD000556.2: Hydraulic system - Valves 860.1 & 860.2 (Rotor brakes applied) - Check pressure at M2 and M4 and in Visu 900.1 & 900.2 (Hydratech) or 905.1 & 905.2 (Hydac)</p> <p>Pressure at M2 <input type="text"/> bar</p> <p>Pressure at M4 <input type="text"/> bar</p> <p>Pressure in Visu 900.1 (Hydratech) or 905.1 (Hydac) <input type="text"/> bar</p> <p>Pressure in Visu 900.2 (Hydratech) or 905.2 (Hydac) <input type="text"/> bar</p> | | | |
| 226 | <p>ATD000556.3: Hydraulic system - Valve 670.1 and 670.2 (Pressure yaw brake 25% button activated) - Check pressure at M1 (750.1) & M3 (750.2) and 720.1 & 720.2</p> <p>Pressure at M1 (750.1) <input type="text"/> bar</p> <p>Pressure at M3 (750.2) <input type="text"/> bar</p> | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|---|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| | Pressure at 720.1 | | | |
| | Pressure at 720.2 | | | |
| 227 | ATD000556.4: Hydraulic system - Valves 320.1 and 320.2 (Valves 350.3, 350.4 and 350.5 closed and pump 1 running) - Check pressure at digital switch 360 | | | |
| | Pressure at digital switch 360 | | | |
| 228 | ATD000556.5: Hydraulic system - Valves 320.1 and 320.2 (Valves 350.3, 350.4 and 350.5 closed and pump 2 running) - Check pressure at digital switch 360 | | | |
| | Pressure at digital switch 360 | | | |
| 229 | ATD000556.6: Hydraulic system - Ball valves 290.1, 590 and 1080 - Inspection | | | |
| 230 | ATD000591.0: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing - Inspection | | | |
| 231 | ATD000591.1: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing teeth involved - Inspection | | | |
| 232 | ATD000591.2-10: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth -20 right side gap - Measure | | | |
| | Gap upper position | | | |
| | Gap middle position | | | |
| | Gap lower position | | | |
| 233 | ATD000591.2-11: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth -30 left side gap - Measure | | | |
| | Gap upper position | | | |
| | Gap middle position | | | |
| | Gap lower position | | | |
| 234 | ATD000591.2-12: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth -30 right side gap - Measure | | | |
| | Gap upper position | | | |
| | Gap middle position | | | |
| | Gap lower position | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|---|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 235 | ATD000591.2-1: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 236 | ATD000591.2-2: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 237 | ATD000591.2-3: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth +1 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 238 | ATD000591.2-4: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth +1 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 239 | ATD000591.2-5: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth -1 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 240 | ATD000591.2-6: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth -1 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 241 | ATD000591.2-7: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth -10 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 242 | ATD000591.2-8: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth -10 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 243 | ATD000591.2-9: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 1 - Blade bearing 0° tooth -20 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 244 | ATD000591.3: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing - Inspection | | | |
| 245 | ATD000591.4: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing teeth involved - Inspection | | | |
| 246 | ATD000591.5-10: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth -20 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 247 | ATD000591.5-11: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth -30 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 248 | ATD000591.5-12: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth -30 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 249 | ATD000591.5-1: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 250 | ATD000591.5-2: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 251 | ATD000591.5-3: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth +1 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 252 | ATD000591.5-4: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth +1 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 253 | ATD000591.5-5: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth -1 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 254 | ATD000591.5-6: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth -1 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 255 | ATD000591.5-7: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth -10 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 256 | ATD000591.5-8: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth -10 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |

AD 5-135_1_1_5_Preventive_year_7.0













| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 257 | ATD000591.5-9: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 2 - Blade bearing 0° tooth -20 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 258 | ATD000591.6: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing - Inspection | | | |
| 259 | ATD000591.7: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing teeth involved - Inspection | | | |
| 260 | ATD000591.8-10: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth -20 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 261 | ATD000591.8-11: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth -30 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 262 | ATD000591.8-12: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth -30 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 263 | ATD000591.8-1: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|---|---------|-------|--------|
| Location: | | | | |
| 264 | ATD000591.8-2: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 265 | ATD000591.8-3: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth +1 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 266 | ATD000591.8-4: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth +1 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 267 | ATD000591.8-5: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth -1 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 268 | ATD000591.8-6: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth -1 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|--|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 269 | ATD000591.8-7: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth -10 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 270 | ATD000591.8-8: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth -10 right side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 271 | ATD000591.8-9: (WK09, WK10, WK32, WK45, WK46, WK49, WK69) Rotor blade 3 - Blade bearing 0° tooth -20 left side gap - Measure Gap upper position <input type="text"/> mm Gap middle position <input type="text"/> mm Gap lower position <input type="text"/> mm | | | |
| 272 | ATD000614.0: Rotor brake - Calliper 1 - Clean | | | |
| 273 | ATD000614.10: Rotor brake - Calliper 3 - Clean | | | |
| 274 | ATD000614.13: Rotor brake - Thickness of rotor brake pad calliper 3 (rotor side) - Measure Wear of rotor brake pad calliper 3 (rotor side) <input type="text"/> mm Wear of rotor brake pad calliper 3 (rotor side) picture Image card | | | |
| 275 | ATD000614.14: Rotor brake - Thickness of rotor brake pad calliper 3 (generator side) - Measure Wear of rotor brake pad calliper 3 (generator side) <input type="text"/> mm Wear of rotor brake pad calliper 3 (generator side) picture Image card | | | |
| 276 | ATD000614.15: Rotor brake - Calliper 4 - Clean | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|--|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 277 | ATD000614.18: Rotor brake - Thickness of rotor brake pad calliper 4 (rotor side) - Measure Wear of rotor brake pad calliper 4 (rotor side) <input type="text"/> mm Wear of rotor brake pad calliper 4 (rotor side) picture Image card | | | |
| 278 | ATD000614.19: Rotor brake - Thickness of rotor brake pad calliper 4 (generator side) - Measure Wear of rotor brake pad calliper 4 (generator side) <input type="text"/> mm Wear of rotor brake pad calliper 4 (generator side) picture Image card | | | |
| 279 | ATD000614.20: Rotor brake - Calliper 5 - Clean | | | |
| 280 | ATD000614.23: Rotor brake - Thickness of rotor brake pad calliper 5 (rotor side) - Measure Wear of rotor brake pad calliper 5 (rotor side) <input type="text"/> mm Wear of rotor brake pad calliper 5 (rotor side) picture Image card | | | |
| 281 | ATD000614.24: Rotor brake - Thickness of rotor brake pad calliper 5 (generator side) - Measure Wear of rotor brake pad calliper 5 (generator side) <input type="text"/> mm Wear of rotor brake pad calliper 5 (generator side) picture Image card | | | |
| 282 | ATD000614.25: Rotor brake - Calliper 6 - Clean | | | |
| 283 | ATD000614.28: Rotor brake - Thickness of rotor brake pad calliper 6 (rotor side) - Measure Wear of rotor brake pad calliper 6 (rotor side) <input type="text"/> mm Wear of rotor brake pad calliper 6 (rotor side) picture Image card | | | |
| 284 | ATD000614.29: Rotor brake - Thickness of rotor brake pad calliper 6 (generator side) - Measure Wear of rotor brake pad calliper 6 (generator side) <input type="text"/> mm Wear of rotor brake pad calliper 6 (generator side) picture Image card | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|--|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 285 | ATD000614.30: Rotor brake - Rotor brake, sensors fixations to the Beckhoff module - Inspection Module of the right side picture  Module of the left side picture  Module of the upper side picture  | | | |
| 286 | ATD000614.31: Rotor brake - Rotor brake pad, resistance of the connectors - Measure Resistance between pin 1 and 2  Ohm Resistance between pin 1 and 3  Ohm Resistance between pin 1 and 4  Ohm Resistance between pin 2 and 3  Ohm Resistance between pin 2 and 4  Ohm Resistance between pin 3 and 4  Ohm | | | |
| 287 | ATD000614.3: Rotor brake - Thickness of rotor brake pad calliper 1 (rotor side) - Measure Wear of rotor brake pad calliper 1 (rotor side)  mm Wear of rotor brake pad calliper 1 (rotor side) picture Image card | | | |
| 288 | ATD000614.4: Rotor brake - Thickness of rotor brake pad calliper 1 (generator side) - Measure Wear of rotor brake pad calliper 1 (generator side)  mm Wear of rotor brake pad calliper 1 (generator side) picture Image card | | | |
| 289 | ATD000614.5: Rotor brake - Calliper 2 - Clean | | | |
| 290 | ATD000614.8: Rotor brake - Thickness of rotor brake pad calliper 2 (rotor side) - Measure Wear of rotor brake pad calliper 2 (rotor side)  mm Wear of rotor brake pad calliper 2 (rotor side) picture Image card | | | |

AD 5-135_1_1_5_Preventive_year_7.0

| # | Measuring points | Remarks | Tools | Status |
|-----------|--|---------|-------|--------|
| Location: | | | | |
| 291 | ATD000614.9: Rotor brake - Thickness of rotor brake pad calliper 2 (generator side) - Measure Wear of rotor brake pad calliper 2 (generator side) mm Wear of rotor brake pad calliper 2 (generator side) picture Image card | | | |
| 292 | ATD000615.0: Installation system - Emergency light of P7 - Test | | | |
| 293 | ATD000615.1: Installation system - Emergency light of P6 - Test | | | |
| 294 | ATD000615.2: Installation system - Emergency light of P5 - Test | | | |
| 295 | ATD000615.3: Installation system - Emergency light of P4 - Test | | | |
| 296 | ATD000615.4: Installation system - Emergency light of S2 and S1 - Test | | | |
| 297 | ATD000615.5: Installation system - Emergency light of P3 - Test | | | |
| 298 | ATD000615.6: Installation system - Emergency light of P2 - Test | | | |
| 299 | ATD000615.7: Installation system - Emergency light of P1 - Test | | | |
| 300 | ATD000615.8: Installation system - Emergency light of lower deck - Test | | | |
| 301 | ATD000615.9: Installation system - Emergency light of nacelle - Test | | | |
| 302 | ATD000638.0: Drive train system - Surface of the gearbox - Inspection | | | |
| 303 | ATD000638.10: Drive train system - Torque arms of the gearbox - Inspection | | | |
| 304 | ATD000638.12: Drive train system - Rotor hollow shaft and the center tube interface (from inside the hub) - Inspection | | | |
| 305 | ATD000638.13: Drive train system - Rotor bearing - Inspection | | | |
| 306 | ATD000638.5: Drive train system - Surface of the hollow shaft (from inside the hub) - Inspection | | | |
| 307 | ATD000638.7: Drive train system - O-ring between the gearbox housing and the callipers plate - Inspection | | | |
| 308 | ATD000638.8: Drive train system - O-ring between the brake disc and the callipers plate - Inspection | | | |
| 309 | ATD000642.0: Rotor blade 1 - Encoder, encoder support, wires, teeth and connector - Inspection | | | |
| 310 | ATD000642.1: Rotor blade 2 - Encoder, encoder support, wires, teeth and connector - Inspection | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|---|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 311 | ATD000642.2: Rotor blade 3 - Encoder, encoder support, wires, teeth and connector - Inspection | | | |
| 312 | ATD000643.0: Hub - Central lubrication components - Inspection | | | |
| 313 | ATD000643.10: Rotor blade 2 - Lubrication pinion & pinion support - Inspection | | | |
| 314 | ATD000643.12: Rotor blade 3 - Lubrication pinion & pinion support - Inspection | | | |
| 315 | ATD000643.14: Rotor blade 3 - Central lubrication components - Auditory inspection | | | |
| 316 | ATD000643.15: Rotor blade 2 - Central lubrication components - Auditory inspection | | | |
| 317 | ATD000643.16: Rotor blade 1 - Central lubrication components - Auditory inspection | | | |
| 318 | ATD000643.17: Rotor blade 3 - Lubrication system relief valve - Inspection | | | |
| 319 | ATD000643.18: Rotor blade 2 - Lubrication system relief valve - Inspection | | | |
| 320 | ATD000643.19: Rotor blade 1 - Lubrication system relief valve - Inspection | | | |
| 321 | ATD000643.1: Rotor blade 1 - Grease tank for the blade gear rims - Refill and reset strokes, if necessary Grease level before refill <input type="text"/> % Grease level in range? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 322 | ATD000643.4: Rotor blade 2 - Grease tank for the blade bearing - Inspection | | | |
| 323 | ATD000643.5: Rotor blade 2 - Grease tank for the blade gear rims - Refill and reset strokes, if necessary Grease level before refill <input type="text"/> % Grease level in range? 1 <input type="text"/> Yes, it was as needed 2 <input type="text"/> Yes, after refill 3 <input type="text"/> No, has to be refilled next visit (Case created) | | | |
| 324 | ATD000643.8: Rotor blade 1 - Lubrication pinion & pinion support - Inspection | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|---|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 325 | ATD000670.0: Lightning protection blade 1 - Sheath of LPS cable - Inspection | | | |
| 326 | ATD000670.1: Lightning protection blade 1 - Connection point of the LPS cable in the bearing - Inspection | | | |
| 327 | ATD000670.2: Lightning protection blade 1 - Bolted joint of the electrical connections - Inspection | | | |
| 328 | ATD000670.3: Lightning protection blade 2 - Sheath of LPS cable - Inspection | | | |
| 329 | ATD000670.4: Lightning protection blade 2 - Connection point of the LPS cable in the bearing - Inspection | | | |
| 330 | ATD000670.5: Lightning protection blade 2 - Bolted joint of the electrical connections - Inspection | | | |
| 331 | ATD000670.6: Lightning protection blade 3 - Sheath of LPS cable - Inspection | | | |
| 332 | ATD000670.7: Lightning protection blade 3 - Connection point of the LPS cable in the bearing - Inspection | | | |
| 333 | ATD000670.8: Lightning protection blade 3 - Bolted joint of the electrical connections - Inspection | | | |
| 334 | ATD000691.0: Brake disk - Upper grounding reels - Inspection | | | |
| 335 | ATD000691.1: Brake disk - Right grounding reels - Inspection | | | |
| 336 | ATD000691.2: Brake disk - Left grounding reels - Inspection | | | |
| 337 | ATD000692.0: Rotor blade 1 - Pitch motor brushes - Inspection | | | |
| 338 | ATD000692.10: Rotor blade 3 - Pitch motor brushes - Inspection | | | |
| 339 | ATD000692.11: Rotor blade 3 - Pitch motor brushes wear - Measure Length of the shortest carbon brush <input type="text"/> mm | | | |
| 340 | ATD000692.12: Rotor blade 3 - Pitch motor slip ring traces - Inspection | | | |
| 341 | ATD000692.1: Rotor blade 1 - Pitch motor brushes wear - Measure Length of the shortest carbon brush <input type="text"/> mm | | | |
| 342 | ATD000692.2: Rotor blade 1 - Pitch motor slip ring traces - Inspection | | | |
| 343 | ATD000692.5: Rotor blade 2 - Pitch motor brushes - Inspection | | | |
| 344 | ATD000692.6: Rotor blade 2 - Pitch motor brushes wear - Measure Length of the shortest carbon brush <input type="text"/> mm | | | |

| AD 5-135_1_1_5_Preventive_year_7.0 | | | | |
|------------------------------------|--|---------|-------|--------|
| # | Measuring points | Remarks | Tools | Status |
| Location: | | | | |
| 345 | ATD000692.7: Rotor blade 2 - Pitch motor slip ring traces - Inspection | | | |
| 346 | ATD000693.0: Rotor blade 1 - Pitch motor collector room - Clean | | | |
| 347 | ATD000693.1: Rotor blade 2 - Pitch motor collector room - Clean | | | |
| 348 | ATD000693.2: Rotor blade 3 - Pitch motor collector room - Clean | | | |
| 349 | ATD000695.0: Rotor blade 1 - Pitch motor and gearbox - Inspection | | | |
| 350 | ATD000695.1: Rotor blade 2 - Pitch motor and gearbox - Inspection | | | |
| 351 | ATD000695.2: Rotor blade 3 - Pitch motor and gearbox - Inspection | | | |
| 352 | ATD000704.0: ventilation system - Drainage conduits on TP - Inspection | | | |
| 353 | ATD000704.1: ventilation system - Drainage conduits on P7 - Inspection | | | |
| 354 | ATD000704.2: ventilation system - Drainage conduits on P6 - Inspection | | | |
| 355 | ATD000704.3: ventilation system - Drainage conduits on P5 - Inspection | | | |
| 356 | ATD000704.4: ventilation system - Drainage conduits on P4 - Inspection | | | |
| Location: Tower | | | | |
| 357 | ATD000704.5: Transition piece - Main transformer oil spill conduit and barrel - Inspection | | | |
| 358 | ATD000704.6: P7 - Main transformer oil spill conduit - Inspection | | | |
| Location: | | | | |
| 359 | ATD000719.0: Air treatment system - Ball siphon valves - Inspection | | | |
| 360 | ATD000719.1: Air treatment system - Ball siphon valves - Test | | | |