

Week-6: Code-along

NM2207: Computational Media Literacy

2023-09-18

II. Code to edit and execute using the Code-along-6.Rmd file

A. for loop

1. Simple for loop (Slide #6)

```
for (x in c(3, 6, 9)) {  
  print(x)  
}
```

```
## [1] 3  
## [1] 6  
## [1] 9
```

2. for loops structure (Slide #7)

```
for (x in 1:8) {print(x)}
```

```
## [1] 1  
## [1] 2  
## [1] 3  
## [1] 4  
## [1] 5  
## [1] 6  
## [1] 7  
## [1] 8
```

```
for (x in 1:8)  
{y <- seq(from=100,to=200,by=5)  
  print(y[x])}
```

```
## [1] 100
## [1] 105
## [1] 110
## [1] 115
## [1] 120
## [1] 125
## [1] 130
## [1] 135
```

3. Example: find sample means (Slide #9)

```
sample_sizes <- c(5, 10, 15, 20, 25000)
sample_means <- double(length(sample_sizes))
for (i in seq_along(sample_sizes)) {
  sample_means[i] <- mean(rnorm(sample_sizes[i]))
}
sample_means
```

```
## [1] 0.340739735 -0.247494849 0.085597512 -0.146461423 0.006896449
```

4. Alternate ways to pre-allocate space (Slide #12)

```
sample_means <- vector("double", length = 5)
sample_means <- double(5)
sample_means <- rep(0, length(sample_sizes))
```

```
sample_sizes <- c(5, 10, 15, 20, 25000)
sample_means <- rep(0, length(sample_sizes))
for (i in seq_along(sample_sizes)) {
  sample_means[i] <- mean(rnorm(sample_sizes[i]))
}
```

5. Review: Vectorized operations (Slide #18)

```
a <- 7:11
b <- 8:12
out <- rep(0L, 5)
for (i in seq_along(a)) {
  out[i] <- a[i] + b[i]
}
out
```

```
## [1] 15 17 19 21 23
```

```
a <- 7:11
b <- 8:12
out <- a + b
out
```

```
## [1] 15 17 19 21 23
```

B. Functionals

6. for loops vs Functionals (Slides #23 and #24)

```
sample_sizes <- c(5, 10, 15, 20, 25000)
sample_summary <- function(sample_sizes, fun) {
  out <- vector("double", length(sample_sizes))
  for (i in seq_along(sample_sizes)) {
    out[i] <- fun(rnorm(sample_sizes[i]))
  }
  return(out)
}
```

```
sample_summary(sample_sizes, mean)

sample_summary(sample_sizes, median)

sample_summary(sample_sizes, sd)
```

C. while loop

7. while loop (Slides #27)

```
for(i in 1:5){
  print(i)
}
```

```
## [1] 1
## [1] 2
## [1] 3
## [1] 4
## [1] 5
```

```
i <- 1
while (i <= 5) {
  print(i)
  i <- i + 1
}
```

```
## [1] 1
## [1] 2
## [1] 3
## [1] 4
## [1] 5
```