c0a2511850 / ProjExD_2

Code Issues 1 Pull requests Actions Projects Wiki More

Commits

main

All users All time

Commits on Apr 21, 2026

追加機能３実装中コメント修正
f412ac5
c0a2511850 committed 5 minutes ago

追加機能３実装中
499bd42
c0a2511850 committed 24 minutes ago

練習4
c3aa078
c0a2511850 committed 2 hours ago

練習3
39580de
c0a2511850 committed 2 hours ago

練習2
78c70ca
c0a2511850 committed 3 hours ago

練習1
c4944bc
c0a2511850 committed 3 hours ago

初期状態
eaa858e
c0a2511850 committed 4 hours ago

c0a2511850 / ProjExD_2

Code Issues 1 Pull requests Actions Projects Wiki More

main ProjExD_2 / dodge_bomb.py Go to file T

c0a2511850 追加機能３実装中コメント修正 f412ac5 · 6 minutes ago

153 lines (134 loc) · 4.43 KB

main ProjExD_2 / dodge_bomb.py Top

Code Blame Raw

```python
import pygame as pg


WIDTH, HEIGHT = 1100, 650
DELTA = {
    pg.K_UP: (0,-10),
    pg.K_DOWN: (0,+10),
    pg.K_LEFT: (-10,0),
    pg.K_RIGHT: (+10,0),
}
os.chdir(os.path.dirname(os.path.abspath(__file__)))
def get_kk_imgs(kk_img: pg.Surface) -> dict[tuple[int, int], pg.Surface]:
    hidari=kk_img
    migi=pg.transform.flip(hidari,True,False)
    kk_dict = {
        ( 0, 0):pg.transform.rotozoom(migi, 0, 1.0),
        ( 0, -5):pg.transform.rotozoom(migi, 90, 1.0),#上
        ( +5, -5):pg.transform.rotozoom(migi, 45, 1.0),#右上
        ( +5, 0):pg.transform.rotozoom(migi, 0, 1.0),#右
        ( +5, +5):pg.transform.rotozoom(migi, -45, 1.0),#右下
        ( 0, +5):pg.transform.rotozoom(migi, -90, 1.0),#下
        ( -5, +5):pg.transform.rotozoom(hidari, 45, 1.0),#左下
        ( -5, 0):pg.transform.rotozoom(hidari, 0, 1.0),#左
        ( -5, -5):pg.transform.rotozoom(hidari, -45, 1.0),#左上
    }
    return kk_dict

def gameover(screen: pg.Surface) -> None:
    """
    ゲームオーバー画面

    引数：画面Surface
    戻り値：なし
    """
    # 黒背景
    black = pg.Surface(screen.get_size())
    pg.Rect(0, 0, 1100, 650)
    black.set_alpha(200)
```

```python

        if black.get_alpha() is None:
            black.set_alpha(200)

        # フォント
        font = pg.font.Font(None, 80)
        text = font.render("Game Over", True, (255, 255, 255))
        text_rect = text.get_rect()
        text_rect.center = screen.get_rect().center

        # こうかとん画像（左）
        kk_img_left = pg.image.load("fig/8.png")
        kk_rct_left = kk_img_left.get_rect()

        # こうかとん画像（右）
        kk_img_right = pg.image.load("fig/8.png")
        kk_rct_right = kk_img_right.get_rect()

        # 配置（文字の左右）
        kk_rct_left.center = (text_rect.left - 100, text_rect.centery)
        kk_rct_right.center = (text_rect.right + 100, text_rect.centery)

        # 描画
        screen.blit(black, (0, 0))
        screen.blit(text, text_rect)
        screen.blit(kk_img_left, kk_rct_left)
        screen.blit(kk_img_right, kk_rct_right)

        pg.display.update()
        time.sleep(5)
    def check_bound(rct):
        """
        引数：効果とんRectかばくだんRect
        戻り値：横方向、縦方向判定結果（True：画面内　False：画面外）
        """
        yoko, tate =True, True
        if rct.left < 0 or WIDTH < rct.right:
            yoko = False
        if rct.top < 0 or HEIGHT < rct.bottom:
            tate = False
        return yoko, tate

    def main():
        pg.display.set_caption("逃げろ！こうかとん")
        screen = pg.display.set_mode((WIDTH, HEIGHT))
        bg_img = pg.image.load("fig/pg_bg.jpg")
        kk_img = pg.transform.rotozoom(pg.image.load("fig/3.png"), 0, 0.9)
        bb_img = pg.Surface((20,20))
        pg.draw.circle(bb_img, (255, 0, 0,),(10, 10), 10)
        bb_img.set_colorkey((0, 0, 0))
        kk_rct = kk_img.get_rect()
        kk_hidari = pg.image.load("fig/3.png")
        kk_imgs = get_kk_imgs(kk_hidari)
        bb_rct = bb_img.get_rect()
        kk_rct.center = 300, 200
        bb_rct.centerx = random.randint(0,WIDTH)
        bb_rct.centery = random.randint(0, HEIGHT)
        vx, vy = +5, +5
```

```python
        clock = pg.time.Clock()
        tmr = 0
        while True:
            for event in pg.event.get():
                if event.type == pg.QUIT:
                    return
            if kk_rct.colliderect(bb_rct):
                return # 衝突したらゲームオーバー

            screen.blit(bg_img, [0, 0])

            key_lst = pg.key.get_pressed()
            sum_mv = [0, 0]
            # if key_lst[pg.K_UP]:
            #     sum_mv[1] -= 5
            # if key_lst[pg.K_DOWN]:
            #     sum_mv[1] += 5
            # if key_lst[pg.K_LEFT]:
            #     sum_mv[0] -= 5
            # if key_lst[pg.K_RIGHT]:
            #     sum_mv[0] += 5
            for key, mv in DELTA.items():
                if key_lst[key]:
                    sum_mv[0] += mv[0]
                    sum_mv[1] += mv[1]
            kk_rct.move_ip(sum_mv)
            if check_bound(kk_rct) != (True, True):
                kk_rct.move_ip(-sum_mv[0], -sum_mv[1])
            kk_img = kk_imgs[tuple(sum_mv)]
            screen.blit(kk_img, kk_rct)
            bb_rct.move_ip(vx, vy)
            yoko, tate=check_bound(bb_rct)
            if not yoko:# 横方向判定
                vx *= -1
            if not tate:
                vy *= -1
            screen.blit(bb_img, bb_rct)
            pg.display.update()
            tmr += 1
            clock.tick(50)
            if kk_rct.colliderect(bb_rct):
                gameover(screen)
                return




    if __name__ == "__main__":
        pg.init()
        main()
        pg.quit()
        sys.exit()
```

c0a2511850 / ProjExD_2

Code Issues 1 Pull requests Actions Projects Wiki More

is:issue state:open

Labels Milestones New issue

Open 1 Closed 0 Author Labels Projects

見やすさについて

#1 · c0a251747f opened 7 minutes ago

Give feedback