

Environment Variables Reference

Complete reference for every environment variable recognized by OmniRoute. For a quick-start template, see `.env.example`.

[!IMPORTANT] Every variable documented here must also appear in `.env.example`, and every variable in `.env.example` must appear here. `npm run check:env-doc-sync` enforces this on commit and in CI. To omit a variable on purpose, add it to the allowlist inside `scripts/check-env-doc-sync.mjs`.

Table of Contents

- 1. Required Secrets
- 2. Storage & Database
- 3. Network & Ports
- 4. Security & Authentication
- 5. Input Sanitization & PII Protection
- 6. Tool & Routing Policies
- 7. URLs & Cloud Sync
- 8. Outbound Proxy
- 9. CLI Tool Integration
- 10. Internal Agent & MCP Integrations
- 11. OAuth Provider Credentials
- 12. Provider User-Agent Overrides
- 13. CLI Fingerprint Compatibility
- 14. API Key Providers
- 15. Timeout Settings
- 16. Logging
- 17. Memory Optimization
- 18. Pricing Sync
- 19. Model Sync (Dev)
- 20. Provider-Specific Settings
- 21. Proxy Health
- 22. Debugging
- 23. GitHub Integration
- 24. Skills Sandbox (v3.8.0+)
- Deployment Scenarios
- Audit: Removed / Dead Variables

1. Required Secrets

These **must** be set before the first run. Without them, the application will either refuse to start or operate with insecure defaults.

Variable	Required	Default	Source File	Description
JWT_SECRET	Yes	(none)	src/lib/auth	Signs/verifies all dashboard session cookies (JWT). Generate with <code>openssl rand -base64 48</code> .
API_KEY_SECRET	Yes	(none)	src/lib/db/apiKeys.ts	AES encryption key for API key values at rest in SQLite. Generate with <code>openssl rand -hex 32</code> .
INITIAL_PASSWORD	Yes	CHANGEME	Bootstrap script	Sets the initial admin dashboard password (matches <code>.env.example</code> default — kept obviously insecure to force a change). Change before first use. After login, change via Dashboard → Settings → Security.
OMNIRoute_WS_BRIDGE_SECRET	Yes (production)	(unset)	src/app/api/internal/codex-responses-ws/route.ts	Shared secret for the internal Codex Responses WebSocket bridge. Authenticates bridge requests between the Electron/browser WS relay and OmniRoute. REQUIRED in production — when unset, all WS bridge requests are rejected. Generate with <code>openssl rand -base64 32</code> .
OMNIRoute_PEER_STAMP_TOKEN	No (auto)	(auto per boot)	src/server/authz/policies/management.ts	Per-process secret proving the trusted peer-IP stamp came from OmniRoute's own HTTP server (<code>scripts/dev/peer-stamp.mjs</code>). The authz middleware trusts request locality (loopback/LAN gating of <code>LOCAL_ONLY</code> routes) only when the stamp carries this token. Auto-generated each boot — leave unset; only pin it for multi-process setups that must share the stamp.

Generation Commands

```
# Generate all four secrets at once:
echo "JWT_SECRET=\$(openssl rand -base64 48)"
echo "API_KEY_SECRET=\$(openssl rand -hex 32)"
echo "INITIAL_PASSWORD=\$(openssl rand -base64 16)"
echo "OMNIRoute_WS_BRIDGE_SECRET=\$(openssl rand -base64 32)"
```

[!CAUTION] Never commit `.env` files with real secrets to version control. The `.gitignore` already excludes `.env`, but verify before pushing.

2. Storage & Database

OmniRoute uses **SQLite** (via `better-sqlite3`) for all persistence. These variables control data location, encryption, and lifecycle.

Variable	Default	Source File	Description
DATA_DIR	~/omniroute/	src/lib/db/core.ts	Root directory for SQLite DB, backups, and data files. Override for Docker volumes or custom paths.
STORAGE_ENCRYPTION_KEY	(empty = disabled)	src/lib/db/encryption.ts	AES key for full SQLite database encryption at rest. Generate with <code>openssl rand -hex 32</code> .
STORAGE_ENCRYPTION_KEY_VERSION	v1	scripts/build/bootstrap-env.mjs, electron/main.js	Version label for the encryption key. Increment when performing key rotation to support decryption of old backups.
DISABLE_SQLITE_AUTO_BACKUP	false	src/lib/db/backup.ts	When true, skips the automatic database backup that runs before migrations on every startup.
OMNIROUTE_CRYPT_KEY	(unset)	src/lib/db/encryption.ts	Legacy alias for STORAGE_ENCRYPTION_KEY. Accepted as a fallback when the primary variable is absent.
OMNIROUTE_API_KEY_BASE64	(unset)	src/lib/db/encryption.ts	Legacy alias (Base64-encoded form) accepted as a fallback. Decoded automatically before use.
OMNIROUTE_DB_HEALTHCHECK_INTERVAL_MS	(unset)	src/lib/db/core.ts	Override the periodic SQLite healthcheck interval (ms). When unset, defaults are derived from <code>NODE_ENV</code> .
OMNIROUTE_SKIP_DB_HEALTHCHECK	0	src/lib/db/core.ts, src/lib/db/healthCheck.ts	Set to 1 to skip the DB healthcheck entirely on startup. Useful for short-lived tasks and integration tests.
OMNIROUTE_FORCE_DB_HEALTHCHECK	0	src/lib/db/core.ts	Set to 1 to force the DB healthcheck loop on, even when it would normally be skipped (e.g., short-lived tasks).
OMNIROUTE_SKIP_POSTINSTALL	0	scripts/postinstall.mjs	Set to 1 to skip the native-runtime warm-up during <code>npm install</code> . Useful in CI/headless installs where <code>sqlite</code> is already built.
OMNIROUTE_MIGRATIONS_DIR	(auto-detect)	src/lib/db/migrationRunner.ts	Override the directory that the migration runner scans. Useful when shipping bundled migrations in custom builds.
OMNIROUTE_SPEND_FLUSH_INTERVAL_MS	(default in code)	src/lib/spend/batchWriter.ts	Flush interval (ms) for the batched spend/cost writer. Lower values reduce write coalescing; higher values reduce DB contention.
OMNIROUTE_SPEND_MAX_BUFFER_SIZE	(default in code)	src/lib/spend/batchWriter.ts	Max buffered spend entries before a forced flush. Raise on high-QPS deployments; lower when bounded memory matters more.
OMNIROUTE_PROXY_FETCH_DEBUG	(unset)	open-sse/utils/proxyFetch.ts	Set to "true" to emit [ProxyFetch] debug logs on the Vercel relay path. Off by default to avoid leaking routing hints.
BATCH_RETRY_DURATION_MS	86400000 (24h)	open-sse/services/batchProcessor.ts	Maximum retry window for individual batch items (ms). Items exceeding this duration are marked failed.
BATCH_BACKOFF_BASE_MS	5000	open-sse/services/batchProcessor.ts	Base delay (ms) for exponential backoff on batch item retries.
BATCH_BACKOFF_MAX_MS	3600000 (1h)	open-sse/services/batchProcessor.ts	Cap (ms) for exponential backoff between batch item retries.
BATCH_MAX_CONCURRENT	1	open-sse/services/batchProcessor.ts	Maximum number of batches processed concurrently. Raise to increase throughput; keep low to avoid rate-limit storms.

Scenarios

Scenario	Configuration
Local development	Leave all defaults. DB lives at <code>~/omniroute/omniroute.db</code> .
Docker	<code>DATA_DIR=/data</code> + mount a volume at <code>/data</code> .
Encrypted at rest	Set <code>STORAGE_ENCRYPTION_KEY</code> + keep backups of the key! Losing it = losing data.
CI/Testing	<code>DATA_DIR=/tmp/omniroute-test</code> — ephemeral, no encryption needed.

3. Network & Ports

Variable	Default	Source File	Description
PORT	20128	src/lib/runtime/ports.ts	Primary port for both Dashboard UI and API endpoints (single-port mode).
API_PORT	(unset)	src/lib/runtime/ports.ts	When set, serves the <code>/v1/*</code> proxy API on this separate port.
API_HOST	0.0.0.0	src/lib/runtime/ports.ts	Bind address for the API port.
DASHBOARD_PORT	(unset)	src/lib/runtime/ports.ts	When set, serves the Dashboard UI on this separate port.
PROD_DASHBOARD_PORT	20130	docker-compose.prod.yml	Host-side published port for the Dashboard in Docker production mode.

Variable	Default	Source File	Description
PROD_API_PORT	20131	docker-compose.prod.yml	Host-side published port for the API in Docker production mode.
OMNIROUTE_PORT	(unset)	src/lib/runtime/ports.ts	Takes precedence over PORT when running inside Electron or other wrappers.
LIVE_WS_PORT	20129	src/server/ws/liveServer.ts	Port for the real-time WebSocket live monitoring server.
LIVE_WS_HOST	127.0.0.1	src/server/ws/liveServer.ts	Bind address for the live WebSocket server. Set to 0.0.0.0 to expose on LAN (also configure LIVE_WS_ALLOWED_ORIGINS).
LIVE_WS_ALLOWED_ORIGINS	(unset)	src/server/ws/liveServer.ts	Comma-separated extra origins allowed to open a live WebSocket. Loopback dashboard origins are already permitted by default.
OMNIROUTE_ENABLE_LIVE_WS	false	src/server/ws/liveServer.ts	Set to 1 or true to enable the real-time WebSocket server (disabled by default).
OMNIROUTE_DISABLE_LIVE_WS	false	scripts/start-ws-server.mjs	CI/harness toggle that disables the standalone live WebSocket helper script.
RELAY_IP_PER_MINUTE	30	src/app/api/v1/relay/chat/completions/route.ts	Per-(token, IP) relay rate limit, requests/minute. In-memory, per instance. 0 or negative disables the IP-dimension gate (per-token DB limit still applies).
NODE_ENV	production	Next.js core	Controls logging verbosity, caching, error detail exposure, and Next.js optimizations.
OMNIROUTE_USE_TURBOPACK	1 (default in .env.example)	package.json / Next.js 16	Toggles the Next.js 16 Turbopack bundler in npm run dev and npm run build. Set to 0 on Windows or when running into native binding incompatibilities.
OMNIROUTE_SKIP_DB_HEALTHCHECK	(unset)	src/lib/db/core.ts / src/lib/db/healthCheck.ts	Set to 1 to skip the SQLite integrity health check on startup. Useful for faster boot on large databases.
CREDENTIAL_HEALTH_CHECK_INTERVAL	300000	open-sse/config/constants.ts / src/lib/credentialHealth/scheduler.ts	Interval (ms) for the background credential health check scheduler. Minimum: 10000 (10s).
CREDENTIAL_HEALTH_CACHE_TTL	300000	open-sse/config/constants.ts / src/lib/credentialHealth/cache.ts	TTL (ms) for cached credential health status.
OMNIROUTE_DISABLE_CREDENTIAL_HEALTH_CHECK	false	src/lib/credentialHealth/scheduler.ts	Set to 1 or true to disable background periodic testing of provider connections.
HOST	0.0.0.0	scripts/dev/run-next.mjs	Bind address for the Next.js dev/start server. Overrides the default 0.0.0.0 when set.
HOSTNAME	127.0.0.1	scripts/dev/run-next-playwright.mjs	Bind address used by the Playwright runner when launching Next.js. Defaults to 127.0.0.1 for hermetic tests.

Port Modes

Single Port (default)

PORT=20128

→ Dashboard: http://localhost:20128

→ API: http://localhost:20128/v1/chat/completions

Split Ports

DASHBOARD_PORT=20128

API_PORT=20129

API_HOST=0.0.0.0

→ Dashboard: http://localhost:20128

→ API: http://0.0.0.0:20129/v1/chat/completions

Use case: Expose API to LAN while restricting Dashboard to localhost.

Docker Production

PROD_DASHBOARD_PORT=443

PROD_API_PORT=8443

→ Maps container ports to host ports in docker-compose.prod.yml.

4. Security & Authentication

Variable	Default	Source File	Description
MACHINE_ID_SALT	endpoint-proxy-salt	src/lib/auth	Salt combined with hardware identifiers for machine fingerprinting. Change per-deployment for isolation.
OMNIRoute_CLI_SALT	omniroute-cli-auth-v1	src/lib/machineToken.ts	HMAC salt for deriving the local CLI auth token. Changing this value rotates all CLI tokens on the machine. See docs/security/CLI_TOKEN.md.
AUTH_COOKIE_SECURE	false	src/lib/auth	Sets the Secure flag on session cookies. Must be true when running behind HTTPS.
REQUIRE_API_KEY	false	API middleware	When true, all /v1/* proxy requests must include a valid API key.
ALLOW_API_KEY_REVEAL	false	Dashboard providers page	Allows revealing full API key values in the Dashboard UI. Security risk on shared instances.
NO_LOG_API_KEY_IDS	(empty)	src/lib/compliance/index.ts	Comma-separated API key IDs that bypass request logging (GDPR compliance).
DEFAULT_RATE_LIMIT_PER_DAY	1000	src/shared/utils/apiKeyPolicy.ts	Fallback per-day request budget applied to API keys whose rate_limits column is null. Default (unset/empty/malformed) keeps the legacy 1000/day, 5000/week, 20000/month windows. Set explicitly to 0 to opt out (unlimited). Any positive integer N enables N/day, 5N/week, 20N/month. Zod-validated; invalid values log a warning and use the legacy default.
MAX_BODY_SIZE_BYTES	10485760 (10 MB)	src/shared/middleware/bodySizeGuard.ts	Maximum allowed request body size. Rejects payloads exceeding this limit.
CORS_ORIGIN	*	Next.js middleware	CORS Access-Control-Allow-Origin value. Restrict for production.
OUTBOUND_SSRF_GUARD_ENABLED	true	src/shared/network/outboundUrlGuard.ts	Block provider calls targeting private/loopback/link-local IP ranges. Disable only in isolated test envs.
OMNIRoute_ALLOW_PRIVATE_PROVIDER_URLS	false	src/shared/network/outboundUrlGuard.ts	Allow provider URLs pointing to private/local networks (localhost, 192.168.x.x, 10.x.x.x, etc.). REQUIRED for self-hosted providers (LM Studio, Ollama, vLLM, Llamafire, Triton, SearXNG). When false, the dashboard rejects validation of local URLs.

Hardening Checklist

```
# Production security minimum:
AUTH_COOKIE_SECURE=true           # Requires HTTPS
REQUIRE_API_KEY=true             # Authenticate all proxy calls
ALLOW_API_KEY_REVEAL=false       # Never expose keys in UI
CORS_ORIGIN=https://your.domain.com
MAX_BODY_SIZE_BYTES=5242880      # 5 MB limit
```

5. Input Sanitization & PII Protection

OmniRoute provides a two-layer defense: request-side injection scanning and response-side PII stripping.

Request-Side: Prompt Injection Guard

Variable	Default	Source File	Description
INPUT_SANITIZER_ENABLED	false	src/middleware/promptInjectionGuard.ts	Enable scanning of incoming messages for prompt injection patterns.
INPUT_SANITIZER_MODE	warn	src/middleware/promptInjectionGuard.ts	warn = log only, block = reject request with 400, redact = strip suspicious patterns.
INJECTION_GUARD_MODE	(unset)	src/middleware/promptInjectionGuard.ts	Legacy alias for INPUT_SANITIZER_MODE — same behavior.
PII_REDACTION_ENABLED	false	src/middleware/promptInjectionGuard.ts	Detect PII (emails, phones, SSNs) in incoming requests.

Response-Side: PII Sanitizer

Variable	Default	Source File	Description
PII_RESPONSE_SANITIZATION	false	src/lib/piiSanitizer.ts	Scan LLM responses for leaked PII before returning to client.
PII_RESPONSE_SANITIZATION_MODE	redact	src/lib/piiSanitizer.ts	redact = mask PII, warn = log only, block = drop entire response.

Scenarios

Scenario	Configuration
Enterprise compliance	INPUT_SANITIZER_ENABLED=true, INPUT_SANITIZER_MODE=block, PII_REDACTION_ENABLED=true, PII_RESPONSE_SANITIZATION=true

Scenario	Configuration
Monitoring only	INPUT_SANITIZER_ENABLED=true, INPUT_SANITIZER_MODE=warn — logs but never blocks
Personal use	Leave all disabled — zero overhead

6. Tool & Routing Policies

Variable	Default	Source File	Description
TOOL_POLICY_MODE	disabled	src/lib/toolPolicy.ts	Controls LLM tool/function-calling access. allowlist = only listed tools, denylist = all except listed, disabled = no restrictions.
OMNIRoute_PAYLOAD_RULES_PATH	./config/payloadRules.json	open-sse/services/payloadRules.ts	Path to payload manipulation rules JSON file (per-model/protocol upstream tweaks).
OMNIRoute_PAYLOAD_RULES_RELOAD_MS	5000	open-sse/services/payloadRules.ts	Reload interval (ms) for hot-reloading the payload rules file. Minimum 1000.

7. URLs & Cloud Sync

Variable	Default	Source File	Description
BASE_URL	http://localhost:20128	src/lib/cloudSync.ts	Server-side URL for internal sync jobs to call /api/sync/cloud.
CLOUD_URL	(empty)	src/lib/cloudSync.ts	Cloud relay endpoint URL (premium feature).
CLOUD_SYNC_TIMEOUT_MS	12000	src/lib/cloudSync.ts	HTTP timeout for cloud sync requests.
OMNIRoute_BUILD_PROFILE	full	Webpack build config	Build-time profile (set to minimal to physically exclude privileged modules from bundle).
OMNIRoute_CLOUD_SYNC_SECRET	(empty)	src/lib/cloudSync.ts	Shared secret used to verify the HMAC-SHA256 signature of Cloud Sync responses.
OMNIRoute_CLOUD_SYNC_SECRETS	false	src/lib/cloudSync.ts	Set to true to allow the Cloud Sync endpoint to overwrite local credentials. Default is false.
OMNIRoute_ZED_IMPORT_LEGACY_ONE_STEP	false	src/app/api/providers/zed/import/route.ts	Set to true to fall back to the v3.8.5 one-step "import everything" behavior without user confirmation.
NEXT_PUBLIC_BASE_URL	http://localhost:20128	OAuth, Dashboard, sync	Public-facing URL for OAuth redirect_uri, Dashboard links. Must match your public URL behind reverse proxy.
NEXT_PUBLIC_CLOUD_URL	(empty)	Client-side	Client-side mirror of CLOUD_URL.
NEXT_PUBLIC_APP_URL	(unset)	src/shared/services/cloudSyncScheduler.ts	Legacy fallback for NEXT_PUBLIC_BASE_URL.
OMNIRoute_PUBLIC_BASE_URL	(unset)	open-sse/executors/chatgpt-web.ts	Browser-facing OmniRoute origin used for image URLs in API responses (e.g., /v1/chatgpt-web/image/<id>). Set this when OpenWebUI or another relay reaches OmniRoute by an internal URL but the user's browser must fetch images from a LAN, tunnel, or public origin. Do not include /v1.
OMNIRoute_CGPT_WEB_IMAGE_TIMEOUT_MS	180000 (3 min)	open-sse/executors/chatgpt-web.ts	Max wait time for an async chatgpt-web image to land via the celsius WebSocket. Increase during upstream queue-deep windows.
OMNIRoute_CGPT_WEB_IMAGE_CACHE_MAX_MB	256	open-sse/services/chatgptImageCache.ts	Total in-memory byte budget (MB) for the chatgpt-web image cache serving

Variable	Default	Source File	Description
			/v1/chatgpt-web/image/<id>. Lower on memory-constrained hosts; raise if image generation is heavy and clients race the 30-minute TTL.
THEOLDLLM_NAV_TIMEOUT_MS	30000 (30s)	open-sse/executors/theoldllm.ts	Playwright navigation timeout (ms) for the browser-backed token capture used by the The Old LLM (theoldllm) free provider. Raise on slow networks if the relay page is slow to settle.
KIE_CALLBACK_URL	(unset)	open-sse/utils/kieTask.ts	Public callback URL for asynchronous kie.ai jobs. Highest-priority override before OMNIRoute_KIE_CALLBACK_URL and OMNIRoute_PUBLIC_URL.
OMNIRoute_KIE_CALLBACK_URL	(unset)	open-sse/utils/kieTask.ts	Alternate spelling of KIE_CALLBACK_URL. Falls back when the primary variable is unset.
OMNIRoute_PUBLIC_URL	(unset)	open-sse/utils/kieTask.ts	Public origin used to compose async callback URLs. Lowest-priority fallback for kie.ai callbacks; also used as a generic public URL for other relays.
OMNIRoute_CROF_USAGE_URL	https://crof.ai/usage_api/	open-sse/services/usage.ts	CrofAI quota lookup endpoint used by the Usage page. Override for relays / test fixtures.
OMNIRoute_GEMINI_CLI_USAGE_URL	https://cloudcode-pa.googleapis.com/v1internal:loadCodeAssist	open-sse/services/usage.ts	Gemini CLI quota lookup endpoint. Override for relays / test fixtures.
OMNIRoute_OPENCODE_QUOTA_URL	https://opencode.ai/zen/go/v1/quota	open-sse/services/opencodeQuotaFetcher.ts	OpenCode (zen/go) quota lookup endpoint used by the Usage page. Override for relays / test fixtures.
OMNIRoute_OPENCODE_GO_QUOTA_URL	https://api.z.ai/api/monitor/usage/quota/limit	open-sse/services/usage.ts	OpenCode Go quota lookup endpoint used by the Usage page. Override for relays / test fixtures.
OMNIRoute_CODEWHISPERER_BASE_URL	https://codewhisperer.us-east-1.amazonaws.com	open-sse/services/usage.ts	CodeWhisperer (AWS Kiro) usage limits endpoint. Override for relays / test fixtures.

[!IMPORTANT] When deploying behind a reverse proxy (nginx, Caddy), `NEXT_PUBLIC_BASE_URL` **must** be set to your public URL (e.g., `https://omniroute.example.com`). Without this, OAuth callbacks will fail because the `redirect_uri` won't match.

8. Outbound Proxy

Route upstream LLM provider calls through an HTTP or SOCKS5 proxy for egress control, geo-routing, or IP masking.

Variable	Default	Source File	Description
ENABLE_SOCKS5_PROXY	true	open-sse/executors	Enable SOCKS5 proxy agent for upstream calls.
NEXT_PUBLIC_ENABLE_SOCKS5_PROXY	true	Client-side	Client-side awareness of SOCKS5 availability.
HTTP_PROXY	(unset)	Node.js standard	HTTP proxy for upstream calls.
HTTPS_PROXY	(unset)	Node.js standard	HTTPS proxy for upstream calls.
ALL_PROXY	(unset)	Node.js standard	Universal proxy (supports socks5://).
NO_PROXY	(unset)	Node.js standard	Comma-separated hostnames/IPs to bypass the proxy.
ENABLE_TLS_FINGERPRINT	false	open-sse/executors	Spoof TLS fingerprint using wreq-js (mimics Chrome 124). Counters JA3/JA4 blocking.
OMNIRoute_TURNSTILE_IGNORE_TLS_ERRORS	false	open-sse/services/claudeTurnstileSolver.ts	Allow the Claude Turnstile Playwright browser context to ignore HTTPS certificate errors.

Scenarios

Scenario	Configuration
SOCKS5 through SSH tunnel	ALL_PROXY=socks5://127.0.0.1:7890, ENABLE_SOCKS5_PROXY=true
Corporate HTTP proxy	HTTP_PROXY=http://proxy.corp.com:3128, HTTPS_PROXY=http://proxy.corp.com:3128, NO_PROXY=localhost,internal.corp.com
Anti-fingerprint	ENABLE_TLS_FINGERPRINT=true — requires wreq-js (included)

9. CLI Tool Integration

Controls how OmniRoute discovers and launches CLI sidecars (Claude Code, Codex, etc.).

Variable	Default	Source File	Description
CLI_MODE	auto	src/shared/services/cliRuntime.ts	auto = search system PATH; manual = use explicit paths only.
CLI_EXTRA_PATHS	(unset)	src/shared/services/cliRuntime.ts	Additional PATH entries for CLI binary discovery (colon-separated).
CLI_CONFIG_HOME	(unset)	src/shared/services/cliRuntime.ts	Override home directory for reading CLI configs (~/.claude, ~/.codex).
CLI_ALLOW_CONFIG_WRITES	false	src/shared/services/cliRuntime.ts	Allow OmniRoute to write CLI config files (token refresh, session data).
CLI_CLAUDE_BIN	claude	src/shared/services/cliRuntime.ts	Custom path to Claude CLI binary.
CLI_CODEX_BIN	codex	src/shared/services/cliRuntime.ts	Custom path to Codex CLI binary.
CLI_DROID_BIN	droid	src/shared/services/cliRuntime.ts	Custom path to Droid CLI binary.
CLI_OPENCLAW_BIN	openclaw	src/shared/services/cliRuntime.ts	Custom path to OpenClaw CLI binary.
CLI_CURSOR_BIN	agent	src/shared/services/cliRuntime.ts	Custom path to Cursor agent binary.
CLI_CLINE_BIN	cline	src/shared/services/cliRuntime.ts	Custom path to Cline CLI binary.
CLI_CONTINUE_BIN	cn	src/shared/services/cliRuntime.ts	Custom path to Continue CLI binary.
CLI_QODER_BIN	qoder	src/shared/services/cliRuntime.ts	Custom path to Qoder CLI binary.
CLI_QWEN_BIN	qwen	src/shared/services/cliRuntime.ts	Custom path to the Qwen Code CLI binary.
CLI_DEVIN_BIN	devin	open-sse/executors/devin-cli.ts	Custom path to the Devin CLI binary (v3.8.0). Used by the Windsurf/Devin executor.

Docker Example

```
# Mount host binaries into the container and tell OmniRoute where they are:
CLI_EXTRA_PATHS=/host-cli/bin
CLI_CONFIG_HOME=/root
CLI_ALLOW_CONFIG_WRITES=true
CLI_CLAUDE_BIN=/host-cli/bin/claude
```

CLI Binary (omniroute) helpers

These variables tune the `omniroute` CLI binary's own behavior (not the sidecar detection above).

Variable	Default	Source File	Description
OMNIROUTE_LANG	(system)	bin/cli/i18n.mjs	Force CLI output language. BCP-47 locale (e.g. en, pt-BR). Overrides system locale env vars (LC_ALL, LC_MESSAGES).
OMNIROUTE_SHOW_LOG	(unset)	bin/cli/runtime/processSupervisor.mjs	Set to 1 to forward server stdout/stderr to the terminal in supervised mode. Equivalent to --log flag on <code>omniroute serve</code> .
OMNIROUTE_CLI_TOKEN	(unset)	bin/cli/api.mjs	Machine-auth token injected as <code>x-omniroute-cli-token</code> header. Auto-generated in task 8.12.
OMNIROUTE_HTTP_TIMEOUT_MS	30000	bin/cli/api.mjs	Per-attempt HTTP timeout (ms) for CLI → server requests.
OMNIROUTE_VERBOSE	0	bin/cli/api.mjs	Set to 1 to print retry/backoff diagnostics to stderr during CLI commands.
OMNIROUTE_PLUGIN_PATH	(unset)	bin/cli/plugins.mjs	Custom directory for CLI plugin discovery (<code>omniroute-cmd-*</code> packages). Defaults to <code>~/.omniroute/plugins/</code> when unset.
OMNIROUTE_PLUGINS_ALLOW_EXEC	0	src/lib/plugins/pluginWorker.ts	Set to 1 to allow plugins to request the <code>exec</code> permission (spawn child processes from the worker sandbox). Local operator only.

10. Internal Agent & MCP Integrations

Variable	Default	Source File	Description
OMNIROUTE_BASE_URL	auto-detect	open-sse/mcp-server/server.ts	Explicit URL for MCP/A2A tools to reach OmniRoute. Overrides localhost auto-detection.
OMNIROUTE_API_KEY	(unset)	MCP/A2A modules	API key for internal MCP tool and A2A skill calls.

Variable	Default	Source File	Description
OMNIRoute_API_Key_ID	<i>(unset)</i>	open-sse/mcp-server/audit.ts	Key ID for MCP audit log attribution.
Router_API_Key	<i>(unset)</i>	Legacy	Legacy alias for OMNIRoute_API_Key.
OMNIRoute_MCP_Enforce_Scopes	false	open-sse/mcp-server/server.ts	Enforce scope-based access control on MCP tool calls.
OMNIRoute_MCP_Scopes	<i>(all)</i>	open-sse/mcp-server/server.ts	Comma-separated scopes: admin, combos, health, models, routing, budget, metrics, pricing, memory, skills.
OMNIRoute_MCP_Compress_Descriptions	enabled	open-sse/mcp-server/descriptionCompressor.ts	Compress MCP tool descriptions before serializing the manifest. Disable values: 0, false, off.
OMNIRoute_MCP_Description_Compression	rtk	open-sse/mcp-server/descriptionCompressor.ts	Compression algorithm/profile. Disable values: 0, false, off.
Model_Sync_Interval_Hours	24	src/shared/services/modelSyncScheduler.ts	Model catalog sync interval in hours.
Provider_Limits_Sync_Interval_Minutes	70	src/server-init.ts	Provider rate-limit and quota polling interval.
Provider_Limits_Sync_Spacing_Ms	1500	src/lib/usage/providerLimits.ts	Gap (ms) between consecutive OAuth quota fetches in a bulk sync; OAuth connections are fetched one at a time to avoid bursting an upstream. 0 opts out (concurrent).
OMNIRoute_Disable_Background_Services	false	src/instrumentation-node.ts	Disable all background services (sync, pricing, model refresh). Useful for CI/test.
OMNIRoute_Enable_Runtime_Background_Tasks	<i>(unset)</i>	src/lib/config/runtimeSettings.ts	Force background tasks on under automated test detection. Set 1 to override the test heuristic.
OMNIRoute_Budget_Reset_Job_Interval_Ms	600000	src/lib/jobs/budgetResetJob.ts	Budget reset check cadence (ms). Floor 10000.
OMNIRoute_Reasoning_Cache_Cleanup_Interval_Ms	1800000	src/lib/jobs/reasoningCacheCleanupJob.ts	Reasoning cache cleanup cadence (ms). Floor 60000.
OMNIRoute_Config_Hot_Reload_Ms	5000	src/lib/config/hotReload.ts	Polling interval (ms) for config hot-reload. Lower than 1000 is rejected.
OMNIRoute_Disable_Redis_Auth_Cache	<i>(enabled)</i>	src/lib/db/apiKeys.ts	Set 1 to bypass the Redis-backed API-key auth cache (forces DB reads).
OMNIRoute_RTK_Trust_Project_Filters	0	open-sse/services/compression/engines/rtk/filterLoader.ts	Trust user-managed RTK project filter rules without strict signature checks.
OMNIRoute_Bootstrapped	false	src/app/(dashboard)/dashboard/page.tsx	Set true by bootstrap script after initial setup. Controls setup wizard visibility.
OMNIRoute_Allow_Body_Project_Override	0	open-sse/executors/antigravity.ts	Escape hatch: allow request body to override the Antigravity project field.
Antigravity_Credits	<i>(unset)</i>	open-sse/services/antigravityCredits.ts	Override Antigravity's advertised remaining credits (testing / forced values).
AGY_Token_File	~/.gemini/antigravity-cli/antigravity-oauth-token	src/app/api/providers/agy-auth/apply-local/route.ts	Override the Antigravity CLI (agy) token-file path for the auto-detect local login import.

OAuth CLI Bridge (Internal)

Variable	Default	Source File	Description
OMNIROUTE_SERVER	auto-detect	src/lib/oauth/config/index.ts	Server URL for CLI ↔ OmniRoute auth bridge.
OMNIROUTE_TOKEN	(unset)	src/lib/oauth/config/index.ts	Auth token for CLI bridge.
OMNIROUTE_USER_ID	cli	src/lib/oauth/config/index.ts	User ID for CLI bridge sessions.
SERVER_URL	(unset)	src/lib/oauth/config/index.ts	Legacy alias for OMNIROUTE_SERVER.
CLI_TOKEN	(unset)	src/lib/oauth/config/index.ts	Legacy alias for OMNIROUTE_TOKEN.
CLI_USER_ID	(unset)	src/lib/oauth/config/index.ts	Legacy alias for OMNIROUTE_USER_ID.

11. OAuth Provider Credentials

Built-in credentials for **localhost development**. For remote deployments, register your own at each provider's developer console.

Variable	Provider	Notes
CLAUDE_OAUTH_CLIENT_ID	Claude Code (Anthropic)	Public client — no secret needed.
CLAUDE_CODE_REDIRECT_URI	Claude Code	Override redirect URI. Default: <code>https://platform.claude.com/oauth/code/callback</code>
CODEX_OAUTH_CLIENT_ID	Codex / OpenAI	Public client.
GEMINI_OAUTH_CLIENT_ID	Gemini (Google)	Requires matching <code>_SECRET</code> .
GEMINI_OAUTH_CLIENT_SECRET	Gemini (Google)	—
GEMINI_CLI_OAUTH_CLIENT_ID	Gemini CLI	Usually same as Gemini.
GEMINI_CLI_OAUTH_CLIENT_SECRET	Gemini CLI	—
QWEN_OAUTH_CLIENT_ID	Qwen (Alibaba)	Public client.
KIMI_CODING_OAUTH_CLIENT_ID	Kimi Coding (Moonshot)	Public client.
ANTIGRAVITY_OAUTH_CLIENT_ID	Antigravity (Google)	Requires matching <code>_SECRET</code> .
ANTIGRAVITY_OAUTH_CLIENT_SECRET	Antigravity (Google)	—
GITHUB_OAUTH_CLIENT_ID	GitHub Copilot	Public client.
WINDSURF_FIREBASE_API_KEY	Windsurf / Devin (v3.8)	Public Firebase Web API key used by Windsurf's Secure Token Service to refresh short-lived browser-flow tokens. Client-side credential (not a secret). Long-lived import tokens skip this entirely. Source: extracted from Devin CLI binary.
WINDSURF_API_KEY	Windsurf / Devin (v3.8)	API key fallback used by <code>open-sse/executors/devin-cli.ts</code> when no per-connection credential is available. Optional.
CLI_DEVIN_BIN	Devin CLI (v3.8)	Custom path to the Devin CLI binary (<code>devin</code>). Resolved by <code>open-sse/executors/devin-cli.ts</code> .
GITLAB_DUO_OAUTH_CLIENT_ID	GitLab Duo (v3.8)	OAuth client ID for GitLab Duo. Register an app at <code>https://gitlab.com/-/profile/applications</code> with redirect URI <code><NEXT_PUBLIC_BASE_URL>/callback</code> and scopes <code>api, read_user, openid, profile, email</code> . Falls back to <code>GITLAB_OAUTH_CLIENT_ID</code> .
GITLAB_DUO_OAUTH_CLIENT_SECRET	GitLab Duo (v3.8)	OAuth client secret for GitLab Duo. Optional — PKCE flow does not require a secret. Falls back to <code>GITLAB_OAUTH_CLIENT_SECRET</code> .
GITLAB_DUO_BASE_URL	GitLab Duo (v3.8)	Override GitLab base URL (self-hosted GitLab). Defaults to <code>https://gitlab.com</code> . Falls back to <code>GITLAB_BASE_URL</code> .
GITLAB_BASE_URL	GitLab Duo (v3.8)	Legacy fallback for <code>GITLAB_DUO_BASE_URL</code> . Used when the <code>_DUO_</code> variant is unset.
GITLAB_OAUTH_CLIENT_ID	GitLab Duo (v3.8)	Legacy fallback for <code>GITLAB_DUO_OAUTH_CLIENT_ID</code> consumed by <code>src/lib/oauth/constants/oauth.ts</code> .
GITLAB_OAUTH_CLIENT_SECRET	GitLab Duo (v3.8)	Legacy fallback for <code>GITLAB_DUO_OAUTH_CLIENT_SECRET</code> consumed by <code>src/lib/oauth/constants/oauth.ts</code> .
QODER_OAUTH_CLIENT_SECRET	Qoder	—
QODER_OAUTH_AUTHORIZE_URL	Qoder	Set to enable Qoder OAuth.
QODER_OAUTH_TOKEN_URL	Qoder	—
QODER_OAUTH_USERINFO_URL	Qoder	—
QODER_OAUTH_CLIENT_ID	Qoder	—
QODER_PERSONAL_ACCESS_TOKEN	Qoder	Direct API key fallback (bypasses OAuth).

Variable	Provider	Notes
QODER_CLI_WORKSPACE	Qoder	Workspace ID for Qoder CLI.
OMNIRoute_QODER_WORKSPACE	Qoder	Alias for QODER_CLI_WORKSPACE.
BLACKBOX_WEB_VALIDATED_TOKEN	Blackbox Web	Frontend tk token to send as validated on /api/chat. Required when Blackbox enforces token matching; otherwise OmniRoute falls back to a random UUID. See issue #2252.
VISION_BRIDGE_BASE_URL	Vision Bridge guardrail	OpenAI-compatible base URL for non-Anthropic vision-bridge calls. Defaults to the legacy OpenAI URL env or api.openai.com. Point at OmniRoute's /v1 self-loop or any OpenAI-compatible endpoint (Gemini OpenAI-compatible, OpenRouter). Issue #2232.
VISION_BRIDGE_API_KEY	Vision Bridge guardrail	API key for the URL above. Overrides per-provider OpenAI / Google env vars for non-Anthropic vision-bridge calls. Anthropic models keep their dedicated Anthropic key path. Issue #2232.

[!WARNING] **Google OAuth** (Antigravity, Gemini CLI) credentials **only work on localhost**. For remote servers:

1. Go to [Google Cloud Console → Credentials](#)
2. Create an OAuth 2.0 Client ID (type: "Web application")
3. Add your server URL as Authorized redirect URI
4. Replace the credential values in .env.

12. Provider User-Agent Overrides

Override the `User-Agent` header sent to each upstream provider. This is dynamically resolved at runtime by the executor base class:

```
process.env[`${PROVIDER_ID}_USER_AGENT`]
```

Source: `open-sse/executors/base.ts` → `buildHeaders()`

Variable	Default Value	When to Update	
CLAUDE_USER_AGENT	claude-cli/2.1.145 (external, cli)	When Anthropic releases a new CLI version	
CLAUDE_DISABLE_TOOL_NAME_CLOAK	false	executors/base.ts + executors/cliproxyapi.ts	Set to 1/true to forward third-party harness tool names verbatim to Anthropic on both Anthropic-bound paths (native OAuth and CLIProxyAPI). By default the executor deterministically aliases non-Claude-Code tool names (Claude Code canonical mapping where one exists, otherwise PascalCase) and reverses them on the response via _toolNameMap, so harnesses with snake_case tools are not refused as fingerprinted third-party clients. Debugging only.
CODEX_USER_AGENT	codex-cli/0.132.0 (Windows 10.0.26200; x64)	When OpenAI updates the Codex CLI	
CODEX_CLIENT_VERSION	0.131.0	Override Codex client version independently of full UA string	
GITHUB_USER_AGENT	GitHubCopilotChat/0.45.1	When GitHub Copilot Chat updates	
ANTIGRAVITY_USER_AGENT	antigravity/2.0.1 darwin/arm64	When Antigravity IDE updates	
KIRO_USER_AGENT	AWS-SDK-JS/3.0.0 kiro-ide/1.0.0	When Kiro IDE updates	
KIRO_OAUTH_CLIENT_ID	kiro-cli	Override the Kiro social device-code clientId (public id)	
QODER_USER_AGENT	Qoder-CLI	When Qoder CLI updates	
QWEN_USER_AGENT	QwenCode/0.15.9 (linux; x64)	When Qwen Code updates	
CURSOR_USER_AGENT	Cursor/3.3	When Cursor updates	
GEMINI_CLI_USER_AGENT	google-api-nodejs-client/10.3.0	When Google API client updates	

[!TIP] You can add User-Agent overrides for **any** provider using the pattern `{PROVIDER_ID}_USER_AGENT`. The executor dynamically constructs the env var name.

13. CLI Fingerprint Compatibility

When enabled, OmniRoute reorders HTTP headers and JSON body fields to match the exact signature of official CLI tools. This reduces the risk of account flagging while preserving your proxy IP.

Source: `open-sse/config/cliFingerprints.ts`, `open-sse/executors/base.ts`

Per-Provider

Variable	Activation	Effect
CLI_COMPAT_CODEX	=1	Mimics Codex CLI request signature
CLI_COMPAT_CLAUDE	=1	Mimics Claude Code request signature
CLI_COMPAT_GITHUB	=1	Mimics GitHub Copilot request signature
CLI_COMPAT_ANTIGRAVITY	=1	Mimics Antigravity request signature
CLI_COMPAT_CURSOR	=1	Mimics Cursor request signature
CLI_COMPAT_KIMI_CODING	=1	Mimics Kimi Coding request signature
CLI_COMPAT_KILOCODE	=1	Mimics Kilo Code request signature
CLI_COMPAT_CLINE	=1	Mimics Cline request signature
CLI_COMPAT_QWEN	=1	Mimics Qwen Code request signature

Global

Variable	Activation	Effect
CLI_COMPAT_ALL	=1	Enable fingerprint compatibility for all providers at once.

Kimi Coding CLI identity overrides

Variable	Default	Source File	Description
KIMI_CLI_VERSION	1.36.0	src/lib/oauth/providers/kimi-coding.ts	Override the Kimi CLI version sent during OAuth/API calls.
KIMI_CODING_DEVICE_ID	(captured default)	src/lib/oauth/providers/kimi-coding.ts	Override the captured Kimi device ID used in client headers.

[!NOTE] This feature works alongside the User-Agent overrides (§12). The fingerprint system handles header ordering and body field ordering, while User-Agent overrides handle the specific UA string. Both can be enabled independently.

14. API Key Providers

API keys for providers that use direct authentication. **Preferred setup:** Dashboard → Providers → Add API Key.

Setting via environment variables is an alternative for Docker or headless deployments.

Recognized pattern: `{PROVIDER_ID}_API_KEY`

Variable	Provider
DEEPSEEK_API_KEY	DeepSeek
NVIDIA_API_KEY	NVIDIA NIM

[!NOTE] Static `\${PROVIDER}_API_KEY` entries for Groq, xAI, Mistral, Perplexity, Together AI, Fireworks, Cerebras, Cohere, Nebius, and Qianfan were removed in v3.8.0 because the runtime no longer reads them — those providers rely exclusively on Dashboard / `data/provider-credentials.json` / the encrypted DB. See the *Audit: Removed / Dead Variables* section at the bottom of this document for the migration path.

[!TIP] Keys set via the Dashboard are stored encrypted in SQLite and take precedence over environment variables.

15. Timeout Settings

All values are in **milliseconds**. Centralized resolution in `src/shared/utils/runtimeTimeouts.ts`.

Timeout Hierarchy

```
REQUEST_TIMEOUT_MS (global override)
├─→ FETCH_TIMEOUT_MS (upstream provider calls, default: 600000)
│   ├─→ FETCH_HEADERS_TIMEOUT_MS (inherits from FETCH_TIMEOUT_MS)
│   ├─→ FETCH_BODY_TIMEOUT_MS (inherits from FETCH_TIMEOUT_MS)
│   ├─→ TLS_CLIENT_TIMEOUT_MS (inherits from FETCH_TIMEOUT_MS)
│   └─ FETCH_CONNECT_TIMEOUT_MS (independent, default: 30000)
│       └─ FETCH_KEEPALIVE_TIMEOUT_MS (independent, default: 4000)
├─→ STREAM_IDLE_TIMEOUT_MS (inherits from REQUEST_TIMEOUT_MS, default: 600000)
└─→ API_BRIDGE_PROXY_TIMEOUT_MS (inherits from REQUEST_TIMEOUT_MS, default: 30000)
    ├─→ API_BRIDGE_SERVER_REQUEST_TIMEOUT_MS (derived, default: 300000)
    └─ API_BRIDGE_SERVER_HEADERS_TIMEOUT_MS (default: 60000)
        └─ API_BRIDGE_SERVER_KEEPALIVE_TIMEOUT_MS (default: 5000)
            └─ API_BRIDGE_SERVER_SOCKET_TIMEOUT_MS (default: 0 = disabled)
```

Variable	Default	Description
REQUEST_TIMEOUT_MS	<i>(unset)</i>	Global shortcut — overrides both <code>FETCH_TIMEOUT_MS</code> and <code>STREAM_IDLE_TIMEOUT_MS</code> defaults.
FETCH_TIMEOUT_MS	600000	Total HTTP request timeout for upstream provider calls.
STREAM_IDLE_TIMEOUT_MS	600000	Max silence between SSE chunks before aborting. Extended-thinking models rarely pause >90s.
FETCH_HEADERS_TIMEOUT_MS	= FETCH_TIMEOUT_MS	Time to receive response headers.
FETCH_BODY_TIMEOUT_MS	= FETCH_TIMEOUT_MS	Time to receive the full response body.
FETCH_CONNECT_TIMEOUT_MS	30000	TCP connection establishment timeout.
FETCH_KEEPALIVE_TIMEOUT_MS	4000	Keep-alive socket idle timeout.
TLS_CLIENT_TIMEOUT_MS	= FETCH_TIMEOUT_MS	TLS fingerprint proxy (wreq-js) timeout.
API_BRIDGE_PROXY_TIMEOUT_MS	30000	Proxy hop timeout for /v1 bridge requests.
API_BRIDGE_SERVER_REQUEST_TIMEOUT_MS	300000	Overall server request timeout for the bridge.
API_BRIDGE_SERVER_HEADERS_TIMEOUT_MS	60000	Time to send response headers via the bridge.
API_BRIDGE_SERVER_KEEPALIVE_TIMEOUT_MS	5000	Bridge keep-alive idle timeout.
API_BRIDGE_SERVER_SOCKET_TIMEOUT_MS	0	Raw socket timeout (0 = disabled).
SHUTDOWN_TIMEOUT_MS	30000	Grace period on SIGTERM/SIGINT before force-exit.
OMNIROUTE_DEFAULT_FETCH_TIMEOUT_MS	120000	Fallback used by <code>src/shared/utils/fetchTimeout.ts</code> when <code>FETCH_TIMEOUT_MS</code> is unset.
OMNIROUTE_CHATGPT_TLS_TIMEOUT_MS	60000	Wire-level timeout for the bogdanfinn/tls-client koffi binding (<code>chatgptTlsClient.ts</code>).
OMNIROUTE_CHATGPT_TLS_GRACE_MS	10000	JS-side grace added on top of the wire timeout when the native binding is wedged.
OMNIROUTE_CLAUDE_TLS_TIMEOUT_MS	60000	Wire-level timeout for the bogdanfinn/tls-client koffi binding (<code>claudeTlsClient.ts</code>).
OMNIROUTE_CLAUDE_TLS_GRACE_MS	10000	JS-side grace added on top of the wire timeout when the native binding is wedged.
OMNIROUTE_PPLX_TLS_TIMEOUT_MS	30000	Wire-level timeout for the bogdanfinn/tls-client koffi binding (<code>perplexityTlsClient.ts</code>).
OMNIROUTE_PPLX_TLS_GRACE_MS	10000	JS-side grace added on top of the wire timeout when the native binding is wedged.
OMNIROUTE_GROK_TLS_TIMEOUT_MS	60000	Wire-level timeout for the bogdanfinn/tls-client koffi binding (<code>grokTlsClient.ts</code>).
OMNIROUTE_GROK_TLS_GRACE_MS	10000	JS-side grace added on top of the wire timeout when the native binding is wedged.
OMNIROUTE_BROWSER_POOL	on	Shared Playwright browser pool for browser-backed web-cookie chat (<code>browserPool.ts</code>); set off to disable.
WEB_COOKIE_USE_BROWSER	0	Opt a web-cookie chat request into the browser-backed path (<code>browserBackedChat.ts</code>); 1 to enable.

Combo target attempts inherit the resolved upstream request timeout (`FETCH_TIMEOUT_MS`, or `REQUEST_TIMEOUT_MS` when it supplies the fetch default). Set `targetTimeoutMs` in a combo, combo defaults, or provider override only to make combo fallback faster; values above the current upstream timeout are capped to the upstream timeout.

Circuit Breaker Thresholds

Provider-level circuit breaker tuning. Defaults reflect the scaled values used since v3.6 for 500+ connections.

Variable	Default	Source File	Description
OMNIROUTE_CIRCUIT_BREAKER_OAUTH_THRESHOLD	8	open-sse/config/constants.ts	Consecutive failure threshold for OAuth providers before the breaker trips.
OMNIROUTE_CIRCUIT_BREAKER_OAUTH_RESET_MS	60000	open-sse/config/constants.ts	Reset window (ms) for OAuth provider breaker.
OMNIROUTE_CIRCUIT_BREAKER_API_KEY_THRESHOLD	12	open-sse/config/constants.ts	Consecutive failure threshold for API-key providers.
OMNIROUTE_CIRCUIT_BREAKER_API_KEY_RESET_MS	30000	open-sse/config/constants.ts	Reset window (ms) for API-key provider breaker.
OMNIROUTE_CIRCUIT_BREAKER_LOCAL_THRESHOLD	2	open-sse/config/constants.ts	Consecutive failure threshold for local providers (Ollama, LM Studio, ...).
OMNIROUTE_CIRCUIT_BREAKER_LOCAL_RESET_MS	15000	open-sse/config/constants.ts	Reset window (ms) for local provider breaker.

Scenarios

Scenario	Configuration
Long-running code generation	REQUEST_TIMEOUT_MS=900000 (15 min)
Fast-fail for production API	API_BRIDGE_PROXY_TIMEOUT_MS=10000
Extended thinking models	STREAM_IDLE_TIMEOUT_MS=300000 (5 min between chunks)

16. Logging

The logging system writes to both stdout and rotated log files. All configuration is read by `src/lib/logEnv.ts`.

Variable	Default	Description
APP_LOG_LEVEL	info	Minimum log level: debug, info, warn, error.
APP_LOG_FORMAT	text	Output format: text (human-readable) or json (structured).
APP_LOG_TO_FILE	true	Write logs to file alongside stdout.
APP_LOG_FILE_PATH	logs/application/app.log	Log file path (relative to project root or DATA_DIR).
APP_LOG_MAX_FILE_SIZE	50M	Max file size before rotation. Accepts: 50M, 1G, 512K, or plain bytes.
APP_LOG_RETENTION_DAYS	7	Days to keep rotated application log files.
APP_LOG_MAX_FILES	20	Maximum rotated log file backups.
CALL_LOG_RETENTION_DAYS	7	Days to keep request/call log entries in the database.
CALL_LOG_MAX_ENTRIES	10000	Max call log entries in the in-memory buffer.
CALL_LOGS_TABLE_MAX_ROWS	100000	Max rows in the call_logs SQLite table before pruning.
CALL_LOG_PIPELINE_CAPTURE_STREAM_CHUNKS	true	Store stream chunks in pipeline artifacts when call_log_pipeline_enabled=true.
CALL_LOG_PIPELINE_MAX_SIZE_KB	512	Max pipeline call log artifact size in KB when call_log_pipeline_enabled=true.
PROXY_LOGS_TABLE_MAX_ROWS	100000	Max rows in the proxy_logs SQLite table before pruning.
APP_LOG_ROTATION_CHECK_INTERVAL_MS	60000 (1 min)	How often src/lib/logRotation.ts re-checks the active log file size.
CHAT_LOG_TEXT_LIMIT	65536	Max string length retained in chat log artifacts (default 64 KB).
CHAT_LOG_ARRAY_TAIL_ITEMS	24	Number of array items retained from the tail when truncating chat log payloads.
CHAT_LOG_MAX_DEPTH	6	Max nesting depth before chat log payloads are truncated.
CHAT_LOG_MAX_OBJECT_KEYS	80	Max object keys retained in chat log payloads (0 = unlimited).
CHAT_DEBUG_FILE	false	When true, serializeArtifactForStorage skips size-based truncation. Debug only.

17. Memory Optimization

Variable	Default	Description
OMNIROUTE_MEMORY_MB	512	Runtime V8 heap limit. Docker standalone and omniroute serve use it to set --max-old-space-size.
PROMPT_CACHE_MAX_SIZE	50	Max cached system prompt entries.
PROMPT_CACHE_MAX_BYTES	2097152 (2 MB)	Max total prompt cache size.
PROMPT_CACHE_TTL_MS	300000 (5 min)	Prompt cache entry TTL.
SEMANTIC_CACHE_MAX_SIZE	100	Max cached temperature=0 responses.
SEMANTIC_CACHE_MAX_BYTES	4194304 (4 MB)	Max total semantic cache size.
SEMANTIC_CACHE_TTL_MS	1800000 (30 min)	Semantic cache entry TTL.
STREAM_HISTORY_MAX	50	Max recent stream events in the Dashboard live view buffer.
CONTEXT_LENGTH_DEFAULT	128000	Global fallback max context length for models without explicit config.
USAGE_TOKEN_BUFFER	100	Extra token headroom reserved when tracking usage quotas.

Compression

Variable	Default	Description
OMNIROUTE_RTK_TRUST_PROJECT_FILTERS	unset	Trust project .rtk/filters.json without a .rtk/trust.json hash. Use only in controlled local development.

Memory Engine (plan 21)

Embedding layer, vector store and reranking knobs for the persistent memory subsystem (`src/lib/memory/`).

Variable	Default	Description
MEMORY_EMBEDDING_CACHE_TTL_MS	300000 (5 min)	TTL for the in-memory embedding cache (per source/model/dim signature).
MEMORY_EMBEDDING_CACHE_MAX	1000	Max LRU entries kept in the embedding cache.
MEMORY_TRANSFORMERS_MODEL	Xenova/all-MiniLM-L6-v2	HF repo id for the opt-in @huggingface/transformers local MiniLM pipeline (~23 MB int8, ~400 MB RAM).
MEMORY_STATIC_MODEL	minishlab/potion-base-8M	HF repo id for the static potion/Model2Vec lookup-table embedder. Downloaded lazily into the cache dir.
MEMORY_STATIC_CACHE_DIR	<DATA_DIR>/embeddings	Directory used to cache the static potion model files. Defaults under DATA_DIR when unset.

Variable	Default	Description
MEMORY_VEC_TOP_K	20	Default top-K used by the <code>sqlite-vec</code> brute-force vector search inside <code>src/lib/memory/vectorStore.ts</code> .
MEMORY_RRF_K	60	Reciprocal Rank Fusion constant <code>k</code> for hybrid FTS5 + vector retrieval (<code>sqlite-vec</code> recipe).
HF_HUB_ENDPOINT	<code>https://huggingface.co</code>	Override Hugging Face Hub base URL used by <code>staticPotion.ts</code> (e.g. mirror endpoint for air-gapped setups).

Low-RAM Docker Example

```
OMNIROUTE_MEMORY_MB=128
PROMPT_CACHE_MAX_SIZE=20
PROMPT_CACHE_MAX_BYTES=524288      # 512 KB
SEMANTIC_CACHE_MAX_SIZE=25
SEMANTIC_CACHE_MAX_BYTES=1048576    # 1 MB
STREAM_HISTORY_MAX=10
```

18. Pricing Sync

Automatic model pricing data synchronization from external sources.

Variable	Default	Source File	Description
PRICING_SYNC_ENABLED	false	<code>src/lib/pricingSync.ts</code>	Opt-in periodic pricing sync.
PRICING_SYNC_INTERVAL	86400 (24h)	<code>src/lib/pricingSync.ts</code>	Sync interval in seconds.
PRICING_SYNC_SOURCES	litellm	<code>src/lib/pricingSync.ts</code>	Comma-separated data sources.

19. Model Sync (Dev)

Variable	Default	Source File	Description
MODELS_DEV_SYNC_INTERVAL	86400 (24h)	<code>src/lib/modelsDevSync.ts</code>	Development-time model catalog sync interval in seconds.

20. Provider-Specific Settings

Variable	Default	Source File	Description
OPENROUTER_CATALOG_TTL_MS	86400000 (24h)	<code>src/lib/catalog/openrouterCatalog.ts</code>	OpenRouter model catalog cache TTL.
MODEL_CATALOG_INCLUDE_NAMES	true	<code>src/shared/constants/featureFlagDefinitions.ts</code>	Include display-friendly <code>name</code> fields in <code>/v1/models</code> responses. Disable for clients that expect IDs only.
NANOBANANA_POLL_TIMEOUT_MS	120000	<code>open-sse/handlers/imageGeneration.ts</code>	Max wait for NanoBanana image generation jobs.
NANOBANANA_POLL_INTERVAL_MS	2500	<code>open-sse/handlers/imageGeneration.ts</code>	NanoBanana job polling frequency.
AWS_REGION	(unset)	<code>src/lib/providers/validation.ts</code> , <code>open-sse/handlers/audioSpeech.ts</code>	Region used to construct AWS Bedrock endpoints (Kiro, audio).
AWS_DEFAULT_REGION	(unset)	<code>src/lib/providers/validation.ts</code> , <code>open-sse/handlers/audioSpeech.ts</code>	Fallback when <code>AWS_REGION</code> is not set.
CLOUDFLARE_ACCOUNT_ID	(unset)	<code>open-sse/executors/cloudflare-ai.ts</code>	Account ID for Cloudflare Workers AI.
CLOUDFLARED_BIN	auto-detect	<code>src/lib/cloudflaredTunnel.ts</code>	Custom path to <code>cloudflared</code> binary.
SEARCH_CACHE_TTL_MS	300000 (5 min)	<code>open-sse/services/searchCache.ts</code>	TTL for search API (Perplexity, Brave, etc.) response caching.
ALLOW_MULTI_CONNECTIONS_PER_COMPAT_NODE	false	<code>src/app/api/providers/route.ts</code>	Allow multiple simultaneous connections per OpenAI-compatible provider.
ENABLE_CC_COMPATIBLE_PROVIDER	false	<code>src/shared/utils/featureFlags.ts</code>	Reveal the experimental CC-compatible provider UI for Claude Code-only relays.
NINEROUTER_HOST	127.0.0.1	<code>open-sse/executors/ninerouter.ts</code>	Override the host where the embedded 9router instance listens.
NINEROUTER_PORT	20130	<code>open-sse/executors/ninerouter.ts</code>	Override the port where the embedded 9router instance listens.
EMBED_WS_PROXY_HOST	127.0.0.1	<code>src/lib/services/embedWsProxy.ts</code>	Bind host for the embedded-service WebSocket proxy (loopback only by default).
EMBED_WS_PROXY_PORT	20131	<code>src/lib/services/embedWsProxy.ts</code>	Port for the embedded-service WebSocket proxy server.

Variable	Default	Source File	Description
CLIPROXYAPI_HOST	127.0.0.1	open-sse/executors/cliproxyapi.ts	CLIProxyAPI bridge host (legacy integration).
CLIPROXYAPI_PORT	5544	open-sse/executors/cliproxyapi.ts	CLIProxyAPI bridge port.
CLIPROXYAPI_CONFIG_DIR	~/cli-proxy-api	src/lib/versionManager/processManager.ts	CLIProxyAPI config directory.
LOCAL_HOSTNAMES	(empty)	open-sse/config/providerRegistry.ts	Comma-separated additional hostnames treated as "local" (Docker service names, etc.).

`ENABLE_CC_COMPATIBLE_PROVIDER` is only for third-party relays that accept Claude Code clients exclusively. OmniRoute rewrites requests so those relays accept them. If you only want to use Claude Code CLI, or you are not sure what these relays are, keep this disabled and add a regular Anthropic-compatible provider instead.

21. Proxy Health

Variable	Default	Source File	Description
PROXY_FAST_FAIL_TIMEOUT_MS	2000	src/lib/proxyHealth.ts	Fast-fail health check timeout.
PROXY_HEALTH_CACHE_TTL_MS	30000	src/lib/proxyHealth.ts	Health check result cache TTL.
RATE_LIMIT_MAX_WAIT_MS	120000 (2 min)	open-sse/services/rateLimitManager.ts	Max time to wait on a 429 before failing the request.
RATE_LIMIT_AUTO_ENABLE	(unset)	open-sse/services/rateLimitManager.ts	Force the auto-enable rate limit safety net on/off regardless of the persisted Dashboard setting. Accepts <code>true/1/on</code> to force on, <code>false/0/off</code> to force off.
PROVIDER_COOLDOWN_ENABLED	(unset → off)	open-sse/services/providerCooldownTracker.ts	Opt-in global cross-request provider/connection cooldown tracking. OFF by default (overlaps Connection Cooldown / Provider Circuit Breaker). Accepts <code>true/1/on</code> to enable.
PROVIDER_COOLDOWN_MIN_MS	5000	open-sse/services/providerCooldownTracker.ts	Minimum cooldown (ms) before a failed provider/connection is retried. Scaled exponentially with consecutive failures. Only used when <code>PROVIDER_COOLDOWN_ENABLED</code> .
PROVIDER_COOLDOWN_MAX_MS	300000 (5 min)	open-sse/services/providerCooldownTracker.ts	Maximum cooldown (ms) cap before a failed provider/connection is retried regardless. Only used when <code>PROVIDER_COOLDOWN_ENABLED</code> .
HEALTHCHECK_STAGGER_MS	3000	src/lib/tokenHealthCheck.ts	Stagger interval (ms) between provider token healthchecks at startup.
REQUEST_RETRY	2	src/sse/services/cooldownAwareRetry.ts	Number of automatic retries on model-scoped cooldown responses before returning error to client.
MAX_RETRY_INTERVAL_SEC	30	src/sse/services/cooldownAwareRetry.ts	Max backoff interval (seconds) between cooldown retries. Capped by this value regardless of upstream <code>Retry-After</code> .

22. Debugging

[!CAUTION] These variables produce **verbose output** and may leak sensitive data. **Never enable in production.**

Variable	Default	Source File	Description
CURSOR_DEBUG	(unset)	open-sse/executors/cursor.ts	Set 1 to enable verbose Cursor executor logs (decoded SSE chunks, etc.).
CURSOR_STREAM_DEBUG	(unset)	open-sse/executors/cursor.ts	Backward-compatible alias of <code>CURSOR_DEBUG</code> .
CURSOR_DUMP_FILE	(unset)	open-sse/executors/cursor.ts	Optional file path that receives raw decoded Cursor chunks when <code>CURSOR_DEBUG=1</code> .
CURSOR_STREAM_TIMEOUT_MS	300000	open-sse/executors/cursor.ts	Stream idle timeout (ms) for the Cursor executor.
CURSOR_TOOL_DIRECTIVE	enabled (!="0")	open-sse/executors/cursor.ts	Tool-commit directive that makes composer-2.5 reliably issue tool calls. Set 0 to disable.
CURSOR_IMAGE_FETCH_TIMEOUT_MS	15000	open-sse/utils/cursorImages.ts	Per-image fetch timeout (ms) for remote <code>image_url</code> vision input.
CURSOR_STATE_DB_PATH	(probed)	open-sse/utils/cursorVersionDetector.ts	Override the Cursor state DB lookup used for version detection.
CURSOR_TOKEN	(unset)	scripts/ad-hoc/cursor-tap.cjs	Direct Cursor bearer token used by developer tooling.
OMNIRoute_LOG_REQUEST_SHAPE	enabled (!="0")	src/app/api/v1/chat/completions/route.ts	Log content-type/length markers for large chat payloads. Set "0" to silence.
DEBUG_RESPONSES_SSE_TO_JSON	(unset)	open-sse/handlers/responseTranslator.ts	Set true to log Responses API SSE → JSON translation details.
NEXT_PUBLIC_OMNIRoute_E2E_MODE	(unset)	E2E test harness	Set true to enable E2E test mode (relaxed auth, test hooks).

23. GitHub Integration

Allow users to report issues directly from the Dashboard.

Variable	Default	Source File	Description
GITHUB_ISSUES_REPO	<i>(unset)</i>	src/app/api/v1/issues/report/route.ts	Repository in owner/repo format.
GITHUB_ISSUES_TOKEN	<i>(unset)</i>	src/app/api/v1/issues/report/route.ts	GitHub Personal Access Token with issues:write scope.
GITHUB_TOKEN	<i>(unset)</i>	issue triage / cloud agent helpers	Generic GitHub access token used as fallback for GITHUB_ISSUES_TOKEN and consumed by cloud agent helpers in src/lib/cloudAgent/*.

Deployment Scenarios

Minimal Local Development

```
JWT_SECRET=\$(openssl rand -base64 48)
API_KEY_SECRET=\$(openssl rand -hex 32)
INITIAL_PASSWORD=dev123
PORT=20128
NODE_ENV=development
```

Docker Production

```
JWT_SECRET=<generated>
API_KEY_SECRET=<generated>
INITIAL_PASSWORD=<generated>
STORAGE_ENCRYPTION_KEY=<generated>
DATA_DIR=/data
PORT=20128
API_PORT=20129
NODE_ENV=production
AUTH_COOKIE_SECURE=true
REQUIRE_API_KEY=true
NEXT_PUBLIC_BASE_URL=https://omniroute.example.com
BASE_URL=http://localhost:20128
OMNIROUTE_MEMORY_MB=512
CORS_ORIGIN=https://your-frontend.example.com
```

Air-Gapped / CI

```
JWT_SECRET=test-jwt-secret-for-ci
API_KEY_SECRET=test-api-key-secret-for-ci
INITIAL_PASSWORD=testpass
NODE_ENV=production
OMNIROUTE_DISABLE_BACKGROUND_SERVICES=true
APP_LOG_TO_FILE=false
```

VPS with Reverse Proxy (nginx + Cloudflare)

```
JWT_SECRET=<generated>
API_KEY_SECRET=<generated>
STORAGE_ENCRYPTION_KEY=<generated>
PORT=20128
AUTH_COOKIE_SECURE=true
REQUIRE_API_KEY=true
NEXT_PUBLIC_BASE_URL=https://omniroute.example.com
BASE_URL=http://127.0.0.1:20128
CORS_ORIGIN=https://omniroute.example.com
ENABLE_TLS_FINGERPRINT=true
CLI_COMPAT_ALL=1
```

24. Skills Sandbox (v3.8.0+)

Limits and safety knobs applied when the Skills framework (`src/lib/skills/`) executes user-defined automations in a sandboxed environment.

Variable	Default	Source File	Description
SKILLS_SANDBOX_TIMEOUT_MS	10000 (10 s)	src/lib/skills/builtins.ts	Per-execution wall-clock timeout for sandboxed skill code. Hard cap; anything longer is killed.

Variable	Default	Source File	Description
SKILLS_EXECUTION_TIMEOUT_MS	<i>(falls back to SKILLS_SANDBOX_TIMEOUT_MS)</i>	src/lib/skills/	High-level skill orchestration timeout. Set higher than SKILLS_SANDBOX_TIMEOUT_MS to allow multi-step workflows.
SKILLS_MAX_FILE_BYTES	1048576 (1 MB)	src/lib/skills/builtins.ts	Max bytes a skill may read from any single sandboxed file.
SKILLS_MAX_HTTP_RESPONSE_BYTES	256000 (250 KB)	src/lib/skills/builtins.ts	Max bytes captured from any single HTTP response inside a skill.
SKILLS_MAX_SANDBOX_OUTPUT_CHARS	100000	src/lib/skills/builtins.ts	Hard cap on stdout/stderr characters returned from a sandbox invocation.
SKILLS_SANDBOX_NETWORK_ENABLED	false	src/lib/skills/builtins.ts	Set 1/true to allow outbound network from inside the sandbox. Defaults to isolated for safety.
SKILLS_ALLOWED_SANDBOX_IMAGES	<i>(empty)</i>	src/lib/skills/builtins.ts	Comma-separated allowlist of container images permitted for sandbox execution. Empty means built-in default only.
SKILLS_SANDBOX_DOCKER_IMAGE	<i>(built-in default)</i>	src/lib/skills/	Container image used when spawning a Docker-backed sandbox. Override to pin a custom hardened base image.

[!CAUTION]
Enabling `SKILLS_SANDBOX_NETWORK_ENABLED=true` opens an egress path from arbitrary skill code. Pair with `OUTBOUND_SSRF_GUARD_ENABLED=true` and a strict `CORS_ORIGIN`/proxy policy in shared deployments.

25. Provider Quotas, Tunnels, Backups & Misc Runtime

Provider quota endpoints, network tunnels (Tailscale, Ngrok, MITM debug proxy), the 1Proxy egress pool, database backups and small per-feature overrides referenced by the executor layer or scripts.

Variable	Default	Source File	Description
REDIS_URL	redis://localhost:6379	src/shared/utils/rateLimiter.ts	Redis connection string for the rate limiter backend.
ALIBABA_CODING_PLAN_HOST	<i>(production host)</i>	open-sse/services/bailianQuotaFetcher.ts	Override the host used to fetch Alibaba Bailian coding-plan quotas.
ALIBABA_CODING_PLAN_QUOTA_URL	derived from host	open-sse/services/bailianQuotaFetcher.ts	Full quota URL override for Alibaba Bailian.
CONTEXT_RESERVE_TOKENS	1024	open-sse/services/contextManager.ts	Tokens reserved for completion output when computing prompt budgets.
MODEL_ALIAS_COMPAT_ENABLED	enabled	open-sse/services/model.ts	Toggle the legacy model alias compatibility layer used by older clients.
COMMAND_CODE_CALLBACK_PORT	<i>(unset)</i>	src/app/api/providers/command-code/auth/shared.ts	Local port used for OAuth style callbacks from the Command Code CLI helper.
COMMAND_CODE_VERSION	0.33.2	open-sse/executors/commandCode.ts	Value sent as the x-command-code-version header to the Command Code upstream. Override to bump the CLI version.
MITM_LOCAL_PORT	443	src/mitm/server.cjs	Local bind port for the MITM debug proxy.
MITM_DISABLE_TLS_VERIFY	0	src/mitm/server.cjs	Set 1 to disable upstream TLS verification (development only).
ONEPROXY_ENABLED	true	src/lib/oneproxySync.ts	Enable the 1Proxy egress pool sync.
ONEPROXY_API_URL	https://1proxy-api.aitradepulse.com	src/lib/oneproxySync.ts	1Proxy service API URL override.
ONEPROXY_MAX_PROXIES	500	src/lib/oneproxySync.ts	Maximum proxies imported per sync.
ONEPROXY_MIN_QUALITY_THRESHOLD	50	src/lib/oneproxySync.ts	Minimum quality score for imported proxies.
FREE_PROXY_1PROXY_ENABLED	true	src/lib/freeProxyProviders/oneproxy.ts	Enable the 1proxy free proxy source. Set to false to disable.
FREE_PROXY_1PROXY_API_URL	<i>(see oneproxy.ts)</i>	src/lib/freeProxyProviders/oneproxy.ts	1proxy API URL override.
FREE_PROXY_1PROXY_MAX	500	src/lib/freeProxyProviders/oneproxy.ts	Maximum proxies fetched per sync from 1proxy.

Variable	Default	Source File	Description
FREE_PROXY_1PROXY_MIN_QUALITY	50	src/lib/freeProxyProviders/oneproxy.ts	Minimum quality score threshold for 1proxy imports.
FREE_PROXY_PROXIFLY_ENABLED	true	src/lib/freeProxyProviders/proxifly.ts	Enable the Proxifly free proxy source. Set to false to disable.
FREE_PROXY_PROXIFLY_QUANTITY	100	src/lib/freeProxyProviders/proxifly.ts	Number of proxies to fetch per Proxifly sync.
FREE_PROXY_PROXIFLY_ANONYMITY	elite	src/lib/freeProxyProviders/proxifly.ts	Anonymity level filter for Proxifly (elite, anonymous, transparent).
FREE_PROXY_IPLOCATE_ENABLED	false	src/lib/freeProxyProviders/iplocate.ts	Enable the IPLocate free proxy source. Opt-in only.
FREE_PROXY_IPLOCATE_BASE_URL	https://raw.githubusercontent.com/iplocate/free-proxy-list/main/protocols	src/lib/freeProxyProviders/iplocate.ts	IPLocate proxy list base URL override.
NEXT_PUBLIC_VERCEL_RELAY_ENABLED	true	src/app/(dashboard)/.../ProxyPoolTab.tsx	Show/hide the Deploy Vercel Relay button in the Proxy Pool tab.
VERCEL_API_BASE	https://api.vercel.com	src/app/api/settings/proxy/vercel-deploy/route.ts	Vercel API base URL override (for testing).
NEXT_PUBLIC_VERCEL_RELAY_DEFAULT_PROJECT	omniroute-relay	src/app/(dashboard)/.../VercelRelayModal.tsx	Default project name pre-filled in the Vercel Relay deploy modal.
TAILSCALE_BIN	<i>(auto-detect)</i>	src/lib/tailscaleTunnel.ts	Explicit path to the tailscale binary.
TAILSCALED_BIN	<i>(auto-detect)</i>	src/lib/tailscaleTunnel.ts	Explicit path to the tailscaled daemon binary.
NGROK_AUTHTOKEN	<i>(unset)</i>	src/lib/ngrokTunnel.ts	Authenticates outbound ngrok tunnels.
DB_BACKUP_MAX_FILES	20	src/lib/db/backup.ts	Maximum SQLite backup files retained on disk.
DB_BACKUP_RETENTION_DAYS	0	src/lib/db/backup.ts	Maximum age (days) of retained backups. 0 disables age-based pruning.
OMNIROUTE_TLS_PROXY_URL	<i>(unset)</i>	open-sse/services/chatgptTlsClient.ts	Override the TLS sidecar URL for tests. Production should leave unset.
CONTAINER_HOST	docker	scripts/check-permissions.sh	Container runtime hint for the entrypoint permission check. Set to podman under rootless Podman so the fix instructions use podman unshare -chown instead of sudo chown.
QUOTA_STORE_DRIVER	sqlite	src/lib/quota/storeFactory.ts	Quota-share consumption store backend: sqlite (default) or redis.
QUOTA_STORE_REDIS_URL	<i>(unset)</i>	src/lib/quota/storeFactory.ts	Redis connection string used when QUOTA_STORE_DRIVER=redis (e.g. redis://localhost:6379).
QUOTA_SATURATION_THRESHOLD	0.5	src/lib/quota/enforce.ts	Pool saturation ratio (0..1); at/above it the pool enters strict mode (no borrowing).
QUOTA_SOFT_DEPRIORITIZE_FACTOR	0.7	open-sse/services/combo.ts	Score multiplier (0..1) applied to a target when the soft quota policy deprioritizes it.
QUOTA_CONSUMPTION_RETENTION_DAYS	14	src/lib/db/quotaConsumption.ts	Retention window (days) for quota_consumption buckets before GC (gcQuotaConsumption).
AGENTBRIDGE_UPSTREAM_CA_CERT	<i>(unset)</i>	src/mitm/manager.ts	Extra CA certificate (PEM) trusted for AgentBridge upstream TLS connections.

Variable	Default	Source File	Description
INSPECTOR_BUFFER_SIZE	1000	src/mitm/inspector/buffer.ts	Max captured requests held in the Traffic Inspector ring buffer.
INSPECTOR_MAX_BODY_KB	1024	src/mitm/inspector/buffer.ts	Max captured request/response body size (KB) before truncation.
INSPECTOR_HTTP_PROXY_PORT	8080	src/mitm/inspector/httpProxyServer.ts	Local port for the Traffic Inspector HTTP proxy.
INSPECTOR_HTTP_PROXY_AUTOSTART	false	src/mitm/inspector/httpProxyServer.ts	Auto-start the inspector HTTP proxy on boot.
INSPECTOR_TLS_INTERCEPT	false	src/lib/inspector/captureState.ts	Enable TLS interception (MITM) for captured HTTPS traffic.
INSPECTOR_LLM_HOSTS_EXTRA	(unset)	src/lib/inspector/captureState.ts	Extra hostnames (comma-separated) treated as LLM endpoint for capture.
INSPECTOR_MASK_SECRETS	true	src/mitm/inspector/buffer.ts	Mask secrets (auth headers / API keys) in captured traffic.
INSPECTOR_SYSTEM_PROXY_GUARD_MINUTES	30	src/app/api/tools/traffic-inspector/capture-modes/system-proxy/route.ts	Minutes before the system-proxy guard auto-reverts OS proxy settings.
INSPECTOR_INTERNAL_INGEST_TOKEN	(auto)	src/app/api/tools/traffic-inspector/internal/ingest/route.ts	Token authenticating internal capture ingest into the inspector.
PLAYGROUND_COMPARE_MAX_COLUMNS	4	src/app/(dashboard)/dashboard/playground/	Max number of side-by-side columns in the Playground compare mode.
PLAYGROUND_IMPROVE_PROMPT_DEFAULT_MODEL	(unset)	src/app/(dashboard)/dashboard/playground/	Default model for the Playground 'improve prompt' action (falls back to the active model when unset).

26. Test & E2E Harness

Used by `scripts/dev/run-next-playwright.mjs`, `scripts/dev/smoke-electron-packaged.mjs`, `scripts/dev/run-ecosystem-tests.mjs`, and `scripts/build/uninstall.mjs`. Leave every value below unset in production deployments.

Variable	Default	Source File	Description
OMNIRoute_E2E_BOOTSTRAP_MODE	auth	scripts/dev/run-next-playwright.mjs	E2E bootstrap mode (auth, fresh, reuse) for the Playwright runner.
OMNIRoute_E2E_PASSWORD	falls back to INITIAL_PASSWORD	scripts/dev/run-next-playwright.mjs	Admin password injected into the Playwright environment.
OMNIRoute_DISABLE_LOCAL_HEALTHCHECK	true	scripts/dev/run-next-playwright.mjs	Disable the local healthcheck poll during Playwright runs.
OMNIRoute_DISABLE_TOKEN_HEALTHCHECK	true	scripts/dev/run-next-playwright.mjs	Disable the OAuth token healthcheck loop during tests.
OMNIRoute_HEALTHCHECK_SKIP_PROVIDERS	(unset)	src/lib/tokenHealthCheck.ts	Comma-separated providers excluded from the proactive token-refresh sweep (e.g. codex, openai). Targeted alternative to fully disabling the healthcheck – short-TTL providers keep refreshing while cascade providers stay reactive-only.
OMNIRoute_HIDE_HEALTHCHECK_LOGS	true	scripts/dev/run-next-playwright.mjs	Silence healthcheck noise in Playwright stdout.
OMNIRoute_PLAYWRIGHT_SKIP_BUILD	0	scripts/dev/run-next-playwright.mjs	Skip the Next.js production build before Playwright starts (CI optimization).
OMNIRoute_SKIP_UNINSTALL_HOOK	0	scripts/build/uninstall.mjs	Skip the OmniRoute uninstall hook (used by CI to keep node_modules intact).
ECOSYSTEM_SERVER_WAIT_MS	180000	scripts/dev/run-ecosystem-tests.mjs	Wait time (ms) for the server to become healthy before running ecosystem/protocol tests.
ELECTRON_SMOKE_URL	http://127.0.0.1:20128/login	scripts/dev/smoke-electron-packaged.mjs	URL the Electron smoke harness expects the packaged app to serve.
ELECTRON_SMOKE_TIMEOUT_MS	45000	scripts/dev/smoke-electron-packaged.mjs	Total timeout (ms) before the smoke harness gives up.

Variable	Default	Source File	Description
ELECTRON_SMOKE_SETTLE_MS	2000	scripts/dev/smoke-electron-packaged.mjs	Settle window (ms) after the page loads.
ELECTRON_SMOKE_APP_EXECUTABLE	(auto)	scripts/dev/smoke-electron-packaged.mjs	Explicit path to the packaged Electron executable.
ELECTRON_SMOKE_DATA_DIR	(tmpdir)	scripts/dev/smoke-electron-packaged.mjs	Data directory for the Electron smoke run.
ELECTRON_SMOKE_KEEP_DATA	0	scripts/dev/smoke-electron-packaged.mjs	Set 1 to preserve the smoke data directory after the run.
ELECTRON_SMOKE_STREAM_LOGS	0	scripts/dev/smoke-electron-packaged.mjs	Set 1 to stream Electron logs to stdout during the run.
CLI_DEVIN_BIN	(PATH lookup)	open-sse/executors/devin-cli.ts	Override the Devin CLI binary path.

Docs translation pipeline

Used by `scripts/i18n/run-translation.mjs` (the `npm run i18n:run` command). All five variables are unset by default — set them in `.env` only on machines that should be able to run the docs translator.

Variable	Default	Source File	Description
OMNIROUTE_TRANSLATION_API_URL	(unset)	scripts/i18n/run-translation.mjs	OpenAI-compatible base URL for the translation backend.
OMNIROUTE_TRANSLATION_API_KEY	(unset)	scripts/i18n/run-translation.mjs	Bearer token for the translation backend (never logged).
OMNIROUTE_TRANSLATION_MODEL	(unset)	scripts/i18n/run-translation.mjs	Model id, e.g. gpt-4o-mini Or cx/gpt-5.4-mini.
OMNIROUTE_TRANSLATION_TIMEOUT_MS	60000	scripts/i18n/run-translation.mjs	Per-request timeout in milliseconds.
OMNIROUTE_TRANSLATION_CONCURRENCY	4	scripts/i18n/run-translation.mjs	Parallel translation requests when running over multiple files / locales.

Audit: Removed / Dead Variables

The following variables appeared in previous versions of `.env.example` but have **no runtime references** in the current codebase. They have been removed:

Variable	Reason
STORAGE_DRIVER=sqlite	Never read by any source file. SQLite is the only supported driver — no selection needed.
INSTANCE_NAME=omniroute	Present in old docs/env templates but unused at runtime. May return in a future multi-instance feature.
SQLITE_MAX_SIZE_MB=2048	Not referenced in source code. Database size is not artificially limited.
SQLITE_CLEAN_LEGACY_FILES=true	Not referenced in source code. Legacy cleanup was likely removed.
CLI_ROO_BIN	Not registered in <code>src/shared/services/cliRuntime.ts</code> .
CLI_KIMI_CODING_BIN	Not registered in <code>src/shared/services/cliRuntime.ts</code> (Kimi Coding uses OAuth, not a CLI binary).
IFLOW_OAUTH_CLIENT_ID / IFLOW_OAUTH_CLIENT_SECRET	Not referenced anywhere in source code.
CEREBRAS_API_KEY / COHERE_API_KEY / FIREWORKS_API_KEY / GROQ_API_KEY / MISTRAL_API_KEY / NEBIUS_API_KEY / PERPLEXITY_API_KEY / TOGETHER_API_KEY / XAI_API_KEY	Removed in v3.8.0. The runtime no longer reads these env vars — credentials come from Dashboard / <code>data/provider-credentials.json</code> / encrypted DB.
CURSOR_PROTOBUF_DEBUG	Removed in v3.8.0. Cursor executor uses <code>CURSOR_DEBUG</code> / <code>CURSOR_STREAM_DEBUG</code> (see §22).
CLI_COMPAT_KIRO	Removed in v3.8.0. Kiro is in <code>CLI_COMPAT_OMITTED_PROVIDER_IDS</code> — its toggle has no effect.
QIANFAN_API_KEY	Removed alongside other unused provider API key stubs in v3.8.0.

Default Value Corrections

Variable	Old <code>.env.example</code> Value	Actual Code Default	Fixed
APP_LOG_RETENTION_DAYS	90	7	✅ Removed misleading value; documented 7 as default
CALL_LOG_RETENTION_DAYS	90	7	✅ Removed misleading value; documented 7 as default

OpenCode config regeneration (ad-hoc tooling)

Used by `scripts/ad-hoc/regen-opencode-config.ts` to regenerate an `opencode.json` with accurate `limit.context` and `limit.output` values pulled from the running OmniRoute instance. None of these are required for normal operation — the script is developer tooling only.

Variable	Default	Source File	Description
OMNIROUTE_URL	<code>http://localhost:20128</code>	<code>scripts/ad-hoc/regen-opencode-config.ts</code>	Base URL of the OmniRoute instance to query for <code>/v1/models</code> .

Variable	Default	Source File	Description
OMNIRoute_KEY	(unset)	scripts/ad-hoc/regen-opencode-config.ts	API key to authenticate against the OmniRoute /v1/models endpoint. Falls back to OPENCODE_API_KEY when unset.
OPENCODE_API_KEY	(unset)	scripts/ad-hoc/regen-opencode-config.ts	OpenCode-style API key (sk-...) written into the regenerated opencode.json. Falls back to OMNIRoute_KEY when unset.
