

MAP.md — novus-aexenti

Cognitive Architecture & Navigation Map

novus-aexenti/

- |— MAP.md # This directory map and cognitive pipeline topology
- |— manifest.jsonl # Machine-readable registry of files, SHA256 hashes, and types
- |— AGENTS.md # Operational constraints, triage vs executor model roles
- |— RESUME.md # Active model weights, execution state, and session checkpoints
- |— UNRESOLVED.md # Open optimization tickets, benchmark gaps, and backlog tasks
- |
- |— dual_agent_router/ # Dynamic query analysis, model routing & prompt bridging
- | |— query_analyzer.py # Evaluates token complexity and intent (0.8B vs 9B)
- | |— executor_bridge.py # Formats clean, compressed meta-prompts for execution models
- | |— model_profile_registry.json # Model specs, context window sizes, quantization types
- |
- |— mem0_episodic/ # In-session episodic facts, habit retention & preferences
- | |— vector_recall_engine.py # Local semantic lookup script for conversational facts
- | |— rolling_habits.json # Concrete syntax rules, naming invariants & user habits
- |
- |— reasoning_bank/ # Execution flywheel, crash recovery & test batteries

|— active_execution_paths.json # Persistent ledger of fractional task steps

|— baseline_tests.json # Standardized regression capability test battery

Subsystem Pipeline Flow

1. **Ingress:** Incoming user prompt arrives at `dual_agent_router/query_analyzer.py`.
2. **Triage:** Short, deterministic requests route to local on-device 0.8B triage. Complex tasks route to 9B executor.
3. **Context Enrichment:** `mem0_episodic/vector_recall_engine.py` injects relevant episodic facts and user habits from `rolling_habits.json`.
4. **Formatting:** `dual_agent_router/executor_bridge.py` strips conversational fluff and builds structured meta-prompts.
5. **Execution & Checkpointing:** Tasks are checkpointed in `reasoning_bank/active_execution_paths.json` to enable zero-loss crash recovery.