

Large scale deep learning parameter server

Ching-Yuan, Tsai

2017,4,26

Presented by Ching-Yuan, Tsai

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Abstract
Goals
Architecture

Outline

- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull
- 5 Reduce idle

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Abstract
Goals
Architecture

Abstract

- We propose a parameter server framework for distributed deep learning problems.

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Abstract
Goals
Architecture


Goals

- Efficient communication
- Fast computation
- Fault tolerance
- Scalability

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Abstract
Goals
Architecture

Architecture



Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Parameters
Long idle time

Outline

- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull
- 5 Reduce idle

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Parameters
Long idle time

Parameters

- Realistic training models have 10^9 to 10^{12} parameters.
- Accessing parameters need high network bandwidth.

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Parameters
Long idle time

Long idle time

- Worker waits until server aggregates all parameters.



Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD


Key
Value
Vector

Outline

- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull
- 5 Reduce idle


Key

- Key indicate neural id.



Value

- Value indicate weights with respect to the neural id.



Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Key
Value
Vector

Vector

- Vector is the combination of key and values.
- Vector is the minimum communication unit.

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Motivation
Idea
Is it correct ?

Outline

- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull**
- 5 Reduce idle

Motivation

- Workers waste a lot of time to wait network communication and parameter aggregation.




Idea

- Sending less data to server.
- Sending vectors whose key is within the given range.

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Motivation
Idea
Is it correct ?

Is it correct ?



Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Assumption
What range size is the best ?
Best size
Server view

Outline

- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull
- 5 **Reduce idle**

Assumption


What range size is the best ?
Best size
Server view

Assumption

- Computation time is fixed.
- Message communication time decrease as communication range decrease.
- Aggregation time decrease as communication range decrease.

What range size is the best ?


- We can decrease size ...



Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Assumption
What range size is the best ?
Best size
Server view


Best size



Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Assumption
What range size is the best ?
Best size
Server view

Server view



Outline


- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull
- 5 Reduce idle

Handwritten digits

- Subset of a larger set from NIST.
- 60000 examples
- One color channel
- fixed-size image

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implimentation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Handwritten digits



Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Training Model
Server Synchronization

Outline

- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull
- 5 Reduce idle


Training Model

- Use keras
- Three dense layers each has 512 neurals
- 98 percent accuracy

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Training Model
Server Synchronization

Training Model



Server Synchronization

- Synchronize client iterations
- Python client, C server
- Two states machine
 - Push state
 - Pull state

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Future work

Outline

- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull
- 5 Reduce idle

Future work

- How to fit computation time and message communication time.
- If Computation time is not fixed.
- Implement parameter server.

Outline

- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull
- 5 Reduce idle

Sliding Window

- Sliding Window is an integer range indicating the valid iterations.
- Clients can not push parameters with the invalid iterations.
- Server checks the low bound of the sliding window when the clients push parameters.
- Shift the sliding window.

Sliding Window

- Time complexity
 - Clients push parameters: $O(1)$
 - Server check low bound: $O(1)$
- Space complexity: $O(l)$ which l is the length of the sliding window.
 - Independent on the # of clients thus has good scalability.

BSP

- Bulk Synchronous Parallel
- Clients can not continue to the next iteration until the server receives all gradients.
- It guarantees convergence.

ASP

- Asynchronous Parallel
- Clients continue to the next iteration without waiting for each other.
- It may not converge.
- It can be up to 10X slower when the heterogeneity increases.

SSP

- Stale Synchronous Parallel
- The faster client can not go ahead the slowest one more than a predefined staleness.
- SGD usually uses this method.
- It can be slower when the heterogeneity increase.

Constant learning rate, Dynamic learning rate

- CONSGD
 - A constant global learning rate and multiplies it to each local update.
- DYNSSGC
 - To further improve performance over CONSGD.
 - Server dynamic update global learning rate basing on maximum staleness.

Introduction
Challenge
(key, value) Vector
Range push and pull
Reduce idle
Mnist model
Implementation
Future work
Stale Synchronous Parallel
Global learning rate with SSP SGD

Angel Parameter Server
Splitting gradients

Outline

- 1 Introduction
- 2 Challenge
- 3 (key, value) Vector
- 4 Range push and pull
- 5 Reduce idle

Constant learning rate, Dynamic learning rate

- CONSGD
 - A constant global learning rate and multiplies it to each local update.
- DYNSSGC
 - To further improve performance over CONSGD.
 - Server dynamic update global learning rate basing on maximum staleness.

Things they do not consider

- The workers with smaller iterations have larger local learning rate.

- $$w_{t+1} = w_t + \frac{\eta}{\sqrt{\sum_{i \leq t+1} (g_i)^2}} g_{t+1}$$

Spliting gradients

- Spliting gradient into 'direction' and 'distance'.
 - Distance: $|gradient|$.
 - Dircetion: $\frac{gradient}{|gradient|}$
 - Gradient = Distance * Direction
- Scheduling distance of each gradient.
 - Do not change the distance of the sum of all latest gradients of each worker.

Computing distances

- Server computes the the following t when push commands occur.
 - $t \left| \sum_{i=0}^M \alpha_c \frac{g_c^i}{|g_c^i|} \right| = \left| \sum_{i=0}^M g_c^i \right|$
- $t * \alpha_c$ is the new distance of g_c^i