

# 381V Visual Recognition Final Project Proposal

Keivaun Waugh  
University of Texas at Austin  
keivaunwaugh@gmail.com

Paul Choi  
University of Texas at Austin  
choipaul96@gmail.com

## Abstract

*In this project, we plan to explore the benefits of providing semantic segmentation data to an image super-resolution (SR) system.*

## 1. Introduction

Image super-resolution is a compelling area of computer vision. Being able to convert low resolution photos and video to higher resolution counterparts is an important problem as hardware continues to improve. With higher resolution displays and cameras available today than ever before, it would be nice if we could convert old media to the same resolution standards as current photos and video. Naive methods of upsampling using bicubic interpolation introduce many artifacts and produce visually displeasing images. With the increase in popularity of deep networks sparked by work from Krizhevsky et al. [7], it appears that some variant of a deep network could provide good results for this task. We also plan to combine semantic segmentation with state-of-the-art SR techniques to provide for better results.

## 2. Related Work

Prior work involving image synthesis with deep networks involves one of two techniques: using a more conventional CNN for upsampling [5] [9] [6] or using a generative adversarial network (GAN) [3]. Typically, the CNN approaches attempt to minimize the per-pixel loss between the upsampled output image and the original unmodified image. The error metric frequently used is peak signal-to-noise ratio (PSNR). However, when this is applied directly on the pixel space, this often encourages the network to make soft changes in the upsampled image rather than generate the high-frequency changes often found in real images. GAN based approaches like in [8] attempt to overcome this by using an adversarial network. Though they get lower PSNR values, the images often look more realistic, which suggests that some other metric should be used to get better results.

In [1], Chen and Koltun experiment with using semantic segmentation from the cityscapes dataset [2] to perform image generation of arbitrary size. However, to our knowledge, there have been no papers published that attempt to merge together this explicit semantic data with a SR technique for better results. We believe that this will provide for better results than what is currently achievable with the published methods.

## 3. Technical Plan

## 4. Experimental Plan

## 5. Sources of Data

## 6. Partner Plan

## 7. Speculation of Results

Current state-of-the-art semantic segmentation methods already involve CNNs. One may argue that a CNN based approach for SR would automatically learn information regarding segmentation if it is useful for providing better results. However, this argument does not take into account the difficulty of learning such information. A parallel argument was made for residual networks in [4] with regards to learning identity mappings. However, the authors found that it was often difficult for networks to learn such mappings. We predict that adding the semantic segmentation data explicitly to the network will allow it to make more intelligent decisions along object boundaries. We expect this will help provide more crisp edges. Because of the success with using semantic masks alongside CNNs for image generation of arbitrary size in [1], we expect that our results will be better at high upsampling factors.

## References

- [1] Q. Chen and V. Koltun. Photographic image synthesis with cascaded refinement networks. *CoRR*, abs/1707.09405, 2017.
- [2] M. Cordts, M. Omran, S. Ramos, T. Rehfeld, M. Enzweiler, R. Benenson, U. Franke, S. Roth, and B. Schiele. The cityscapes dataset for semantic urban scene understanding. *CoRR*, abs/1604.01685, 2016.

- [3] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems 27*, pages 2672–2680. Curran Associates, Inc., 2014.
- [4] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. *CoRR*, abs/1512.03385, 2015.
- [5] J. Johnson, A. Alahi, and F. Li. Perceptual losses for real-time style transfer and super-resolution. *CoRR*, abs/1603.08155, 2016.
- [6] J. Kim, J. K. Lee, and K. M. Lee. Deeply-recursive convolutional network for image super-resolution. *CoRR*, abs/1511.04491, 2015.
- [7] A. Krizhevsky, I. Sutskever, and G. E. Hinton. Imagenet classification with deep convolutional neural networks. In F. Pereira, C. J. C. Burges, L. Bottou, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems 25*, pages 1097–1105. Curran Associates, Inc., 2012.
- [8] C. Ledig, L. Theis, F. Huszar, J. Caballero, A. P. Aitken, A. Tejani, J. Totz, Z. Wang, and W. Shi. Photo-realistic single image super-resolution using a generative adversarial network. *CoRR*, abs/1609.04802, 2016.
- [9] W. Shi, J. Caballero, F. Huszár, J. Totz, A. P. Aitken, R. Bishop, D. Rueckert, and Z. Wang. Real-time single image and video super-resolution using an efficient sub-pixel convolutional neural network. *CoRR*, abs/1609.05158, 2016.