



Title	<i>getkey</i> Access to the ListTrac API is a two-step process: 1. Generate a key using the <i>getKey</i> method as detailed here 2. Create a token by hashing the key with your ListTrac password using MD5 The token is a required parameter for each subsequent request to the ListTrac API.
Version	1.0
URL	<code>https://b2b.listtrac.com/api/getkey?orgID=xxx&username=xxx</code>
Method	<i>GET</i>
URL Parameters	Required Parameters: <code>orgID=[xxx]&username=[xxx]</code> example: orgID=17&username=123456 description: orgID and username are identifiers provided by the ListTrac support team allowing the API to uniquely identify the requestor.



Sample Response and Token Generation	<i>Successful Response</i> <pre>{ "key": "26a5560f-11c6-4969-866d-2c5393757517", "message": "", "returncode": 0 }</pre> <i>Unsuccessful Response</i> <pre>{ "key": "", "message": "combination of username and org ID does not exist", "returncode": -1 }</pre> ListTrac Token Generation The key in the getKey response should be combined with your ListTrac password and the resulting string encrypted using the MD5 algorithm to generate a token: MD5("password26a5560f-11c6-4969-866d-2c5393757517") Sample resulting token: 50b2060ba108faa7cce9b93611f7e8c0 Note: Replace password with your ListTrac password provided during the account setup process.
---	--



Response Codes	returncode = 0 - Success returncode = -1 - Error: Authentication Failed
Notes	



Title	<i>getmetricsbyorganization</i> getmetricsbyorganization is a ListTrac API endpoint that supports requests for online metrics related to real estate listings. Metrics include number of listing views, number of listing inquiries, and other metric types detailed below in the <i>payload parameters</i> section. The response includes aggregate counts of the metric for each site vendor with optional detail also providing counts at the listing level.
Version	1.0
URL	<code>https://b2b.listtrac.com/api/getmetricsbyorganization</code>
Method	<i>POST</i>
Sample Request	<pre>{ "request":{ "token":"7f8607318d851ef777c15394c7658ff6", "viewtype":"agent", "viewtypeID":"agent123", "metric":"view,inquiry", "details":"true", "startdate":"20151201", "enddate":"20151202" } }</pre>
Payload Parameters	Required Parameters:



token=[GUID]

example: "token"=3F2504E0-4F89-41D3-9A0C-0305E82C3301

description: token generated as described in the getKey section

viewtype=[string]

example: "viewtype"="broker"

allowable values: mls, broker, agent, listing

description: metrics may be provided for a specific listing or in aggregate for an agent, broker, or MLS's on-market inventory; this parameter determines which view of data will be provided in the response.

viewtypeID=[string]

example: "viewtypeID"="broker123"

description: viewtypeID is the identifier related to the viewtype; for each of the allowable viewtypes; the identifiers passed in this parameter are as follows:

mls: ID representing the MLS as provided during setup

broker: ID from MLS membership representing the broker

agent: ID from MLS membership representing the agent, i.e., Agent ID

listing: MLS or listing ID

metric=[string]

example: "metric"="view"

allowable values: view, inquiry, share, favorite, gallery, vtour

description: metric defines the activity type for which metrics are delivered in the response; multiple metrics may be requested using a comma-delimited list, e.g., "view,inquiry".

startdate=[date]

example: "startdate"="20151028"

description: beginning of the date range for which metrics are provided; format is YYYYMMDD.



	enddate=[date] example: "enddate"="20151029" description: end of the date range for which metrics are provided; format is YYYYMMDD. Optional Parameters: details=[boolean] example: "details"="true" description: if set to true, in addition to the aggregate count for the requested metric for the given date range, the response shall also include counts for each listing within the requested date range.
Sample Response with Listing-level Metrics	<pre>{ "request":{ "token":"7f8607318d851ef777c15394c7658ff6", "viewtype":"mls", "viewtypeID":"gamls", "metric":"view,inquiry", "details":"true", "startdate":"20151201", "enddate":"20151202" }, "response":{ "message":""," "returncode":0, "metrics":{ "sites":[{ "sitename":"Diverse Solutions", "sitetype":"IDX",</pre>



```
"dates":[
  {
    "date":"20151201",
    "details":[
      {
        "listingid":"7535955",
        "view":"1",
        "inquiry":""
      },
      {
        "listingid":"7549799",
        "view":"1",
        "inquiry":""
      }
    ]
  },
  {
    "date":"20151202",
    "details":[
      {
        "listingid":"7535955",
        "view":"10",
        "inquiry":"1"
      },
      {
        "listingid":"7549799",
        "view":"12",
        "inquiry":"2"
      }
    ]
  }
]
```



```
    },
    {
      "sitename": "Market Leader",
      "sitetype": "IDX",
      "dates": [
        {
          "date": "20151201",
          "details": [
            {
              "listingid": "7535955",
              "view": "19",
              "inquiry": ""
            },
            {
              "listingid": "7549799",
              "view": "14",
              "inquiry": ""
            }
          ]
        },
        {
          "date": "20151202",
          "details": [
            {
              "listingid": "7535955",
              "view": "14",
              "inquiry": "1"
            },
            {
              "listingid": "7549799",
              "view": "11",
```



	<pre>"inquiry": "1" }] }] }] }] } } }</pre>
Response Codes	returncode = 0 - Success returncode = 98 - Error: 'No stats are available for the given date range' returncode = 99 - Error: Message will contain error details
Notes	