

Este é nosso CTF de Hardware Hacking, usando a firmware vulnerável IoTGoat. Vamos testar o seu conhecimento em Hardware Hacking descobrindo alguns artefatos nesta imagem.

Qual o nome da interface de rede que recebeu IP?

Utilizado o comando `ip addr` para analisar a interface de rede.

```
root@IoTGoat:~# ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel master br-lan
    state UP qlen 1000
    link/ether 08:00:27:bb:27:68 brd ff:ff:ff:ff:ff:ff
3: br-lan: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state UP qlen 1000
    link/ether 08:00:27:bb:27:68 brd ff:ff:ff:ff:ff:ff
    inet 10.0.2.15/24 brd 10.0.2.255 scope global br-lan
        valid_lft forever preferred_lft forever
    inet6 fe80::a00:27ff:febb:2768/64 scope link
        valid_lft forever preferred_lft forever
root@IoTGoat:~#
```

Rede identificada sendo br-lan.

R: FIAP{br-lan}