2650026_lab6_updated

November 8, 2026

Roll No.	Subject Code	Assignment No.
2650026	CS69101	Lab 6

Given a set of integer elements stored in an input file, `input.txt`, construct a **Segment Tree** to efficiently perform **Range Minimum Query (RMQ)** and **Range Maximum Query** operations.

The Segment Tree should store both the minimum and maximum values corresponding to each segment of the input array. Implement range query and point update operations while maintaining the correctness of the Segment Tree.

[1]:
```
import os
import sys
from io import TextIOWrapper
from typing import Self, Any, Callable, TypeVar, Generic, Optional
import random
import pandas as pd
import matplotlib.pyplot as plt
from matplotlib.pylab import figure

sys.setrecursionlimit(100000) # Fix to avoid RecursionError

prep_arr = [random.randint(1, (i+1)*10) for i in range(10000)] # Random Array␣
 ↪of 10000 Elements
# prep_arr.sort() # Sorted Array for Worst Case Scenario
print(prep_arr[:25])
print(len(prep_arr))

# Write the array to a file
f = open("./2650026_lab6_data/input0.txt", "w")
for i in prep_arr:
    f.write(f"{i}, ")
f.write("\n")
f.close()

del prep_arr
del f
```

```
iterations = 0
PRINT_DEBUG = False
```

```
[9, 1, 16, 14, 48, 20, 70, 20, 38, 94, 42, 27, 27, 99, 109, 14, 26, 128, 6, 143,
75, 24, 207, 164, 80]
10000
```

1 Q1.

Read integer elements from `input.txt` and construct a Segment Tree using the given array elements.

1.1 File Read

[2]:
```
# Read a set of integer elements from an input file (input.txt)
arr0 = []
data0 = open("./2650026_lab6_data/input.txt", 'r')

try:
    for line in data0.readlines():
        line_data = line.rstrip().rstrip(',').replace(',',' ').split() #using␣
 ↪rstrip to remove the \n
        for data in line_data:
            arr0.append(int(data))
    data0.close()
except Exception as e:
    sys.exit("[ERROR] Invalid data" + str(e))

n = len(arr0)
assert n >= 4, "[FATAL!] input.txt must contain at least 4 integer elements"
```

[3]:
```
print(arr0)
```

```
[70, 50, 90, 77, 55, 348, 76, 67, 69, 420, 25, 911, 210, 108, 768, 1080, 720]
```

1.2 Segment Tree

[4]:
```
# LEGACY CODE LOL

# class Segment_Node:
#     def __init__(self, value: int | None = None):
#         self.__lchild = None
#         self.__rchild = None
#         self.__value = None

#     def find_leaf(self) -> Self:
#         if self.__lchild is None and self.__rchild is None:
#             return self
#         elif self.__lchild is not None:
```

```
#             return self.__lchild.find_leaf()
#         else:
#             assert self.__rchild is not None # This is to shut the LSP up.
#             return self.__rchild.find_leaf()

#     def insert(self, value: int) -> Self: # Guess why this is wrong.
#         if self.__value is None:
#             self.__value = value
#         if self.__value == value:
#             return self
#         elif value < self.__value: #
#             if self.__lchild is None:
#                 new_node = type(self)(value) # type(self) instead of␣
 ↪Segment_Node to shut the linter up.
#                 self.__lchild = (new_node)
#             else:
#                 self.__lchild.insert(value)
#         else:
#             if self.__rchild is None:
#                 new_node = type(self)(value)
#                 self.__rchild = new_node
#             else:
#                 self.__rchild.insert(value)
#         return self
```

[5]:
```
class Segment_Tree:
    def __init__(self):
        self.__size = 0
        self.__min = []  # minimum of every segment (heap-indexed: children of␣
 ↪i are 2i+1 and 2i+2)
        self.__max = []  # maximum of every segment

    def __node(self, index: int) -> tuple[int, int]:
        return (self.__min[index], self.__max[index])

    # Q4: combine the (minimum, maximum) results of two child nodes
    def merge(self, left: tuple[int, int], right: tuple[int, int]) ->␣
 ↪tuple[int, int]:
        return (min(left[0], right[0]), max(left[1], right[1]))

    # Q2: build the tree over arr; every node stores the minimum and the␣
 ↪maximum of its segment
    def build(self, arr: list[int], left_bound: int = 0, right_bound: int |␣
 ↪None = None, index: int = 0) -> None:
        global iterations
        if right_bound is None:  # top-level call: allocate the tree for␣
 ↪len(arr) elements
```

```
            assert len(arr) > 0, "Cannot build a Segment Tree over an empty␣
↪array"
            self.__size = len(arr)
            self.__min = [0] * 4 * self.__size
            self.__max = [0] * 4 * self.__size
            right_bound = self.__size - 1
        iterations += 1  # one node visited
        if left_bound == right_bound:
            self.__min[index] = self.__max[index] = arr[left_bound]
            return
        mid = (left_bound + right_bound) // 2
        left_child_index = index * 2 + 1
        right_child_index = index * 2 + 2

        self.build(arr, left_bound, mid, left_child_index)
        self.build(arr, mid + 1, right_bound, right_child_index)

        self.__min[index], self.__max[index] = self.merge(self.
↪__node(left_child_index), self.__node(right_child_index))

    # Q3: (minimum, maximum) of arr[query_start..query_end]
    def query(self, query_start: int, query_end: int, left_bound: int = 0,␣
↪right_bound: int | None = None, index: int = 0) -> Optional[tuple[int, int]]:
        global iterations
        if right_bound is None:  # top-level call
            assert 0 <= query_start <= query_end < self.__size, f"Invalid range␣
↪[{query_start}, {query_end}]"
            right_bound = self.__size - 1
        iterations += 1  # one node visited
        if right_bound < query_start or query_end < left_bound:
            return None  # segment lies completely outside the query range

        if query_start <= left_bound and right_bound <= query_end:
            return self.__node(index)  # segment lies completely inside the␣
↪query range

        mid = (left_bound + right_bound) // 2
        left_child_index = index * 2 + 1
        right_child_index = index * 2 + 2

        left_result = self.query(query_start, query_end, left_bound, mid,␣
↪left_child_index)
        right_result = self.query(query_start, query_end, mid + 1, right_bound,␣
↪right_child_index)

        if left_result is not None and right_result is not None:
```

```
            return self.merge(left_result, right_result)
        elif left_result is not None:
            return left_result
        else:
            return right_result

    # Q5: set arr[target_index] = value and recompute every segment on the path to the root
    def update(self, target_index: int, value: int, left_bound: int = 0, right_bound: int | None = None, index: int = 0) -> None:
        global iterations
        if right_bound is None:  # top-level call
            assert 0 <= target_index < self.__size, f"Invalid index {target_index}"
            right_bound = self.__size - 1
        iterations += 1  # one node visited
        if left_bound == right_bound:
            self.__min[index] = self.__max[index] = value
            return
        mid = (left_bound + right_bound) // 2
        left_child_index = index * 2 + 1
        right_child_index = index * 2 + 2

        if target_index <= mid:
            self.update(target_index, value, left_bound, mid, left_child_index)
        else:
            self.update(target_index, value, mid + 1, right_bound, right_child_index)

        self.__min[index], self.__max[index] = self.merge(self.__node(left_child_index), self.__node(right_child_index))

    # Height in levels (a single node is 1)
    def height(self, left_bound: int = 0, right_bound: int | None = None) -> int:
        if right_bound is None:
            assert self.__size > 0, "The tree has not been built yet"
            right_bound = self.__size - 1
        if left_bound == right_bound:
            return 1
        mid = (left_bound + right_bound) // 2
        return 1 + self.height(left_bound, mid)  # the left half is never smaller than the right half, so it is the deepest

    # Q6: one line per node, indented by depth (pre-order)
```

```
    def representation(self, left_bound: int = 0, right_bound: int | None =␣
↪None, index: int = 0, depth: int = 0) -> list[str]:
        if right_bound is None:
            right_bound = self.__size - 1
        line = f"{'    ' * depth}[{left_bound}, {right_bound}]  minimum = {self.
↪__min[index]}, maximum = {self.__max[index]}"
        if left_bound == right_bound:
            return [line]
        mid = (left_bound + right_bound) // 2
        return ([line]
                + self.representation(left_bound, mid, index * 2 + 1, depth + 1)
                + self.representation(mid + 1, right_bound, index * 2 + 2,␣
↪depth + 1))
```

[6]:
```
def linear_range_search(arr: list[int], query_start: int, query_end: int, index:
↪ int | None = None) -> tuple[int, int]:
    global iterations
    if index is None:
        index = query_start
    iterations += 1  # one element scanned
    if index == query_end:
        return (arr[index], arr[index])
    rest_min, rest_max = linear_range_search(arr, query_start, query_end, index␣
↪+ 1)
    return (min(arr[index], rest_min), max(arr[index], rest_max))
```

[7]:
```
stree0 = Segment_Tree()
# stree0.set_rangefn("SUM")
```

2 Q2.

Implement the `build()` operation to construct the Segment Tree such that each node stores:

- Minimum value of its corresponding range.
- Maximum value of its corresponding range.

[8]:
```
iterations = 0
stree0.build(arr0)

print(f"build() visited {iterations} nodes for {n} elements (2n - 1 = {2 * n -␣
↪1}).")
print(f"Tree height: {stree0.height()} levels")
```

```
build() visited 33 nodes for 17 elements (2n - 1 = 33).
Tree height: 6 levels
```

3 Q3.

Implement `query(L, R)` to find:

- Minimum element in the range [L, R].
- Maximum element in the range [L, R].

[9]:
```
# queries.txt: the number of range queries, followed by one "L R" pair per line
queries = []
try:
    data1 = open("./2650026_lab6_data/queries.txt", 'r')
    num_queries = int(data1.readline())
    for _ in range(num_queries):
        left, right = map(int, data1.readline().split())
        assert 0 <= left <= right < n, f"Query [{left}, {right}] is outside the␣
 ↪array"
        queries.append((left, right))
    data1.close()
except Exception as e:
    sys.exit("[ERROR] Invalid queries" + str(e))

print(queries)
```

```
[(0, 3), (2, 6), (1, 5), (4, 7)]
```

[10]:
```
def verify_queries(tree: Segment_Tree, arr: list[int], max_checks: int = 500)␣
 ↪-> None:
    # Compare the tree with brute force on every range (or on a random subset␣
 ↪of max_checks ranges)
    ranges = [(l, r) for l in range(len(arr)) for r in range(l, len(arr))]
    if len(ranges) > max_checks:
        ranges = random.sample(ranges, max_checks)
    for left, right in ranges:
        assert tree.query(left, right) == (min(arr[left:right + 1]),␣
 ↪max(arr[left:right + 1])), f"query({left}, {right}) is wrong"
    print(f"Verified {len(ranges)} range queries against brute force.")

random.seed(911)  # reproducible random checks and updates
verify_queries(stree0, arr0)
```

```
Verified 153 range queries against brute force.
```

4 Q4.

Implement a `merge()` operation to combine the results of two child nodes:

- minimum = min(left.minimum, right.minimum)
- maximum = max(left.maximum, right.maximum)

[11]:
```
# Merging the results of the two halves of the array must give the result for␣
↪the whole array
half = n // 2
left_result, right_result = stree0.query(0, half - 1), stree0.query(half, n - 1)
merged = stree0.merge(left_result, right_result)
assert merged == stree0.query(0, n - 1)
print(f"merge({left_result}, {right_result}) = {merged}")
```

```
merge((50, 348), (25, 1080)) = (25, 1080)
```

5 Q5.

Implement `update(index, value)` to modify an element at a specified index and update all affected nodes of the Segment Tree.

[12]:
```
# Updates are applied to a separate copy so that stree0 is untouched for Q6
check_arr = arr0.copy()
check_tree = Segment_Tree()
check_tree.build(check_arr)

for _ in range(20):
    index, value = random.randrange(n), random.randint(1, 10 * n)
    check_tree.update(index, value)
    check_arr[index] = value

verify_queries(check_tree, check_arr)
```

```
Verified 153 range queries against brute force.
```

6 Q6.

Display the following after construction:

- Original array.
- Segment Tree representation.
- Minimum value of a specified range.
- Maximum value of the same range.

The result after every point update is displayed as well, and everything is stored in `output.txt`.

[13]:
```
output_lines = []

def emit(line: str = "") -> None:
    print(line)
    output_lines.append(line)

def emit_query(tree: Segment_Tree, left: int, right: int) -> None:
    minimum, maximum = tree.query(left, right)
```

```
    emit(f"Query [{left}, {right}]")
    emit(f"Minimum = {minimum}")
    emit(f"Maximum = {maximum}")

emit("Original array:")
emit(" ".join(map(str, arr0)))
emit()
emit("Segment Tree:")
for line in stree0.representation():
    emit(line)
emit()

for left, right in queries:
    emit_query(stree0, left, right)
    emit()

# The first update is the one from the assignment's example; the others are␣
 ↪random
updates = [(3, 25)] + [(random.randrange(n), random.randint(1, 10 * n)) for _␣
 ↪in range(2)]
current = arr0.copy()
for index, value in updates:
    stree0.update(index, value)
    current[index] = value
    assert stree0.query(0, n - 1) == (min(current), max(current))
    emit("Update:")
    emit(f"Index = {index}")
    emit(f"New Value = {value}")
    emit_query(stree0, 0, n - 1)
    emit()
```

```
Original array:
70 50 90 77 55 348 76 67 69 420 25 911 210 108 768 1080 720

Segment Tree:
[0, 16]  minimum = 25, maximum = 1080
    [0, 8]  minimum = 50, maximum = 348
        [0, 4]  minimum = 50, maximum = 90
            [0, 2]  minimum = 50, maximum = 90
                [0, 1]  minimum = 50, maximum = 70
                    [0, 0]  minimum = 70, maximum = 70
                    [1, 1]  minimum = 50, maximum = 50
                [2, 2]  minimum = 90, maximum = 90
            [3, 4]  minimum = 55, maximum = 77
                [3, 3]  minimum = 77, maximum = 77
                [4, 4]  minimum = 55, maximum = 55
        [5, 8]  minimum = 67, maximum = 348
```

```
            [5, 6]  minimum = 76, maximum = 348
                [5, 5]  minimum = 348, maximum = 348
                [6, 6]  minimum = 76, maximum = 76
            [7, 8]  minimum = 67, maximum = 69
                [7, 7]  minimum = 67, maximum = 67
                [8, 8]  minimum = 69, maximum = 69
    [9, 16]  minimum = 25, maximum = 1080
        [9, 12]  minimum = 25, maximum = 911
            [9, 10]  minimum = 25, maximum = 420
                [9, 9]  minimum = 420, maximum = 420
                [10, 10]  minimum = 25, maximum = 25
            [11, 12]  minimum = 210, maximum = 911
                [11, 11]  minimum = 911, maximum = 911
                [12, 12]  minimum = 210, maximum = 210
        [13, 16]  minimum = 108, maximum = 1080
            [13, 14]  minimum = 108, maximum = 768
                [13, 13]  minimum = 108, maximum = 108
                [14, 14]  minimum = 768, maximum = 768
            [15, 16]  minimum = 720, maximum = 1080
                [15, 15]  minimum = 1080, maximum = 1080
                [16, 16]  minimum = 720, maximum = 720

Query [0, 3]
Minimum = 50
Maximum = 90

Query [2, 6]
Minimum = 55
Maximum = 348

Query [1, 5]
Minimum = 50
Maximum = 348

Query [4, 7]
Minimum = 55
Maximum = 348

Update:
Index = 3
New Value = 25
Query [0, 16]
Minimum = 25
Maximum = 1080

Update:
Index = 5
New Value = 144
```

```
Query [0, 16]
Minimum = 25
Maximum = 1080

Update:
Index = 5
New Value = 113
Query [0, 16]
Minimum = 25
Maximum = 1080
```

[14]:
```python
with open("./2650026_lab6_data/output.txt", "w") as out_file:
    out_file.write("\n".join(output_lines).rstrip("\n") + "\n")
```

7 Q7.

For different numbers of elements, such as 100, 500, 1000, 5000 and 10000, measure and plot:

- Construction Time vs. Number of Elements
- Range Query Time vs. Number of Elements
- Point Update Time vs. Number of Elements
- Tree Height vs. Number of Elements

Time is measured as the number of iterations: one iteration is one node visited (one element scanned for the linear search).

[15]:
```python
arr1 = []
with open("./2650026_lab6_data/input0.txt", 'r') as data0:
    for line in data0.readlines():
        line_data = line.rstrip().rstrip(',').replace(' ','').split(',')
        for data in line_data:
            arr1.append(int(data))
```

[16]:
```python
SIZES = [100, 500, 1000, 5000, 10000]
N = SIZES[-1]

random.seed(911)

def ST_Build_Measured(values: list[int]):
    global iterations
    iterations = 0
    stree = Segment_Tree()
    stree.build(values)
    return stree, iterations


def ST_Query_Measured(stree: Segment_Tree, left: int, right: int):
```

```
    global iterations
    iterations = 0
    result = stree.query(left, right)
    return result, iterations


def ST_Update_Measured(stree: Segment_Tree, index: int, value: int):
    global iterations
    iterations = 0
    stree.update(index, value)
    return stree, iterations


def Linear_Search_Measured(values: list[int], left: int, right: int):
    global iterations
    iterations = 0
    result = linear_range_search(values, left, right)
    return result, iterations


def ST_Recorded(values: list[int], query_ranges: list, point_updates: list) ->␣
↪dict:
    height_store, construction_counts, query_counts, update_counts = [], [],␣
↪[], []
    for k in range(1, len(values) + 1):
        window = values[:k]  # the first k elements
        stree, build_count = ST_Build_Measured(window)
        height_store.append(stree.height())  # recorded once for every size, as␣
↪in lab 3
        assert build_count == 2 * k - 1, "construction must visit exactly 2k -␣
↪1 nodes"
        construction_counts.append(build_count)

        left, right = query_ranges[k - 1]
        result, query_count = ST_Query_Measured(stree, left, right)
        assert result == (min(window[left:right + 1]), max(window[left:right +␣
↪1])), f"query({left}, {right}) is wrong"
        assert query_count <= 4 * height_store[-1], "a query visits at most 4␣
↪nodes per level"
        query_counts.append(query_count)

        index, value = point_updates[k - 1]
        update_counts.append(ST_Update_Measured(stree, index, value)[1])
        assert update_counts[-1] <= height_store[-1], "an update visits at most␣
↪one node per level"
        window[index] = value
```

```
        assert stree.query(0, k - 1) == (min(window), max(window)), "Segment␣
 ↪Tree is wrong after the update"

    return {"Height": height_store, "Construction": construction_counts,␣
 ↪"Query": query_counts, "Update": update_counts}


def size_mean(series: list, n: int) -> float:
    # Mean of the values recorded for the last 10% of the sizes up to n␣
 ↪(smooths the per-size noise)
    window = series[n - max(1, n // 10) : n]
    return sum(window) / len(window)


assert N <= len(arr1), "n cannot exceed the length of arr1"
start_idx = random.randint(0, len(arr1) - N)
random_values = arr1[start_idx : start_idx + N]

# The operations of size k: a random range [L, R] of the k elements and a␣
 ↪random point update
query_ranges, point_updates = [], []
for k in range(1, N + 1):
    left = random.randrange(k)
    query_ranges.append((left, random.randrange(left, k)))
    point_updates.append((random.randrange(k), random.randint(1, 10 * k)))

records = {}
records["Random"] = ST_Recorded(random_values, query_ranges, point_updates)

rec = records["Random"]
task7_df = pd.DataFrame({
    "Elements": SIZES,
    "Height": [rec["Height"][n - 1] for n in SIZES],
    "Construction Iterations": [rec["Construction"][n - 1] for n in SIZES],
    "Query Iterations": [size_mean(rec["Query"], n) for n in SIZES],
    "Update Iterations": [size_mean(rec["Update"], n) for n in SIZES],
})
print("Height and construction at each size; iterations of query/update are the␣
 ↪mean over the last 10% of the sizes up to that size")
task7_df
```

```
Height and construction at each size; iterations of query/update are the mean
over the last 10% of the sizes up to that size
```

[16]:


	Elements	Height	Construction Iterations	Query Iterations	\
0	100	8	199	16.600	
1	500	10	999	26.960	

```
2      1000      11                    1999           31.300
3      5000      14                    9999           40.988
4     10000      15                   19999           44.880

   Update Iterations
0              7.700
1              9.940
2             10.920
3             13.332
4             14.261
```


7.1 Construction Time v/s Number of Elements

[17]:
```
figure(figsize=(12, 4.5), dpi=97)
y = records["Random"]["Construction"]
x = [i+1 for i in range(len(y))]
plt.plot(x, y, label="Construction iterations")
plt.xlim(left=0)
plt.ylim(bottom=0)
plt.legend()
plt.xlabel("Number of Elements")
plt.ylabel("Iterations")
plt.grid(visible=True, linestyle=':')
plt.savefig("./2650026_lab6_data/task7_construction.png", dpi=150,␣
 ↪bbox_inches="tight")
plt.show()
```




7.2 Range Query Time v/s Number of Elements

[18]:
```
figure(figsize=(12, 4.5), dpi=97)
y = records["Random"]["Query"]
x = [i+1 for i in range(len(y))]
plt.plot(x, y, label="Iterations per query", linewidth=0.7)
plt.xlim(left=0)
plt.ylim(bottom=0)
plt.legend()
plt.xlabel("Number of Elements")
plt.ylabel("Iterations per Query")
plt.grid(visible=True, linestyle=':')
plt.savefig("./2650026_lab6_data/task7_query.png", dpi=150, bbox_inches="tight")
plt.show()
```




7.3 Point Update Time v/s Number of Elements

[19]:
```
figure(figsize=(12, 4.5), dpi=97)
y = records["Random"]["Update"]
x = [i+1 for i in range(len(y))]
plt.plot(x, y, label="Iterations per update", linewidth=0.7)
plt.xlim(left=0)
plt.ylim(bottom=0)
plt.legend()
plt.xlabel("Number of Elements")
plt.ylabel("Iterations per Update")
plt.grid(visible=True, linestyle=':')
plt.savefig("./2650026_lab6_data/task7_update.png", dpi=150,␣
↪bbox_inches="tight")
plt.show()
```



7.4 Tree Height v/s Number of Elements

[20]:
```
figure(figsize=(12, 4.5), dpi=97)
y = records["Random"]["Height"]
x = [i+1 for i in range(len(y))]
plt.plot(x, y, label="Height h of Segment Tree")
plt.xlim(left=0)
plt.ylim(bottom=0)
plt.legend()
plt.xlabel("Number of Elements")
plt.ylabel("Tree Height")
plt.grid(visible=True, linestyle=':')
plt.savefig("./2650026_lab6_data/task7_height.png", dpi=150,␣
 ↪bbox_inches="tight")
plt.show()
```



7.5 Save to CSV

[21]:
```
task7_df.to_csv("./2650026_lab6_data/q7_summary.csv", index=False)

# The series plotted in the four graphs above, one row per number of elements
task7_graph_df = pd.DataFrame({
    "Elements": [i+1 for i in range(N)],
    "Height": records["Random"]["Height"],
    "Construction Iterations": records["Random"]["Construction"],
    "Iterations per Query": records["Random"]["Query"],
    "Iterations per Update": records["Random"]["Update"],
})
task7_graph_df.to_csv("./2650026_lab6_data/q7_graph_data.csv", index=False)
```

8 Q8.

Implement a linear-search-based approach for finding the minimum and maximum in a given range and experimentally compare its execution time with the Segment Tree approach.

8.1 Segment Tree v/s Linear Search (Query)

[22]:
```
def ST_Query_Compared(values: list[int], query_ranges: list):
    # Average iterations of the Segment Tree and of the linear search on the␣
 ↪same ranges
    stree, _ = ST_Build_Measured(values)
    query_counts, linear_counts = [], []
    for left, right in query_ranges:
        result, query_count = ST_Query_Measured(stree, left, right)
        expected, linear_count = Linear_Search_Measured(values, left, right)
        assert result == expected, f"query({left}, {right}) disagrees with␣
 ↪linear search"
        query_counts.append(query_count)
        linear_counts.append(linear_count)
    return sum(query_counts) / len(query_counts), sum(linear_counts) /␣
 ↪len(linear_counts)


task8_rows = []
for size in SIZES:
    assert size <= len(arr1), "n cannot exceed the length of arr1"
    start_idx = random.randint(0, len(arr1) - size)
    values = arr1[start_idx : start_idx + size]
    size_ranges = []
    for _ in range(100):
        left = random.randrange(size)
        size_ranges.append((left, random.randrange(left, size)))
    query_avg, linear_avg = ST_Query_Compared(values, size_ranges)
```


```
    task8_rows.append({"Elements": size, "Segment Tree Average Query␣
 ↪Iterations": query_avg,
                       "Linear Search Average Iterations": linear_avg})

task8_df = pd.DataFrame(task8_rows)
task8_df
```

[22]:

	Elements	Segment Tree Average Query Iterations	Linear Search Average Iterations
0	100	18.94	25.45
1	500	27.34	133.20
2	1000	31.28	276.88
3	5000	40.90	1301.95
4	10000	43.90	2113.07

[23]:
```
plt.figure(figsize=(6, 12))
plt.plot(task8_df["Elements"], task8_df["Segment Tree Average Query␣
 ↪Iterations"], marker="o", label="Segment Tree")
plt.plot(task8_df["Elements"], task8_df["Linear Search Average Iterations"],␣
 ↪marker="o", label="Linear Search")
plt.xlabel("Number of Elements")
plt.ylabel("Average Iterations per Query")
plt.ylim(bottom=0)
plt.title("Segment Tree vs Linear Search Query Iterations")
plt.legend()
plt.grid(True, linestyle=":", alpha=0.7)
plt.tight_layout()
plt.savefig("./2650026_lab6_data/task8_query_vs_linear.png", dpi=150,␣
 ↪bbox_inches="tight")
plt.ylim(bottom=0, top=1000)
plt.xlim(left=0)
plt.show()
```


Segment Tree vs Linear Search Query Iterations
Segment Tree
Linear Search
Average Iterations per Query
Number of Elements
0
200
400
600
800
1000
0
2000
4000
6000
8000
10000

8.2 Save to CSV

[24]:
```
task8_df.to_csv("./2650026_lab6_data/q8_query_vs_linear.csv", index=False)
```

9 Q9.

Perform experiments using random, sorted, and reverse-sorted input data and provide a brief analysis of the results.

[25]:
```
sorted_values = sorted(random_values)
input_orders = {
    "Sorted": sorted_values,
    "Reverse Sorted": list(reversed(sorted_values)),
}
for order_name, values in input_orders.items():
    records[order_name] = ST_Recorded(values, query_ranges, point_updates)

task9_rows = []
for order_name in ["Random", "Sorted", "Reverse Sorted"]:
    rec = records[order_name]
    task9_rows.append({
        "Elements": N,
        "Input Order": order_name,
        "Height": rec["Height"][N - 1],
        "Construction Iterations": rec["Construction"][N - 1],
        "Query Iterations": size_mean(rec["Query"], N),
        "Update Iterations": size_mean(rec["Update"], N),
    })

task9_df = pd.DataFrame(task9_rows)
print("Values at 10000 elements; query/update iterations are the mean over the␣
 ↪last 10% of the sizes")
task9_df
```

```
Values at 10000 elements; query/update iterations are the mean over the last 10%
of the sizes
```


[25]:

	Elements	Input Order	Height	Construction Iterations	Query Iterations	Update Iterations
0	10000	Random	15	19999	44.88	14.261
1	10000	Sorted	15	19999	44.88	14.261
2	10000	Reverse Sorted	15	19999		

```
2              44.88              14.261
```


9.1 Construction Comparison

[26]:
```
fig, axes = plt.subplots(3, 1, figsize=(8, 12))
for ax, order_name in zip(axes, ["Random", "Sorted", "Reverse Sorted"]):
    y = records[order_name]["Construction"]
    x = [i+1 for i in range(len(y))]
    ax.plot(x, y)
    ax.set_title(f"Segment Tree: {order_name}")
    ax.set_xlabel("Number of Elements")
    ax.set_ylabel("Iterations")
    ax.set_xlim(left=0)
    ax.set_ylim(bottom=0)
    ax.grid(True, linestyle=":", alpha=0.7)
fig.suptitle("Task 9: Construction Iterations by Input Order", y=1.01)
plt.tight_layout()
plt.savefig("./2650026_lab6_data/task9_construction.png", dpi=150,␣
 ↪bbox_inches="tight")
plt.show()
```


Task 9: Construction Iterations by Input Order
Segment Tree: Random
Segment Tree: Sorted
Segment Tree: Reverse Sorted
Iterations
Number of Elements
0
2500
5000
7500
10000
12500
15000
17500
20000
0
2000
4000
6000
8000
10000


9.2 Range Query Comparison

[27]:
```
fig, axes = plt.subplots(3, 1, figsize=(8, 12))
for ax, order_name in zip(axes, ["Random", "Sorted", "Reverse Sorted"]):
    y = records[order_name]["Query"]
    x = [i+1 for i in range(len(y))]
    ax.plot(x, y, linewidth=0.7)
    ax.set_title(f"Segment Tree: {order_name}")
    ax.set_xlabel("Number of Elements")
    ax.set_ylabel("Iterations per Query")
    ax.set_xlim(left=0)
    ax.set_ylim(bottom=0)
    ax.grid(True, linestyle=":", alpha=0.7)
fig.suptitle("Task 9: Range Query Iterations by Input Order", y=1.01)
plt.tight_layout()
plt.savefig("./2650026_lab6_data/task9_query.png", dpi=150, bbox_inches="tight")
plt.show()
```


Task 9: Range Query Iterations by Input Order
Segment Tree: Random
Iterations per Query
Number of Elements
Segment Tree: Sorted
Iterations per Query
Number of Elements
Segment Tree: Reverse Sorted
Iterations per Query
Number of Elements


9.3 Point Update Comparison

[28]:
```
fig, axes = plt.subplots(3, 1, figsize=(8, 12))
for ax, order_name in zip(axes, ["Random", "Sorted", "Reverse Sorted"]):
    y = records[order_name]["Update"]
    x = [i+1 for i in range(len(y))]
    ax.plot(x, y, linewidth=0.7)
    ax.set_title(f"Segment Tree: {order_name}")
    ax.set_xlabel("Number of Elements")
    ax.set_ylabel("Iterations per Update")
    ax.set_xlim(left=0)
    ax.set_ylim(bottom=0)
    ax.grid(True, linestyle=":", alpha=0.7)
fig.suptitle("Task 9: Point Update Iterations by Input Order", y=1.01)
plt.tight_layout()
plt.savefig("./2650026_lab6_data/task9_update.png", dpi=150,␣
 ↪bbox_inches="tight")
plt.show()
```


Task 9: Point Update Iterations by Input Order
Segment Tree: Random
Segment Tree: Sorted
Segment Tree: Reverse Sorted
Iterations per Update
Number of Elements
0
2
4
6
8
10
12
14
0
2000
4000
6000
8000
10000

9.4 Height Comparison

[29]:
```
fig, axes = plt.subplots(3, 1, figsize=(8, 12))
for ax, order_name in zip(axes, ["Random", "Sorted", "Reverse Sorted"]):
    y = records[order_name]["Height"]
    x = [i+1 for i in range(len(y))]
    ax.plot(x, y)
    ax.set_title(f"Segment Tree: {order_name}")
    ax.set_xlabel("Number of Elements")
    ax.set_ylabel("Tree Height")
    ax.set_xlim(left=0)
    ax.set_ylim(bottom=0)
    ax.grid(True, linestyle=":", alpha=0.7)
fig.suptitle("Task 9: Tree Height by Input Order", y=1.01)
plt.tight_layout()
plt.savefig("./2650026_lab6_data/task9_height.png", dpi=150,␣
 ↪bbox_inches="tight")
plt.show()
```


Task 9: Tree Height by Input Order
Segment Tree: Random
Tree Height
Number of Elements
Segment Tree: Sorted
Tree Height
Number of Elements
Segment Tree: Reverse Sorted
Tree Height
Number of Elements

9.5 Segment Tree v/s Linear Search Comparison

[30]:
```
task9_compare_rows = []
for size in SIZES:
    assert size <= len(arr1), "n cannot exceed the length of arr1"
    start_idx = random.randint(0, len(arr1) - size)
    random_window = arr1[start_idx : start_idx + size]
    sorted_window = sorted(random_window)
    window_orders = {
        "Random": random_window,
        "Sorted": sorted_window,
        "Reverse Sorted": list(reversed(sorted_window)),
    }
    size_ranges = []  # the same 100 ranges for all three input orders
    for _ in range(100):
        left = random.randrange(size)
        size_ranges.append((left, random.randrange(left, size)))
    for order_name, values in window_orders.items():
        query_avg, linear_avg = ST_Query_Compared(values, size_ranges)
        task9_compare_rows.append({"Elements": size, "Input Order": order_name,
                                   "Segment Tree Average Query Iterations":␣
 ↪query_avg,
                                   "Linear Search Average Iterations":␣
 ↪linear_avg})

task9_compare_df = pd.DataFrame(task9_compare_rows)
task9_compare_df
```


[30]:


	Elements	Input Order	Segment Tree Average Query Iterations	\
0	100	Random	19.22	
1	100	Sorted	19.22	
2	100	Reverse Sorted	19.22	
3	500	Random	27.76	
4	500	Sorted	27.76	
5	500	Reverse Sorted	27.76	
6	1000	Random	31.74	
7	1000	Sorted	31.74	
8	1000	Reverse Sorted	31.74	
9	5000	Random	41.46	
10	5000	Sorted	41.46	
11	5000	Reverse Sorted	41.46	
12	10000	Random	44.14	
13	10000	Sorted	44.14	
14	10000	Reverse Sorted	44.14	


```
    Linear Search Average Iterations
0                               26.92
1                               26.92
2                               26.92
3                              122.57
4                              122.57
5                              122.57
6                              231.29
7                              231.29
8                              231.29
9                             1160.04
10                            1160.04
11                            1160.04
12                            2628.94
13                            2628.94
14                            2628.94
```

[31]:
```
fig, axes = plt.subplots(3, 1, figsize=(9, 21))
for ax, order_name in zip(axes, ["Random", "Sorted", "Reverse Sorted"]):
    subset = task9_compare_df[task9_compare_df["Input Order"] == order_name]
    ax.plot(subset["Elements"], subset["Segment Tree Average Query␣
 ↪Iterations"], marker="o", label="Segment Tree")
    ax.plot(subset["Elements"], subset["Linear Search Average Iterations"],␣
 ↪marker="o", label="Linear Search")
    ax.set_title(f"Segment Tree: {order_name}")
    ax.set_xlabel("Number of Elements")
    ax.set_ylabel("Average Iterations per Query")
    ax.set_ylim(bottom=0, top=500)
    ax.set_xlim(left=0)
    ax.grid(True, linestyle=":", alpha=0.7)
    ax.legend()
fig.suptitle("Task 9: Segment Tree vs Linear Search by Input Order", y=1.01)
plt.tight_layout()
plt.savefig("./2650026_lab6_data/task9_query_vs_linear.png", dpi=150,␣
 ↪bbox_inches="tight")
plt.show()
```

Task 9: Segment Tree vs Linear Search by Input Order







9.6 Save to CSV

[32]:
```
task9_df.to_csv("./2650026_lab6_data/q9_summary.csv", index=False)

# The series plotted in the construction, query, update and height grids, one␣
 ↪row per input order and number of elements
task9_graph_df = pd.DataFrame([
    {"Input Order": order_name, "Elements": i+1, "Height": rec["Height"][i],
     "Construction Iterations": rec["Construction"][i], "Iterations per Query":␣
 ↪rec["Query"][i],
     "Iterations per Update": rec["Update"][i]}
    for order_name, rec in records.items() for i in range(N)
])
task9_graph_df.to_csv("./2650026_lab6_data/q9_graph_data.csv", index=False)

task9_compare_df.to_csv("./2650026_lab6_data/q9_query_vs_linear.csv",␣
 ↪index=False)
```

Let N be the number of elements and $h = \log\ N\ + 1$ the height of the tree.

Operation	Time	Extra space	Justification (and measured confirmation)
Construction `build()`	O(N)	O(N)	T(N) = 2T(N/2) + O(1), i.e. every one of the 2N - 1 nodes is created once. Measured: exactly 2k - 1 iterations for every size k from 1 to 10000 (asserted).
Range Min/Max Query `query(L, R)`	O(log N)	O(log N) recursion stack	At every level at most two segments are only partially covered and are expanded, so at most 4 nodes per level are visited (at most 4h, asserted for every size). Measured: 16.6 to 44.9 iterations on average for 100 to 10000 elements.

Operation	Time	Extra space	Justification (and measured confirmation)
Point Update `update(i, v)`	O(log N)	O(log N) recursion stack	A single root-to-leaf path is visited and re-merged on the way back, so at most h nodes (asserted for every size). Measured: 7.7 to 14.3 iterations on average.
Linear range search	O(N) worst case, Θ(R - L + 1) per query	O(1) with a loop; O(R - L + 1) in the recursive version above	Every element of the range is scanned once. Measured: about $n/4$ iterations on average for random ranges (26.9 at 100 and 2628.9 at 10000 elements).
Segment Tree (storage)	-	O(N)	Two arrays (minimum and maximum) of $4N$ slots are allocated, of which $2N$ - 1 are used.