

one-piece compression-moulded keypad: LEFT WING, RIGHT WING, two-end DART rocker; 4 carbon pills

Technical drawing of a rectangular plate with the following dimensions and features:

- Overall Dimensions:**
 - Width: 81.19
 - Height: 18.50
- Top Section:**
 - Wing pills: 48.00
 - Wing: 28.00
 - Heat-stake pins: dia 2.2
- Central Section:**
 - Window: dia 13.0 (open)
 - Datum: 0,0 (window centre)
 - Rockers (LOCKED): 44.00
- Bottom Section:**
 - DART pills (LOCKED): 24.00
 - Height: 9.00
- Other Features:**
 - Vertical dimension on the left: 14.20
 - Curved cutouts at the bottom corners.

Key tops matte; no printing

Pill centres: wings (+-24.00, +1.00); DART (+-12.00, -14.20): 24.00 apart (LOCKED)

travel curves for 5 keys of the first samples

Shell holes = key outline + 0.30; flange = outline + 1.00

Handheld coordinates = drawing + (0, -47.0)

no sticking, rebound < 100 ms

Diagram illustrating the cross-section of a shell face assembly. The assembly consists of a central orange component (shell face) mounted on a base. The base is labeled "PCB face (CP1)". The shell face is labeled "shell face 3.0 (ref.)". The height of the shell face is indicated as 7.4. The thickness of the base is indicated as 1.5.

The diagram shows a cross-section of a shell face 3.0 (ref.) assembly. It consists of a green PCB face (CP1) at the bottom, a yellow shell face 3.0 (ref.) in the middle, and a grey shell face 3.0 (ref.) at the top. The shell face 3.0 (ref.) has a thickness of 7.1. The PCB face (CP1) has a thickness of 1.3. The shell face 3.0 (ref.) has a stop 1.1. The shell face 3.0 (ref.) is shown in two positions: one at the bottom and one at the top, indicating it can be flipped.

PART	STRUTHIO-CM1 rev A1.5
PROJECT	STRUTHIO handheld, A1.5 (Build Manual 1.5 lock)
SOURCE	cad/a15/STRUTHIO15.scad, checked by check_a15.py
UNITS	mm; datum = speaker-window centre; general tol. +/-0.15
OWNER	R.A. Peddycoat