

The feasibility of constructing an isolated habitat is directly supported by field-tested applications of CTBs (Cargo Transfer Bag), as detailed in the "[Dual Use of Packaging on the Moon: Logistics-2-Living](#)" document. These packages can be repurposed for both internal and external structures.

- **Internal Compartmentalization:** For creating isolated internal spaces, the document points to a practical result:
"In addition to the right and left halves of the geo-science workstation, partitions and doors were installed using unfolded L2L2009 CTBs, creating a small compartment that could be sealed off from the rest of the Microhab." This proves that CTBs can effectively create functional modules, essential for establishing dedicated workspaces.
- **External Structures:** Furthermore, the concept scales up to the construction of robust external structures, treating the CTB as a primary building material:
"It has also been proposed to use expended CTBs external to the outpost as bricks for in-situ structures. Empty CTBs would be filled with regolith and piled in alternating courses..." This use of CTBs for civil construction allows for the creation of protective walls, supporting the development of a fully independent habitat.

The Core System: Closed-Loop Manufacturing from Mission Waste

A critical aspect of the habitat's autonomy is its ability to convert waste into valuable resources. We propose a dedicated module that houses a sufficient number of shredders and an electromagnetic inductor to transform plastic and metallic trash into standardized 3D printing filament.

- **The Technology: Electromagnetic Induction Heating:** This system's core is electromagnetic induction, a versatile technology for processing both polymers and metals. As described by [Mariani and Malucelli \(2023\)](#), it efficiently heats polymer composites. Furthermore, its effectiveness in processing aluminum alloys—a common aerospace waste material—has been confirmed by [Gariépy and D'Amours \(2023\)](#), making it an ideal all-in-one solution.

- **The Process: From Recycled Waste to Filament:** Once processed, the recycled material must be converted into a usable feedstock. This is achieved through the established process of filament extrusion:

The manufacturing process for 3D filament begins with the critical step of drying polymer pellets to remove any absorbed moisture. Subsequently, these pellets are melted and forced through a precision nozzle within an extruder to form a continuous strand. This filament is then immediately cooled in a water bath while its diameter is continuously monitored and adjusted in real-time via a feedback loop between a laser micrometer and a set of pullers. Finally, the precisely dimensioned filament is wound onto spools, and the final product is vacuum-sealed with a desiccant to ensure its quality and prevent moisture reabsorption.

This integrated process allows for the creation of structured feedstock, perfectly suited for use by manufacturing systems like the NASA Refabricator.

Addressing Challenges: Advanced Composites from Recycled Materials

While recycling is promising, utilizing recycled materials for high-performance applications presents known challenges, especially when incorporating reinforcing agents like carbon fiber (CF).

- **Challenges in Recycled Composite Manufacturing:** According to [Patel et al. \(2023\)](#), the process faces obstacles such as variations in material properties during recycling and ensuring a proper ratio of plastic waste to carbon fiber (CF). Despite these issues, they note that the integration of 3D printing holds significant promise for sustainable manufacturing in aerospace and automotive industries.
- **A Proposed Solution: Enhancing Material Properties:** To overcome these challenges and ensure the structural integrity of printed components, we propose incorporating advanced surface treatment methods. Recycled composites often suffer from poor adhesion between the polymer matrix and reinforcing fibers. As research by [Fazeli et al. \(2024\)](#) shows, this can be solved:
"The electrophoretic deposition of CNT/MFC onto the surface of recycled

carbon fibers proved to be an effective method for enhancing the adhesion and interaction between the matrix and fibers... enhancing chemical bonding sites with the polymer matrix." Incorporating such a process would upgrade the quality of the recycled filament, enabling the fabrication of stronger, more reliable parts directly addressing the challenges noted by Patel et al. (2023).

- **Aluminum Utilization: Electromagnetic Approach:** Electromagnetic inductors can heat aluminum by inducing electric currents, which generate heat directly within the material. A promising application of this method involves using recycled plastics to create molds, enabling the production of tools with more complex shapes. These plastic molds help shape the heated aluminum evenly, and when combined with a press, can shape the aluminum into tools.

Powering the System: Energy Autonomy from Packaging

To achieve true autonomy, the habitat and its recycling systems require a self-sufficient power source. The "Dual Use of Packaging" document presents an elegant solution by integrating power generation directly into the CTB material itself:

"...A third proposal was to manufacture the rectangles with flexible photovoltaic sections, so that the empty CTB could be used to lay across the ground outside and increase the power-generation capacity of the outpost." This visionary concept closes the loop: the packaging used to build the habitat also becomes the solar array that powers it.

Problems to be solved: waste generated

The heating of plastic waste will generate Volatile Organic Compounds (VOCs). According to the [U.S. Environmental Protection Agency](#), VOCs are compounds that have a high vapor pressure and low water solubility. [Dhamodharan \(2019\)](#) affirms that there are various methods to capture volatile organic carbon (VOC) emissions, including incineration (Huang et al., 2014), condensation (Luengas et al., 2015), absorption, adsorption (Jo and Yang, 2009), plasma catalysis (Hoeben et al., 2012), photocatalytic oxidation (Yokosuka et al., 2009), ozone catalytic oxidation, membrane separation (Zhang et al., 2017), and biological methods. Biological

methods include bio-filtration, trickling filters, bio-scrubbers, and membrane bioreactors.

Problems to be solved: Filtering different types of polymers and aluminum alloys

To reutilize the polymer needs to be pure, the presence of unwanted materials may compromise the process of rearranging the polymer or aluminum. The separation by identification code in the polymer item may help and an exclusive shredder for determined material may prevent contamination.

References

Gariépy A, D'Amours G. Modeling induction heating of aluminum sheets for hot stamping. *Eng Proc.* 2023;43(1):26. doi:10.3390/engproc2023043026. Accessed October 4, 2025.

Patel KS, Shah DB, Joshi SJ, Patel KM. Developments in 3D printing of carbon fiber reinforced polymer containing recycled plastic waste: A review. *Clean Mater.* 2023;9:100207. doi:10.1016/j.clema.2023.100207. Accessed October 4, 2025.

Fazeli M, Jayaprakash S, Baniasadi H, Abidnejad R, Lipponen J. Recycled carbon fiber reinforced composites: enhancing mechanical properties through co-functionalization of carbon nanotube-bonded microfibrillated cellulose. *Compos Part A Appl Sci Manuf.* 2024;180:108097. doi:10.1016/j.compositesa.2024.108097. Accessed October 5, 2025.

Mariani A, Malucelli G. Insights into induction heating processes for polymeric materials: an overview of the mechanisms and current applications. *Energies.* 2023;16(11):4535. doi:10.3390/en16114535. Accessed October 5, 2025.

Toups L, Howard R, Jones JDG, Kennedy KJ. Dual use of packaging on the Moon: logistics-2-living. *Eng Proc.* 2023;43(1):26. doi:10.3390/engproc2023043026. Accessed October 5, 2025.

Turner BN, Strong R, Gold SA. A review of melt extrusion additive manufacturing processes. *Rapid Prototyping J.* 2014;20(3):192-204. Accessed October 4, 2025.

Vidakis N, Petousis M, Velidakis E, Mountakis N. A comprehensive review of fused deposition modeling (FDM) 3D printing: from materials to applications. *Mater Today Proc.* 2023. [Epub ahead of print]. Accessed October 4, 2025.

Prusa Research. About Prusament. *Prusa3D Official Website.* <https://www.prusa3d.com>. Published 2023. Accessed October 4, 2025.

U.S. Environmental Protection Agency. **What are volatile organic compounds (VOCs)?** U.S. Environmental Protection Agency. Published November 14, 2022. Accessed October 5, 2025. [https://www.epa.gov/indoor-air-quality-iaq/what-are-volatile-organic-compounds-vocs#:~:text=Air%20Quality%20\(IAQ\)-,What%20are%20volatile%20organic%20compounds](https://www.epa.gov/indoor-air-quality-iaq/what-are-volatile-organic-compounds-vocs#:~:text=Air%20Quality%20(IAQ)-,What%20are%20volatile%20organic%20compounds)

[20compounds%20\(VOCs\)?.products%20numbering%20in%20the%20thousands.](#)

Kondusamy D, Varma VS, Veluchamy C, Pugazhendhi A, Rajendran K. Emission of volatile organic compounds from composting: A review on assessment, treatment and perspectives. *Sci Total Environ.* 2019;695:133725. doi:10.1016/j.scitotenv.2019.133725.

Howe AS, Howard R. Dual use of packaging on the moon: Logistics-2-Living. Version 2. JPL Open Repository. Published July 11, 2010. Available from: <https://hdl.handle.net/2014/45116>. Accessed October 5, 2025.