

Comprehensive QA Test Plan

Notifications overhaul · Public API (access model + tests) · Email health

Prepared for the QA team · v3.0.74-preview · Test cycle 2026-07-22

Ticket Pulse — QA Test Plan (2026-07-22)

Tester: _____ Date: _____ Device / browser: _____

This round validates the **Features Request 07-21** fixes: the Notifications page is now its own destination and redesigned, and the public API accepts ticket references and returns a pagination cursor. Section 2 also documents **how the API access model works** (workspace scoping, scopes, keys vs OAuth) with screenshots and samples, so QA can set up and test it end-to-end.

How to use: Do the smoke check first, then each section. Mark ☐ **Pass** / ☐ **Fail** and note the ticket ref (and, for API items, the `X-Request-Id`). Use a **QA TEST** prefix on tickets. ☐ = tick the box; ✓ = expected result.

Not in this build — don't re-file these yet: the sync-speed items (07-21 #1 tech schedules, #2 slow agent list after workspace switch) and last round's sync-latency/mirror items are in a separate backend pass.

Fast-pass smoke check (≈10 min)

- ☐ **Notifications page:** account menu → Notifications opens a page titled **Notifications** (no "My Competencies" header, no tab bar) — §1.1
- ☐ **Notifications redesign:** with no alerts, "My alerts" shows **starter templates**, not a big empty box — §1.2
- ☐ **My Skills:** the old My Competencies tab bar is **gone** — §1.3
- ☐ **API key:** create a Live key in Settings → API Keys and `GET <BASE_URL>/me` returns your key + workspace — §2.4
- ☐ **API ref lookup:** `GET <BASE_URL>/tickets/TP-####` returns the ticket (not a 500) — §2.5
- ☐ **API cursor:** `GET <BASE_URL>/tickets?pageSize=5` response includes a **next_cursor** — §2.5
- ☐ **Email health:** Settings → Notifications & Public → Notifications shows the **Email delivery health** card — §3

Smoke result: ☐ **Pass** ☐ **Fail** — Notes: _____

1. Notifications page (Features Request 07-21 #3, #4, #5, #6)

1.1 It's a standalone page (no My Competencies chrome)

1. Account menu (top-right) → **Notifications**. On a phone: **More** → **Notifications**.
2. ✓ The header reads **"Notifications"** — **not** "My Competencies".
3. ✓ There is **no tab bar** (My Competencies / Notifications / IT Summit) on the page.

Result: ☐ **Pass** ☐ **Fail** — Notes: _____

1.2 Redesigned layout (delivery preferences + My alerts)

1. ✓ A page intro, then a **"How you're notified"** card (threshold + channels + phone verification), then **"My alerts"**.

2. With **no alerts yet**: ✓ instead of a big empty box, the My alerts area shows **one-click templates** (Urgent tickets · Escalations · A category) + "build from scratch".
3. Tap a template (e.g. **Urgent tickets**): ✓ the form opens **pre-filled**; adjust & **Create alert**. Created alerts show as compact cards; Quiet hours sits in its own row.

Result: ☐ Pass ☐ Fail — Notes: _____

1.3 My Skills no longer shows the nav bar

1. Account menu → **My Skills**: ✓ the old horizontal **tab bar** is **gone**.
2. (IT workspace) ✓ the archived **IT Summit** view is reachable via a small "IT Summit" pill in the header.

Result: ☐ Pass ☐ Fail — Notes: _____

2. Public API — how it works & how to test it

Every credential is **scoped to one workspace** and to a set of **scopes**. Two auth methods — **API keys** and **OAuth2** — and both are workspace-scoped the same way (OAuth isn't a separate permission system).

- **Workspace scoping is automatic** — a key belongs to the workspace you're in when you create it and can never touch another. To make one for a different workspace, switch workspaces first.
- **Scopes** decide what it can do (`tickets:read` , `tickets:write` , ...). Missing scope → `403 insufficient_scope` .
- **Extra restrictions (API keys)**: Test vs Live (test = read-only), expiry, IP allowlist, per-key rate limit.

Ticket Pulse Integration API v2.0.0

Key-authenticated, workspace-scoped. Machine-readable spec: [openapijson](#).

Authentication — two options, both workspace-scoped

1. **API key** (simplest). Issue one per workspace in **Settings** → **API Keys**, scoped to exactly what the integration needs. A `tp_test_...` key is **read-only** — safe to build against; switch to a `tp_live_...` key to make changes (writes with a test key return `403 test_mode_read_only`).

```
curl https://ticket-pulse-app.azurewebsites.net/api/v1/me \
-H "Authorization: Bearer tp_live_..."
```

2. **OAuth2 client-credentials** (for apps). Create a client in **Settings** → **API Keys** → **OAuth clients**, then exchange it for a short-lived token:

```
curl -X POST https://ticket-pulse-app.azurewebsites.net/api/v1/oauth/token \
-d grant_type=client_credentials \
-d client_id=tpc_... -d client_secret=tps_...
# → { "access_token": "eyJ...", "token_type": "Bearer", "expires_in": 3600 }
curl https://ticket-pulse-app.azurewebsites.net/api/v1/tickets -H "Authorization: Bearer eyJ..."
```

Both resolve to a single workspace; a credential can never read or write another workspace's data.

Conventions

- Errors are `application/problem+json` (RFC 9457) with a stable `code`.
- Every response carries `X-Request-Id` and `X-RateLimit-Limit/Remaining/Reset`; 429 includes `Retry-After`.
- Send `Idempotency-Key: <uuid>` on writes so a retry never double-applies.
- Lists page by `?cursor=` (keyset, use the returned `next_cursor`) or `?page=&pageSize=`.

AUTH

POST `/oauth/token` OAuth2 client-credentials token exchange

The live API docs (`.../api/v1/docs`) — "Authentication — two options, both workspace-scoped."

2.1 API keys vs OAuth2 — which to use

API KEY

Scripts & simple integrations

A long-lived bearer token (`tp_live_...` / `tp_test_...`) sent on every request. Supports Test mode, expiry, IP allowlist, per-key rate limit. **Use for:** curl/PowerShell, RMM, cron, QA.

OAUTH2 CLIENT

Apps (app-to-app)

A client id + secret (`tpc_...` / `tps_...`) exchanged at `/oauth/token` for a short-lived (1h) token. Disabling the client revokes tokens immediately. **Use for:** hosted apps.

Integration API keys

BASE URL <https://ticket-pulse-app.azurewebsites.net/api/v1>

Call the API at this host — e.g. `.../api/v1/me`. (The app domain serves the web UI, not the API.)

"NinjaRMM integration" — copy the key now, it is shown only once:

tp live mPNcaPDsL56S1l6EvAEB0BTEc42835cq

NinjaRMM integration

tp_live_mPNca...

tickets:read

tickets:write

```
tasks:write
```

128 calls · last Jul 21 · expires Oct 19

Rotate

Disable

QA sandbox

TEST

tp_test_VVgLK...

tickets:read

search:read

read-only · 42 calls

Rotate

Disable

NiniaRMM integration

Live 

1 year ▾

TICKETS

- ✓ tickets:read List & read tickets

- ✓ tickets:write Create, update, assign, merge

CONVERSATIONS

- ☐ `conversations:read` Read the full thread

✓ **conversations:write** Public replies & notes

TASKS

- ☐ `tasks:read` Read tasks

- ✓ **tasks:write** Create / update / delete

[DIRECTORY](#) · [TAXONOMY](#) · [ATTACHMENTS](#) · [APPROVALS](#) · [SEARCH](#)

☐ `contacts:read` Read requesters

- tags:write Set ticket tags

☐ [search:read](#) Search tickets☐ agents:read Read agents

 `approvals:write` Request approvals

☐ attachments:read List / download

Create key

Cancel

Settings → API Keys — the Base URL card, existing keys (Live + a read-only Test key), and the create form with mode, expiry, and grouped scopes.

Call the API at the Base URL shown here (e.g. `https://ticket-pulse-app.azurewebsites.net/api/v1`) — **not** `ticketpulse.bgcsaas.com`, which serves the web UI and returns HTML.

Tick only what's needed. Wildcards: `tickets:*`, `*:read`, `*`.

Test-mode keys are read-only: a `tp_test_` key reads fine, but any write returns `403 test_mode_read_only`.

2.4 Create a key & confirm identity

1. Confirm the **workspace** (top-left) is the one you want, then **Settings** → **API Keys** → **New API key**. Name it, pick **Live**, an expiry, and scopes (`tickets:read` , `tickets:write`). Copy the secret (shown once).

```
curl <BASE_URL>/me -H "Authorization: Bearer tp_live_xxx"
→ { "success": true, "data": { "authType": "api_key",
    "key": { "name": "QA test", "mode": "live", "scopes": ["tickets:read", "tickets:write"] },
    "workspace": { "id": 1, "name": "IT" }, "rateLimit": { "perMinute": 120 } } }
```

✓ Returns your key name, **workspace**, scopes, and `authType: api_key`. Every response has `X-Request-Id` + `X-RateLimit-*` headers.

Result: ☐ Pass ☐ Fail — Notes: _____

2.5 Read tickets — ref lookup + cursor pagination (07-21 #7, #8)

```
# Lookup by id OR reference (all return the ticket; unknown ref → clean 404):
curl <BASE_URL>/tickets/36533 -H "Authorization: Bearer tp_live_xxx" # internal id
curl <BASE_URL>/tickets/TP-1048 -H "Authorization: Bearer tp_live_xxx" # TP-born ref
curl <BASE_URL>/tickets/%23233976 -H "Authorization: Bearer tp_live_xxx" # FS ref (#233976)

# List — response now includes next_cursor + total:
curl "<BASE_URL>/tickets?pageSize=5" -H "Authorization: Bearer tp_live_xxx"
→ { "data": { "items": [...], "pagination": { "next_cursor": "MzY1MzA", "limit": 5, "total": 14730 } } }
# next page: &cursor=<next_cursor> (null next_cursor = last page)
```

- ✓ `/tickets/TP-1048` returns the ticket JSON — **not** a 500 (this was the bug).
- ✓ `/tickets/TP-999999` (nonexistent) → clean **404** problem+json, never a 500.
- ✓ The list response contains a **next_cursor** (+ `total`); following it returns the next page with no overlap.

Result: ☐ Pass ☐ Fail — Notes: _____

2.6 Create / update / OAuth (Live key + write scopes)

```
curl -X POST <BASE_URL>/tickets -H "Authorization: Bearer tp_live_xxx" \
-H "Content-Type: application/json" -H "Idempotency-Key: qa-001" \
-d '{ "subject": "QA TEST via API", "requesterEmail": "you@bgcengineering.ca", "priority": 2 }'
curl -X PATCH <BASE_URL>/tickets/<id> -H "Authorization: Bearer tp_live_xxx" \
-H "Content-Type: application/json" -d '{ "status": "Pending", "priority": 3 }'

# OAuth2: exchange a client for a short-lived token
curl -X POST <BASE_URL>/oauth/token -d grant_type=client_credentials \
-d client_id=tpc_xxx -d client_secret=tps_xxx
→ { "access_token": "eyJ...", "token_type": "Bearer", "expires_in": 3600, "scope": "tickets:read" }
curl <BASE_URL>/me -H "Authorization: Bearer eyJ..." # authType: "oauth"
```

- ✓ POST creates a ticket (201); PATCH updates it. OAuth token works anywhere a key does.
- ✓ A key **without** a needed scope → `403 insufficient_scope`; a **test** key writing → `403 test_mode_read_only`.

Result: ☐ Pass ☐ Fail — Notes: _____

2.7 Concurrent idempotency (07-20 4.5.3 — now testable)

Fires two identical POSTs in parallel with the same key (PowerShell):

```
$h = @{ Authorization="Bearer tp_live_..."; "Idempotency-Key"="qa-conc-1"; "Content-Type"="application/json" }
$b = '{"subject":"QA TEST concurrent","requesterEmail":"you@bgcengineering.ca"}'
1..2 | ForEach-Object { Start-Job -ArgumentList "<BASE_URL>/tickets",$h,$b {
    param($u,$h,$b) Invoke-WebRequest $u -Method Post -Headers $h -Body $b } } | Wait-Job | Receive-Job
```

✓ Exactly **one** ticket created; the other returns **409** `idempotency_in_flight`.

Result: ☐ **Pass** ☐ **Fail** — Notes: _____

Reference: the endpoint catalogue

TICKETS		
GET	/tickets	List tickets (cursor or offset; filters mirror the queue)
POST	/tickets	Create a ticket
GET	/tickets/{id}	Get a ticket with its public conversation
PATCH	/tickets/{id}	Update a ticket (status/priority/assignee/fields)
POST	/tickets/{id}/merge	Merge another ticket into this one
GET	/tickets/{id}/family	Parent + children of a ticket
PUT	/tickets/{id}/parent	Set this ticket's parent
DELETE	/tickets/{id}/parent	Detach from parent
GET	/search/tickets	Search tickets (?query=...)
CONVERSATIONS		
GET	/tickets/{id}/conversations	Full conversation thread (incl. private notes)

The full endpoint list is on the live docs page — each row shows its method, path, and required scope. Browse it at `.../api/v1/docs`.

3. Email delivery health is findable (Features Request 07-21 #10)

- 1. As an admin, open **Settings**: ✓ the left nav is **grouped** (Integrations · Tickets & AI · Notifications & Public · ...).
- 2. Go to **Notifications & Public** → **Notifications**: ✓ the **Email delivery health** card is at the top (status badge, last success, 24h counts, hint if failing).
- 3. In that section → **SendGrid**, send a test email to yourself: ✓ it arrives and the card shows a recent success.

If you don't see a **Notifications** item under Settings at all, that page is admin-scoped — tell us and we'll check your access level (it's a permission, not a missing feature).

Result: ☐ **Pass** ☐ **Fail** — Notes: _____

Notes for QA

- **API base URL**: always call the **Base URL from Settings** → **API Keys**, not the web address (the web address returns HTML).
- Please report: a Notifications page still showing "My Competencies" or a tab bar; a starter template that doesn't pre-fill; an API ref lookup that 500s; a `/tickets` response with no `next_cursor`; or a credential that can read another workspace's data.

