

SVA Simulation

Christopher Lo

9/6/2022

Simulation Set-Up

Simulation studies inspired from “*A general framework for multiple testing dependence*” (Leek et al. 2008)

We generate X from the following model:

$$X = BS + \Gamma G + U$$

We have $m = 1000$ genes (tests), $n = 20$ samples, and $r = 2$ latent variables.

Sampling noise: $U_{m,n} \sim N(0, 1)$.

The design matrix S is 10 cases and 10 controls: $S_{1,n} = 1$ for $n = 1 : 20$. Then, $S_{2,n} = 0$ for $n = 1 : 10$, $S_{2,n} = 1$ for $n = 11 : 20$.

Control effect for all genes: $b_{m,1} \sim N(0, 1), m = 1 : 1000$

Case effect for DE genes $m = 1 : 300$: $b_{m,2} \sim N(3, 1)$

Case effect for Non-DE genes $m = 301 : 1000$: $b_{m,2} \sim N(0, 2)$

Latent design matrix (kernel) G : $G_{r,n} \sim \text{Bernoulli}(.2), n = 1 : 10$. $G_{r,n} \sim \text{Bernoulli}(.8), n = 11 : 20$, where $r = 1, 2$. (This ensures correlation between the two design matrices.)

Latent effect 1: $\Gamma_{m,1} \sim N(0, 1), m = 1 : 300$, $\Gamma_{m,1} \sim N(1, 2), m = 301 : 1000$. (Positive signal overlaps with Non-DE genes, will lead to FPs if not corrected)

Latent effect 2: $\Gamma_{m,2} \sim N(-1, 2), m = 1 : 300$, $\Gamma_{m,2} \sim N(0, 1), m = 301 : 1000$. (Negative signal overlaps with DE genes, will lead to FNs if not corrected)

Therefore, for every gene, whether it is DE or not, it will be affected by one of the two latent variables

To ask/consider: When there's no effect, should we use $N(0, 1)$, or should we just use 0?

Run SVA and regression to estimate parameters and SVs


We look at the number of SVs estimated, whether the latent variables are spanned by the estimated SVs, the recovered regression coefficients, the null p-value distribution, and the ranks of top genes.

Todo: ranks of top genes code unsure right now.

```
n.sv = num.sv(X, t(S), method = "be")
cat("Number of SVs: ", n.sv, "\n")
```

```
## Number of SVs: 2
```


```
pca = prcomp(t(X))
variance = pca$sdev^2 / sum(pca$sdev^2)
qplot(c(1:length(variance)), variance) + geom_line() + geom_point() +
  geom_hline(yintercept=1/ncol(X), linetype = "dashed") +
  xlab("Principal Component") + ylab("Variance Explained") + ggtitle(paste0("Number of SVs: ", n.sv)) +
```




```
nullMod = t(S)[, 1]
svobj = sva(X, t(S), nullMod, n.sv = n.sv)
```

```
## Number of significant surrogate variables is: 2
## Iteration (out of 5): 1 2 3 4 5
```

```
#visually look at predicted SVs.
qplot(as.numeric(G[1, ]), svobj$sv[, 1], xlab = "True latent variable 1", ylab = "Est. SV1")
```



```
qplot(as.numeric(G[2,]), svobj$sv[, 2], xlab = "True latent variable 2", ylab = "Est. SV2")
```




```

nullmodsv = cbind(nullMod, svobj$sv)
modsv = cbind(t(S), svobj$sv)
#run full regression.
fitsv = lm.fit(modsv, t(X))

#visually look at predicted coefficients
plot_df = data.frame(b1 = B[, 1],
                     b2 = B[, 2],
                     b1_hat = fitsv$coefficients[1,],
                     b2_hat = fitsv$coefficients[2,],
                     b2_labels = c(rep("alt", 300), rep("null", m - 300)),
                     gamma1 = Gamma[, 1],
                     gamma1_hat = fitsv$coefficients[3,],
                     gamma1_labels = c(rep("alt", 300), rep("null", m - 300)),
                     gamma2 = Gamma[, 2],
                     gamma2_hat = fitsv$coefficients[4,],
                     gamma2_labels = c(rep("alt", 300), rep("null", m - 300)))

ggplot(plot_df, aes(b1, b1_hat)) + geom_point() + labs(x = "True b_m1", y = "Est. b_m1")


```




```

ggplot(plot_df, aes(b2, b2_hat)) + geom_point() + facet_wrap(~b2_labels) + labs(x = "True b_m2", y = "Est. b_m2")


```




```
ggplot(plot_df, aes(gamma1, gamma1_hat)) + geom_point() + facet_wrap(~gamma1_labels) + labs(x = "True g
```



```
ggplot(plot_df, aes(gamma2, gamma2_hat)) + geom_point() + facet_wrap(~gamma2_labels) + labs(x = "True g
```



Not sure what's going on here yet regarding p-values and ranking.




```
## Warning in ks.test(qValuesSV2[301:1000], "punif", 0, 1): ties should not be
## present for the Kolmogorov-Smirnov test
```

```
##
## One-sample Kolmogorov-Smirnov test
##
## data: qValuesSV2[301:1000]
## D = 0.72143, p-value < 2.2e-16
## alternative hypothesis: two-sided
```

```
##
## FALSE
## 700
```

```
##
## FALSE
## 300
```



“Knobs to turn” in this experiment:

$\Gamma_{m,1}$: If strong effect relative to $b_{m,1}$ (fixed), then this will generate noise on control samples, leading to false positives.

$\Gamma_{m,2}$: If strong effect relative to $b_{m,2}$ (fixed), then this will generate noise on case samples, leading to false negatives.

Our certainty of Γ to effect case or control samples depends on “the percentage of row space of S explained by G ”. We appprox that by looking at $cor(G_r, S_2), r = 1, 2$. We probably can fix this value for now.

Knob Speculation, within one experiment

$\Gamma_{m,1}$	$\Gamma_{m,2}$	$cor(G_r, S_2)$	DE	Scree plot
strong	weak	strong	more FPs	more even PCA
weak	strong	strong	more FNs	more even PCA
weak	weak	strong	neutral	more dominated PCA
strong	strong	strong	more FPs and FNs	more even PCA

Simulation with multiple experiments

$$X = B_1S_1 + \Gamma_1G_1 + \alpha(B_2S_2 + \Gamma_2G_2) + U$$

where B_i and Γ_i are the same shape and dimension of B and Γ as before.

S_1 is the design matrix of the primary variables of the first experiment, elongated to 0s for the second experiment. etc.

We keep $cor(G_{ir}, S_{i2})$ at the same strength.

```
set.seed(2023)
m = 1000 #number of genes (tests)
n = 20 #number of samples
r = 2 #number of latent variables per studies
s = 2 #number of studies

DE_effect = 5
simulation = expand.grid(alpha = c(.5, 1, seq(2, 50, 8)), #effect of the second experiment relative to
                        gamma = c(.5, seq(1, 30, 2))) #effect of latent variables, relative to DE_effect

simulation$n.sv = NA
simulation$num_PC_signif = NA
simulation$var_explained_PC1 = NA

for(i in 1:nrow(simulation)) {
  alpha = simulation$alpha[i]
  gamma = simulation$gamma[i]
  cat(alpha, "\t", gamma, "\n")

  #generate data
  U = rnorm(n * s, mean = 0, sd = 1)

  b11 = rnorm(m, mean = 0, sd = 1) #intercept
  b12 = mapply(mu = c(rep(DE_effect, 300), rep(0, m - 300)),
              sigma = c(rep(1, 300), rep(1, m - 300)),
              function(mu, sigma) rnorm(1, mean = mu, sd = sigma))
  B1 = cbind(b11, b12)
  b21 = rnorm(m, mean = 0, sd = 1)
  b22 = mapply(mu = c(rep(DE_effect, 300), rep(0, m - 300)),
              sigma = c(rep(1, 300), rep(1, m - 300)),
              function(mu, sigma) rnorm(1, mean = mu, sd = sigma))
  B2 = cbind(b21, b22)
```



```

S1 = matrix(c(rep(1, n), rep(0, n), rep(0, n/2), rep(1, n/2), rep(0, n)), byrow = T, ncol = s*n)
S2 = matrix(c(rep(0, n), rep(1, n), rep(0, n), rep(0, n/2), rep(1, n/2)), byrow = T, ncol = s*n)

gamma11 = mapply(mu = c(rep(0, 300), rep(gamma, m - 300)),
  sigma = c(rep(1, 300), rep(1, m - 300)),
  function(mu, sigma) rnorm(1, mean = mu, sd = sigma))
gamma12 = mapply(mu = c(rep(-gamma, 300), rep(0, m - 300)),
  sigma = c(rep(1, 300), rep(1, m - 300)),
  function(mu, sigma) rnorm(1, mean = mu, sd = sigma))
Gamma1 = cbind(gamma11, gamma12)
gamma21 = mapply(mu = c(rep(0, 300), rep(gamma, m - 300)),
  sigma = c(rep(1, 300), rep(1, m - 300)),
  function(mu, sigma) rnorm(1, mean = mu, sd = sigma))
gamma22 = mapply(mu = c(rep(-gamma, 300), rep(0, m - 300)),
  sigma = c(rep(1, 300), rep(1, m - 300)),
  function(mu, sigma) rnorm(1, mean = mu, sd = sigma))
Gamma2 = cbind(gamma21, gamma22)

G_zeros = matrix(rep(0, n*2), byrow = T, ncol = n)
G1 = cbind(mapply(p = c(rep(.2, 10), rep(.8, 10)),
  function(p) rbinom(2, 1, p)), G_zeros)
G2 = cbind(G_zeros, mapply(p = c(rep(.2, 10), rep(.8, 10)),
  function(p) rbinom(2, 1, p)))

X = B1 %*% S1 + Gamma1 %*% G1 + alpha * (B2 %*% S2 + Gamma2 %*% G2) + U

#inference
S_merged = cbind(S1[, 1:n], S2[, (n+1):(2*n)])
simulation$num.sv[i] = num.sv(X, t(S_merged), method = "be")
pca = prcomp(t(X))
variance = pca$sdev^2 / sum(pca$sdev^2)
simulation$num_PC_signif[i] = length(which(variance > 1/ncol(X)))
simulation$var_explained_PC1[i] = variance[1]
}

```

```

## 0.5    0.5
## 1      0.5
## 2      0.5
## 10     0.5
## 18     0.5
## 26     0.5
## 34     0.5
## 42     0.5
## 50     0.5
## 0.5    1
## 1      1
## 2      1
## 10     1
## 18     1
## 26     1
## 34     1
## 42     1


```

##	50	1
##	0.5	3
##	1	3
##	2	3
##	10	3
##	18	3
##	26	3
##	34	3
##	42	3
##	50	3
##	0.5	5
##	1	5
##	2	5
##	10	5
##	18	5
##	26	5
##	34	5
##	42	5
##	50	5
##	0.5	7
##	1	7
##	2	7
##	10	7
##	18	7
##	26	7
##	34	7
##	42	7
##	50	7
##	0.5	9
##	1	9
##	2	9
##	10	9
##	18	9
##	26	9
##	34	9
##	42	9
##	50	9
##	0.5	11
##	1	11
##	2	11
##	10	11
##	18	11
##	26	11
##	34	11
##	42	11
##	50	11
##	0.5	13
##	1	13
##	2	13
##	10	13
##	18	13
##	26	13
##	34	13
##	42	13


##	50	13
##	0.5	15
##	1	15
##	2	15
##	10	15
##	18	15
##	26	15
##	34	15
##	42	15
##	50	15
##	0.5	17
##	1	17
##	2	17
##	10	17
##	18	17
##	26	17
##	34	17
##	42	17
##	50	17
##	0.5	19
##	1	19
##	2	19
##	10	19
##	18	19
##	26	19
##	34	19
##	42	19
##	50	19
##	0.5	21
##	1	21
##	2	21
##	10	21
##	18	21
##	26	21
##	34	21
##	42	21
##	50	21
##	0.5	23
##	1	23
##	2	23
##	10	23
##	18	23
##	26	23
##	34	23
##	42	23
##	50	23
##	0.5	25
##	1	25
##	2	25
##	10	25
##	18	25
##	26	25
##	34	25
##	42	25

```
## 50    25
## 0.5   27
## 1     27
## 2     27
## 10    27
## 18    27
## 26    27
## 34    27
## 42    27
## 50    27
## 0.5   29
## 1     29
## 2     29
## 10    29
## 18    29
## 26    29
## 34    29
## 42    29
## 50    29
```


```
ggplot(simulation, aes(x = num_PC_signif, y = n.sv)) + geom_point() + ggtitle("Expected SV: 5")
```



```
ggplot(simulation, aes(x = as.factor(alpha/DE_effect), y = as.factor(gamma/DE_effect), fill = n.sv)) +
  labs(x = "Noise:Signal of study effect = alpha/DE_effect",
       y = "Noise:Signal of latent variables = gamma/DE_effect") +
  ggtitle("Expected SV: 5")
```



```
ggplot(simulation, aes(x = as.factor(alpha), y = as.factor(gamma), fill = n.sv)) + geom_tile(width = 1)
  labs(x = "Study effect alpha",
       y = "Latent variables effect gamma") +
  ggtitle("Expected SV: 5, DE effect: 3")
```



```
ggplot(simulation, aes(x = as.factor(alpha/DE_effect), y = as.factor(gamma/DE_effect), fill = var_expl)) +
  labs(x = "Noise:Signal of study effect = alpha/DE_effect",
       y = "Noise:Signal of latent variables = gamma/DE_effect") +
  ggtitle("Expected SV: 5")
```

