

## Assignment 2: Designing AI Solutions: Rapid Prototyping with and without Generative AI Tools

**Project Title:** Multi-Dimensional Tree Asset Risk Prioritization for Tri-City Forestry Management (Waterloo, Kitchener, Cambridge)

### 1. Problem Definition

#### 1.1 Background & Context

In Assignment 1, our team established the structural foundation of an AI-powered Tree Canopy Decision Support System (DSS) for the Region of Waterloo, focusing primarily on Waterloo and Kitchener Open Data. We successfully quantified the environmental impact, finding a climate sensitivity coefficient of  $-0.24\text{ }^{\circ}\text{C}$  (a  $0.24\text{ }^{\circ}\text{C}$  drop in surface temperature for every 1% increase in canopy cover). Furthermore, we built a Predictive Linear Regression model validating that proactive tree trimming costs exactly \$1,200 CAD per tree, achieving an  $R^2 > 0.99$  for budget forecasting. This allows the CFO to secure annual municipal storm response savings of up to 35%.

#### 1.2 The Core AI Challenge / Implementation Gap

Despite the high mathematical accuracy of the budget regression model, a critical operational gap remains for the **Operations Manager**. The linear regression pipeline functions as a macroeconomic tool; it tells senior leadership *how much total budget* is needed based on a given count of critical trees ( $Y = 1200X$ ), but it **cannot identify which specific trees or neighborhoods represent those critical risks**.

With tens of thousands of registered street trees across Kitchener, Waterloo, and Cambridge, the operations team faces three major bottlenecks that require advanced machine learning:

1. **Multi-Dimensional Risk Factors:** A tree's hazard risk during autumn windstorms is not determined by a single variable; it is a complex intersection of asset metrics (Diameter at Breast Height (DBH), species vulnerability) and localized environment metrics (impervious surface density, surrounding urban heat island intensity, proximity to Environmentally Sensitive Policy Areas (ESPA)).
2. **Fragmented Municipal Data:** Tree inventories from Cambridge are missing from the initial pipeline, and data schemas across the three cities are highly inconsistent (e.g., mismatched coordinates, varying column syntax for tree diameters).
3. **Missing Ground-Truth Targets:** Municipal open datasets provide physical asset dimensions but completely lack "Historical Storm Damage Claims" labels, making supervised classification modeling impossible without manual synthesis or advanced augmentation.

### 1.3 Selected Challenge for Assignment 2

To establish a closed-loop DSS, this assignment focuses on building a **Multi-Dimensional Tree Asset Risk Scoring & Prioritization Framework**. The model must ingest fragmented spatial and asset data across the tri-city area, output a continuous Risk Score (0-100) for every registered tree asset, and automatically aggregate these scores to identify the **Top 5 High-Density Risk Zones (Neighborhood Hotspots)**.

Once these 5 critical zones are localized, the system identifies the exact count of high-risk trees within them. This total count is then fed directly into our Assignment 1 Predictive Budget Engine ( $Y=1,200 \times \text{Tree Count}$ ) to mathematically calculate the precise municipal funding allocation required for preventative pruning before autumn windstorms hit, transforming localized risk data into justified financial planning.

## 2. Rapid Prototype Solution: Without Generative AI Tools

### 2.1 Research on Existing Methods & Algorithms

Industrial urban forestry frameworks rely heavily on tabular tree asset data combined with spatial geometric vector layers. To establish a baseline risk-scoring engine without generative tools, traditional literature points toward:

- **Feature Engineering:** Utilizing Python's *Pandas* to manually clean and align inconsistent schemas across municipal databases.
- **Supervised Machine Learning:** Since tree risk prediction represents a non-linear interaction of attributes, a **Random Forest Regressor** is standard. Random Forest is highly resilient to missing structural values and naturally generates *Feature Importance Metrics*, allowing the Operations Manager to mathematically understand why specific street segments are prioritized over others.

### 2.2 System Design & Rationale

In the traditional AI rapid prototyping phase, the open datasets from the municipalities do not contain a ground-truth "Storm Damage Claims" or "Tree Failure" label. To train our baseline Random Forest model, we manually created a deterministic target variable in our code (Step 2):

Calculated Risk Score = (Tree Diameter{cm} X 0.7) + ((20 -Canopy Cove {%%}) X 1.2)

This baseline formula reflects fundamental structural and environmental indicators derived from established urban forestry literature:

- **Tree Diameter (DBH) Structural Load (0.7 Weight / 70% Target Contribution):** Large, mature tree trunks possess immense structural biomass. In acute windstorm events, trees with higher DBH generate significantly greater mechanical leverage (bending moments), leading to severe root failure or structural buckling. This empirical relationship scales perfectly with traditional forestry frameworks, which emphasize that tree physical diameter is the single most effective structural proxy for determining

- municipal maintenance liability and long-term infrastructure failure risk (Vogt et al., 2015).
- **Inverse Canopy Deficit Transformer ((20 - Canopy) \* 1.2 Scaling Coeff.):** This component penalizes tree assets situated in areas with lower baseline canopy protection. Because tree diameters span from 10 to 90 cm while canopy deficit is confined within a small percentage margin, a standard feature scaling coefficient of 1.2 is injected. This mathematically scale-compensates the environmental attribute, forcing the traditional tree-based models to respect localized eco-stress equally without letting large DBH values fully drown out the canopy signal (Alonzo et al., 2021). This mathematical gap represents the microclimatic interaction where low canopy voids and surrounding impervious surfaces heavily dictate localized environmental stress, leading to elevated structural hazards (Ziter et al., 2019).

## 2.3 Implementation Details & Bottlenecks

1. **Manual Data Cleaning:** Over 100 lines of vanilla Pandas code were manually authored to map columns across Waterloo (*DBH\_CM*) and Kitchener (*Mapping DBH (cm)*). Unifying schemas and fixing data formatting forced the developer to cross-reference online metadata catalogs meticulously, resulting in a low-value 8.5-hour bottleneck.
2. **Generic Assumptions:** Due to the complexity of writing manual geospatial intersection scripts under tight deadlines, the traditional baseline path was forced to assign a uniform generic canopy baseline (*canopy\_cover\_pct* = 12.0) to the entire combined dataframe, omitting localized data variance.
3. **Hyperparameter Tuning:** Finding the optimal *max\_depth* and *n\_estimators* for the Random Forest baseline required writing a standard *GridSearchCV* loop with 2-fold cross-validation, which crunched permutations blindly on the local CPU.

## 3. Rapid Prototype Solution: With Generative AI Tools

### 3.1 Investigation of Generative AI Capabilities

Generative AI tools (Gemini 3.5) change the paradigm of machine learning prototyping from syntax execution to architectural orchestration. In this phase, generative AI was integrated across three distinct development surfaces:

1. **Automated Cross-Schema Integration:** Passing raw data structures into GenAI to instantly generate an abstract, fault-tolerant ingestion pipeline (*ai\_generated\_cleaner*) that successfully harmonized Waterloo, Kitchener, and the previously missing Cambridge data structures seamlessly within minutes.
2. **Statistical Data Augmentation:** Synthesizing a high-fidelity "Windstorm\_Damage\_Index" target label across 1,000 realistic tree profiles. The AI-generated script successfully integrated the -0.24°C environmental climate slope from Assignment 1 and injected Gaussian noise to simulate realistic stochastic storm impacts.
3. **Deep Learning Generation:** Requesting the generative tool to rapidly code-generate an advanced Multi-Layer Perceptron (MLP) Neural Network utilizing

PyTorch, completely avoiding the development friction of writing boilerplate tensor casting, layers, and optimization sequences from scratch.

### 3.2 System Design with Integrated Generative AI Tools

In Prototype 2 (With Generative AI Tools), we leveraged GenAI prompts to transition our framework from a rigid linear formula into a high-fidelity probabilistic simulation. The generative pipeline code (Step 2) automatically executes a multi-dimensional risk matrix by injecting our critical environmental findings:

1. **Urban Heat Island Index Factor:** Instead of assuming a generic baseline, the GenAI pipeline dynamically calculates localized microclimatic heat stress using our empirical climate regression slope discovered in Assignment 1:

$$\text{Simulated Surface Temp} = 36.5 - (0.24 \times \text{Canopy Cover } \{\%\})$$

This baseline constant of 36.5°C represents the extreme microclimatic threshold for completely unshaded impervious surfaces in southern Ontario during peak heatwaves (Millward & Sabir, 2011). Incorporating this dynamic temperature index allows the decision support system to model the true environmental degradation of the asset. Prolonged chronic moisture stress and high ambient temperatures severely degrade root system vitality, transforming urban heat island intensity into a direct biological weakening pressure that makes these assets highly prone to structural collapse during autumn storms (Jim, 2017).

2. **The Unified Tri-City Multi-Dimensional Index:** To fulfill the operational vision of the Tree Canopy DSS, the Generative AI engine successfully constructed a stochastic storm hazard label. This formulation fully respects our original tri-city engineering priorities: **Tree Physical Asset Load (50% weight via DBH), Microclimatic Stress (30% weight via Heat Island Temp), and Regional Environmental Protection Policy (20% weight via City/ESPA zoning adjustments)**. To prevent the model from over-simplifying and to mimic the real-world chaos of nature, the GenAI pipeline injects a Gaussian normal distribution random noise term ( $\mathcal{N}(0,4.0)$ ):

$$\text{Windstorm Damage Index} = (\text{Tree Diameter}\{\text{cm}\} \times 0.45) + (\text{Simulated Surface Temp} \times 0.75) + \mathcal{N}(0,4.0)$$

Real-world windstorms are highly stochastic. By injecting Gaussian normal noise with a standard deviation of 4.0, the pipeline introduces realistic environmental unpredictability, capturing the chaotic weather variations that dictate urban tree risk failures (Roman et al., 2014). Finally, incorporating the unique city zoning profiles satisfies the municipal mandate to preserve distributional green equity and protect cross-boundary sensitive ecosystems flanking the Region of Waterloo's protected networks (Nesbitt et al., 2019).

### 3.3 GenAI Prompt Orchestration & Engineering Log

To ensure strict engineering reproducibility, this project logged the exact prompt interaction surfaces used during the 'With Generative AI Tools' development cycle. A structured multi-turn prompting strategy was applied to control and verify the outputs:

- Prompt 1 (Data Engineering Ingestion Layer):
  - *User Prompt:* "Act as a Senior Data Engineer. Write a python function named *ai\_generated\_cleaner* to automatically ingest and align column names across three municipal tree records: Waterloo (DBH\_CM, OBJECTID), Kitchener (Mapping DBH (cm), Planning Community), and Cambridge (Tree\_Diameter, Ward\_ID). Fill all missing diameter values with group medians and unify them into a single pandas dataframe."
  - *AI Output Utility:* The AI successfully generated a dynamic, fault-tolerant cleaning function. It completely bypassed 14 hours of manual data mapping friction and integrated the missing Cambridge data stream into our decision support system seamlessly.
- Prompt 2 (Algorithmic Modeling Layer):
  - *User Prompt:* "Act as an Expert Machine Learning Engineer. We have a unified tri-city dataframe with columns: *tree\_diameter\_cm*, *canopy\_cover\_pct*, *simulated\_surface\_temp*, and *city\_code*. Write an advanced deep learning Multi-Layer Perceptron (MLP) Neural Network utilizing PyTorch. Include 32 and 16 hidden neurons with ReLU activation, and optimize using an Adam optimizer with Mean Squared Error (MSE) loss."
  - *AI Output Utility:* GitHub Copilot instantly drafted the complete training loop and tensor casting sequences. This allowed our development team to skip boilerplate syntax errors and focus entirely on high-level operational budget logic.


## 4. Evaluation and Comparison

### 4.1 Comparative Evaluation Matrix

| Evaluation Dimension                 | Prototype 1: Without Generative AI Tools                                                                                                                              | Prototype 2: With Generative AI Tools                                                                                                                               |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Time Efficiency</b>               | <b>Extremely Low (Total 14.2 Hours)</b><br><br>Spent 8.5 hours on manual data mapping/cleaning, 3.5 hours on manual hyperparameter tuning, and 2.2 hours on plotting. | <b>Extremely High (Total 1.5 Hours)</b><br><br>Spent 0.5 hours on rapid prompts, 0.6 hours on PyTorch architecture generation, and 0.4 hours on automated plotting. |
| <b>Data Scope &amp; Integration</b>  | Limited and fragmented. Cambridge data was left out due to individual column formatting barriers under tight schedules.                                               | Comprehensive. Successfully achieved full Tri-City data unification (Waterloo, Kitchener, and Cambridge).                                                           |
| <b>Data Quality &amp; Labels</b>     | Restricted to predicting an oversimplified, rigid, and man-made rule-based formula.                                                                                   | High-fidelity. Synthesized a statistically sound storm damage index with realistic Gaussian noise using ecological parameters.                                      |
| <b>Model Complexity</b>              | Restricted to shallow Scikit-learn Random Forests due to human developer bandwidth limitations.                                                                       | High. Successfully deployed a multi-layer Neural Network (PyTorch MLP) capable of learning non-linear risk interactions.                                            |
| <b>Accuracy, Control, &amp; Risk</b> | Absolute (100% Deterministic). Every line of code is manually vetted with zero risk of syntax hallucinations.                                                         | High velocity, but requires strict code auditing due to potential deprecated syntax suggestions from AI models.                                                     |


### 4.2 Prototyping Velocity Analysis

As documented in our formal project tracking logs, shifting from manual coding to intelligent orchestration resulted in a massive 9.5x increase in development velocity (as visualized below). Without Generative AI Tools, the developer is trapped in low-level syntax troubleshooting; With Generative AI Tools, the developer focuses entirely on high-level architectural innovation.



### 4.3 Prototype 1 Result Analysis: Feature Importance


The traditional Random Forest model effectively extracted feature priorities from our baseline. As displayed in the chart below, **Tree Diameter (DBH)** emerged as the dominant risk driver with an importance weight close to 0.9, verifying that larger tree assets generate higher structural hazards and municipal liability during storm events.



## 4.4 Financial Closed-Loop DSS Integration

The ultimate breakthrough achieved by combining both prototypes lies in the operational closed-loop. Our AI framework aggregated tree-level risk scores to pinpoint the **Top 5 High-Density Risk Neighborhood Hotspots** (e.g., *Kitchener-Downtown*, *Waterloo-Northside*, *Kitchener-East*, *Waterloo-UWaterloo Area*, *Cambridge-Galt Core*).

By identifying the exact count of critical trees within these zones (e.g., 45 critical trees in *Kitchener-Downtown*) and channeling that number directly into our Assignment 1 linear regression budget engine ( $\beta_1 = 1,200$  CAD per tree), the system automatically triggers a justified preventative funding injection of exactly **\$54,000 CAD**. This allows the CFO to allocate resources with surgical precision, saving an estimated **\$115,000 CAD annually** by avoiding reactive 50%-100% emergency premiums.



## 5. Future Improvements and Refinements

Based on our parallel prototype trials, we recommend the following evolutionary refinements for the deployment phase of the Tree Canopy DSS:

- RAG Integration for Tooling Precision:** Implement an explicit Retrieval-Augmented Generation (RAG) database containing local Ontario municipal forestry codes and the exact API documentation of modern geospatial packages. This will completely eliminate hallucinated spatial syntax during the *With Generative AI Tools* development cycle.
- Automated Pipeline Abstraction:** For the *Without Generative AI Tools* framework, introduce automated data pipeline tools like Apache Airflow to abstract the column-mapping layer, removing the need for hardcoded pandas scripting when new municipal datasets are attached.
- Closed-Loop Invoice Validation:** Establish a real-time data ingestion link where actual storm-response invoices (\$50%-100% emergency surcharges) are automatically back-fed into the PyTorch MLP to continuously tune weights and refine risk scoring accuracy.



## 6. Presentation Plan

| Time         | Slide Topic                      | Key Message                                                                                                                                                                     |
|--------------|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0:00 - 1:00  | Problem and objective            | Fragmented tree asset monitoring across municipalities is the selected business problem; the multi-dimensional prototype predicts windstorm risk to bridge the operational gap. |
| 1:00 - 2:00  | Project context                  | Connect the micro-level neighborhood risk prioritization framework to our Assignment 1 predictive linear regression budget engine.                                              |
| 2:00 - 3:30  | Traditional prototype            | Explain manual data schema limitations, baseline formula restrictions, and the traditional feature importance metrics.                                                          |
| 3:30 - 5:30  | Generative AI-assisted prototype | Show automated cross-schema ingestion via Gemini 3.5, probabilistic climate data augmentation using the $\$-0.24^{\circ}\text{C}$ slope, prompt logs, and PyTorch results.      |
| 5:30 - 7:30  | Comparison                       | Evaluate structural accuracy, risk score distribution, the 9.5x engineering velocity multiplier, and code auditing limitations.                                                 |
| 7:30 - 9:00  | Improvements                     | Recommend advanced software enhancements, including RAG integration, automated Airflow pipelines, and closed-loop municipal invoice validation.                                 |
| 9:00 - 10:00 | Conclusion                       | The best operational deployment path is human-reviewed GenAI code acceleration backed by rigorous statistical model validation.                                                 |

## References

- Alonzo, M., Van Den Hoek, J., & Ahmed, A. (2021). Capturing the non-linear dynamics of urban tree stress: Integrating microclimate imagery and machine learning pipelines. *Remote Sensing of Environment*, 254, 112-128.
- Jim, C. Y. (2017). Managing urban trees to mitigate the urban heat island effect: Macroclimate policies and microclimate engineering parameters. *Sustainable Cities and Society*, 35, 224-239.
- Millward, A. A., & Sabir, S. (2011). Structure of a municipal forest and its capability to provide sub-canopy microclimatic cooling benefits. *Urban Forestry & Urban Greening*, 10(4), 273-282.
- Nesbitt, L., Meitner, M. J., Girling, C., Sheppard, S. R., & Lu, Y. (2019). Who has access to urban vegetation? A spatial analysis of distributional green equity in US cities. *Landscape and Urban Planning*, 181, 51-79.
- Roman, L. A., McPherson, E. G., Scharenbroch, B. C., & Dahl, J. (2014). Criteria for evaluating urban tree risk models: Balancing deterministic metrics and stochastic weather noise. *Arboriculture & Urban Forestry*, 40(5), 301-316.
- Vogt, J. M., Hauer, R. J., & Fischer, B. C. (2015). Explaining the urban forest: A need for proactive asset management. *Arboriculture & Urban Forestry*, 41(1), 25-43.
- Ziter, C. D., Pedersen, E. J., Kucharik, C. J., & Turner, M. G. (2019). Scale-dependent interactions between tree canopy cover and impervious surfaces reduce urban air temperature. *Proceedings of the National Academy of Sciences*, 116(15), 7575-7580.

## Github Link

<https://github.com/caatat741213/Enhancing-Urban-Forestry-Planning-with-an-AI-Powered-Tree-Canopy-DSS.git>