

All Classes and Interfaces

[All Classes and Interfaces](#)

[Interfaces](#)

[Classes](#)

[Enum Classes](#)

[Record Classes](#)

Class

Description

AnimationWrapper

Animation wrapper class for our projects animations that get used.

Application

The entry point of the application.

DailyRewardController

Controller for the daily reward popup screen.

DailyRewardModel

Model for handling daily reward logic and state.

DailyRewardType

Enum representing the possible daily reward outcomes.

DefinitionController

Controller for definition popup

DefinitionPopup

Represents Definition window called when a word is played

DictionaryDAO

The SQLite Dictionary.

EmptyTileSlotController

Empty Tile controller for EmptyTile view.

EmptyTileSlotModel

An empty tile slot model.

FXMLLoader

FXML Loader wrapper class for the project to load the game screen FXML pages.

GameMusicPlayer

Plays the game music track on repeat.

GameScenes

Game Scenes enum.

GameScreenController

Game screen controller that has some startup on screen thing todo.

GameScreenController.SidebarLoaded

GameScreenModel

Game Screen Model.

GameSoundPlayer

plays an audio clip as a sound effect for the game.

InfiniteFloatingAnimation

Balatro style floating tile animation.

LetterTileController

Controls the layout of the letterUIModel.

LetterTileGroup

tile group that observes an observable list and updates the ui Tile Controller's nodes into their EmptyTileSlotController nodes.

LetterTileModel

Represents the letter tiles the player plays holds, redraws.

LevelController

Controller for the level screen.

LevelModel

Represents the level model.

LevelScoreSequence

Animates each level tile popping up and the score text increasing for every tile in the word row.

Logger

com.example.project.services.Logger for Application and to show up in test and build CI workflow.

LoginController

Controller for the login scene.

LoginModel

Login model class.

MainMenuController

controller for the main menu.

MainMenuModel

main menu model class

PageLoader

Interface for page loading.

PasswordHasher

Hashes passwords.

PopupController<P>

Parent class for PopupControllers

PopupLoader

class to load the popup and initialize it with a controller

PopupModel

Parent class for popup windows

RootLayoutController

Root layout that remains the root scene of the application to switch scenes within.

SceneManager

Represents the scene manager class.

ScoreChimePlayer

plays a note from the F major scale ascending in pitch each time for a nice score combo sound.

ScoreTimeline

Class for total score counter animation

ScrabbleTileProvider

Static class to store the scrabble base letter value.

ScrabbleTileProvider.ScrabbleTileData**Session**

Game Session.

ShopController

Shop view controller.

ShopModel

Shop Model.

SidebarController

The sidebar on shop and level with the current round info.

SQLiteConnection

Abstract SQLiteConnection class.

SQLiteDictionaryConnection

Connection to the dictionary.db

SQLiteUsersConnection

Connection to the users.db

SVGIcons

a static class to hold some icons for the application.

TextEmphasisAnimation

An animation to quickly enlarge text and then return it to its original scale.

TileController<T>

Parent class of TileControllers.

TileControllerFactory

class to load the tile model controller for that tile model type.

TileGroup<modelType,controllerType>

Tile Group abstract class holds a row or column of tiles.

TileModel

Parent tile class for objects in the scene that are tiles.

UpgradeEffects

upgrade effect methods

UpgradeTileController

Controls the upgrade tile view fxml file.

UpgradeTileGroup

tile group that observes an observable list and updates the ui nodes for some game tiles.

UpgradeTileModel

Represents the upgrade tiles sold at the shop.

UpgradeTileModel.UpgradeBuilder

builder class for the upgrades

UpgradeTiles

Static class to store all the possible upgrade tiles available in the game.

User

Represents a user in the application that can log in.

UsersDAO

SQLite Users database.

All Packages

Package Summary
Package
Description
com.example.project
com.example.project.controllers
com.example.project.controllers.gameScreens
com.example.project.controllers.gameScreens.animations
com.example.project.controllers.popupControllers
com.example.project.controllers.tiles
com.example.project.models
com.example.project.models.gameScreens
com.example.project.models.popups
com.example.project.models.tileGroups
com.example.project.models.tiles
com.example.project.services
com.example.project.services.shopItems
com.example.project.services.sound
com.example.project.services.sqlite
com.example.project.services.sqlite.dAOs

Module com.example.project

Package com.example.project.controllers.gameScreens

Class LoginController

```
java.lang.Object
  com.example.project.controllers.gameScreens.GameScreenController
    com.example.project.controllers.gameScreens.LoginController
```

```
public class LoginController
extends GameScreenController
```

Controller for the login scene.

Nested Class Summary

Nested classes/interfaces inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
GameScreenController.SidebarLoaded
```

Field Summary

Fields inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
logger
```

Constructor Summary

Constructors

Constructor

Description

```
LoginController()
```

No arg constructor.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

```
void
```

```
initialize()
```

FXML initialise function called once when the .fxml is loaded on application launch.

```
protected void
```

```
onLoginButtonClick()
```

```
void
```

```
onSceneChangedToThis()
```

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

```
protected void
```

```
onSignupButtonClick()
```

Methods inherited from class com.example.project.controllers.gameScreens.GameScreenController

loadSidebar

Methods inherited from class java.lang.Object

clone[✉], equals[✉], finalize[✉], getClass[✉], hashCode[✉], notify[✉], notifyAll[✉], toString[✉], wait[✉], wait[✉], wait[✉]

Constructor Details

LoginController

public LoginController()

No arg constructor.

Method Details

onSceneChangedToThis

public void onSceneChangedToThis()

Description copied from class: GameScreenController

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

Specified by:

onSceneChangedToThis in class GameScreenController

initialize

public void initialize()

FXML initialise function called once when the .fxml is loaded on application launch.

onLoginButtonClick

protected void onLoginButtonClick()

onSignupButtonClick

protected void onSignupButtonClick()

Uses of Package com.example.project.models.tileGroups

Packages that use com.example.project.models.tileGroups

Package

Description

[com.example.project.controllers.gameScreens](#)

[com.example.project.models.tileGroups](#)

Classes in com.example.project.models.tileGroups used by com.example.project.controllers.gameScreens

Class

Description

[UpgradeTileGroup](#)

tile group that observes an observable list and updates the ui nodes for some game tiles.

Classes in com.example.project.models.tileGroups used by com.example.project.models.tileGroups

Class

Description

[TileGroup](#)

Tile Group abstract class holds a row or column of tiles.

Module com.example.project
Package com.example.project.models.tiles

Class EmptyTileSlotModel

java.lang.Object ↗
 com.example.project.models.tiles.TileModel
 com.example.project.models.tiles.EmptyTileSlotModel

```
public class EmptyTileSlotModel  
extends TileModel
```

An empty tile slot model. Empty tile slots store a letter tile.

Field Summary

Fields inherited from class com.example.project.models.tiles.TileModel

ClackSoundPlayer, CORNER_RADIUS, hoverSoundPlayer

Constructor Summary

Constructors

Constructor

Description

`EmptyTileSlotModel()`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

`String` ↗

`getFXMLPath()`

gets the fxml path.

`LetterTileModel`

`getTile()`

get letter tile in slot.

`void`

`setTile(LetterTileModel tile)`

Set a new tile.

Methods inherited from class com.example.project.models.tiles.TileModel

`getClackSoundPlayer`, `getHoverSoundPlayer`

Methods inherited from class java.lang.Object

`clone` ↗, `equals` ↗, `finalize` ↗, `getClass` ↗, `hashCode` ↗, `notify` ↗, `notifyAll` ↗, `toString` ↗, `wait` ↗, `wait` ↗, `wait` ↗

Constructor Details

EmptyTileSlotModel

```
public EmptyTileSlotModel()
```

Method Details

getTile

```
public LetterTileModel getTile()
```

get letter tile in slot.

Returns:

letter tile.

setTile

```
public void setTile(LetterTileModel tile)
```

Set a new tile.

Parameters:

tile - letter tile.

getFXMLPath

```
public String getFXMLPath()
```

Description copied from class: TileModel

gets the fxml path.

Specified by:

getFXMLPath in class TileModel

Returns:

string path.

Module com.example.project
Package com.example.project.models.tiles

Class LetterTileModel

java.lang.Object
 com.example.project.models.tiles.TileModel
 com.example.project.models.tiles.LetterTileModel

```
public class LetterTileModel  
extends TileModel
```

Represents the letter tiles the player plays holds, redraws.

Field Summary

Fields inherited from class com.example.project.models.tiles.TileModel

ClackSoundPlayer, CORNER_RADIUS, hoverSoundPlayer

Constructor Summary

Constructors

Constructor

Description

`LetterTileModel(Character newLetter)`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

`String`

`getFXMLPath()`

gets the fxml path.

`Character`

`getLetter()`

`Integer`

`getValue()`

Methods inherited from class com.example.project.models.tiles.TileModel

`getClackSoundPlayer, getHoverSoundPlayer`

Methods inherited from class java.lang.Object

`clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()`

Constructor Details

LetterTileModel

```
public LetterTileModel(Character2 newLetter)
```

Parameters:

newLetter - letter

Method Details

getLetter

```
public Character2 getLetter()
```

Returns:

returns the tiles character.

getValue

```
public Integer2 getValue()
```

Returns:

base value of scrabble letter score.

getFXMLPath

```
public String2 getFXMLPath()
```

Description copied from class: [TileModel](#)

gets the fxml path.

Specified by:

[getFXMLPath](#) in class [TileModel](#)

Returns:

string path.

Module com.example.project

Package com.example.project.models.tiles

Record Class ScrabbleTileProvider.ScrabbleTileData

java.lang.Object²
 java.lang.Record²
 com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData

Record Components:

value - value of scrabble letter

frequency - population of tile

Enclosing class:

ScrabbleTileProvider

```
public static record ScrabbleTileProvider.ScrabbleTileData(int value, int frequency)
extends Record2
```

Constructor Summary

Constructors

Constructor

Description

ScrabbleTileData(int value, int frequency)

Creates an instance of a ScrabbleTileData record class.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

final boolean

equals(Object² o)

Indicates whether some other object is "equal to" this one.

int

frequency()

Returns the value of the frequency record component.

final int

hashCode()

Returns a hash code value for this object.

final String²

toString()

Returns a string representation of this record class.

int

value()

Returns the value of the value record component.

Methods inherited from class java.lang.Object²

clone², finalize², getClass², notify², notifyAll², wait², wait², wait²

Constructor Details

ScrabbleTileData

```
public ScrabbleTileData(int value,  
                      int frequency)
```

Creates an instance of a ScrabbleTileData record class.

Parameters:

value - the value for the `value` record component

frequency - the value for the `frequency` record component

Method Details

toString

```
public final String toString()
```

Returns a string representation of this record class. The representation contains the name of the class, followed by the name and value of each of the record components.

Specified by:

`toString` in class `Record`

Returns:

a string representation of this object

hashCode

```
public final int hashCode()
```

Returns a hash code value for this object. The value is derived from the hash code of each of the record components.

Specified by:

`hashCode` in class `Record`

Returns:

a hash code value for this object

equals

```
public final boolean equals(Object o)
```

Indicates whether some other object is "equal to" this one. The objects are equal if the other object is of the same class and if all the record components are equal. All components in this record class are compared with '=='.

Specified by:

`equals` in class `Record`

Parameters:

o - the object with which to compare

Returns:

true if this object is the same as the o argument; false otherwise.

value

```
public int value()
```

Returns the value of the `value` record component.

Returns:

the value of the `value` record component

frequency

```
public int frequency()
```

Returns the value of the `frequency` record component.

Returns:

the value of the `frequency` record component

Module com.example.project
Package com.example.project.models.tiles

Class ScrabbleTileProvider

java.lang.Object
com.example.project.models.tiles.ScrabbleTileProvider

```
public class ScrabbleTileProvider  
extends Object
```

Static class to store the scrabble base letter value.

Nested Class Summary

Nested Classes

Modifier and Type

Class

Description

static final record

ScrabbleTileProvider.ScrabbleTileData

Constructor Summary

Constructors

Constructor

Description

ScrabbleTileProvider()

Constructor.

Method Summary

All Methods

Static Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

Character

drawRandomTile()

int

getValue(Character letter)

Returns Integer of the letter according to scrabble

protected static void

seedRandomNumberGenerator(long newSeed)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

ScrabbleTileProvider

```
public ScrabbleTileProvider()
```

Constructor.

Method Details

seedRandomNumberGenerator

```
protected static void seedRandomNumberGenerator(long newSeed)
```

getValue

```
public int getValue(Character letter)
```

Returns Integer of the letter according to scrabble

Parameters:

letter - letter to get value of

Returns:

Integer value of the letter, or 0 if not found

drawRandomTile

```
public Character drawRandomTile()
```

Returns:

randomly selected tile based on CDF

Module com.example.project
Package com.example.project.models.tiles

Class TileModel

java.lang.Object[↳]
 com.example.project.models.tiles.TileModel

Direct Known Subclasses:

EmptyTileSlotModel, LetterTileModel, UpgradeTileModel

```
public abstract class TileModel
extends Object↳
```

Parent tile class for objects in the scene that are tiles.

Field Summary

Fields

Modifier and Type

Field

Description

protected final GameSoundPlayer

ClackSoundPlayer

static final int

CORNER_RADIUS

corner radius (rounded corners).

protected final GameSoundPlayer

hoverSoundPlayer

Constructor Summary

Constructors

Constructor

Description

TileModel()

Method Summary

All Methods

Instance Methods

Abstract Methods

Concrete Methods

Modifier and Type

Method

Description

GameSoundPlayer

getClackSoundPlayer()

gets the sound player that plays the click sound.

abstract String[↳]

getFXMLPath()

gets the fxml path.

GameSoundPlayer

getHoverSoundPlayer()

gets the hover sound player

Methods inherited from class java.lang.Object

clone[✉], equals[✉], finalize[✉], getClass[✉], hashCode[✉], notify[✉], notifyAll[✉], toString[✉], wait[✉], wait[✉], wait[✉]

Field Details

hoverSoundPlayer

```
protected final GameSoundPlayer hoverSoundPlayer
```

ClackSoundPlayer

```
protected final GameSoundPlayer ClackSoundPlayer
```

CORNER_RADIUS

```
public static final int CORNER_RADIUS
```

corner radius (rounded corners).

See Also:

Constant Field Values

Constructor Details

TileModel

```
public TileModel()
```

Method Details

getFXMLPath

```
public abstract String✉ getFXMLPath()
```

gets the fxml path.

Returns:

string path.

getHoverSoundPlayer

```
public GameSoundPlayer getHoverSoundPlayer()
```

gets the hover sound player

Returns:

sound player

getClackSoundPlayer

```
public GameSoundPlayer getClackSoundPlayer()
```

gets the sound player that plays the click sound.

Returns:

sound player.

Module com.example.project
Package com.example.project.models.tiles

Class UpgradeEffects

java.lang.Object
com.example.project.models.tiles.UpgradeEffects

```
public class UpgradeEffects  
extends Object
```

upgrade effect methods

Constructor Summary

Constructors

Constructor

Description

`UpgradeEffects()`

Method Summary

All Methods

Static Methods

Concrete Methods

Modifier and Type

Method

Description

static void

`braceletEffect()`

Add +1 to score multiplier for every consecutive letter alphabetical order.

static void

`buttonEffect()`

adds 5 to the word score for every x in the tile rack.

static void

`coinEffect()`

20% Chance the total word score is doubled

static void

`diceEffect()`

Value is doubled for a random letter in the played word

static void

`glassesEffect()`

Adds +2 to the score multiplier for every identical pair of letters next to each other

static void

`mirrorEffect()`

If played word is a palindrome, doubles word score.

Methods inherited from class java.lang.Object

`clone()`, `equals()`, `finalize()`, `getClass()`, `hashCode()`, `notify()`, `notifyAll()`, `toString()`, `wait()`, `wait()`, `wait()`

Constructor Details

UpgradeEffects

```
public UpgradeEffects()
```

Method Details

glassesEffect

```
public static void glassesEffect()
```

Adds +2 to the score multiplier for every identical pair of letters next to each other

diceEffect

```
public static void diceEffect()
```

Value is doubled for a random letter in the played word

coinEffect

```
public static void coinEffect()
```

20% Chance the total word score is doubled

mirrorEffect

```
public static void mirrorEffect()
```

If played word is a palindrome, doubles word score.

braceletEffect

```
public static void braceletEffect()
```

Add +1 to score multiplier for every consecutive letter alphabetical order.

buttonEffect

```
public static void buttonEffect()
```

adds 5 to the word score for every x in the tile rack.

Module com.example.project

Package com.example.project.models.tiles

Class UpgradeTileModel.UpgradeBuilder

java.lang.Object[✉]
com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder

Enclosing class:

UpgradeTileModel

```
public static class UpgradeTileModel.UpgradeBuilder  
extends Object✉
```

builder class for the upgrades

Constructor Summary

Constructors

Constructor

Description

`UpgradeBuilder()`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

`UpgradeTileModel`

`build()`

build upgrade

`UpgradeTileModel.UpgradeBuilder`

`cost(double cost)`

upgrade cost builder

`UpgradeTileModel.UpgradeBuilder`

`description(String✉ description)`

upgrade description builder

`UpgradeTileModel.UpgradeBuilder`

`imagePath(String✉ imagePath)`

upgrade image path builder

`UpgradeTileModel.UpgradeBuilder`

`name(String✉ name)`

upgrade name builder

`UpgradeTileModel.UpgradeBuilder`

`upgradeEffect(Runnable✉ upgradeEffect)`

upgrade effect builder

Methods inherited from class java.lang.Object[✉]

`clone✉, equals✉, finalize✉, getClass✉, hashCode✉, notify✉, notifyAll✉, toString✉, wait✉, wait✉, wait✉`

Constructor Details

UpgradeBuilder

```
public UpgradeBuilder()
```

Method Details

description

```
public UpgradeTileModel.UpgradeBuilder description(String2 description)
```

upgrade description builder

Parameters:

description - new upgrade description

Returns:

description

name

```
public UpgradeTileModel.UpgradeBuilder name(String2 name)
```

upgrade name builder

Parameters:

name - new upgrade name

Returns:

name

imagePath

```
public UpgradeTileModel.UpgradeBuilder imagePath(String2 imagePath)
```

upgrade image path builder

Parameters:

imagePath - new upgrade image path

Returns:

image path

cost

```
public UpgradeTileModel.UpgradeBuilder cost(double cost)
```

upgrade cost builder

Parameters:

cost - new upgrade cost

Returns:

cost

upgradeEffect

```
public UpgradeTileModel.UpgradeBuilder upgradeEffect(Runnable2 upgradeEffect)
```

upgrade effect builder

Parameters:

upgradeEffect - new upgrade effect

Returns:

upgrade effect

build

```
public UpgradeTileModel build()
```

build upgrade

Returns:

new upgrade

Module com.example.project
Package com.example.project.models.tiles

Class UpgradeTileModel

java.lang.Object ↗
 com.example.project.models.tiles.TileModel
 com.example.project.models.tiles.UpgradeTileModel

```
public class UpgradeTileModel  
extends TileModel
```

Represents the upgrade tiles sold at the shop.

Nested Class Summary

Nested Classes

Modifier and Type

Class

Description

static class

UpgradeTileModel.UpgradeBuilder

builder class for the upgrades

Field Summary

Fields inherited from class com.example.project.models.tiles.TileModel

ClackSoundPlayer, CORNER_RADIUS, hoverSoundPlayer

Constructor Summary

Constructors

Constructor

Description

UpgradeTileModel(UpgradeTileModel.UpgradeBuilder builder)

public upgrade constructor.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

String ↗

getAbilityImagePath()

gets upgrade tile image path.

double

getCost()

gets the cost

String ↗

getDescription()

gets the description.

String

getFXMLPath()

gets the fxml path.

String

getName()

gets the name.

Runnable

getUpgradeEffect()

gets the effect for this tile.

Methods inherited from class com.example.project.models.tiles.TileModel

getClackSoundPlayer, getHoverSoundPlayer

Methods inherited from class java.lang.Object

clone[✉], equals[✉], finalize[✉], getClass[✉], hashCode[✉], notify[✉], notifyAll[✉], toString[✉], wait[✉], wait[✉], wait[✉]

Constructor Details

UpgradeTileModel

public UpgradeTileModel(UpgradeTileModel.UpgradeBuilder builder)

public upgrade constructor.

Parameters:

builder - upgrade builder

Method Details

getName

public String getName()

gets the name.

Returns:

return name.

getDescription

public String getDescription()

gets the description.

Returns:

description.

getCost

public double getCost()

gets the cost

Returns:

return cost.

getAbilityImagePath

```
public String✉ getAbilityImagePath()
```

gets upgrade tile image path.

Returns:

returns loaded Image for this tile.

getUpgradeEffect

```
public Runnable✉ getUpgradeEffect()
```

gets the effect for this tile.

Returns:

returns the runnable effect for this tile.

getFXMLPath

```
public String✉ getFXMLPath()
```

Description copied from class: TileModel

gets the fxml path.

Specified by:

getFXMLPath in class TileModel

Returns:

string path.

Uses of Class com.example.project.models.tiles.EmptyTileSlotModel

Packages that use EmptyTileSlotModel

Package

Description

com.example.project.controllers.tiles

Uses of EmptyTileSlotModel in com.example.project.controllers.tiles

Methods in com.example.project.controllers.tiles with parameters of type EmptyTileSlotModel

Modifier and Type

Method

Description

void

`EmptyTileSlotController.bind(EmptyTileSlotModel modelToUse)`

Module com.example.project

Package com.example.project.controllers.gameScreens

Class MainMenuController

```
java.lang.Object
    com.example.project.controllers.gameScreens.GameScreenController
        com.example.project.controllers.gameScreens.MainMenuController
```

```
public class MainMenuController
extends GameScreenController
```

controller for the main menu.

Nested Class Summary

Nested classes/interfaces inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
GameScreenController.SidebarLoaded
```

Field Summary

Fields inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
logger
```

Constructor Summary

Constructors

Constructor

Description

```
MainMenuController()
```

No arg constructor.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

```
void
```

```
initialize()
```

FXML initialise function called once when the .fxml is loaded.

```
protected void
```

```
onDailyRewardClicked()
```

```
protected void
```

```
onFastForwardClick()
```

```
protected void
```

```
onLogoutButtonClick()
```

```
void  
onSceneChangedToThis()
```

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

```
protected void  
onStartButtonClick()
```

Methods inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
loadSidebar
```

Methods inherited from class java.lang.Object

```
clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()
```

Constructor Details

MainMenuController

```
public MainMenuController()
```

No arg constructor.

Method Details

onSceneChangedToThis

```
public void onSceneChangedToThis()
```

Description copied from class: GameScreenController

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

Specified by:

onSceneChangedToThis in class GameScreenController

initialize

```
public void initialize()
```

FXML initialise function called once when the .fxml is loaded.

onStartButtonClick

```
protected void onStartButtonClick()
```

onLogoutButtonClick

```
protected void onLogoutButtonClick()
```

onDailyRewardClicked

```
protected void onDailyRewardClicked()
```

onFastForwardClick

```
protected void onFastForwardClick()
```

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.models.tiles.LetterTileModel

Packages that use LetterTileModel

Package

Description

com.example.project.controllers.tiles

com.example.project.models.gameScreens

com.example.project.models.tileGroups

com.example.project.models.tiles

Uses of LetterTileModel in com.example.project.controllers.tiles

Methods in com.example.project.controllers.tiles that return LetterTileModel

Modifier and Type

Method

Description

LetterTileModel

LetterTileController.getModel()

Methods in com.example.project.controllers.tiles with parameters of type LetterTileModel

Modifier and Type

Method

Description

void

LetterTileController.bind(LetterTileModel tile)

LetterTileController

TileControllerFactory.createLetterTileController(LetterTileModel lt)

Uses of LetterTileModel in com.example.project.models.gameScreens

Methods in com.example.project.models.gameScreens that return types with arguments of type LetterTileModel

Modifier and Type

Method

Description

javafx.beans.property.ReadOnlyListProperty<LetterTileModel>

LevelModel.getRedrawWindowTilesProperty()

javafx.beans.property.ReadOnlyListProperty<LetterTileModel>

LevelModel.getTileRackTilesProperty()

```
javafx.beans.property.ReadOnlyListProperty<LetterTileModel>
```

```
LevelModel.getWordWindowTilesProperty()
```

Methods in com.example.project.models.gameScreens with parameters of type LetterTileModel

Modifier and Type

Method

Description

protected void

```
LevelModel.addTileToRack(LetterTileModel tile)
```

protected void

```
LevelModel.addTileToRedrawWindow(LetterTileModel tile)
```

protected void

```
LevelModel.addTileToWordWindow(LetterTileModel tile)
```

void

```
LevelModel.addToCombo(LetterTileModel tile)
```

add combo sum and multiCombo

boolean

```
LevelModel.tryMoveTile(LetterTileModel tile)
```

determines where tile should go and moves it

Uses of LetterTileModel in com.example.project.models.tileGroups

Constructor parameters in com.example.project.models.tileGroups with type arguments of type LetterTileModel

Modifier

Constructor

Description

```
LetterTileGroup(int numberOfEmptyTileSlots, javafx.scene.layout.Pane container,  
javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<  
<LetterTileController> onClickAction)
```

Constructor

```
LetterTileGroup(int numberOfEmptyTileSlots, javafx.scene.layout.Pane container,  
javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<  
<LetterTileController> onClickHandler, List<Runnable> afterSyncActions)
```

Constructor

protected

```
LetterTileGroup(int numberOfEmptyTileSlots, javafx.scene.layout.Pane container,  
javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<  
<LetterTileController> onClickHandler, List<Runnable> afterSyncActions, TileControllerFactory factory)
```

Uses of LetterTileModel in com.example.project.models.tiles

Methods in com.example.project.models.tiles that return LetterTileModel

Modifier and Type

Method**Description**

LetterTileModel

EmptyTileSlotModel.getTile()

get letter tile in slot.

Methods in com.example.project.models.tiles with parameters of type LetterTileModel

Modifier and Type**Method****Description**

void

EmptyTileSlotModel.setTile(LetterTileModel tile)

Set a new tile.

Uses of Record Class

com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData

No usage of com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.models.tiles.ScrabbleTileProvider

No usage of com.example.project.models.tiles.ScrabbleTileProvider

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.models.tiles.TileModel

Packages that use TileModel

Package

Description

com.example.project.controllers.tiles

com.example.project.models.tileGroups

com.example.project.models.tiles

Uses of TileModel in com.example.project.controllers.tiles

Classes in com.example.project.controllers.tiles with type parameters of type TileModel

Modifier and Type

Class

Description

class

TileController<T extends TileModel>

Parent class of TileControllers.

Fields in com.example.project.controllers.tiles declared as TileModel

Modifier and Type

Field

Description

protected T

TileController.model

Methods in com.example.project.controllers.tiles with type parameters of type TileModel

Modifier and Type

Method

Description

<C extends TileController<T>, T extends TileModel>
C

TileControllerFactory.createTileController(T tile, Class<?> controllerType)

Returns controller of type.

Uses of TileModel in com.example.project.models.tileGroups

Classes in com.example.project.models.tileGroups with type parameters of type TileModel

Modifier and Type

Class

Description

class

TileGroup<modelType extends TileModel, controllerType extends TileController<modelType>>

Tile Group abstract class holds a row or column of tiles.

Uses of *TileModel* in *com.example.project.models.tiles*

Subclasses of *TileModel* in *com.example.project.models.tiles*

Modifier and Type

Class

Description

class

[EmptyTileSlotModel](#)

An empty tile slot model.

class

[LetterTileModel](#)

Represents the letter tiles the player plays holds, redraws.

class

[UpgradeTileModel](#)

Represents the upgrade tiles sold at the shop.

Uses of Class **com.example.project.models.tiles.UpgradeEffects**

No usage of com.example.project.models.tiles.UpgradeEffects

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder

Packages that use UpgradeTileModel.UpgradeBuilder

Package

Description

com.example.project.models.tiles

Uses of UpgradeTileModel.UpgradeBuilder in com.example.project.models.tiles

Methods in com.example.project.models.tiles that return UpgradeTileModel.UpgradeBuilder

Modifier and Type

Method

Description

UpgradeTileModel.UpgradeBuilder

UpgradeTileModel.UpgradeBuilder.cost(double cost)

upgrade cost builder

UpgradeTileModel.UpgradeBuilder

UpgradeTileModel.UpgradeBuilder.description(String[✉] description)

upgrade description builder

UpgradeTileModel.UpgradeBuilder

UpgradeTileModel.UpgradeBuilder.imagePath(String[✉] imagePath)

upgrade image path builder

UpgradeTileModel.UpgradeBuilder

UpgradeTileModel.UpgradeBuilder.name(String[✉] name)

upgrade name builder

UpgradeTileModel.UpgradeBuilder

UpgradeTileModel.UpgradeBuilder.upgradeEffect(Runnable[✉] upgradeEffect)

upgrade effect builder

Constructors in com.example.project.models.tiles with parameters of type UpgradeTileModel.UpgradeBuilder

Modifier

Constructor

Description

UpgradeTileModel(UpgradeTileModel.UpgradeBuilder builder)

public upgrade constructor.

Uses of Class com.example.project.models.tiles.UpgradeTileModel

Packages that use UpgradeTileModel

Package

Description

com.example.project.controllers.tiles

com.example.project.models.gameScreens

com.example.project.models.tileGroups

com.example.project.models.tiles

com.example.project.services

com.example.project.services.shopItems

Uses of UpgradeTileModel in com.example.project.controllers.tiles

Methods in com.example.project.controllers.tiles with parameters of type UpgradeTileModel

Modifier and Type

Method

Description

void

`UpgradeTileController.bind(UpgradeTileModel tileModel)`

Uses of UpgradeTileModel in com.example.project.models.gameScreens

Methods in com.example.project.models.gameScreens that return types with arguments of type UpgradeTileModel

Modifier and Type

Method

Description

`javafx.beans.property.ListProperty<UpgradeTileModel>`

`ShopModel.currentShopItemsProperty()`

Current items in the shop row that you can buy.

`javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel>`

`ShopModel.playersUpgradesProperty()`

get what upgrades the player currently has.

Methods in com.example.project.models.gameScreens with parameters of type UpgradeTileModel

Modifier and Type

Method

Description

boolean

`ShopModel.canPurchase(UpgradeTileModel tile)`

Determines whether the player can afford to purchase the specified upgrade tile.

void

ShopModel.purchase(UpgradeTileModel tileClickedOn)

This should attempt to purchase an upgrade tile from the shop.

Uses of UpgradeTileModel in com.example.project.models.tileGroups

Constructor parameters in com.example.project.models.tileGroups with type arguments of type UpgradeTileModel

Modifier

Constructor

Description

**UpgradeTileGroup(javafx.scene.layout.Pane container,
javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> observedList)**

Constructor with no additional sync action parameter.

**UpgradeTileGroup(javafx.scene.layout.Pane container,
javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> observedList, Consumer<
<UpgradeTileController> onClickAction)**

Constructor.

Uses of UpgradeTileModel in com.example.project.models.tiles

Methods in com.example.project.models.tiles that return UpgradeTileModel

Modifier and Type

Method

Description

UpgradeTileModel

UpgradeTileModel.UpgradeBuilder.build()

build upgrade

Uses of UpgradeTileModel in com.example.project.services

Methods in com.example.project.services that return types with arguments of type UpgradeTileModel

Modifier and Type

Method

Description

javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel>

Session.getUpgradeTilesProperty()

gets upgrade tile property

Methods in com.example.project.services with parameters of type UpgradeTileModel

Modifier and Type

Method

Description

void

Session.addUpgrade(UpgradeTileModel upgrade)

Adds an upgrade tile to the player's collection.

Constructor parameters in `com.example.project.services` with type arguments of type `UpgradeTileModel`

Modifier

Constructor

Description

protected

```
Session(int newHandSize, int newWordViewSize, int newRedrawWindowSize,  
javafx.collections.ObservableList<UpgradeTileModel> newUpgrades, User newUser, int newMoney,  
int newLevelsBeaten, int currentLevelRequirement, int newFirstLevelsRequirement, int newInitialMoney)
```

Constructor for injecting values in for unit test.

Uses of `UpgradeTileModel` in `com.example.project.services.shopItems`

Methods in `com.example.project.services.shopItems` that return `UpgradeTileModel`

Modifier and Type

Method

Description

static `UpgradeTileModel`

`UpgradeTiles.getRandomUpgradeTile()`

Gets random upgrade tile.

static `UpgradeTileModel`

`UpgradeTiles.getTile(int index)`

Gets the upgrade tile at index.

Package com.example.project.models.tiles

package com.example.project.models.tiles

Related Packages

Package

Description

[com.example.project.models](#)

[com.example.project.models.gameScreens](#)

[com.example.project.models.popups](#)

[com.example.project.models.tileGroups](#)

All Classes and Interfaces

Classes

Record Classes

Class

Description

[EmptyTileSlotModel](#)

An empty tile slot model.

[LetterTileModel](#)

Represents the letter tiles the player plays holds, redraws.

[ScrabbleTileProvider](#)

Static class to store the scrabble base letter value.

[ScrabbleTileProvider.ScrabbleTileData](#)

[TileModel](#)

Parent tile class for objects in the scene that are tiles.

[UpgradeEffects](#)

upgrade effect methods

[UpgradeTileModel](#)

Represents the upgrade tiles sold at the shop.

[UpgradeTileModel.UpgradeBuilder](#)

builder class for the upgrades

Hierarchy For Package com.example.project.models.tiles

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#)
 - [com.example.project.models.tiles.ScrabbleTileProvider](#)
 - [com.example.project.models.tiles.TileModel](#)
 - [com.example.project.models.tiles.EmptyTileSlotModel](#)
 - [com.example.project.models.tiles.LetterTileModel](#)
 - [com.example.project.models.tiles.UpgradeTileModel](#)
 - [com.example.project.models.tiles.UpgradeEffects](#)
 - [com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder](#)

Record Class Hierarchy

- [java.lang.Object](#)
 - [java.lang.Record](#)
 - [com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData](#)

Copyright © 2025. All rights reserved.

Uses of Package com.example.project.models.tiles

Packages that use com.example.project.models.tiles

Package

Description

com.example.project.controllers.tiles

com.example.project.models.gameScreens

com.example.project.models.tileGroups

com.example.project.models.tiles

com.example.project.services

com.example.project.services.shopItems

Classes in com.example.project.models.tiles used by com.example.project.controllers.tiles

Class

Description

EmptyTileSlotModel

An empty tile slot model.

LetterTileModel

Represents the letter tiles the player plays holds, redraws.

TileModel

Parent tile class for objects in the scene that are tiles.

UpgradeTileModel

Represents the upgrade tiles sold at the shop.

Classes in com.example.project.models.tiles used by com.example.project.models.gameScreens

Class

Description

LetterTileModel

Represents the letter tiles the player plays holds, redraws.

UpgradeTileModel

Represents the upgrade tiles sold at the shop.

Classes in com.example.project.models.tiles used by com.example.project.models.tileGroups

Class

Description

LetterTileModel

Represents the letter tiles the player plays holds, redraws.

TileModel

Parent tile class for objects in the scene that are tiles.

UpgradeTileModel

Represents the upgrade tiles sold at the shop.

Classes in com.example.project.models.tiles used by com.example.project.models.tiles

Class

Description

LetterTileModel

Represents the letter tiles the player plays holds, redraws.

TileModel

Parent tile class for objects in the scene that are tiles.

UpgradeTileModel

Represents the upgrade tiles sold at the shop.

UpgradeTileModel.UpgradeBuilder

builder class for the upgrades

Classes in com.example.project.models.tiles used by com.example.project.services

Class

Description

UpgradeTileModel

Represents the upgrade tiles sold at the shop.

Classes in com.example.project.models.tiles used by com.example.project.services.shopItems

Class

Description

UpgradeTileModel

Represents the upgrade tiles sold at the shop.

Module com.example.project

Package com.example.project.controllers.gameScreens

Class ShopController

```
java.lang.Object
  com.example.project.controllers.gameScreens.GameScreenController
    com.example.project.controllers.gameScreens.ShopController
```

```
public class ShopController
extends GameScreenController
```

Shop view controller.

Nested Class Summary

Nested classes/interfaces inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
GameScreenController.SidebarLoaded
```

Field Summary

Fields inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
logger
```

Constructor Summary

Constructors

Modifier

Constructor

Description

```
ShopController()
```

no arg constructor.

protected

```
ShopController(ShopModel model, UpgradeTileGroup players, UpgradeTileGroup shopItems, Logger logger)
```

protected constructor for unit testing with mock model injection.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

```
initialize()
```

FXML initialise function called once when the .fxml is loaded on application launch.

protected void

```
onNextLevelPressed()
```

void

onSceneChangedToThis()

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

```
protected void
```

```
onUpgradeClicked(UpgradeTileController controller)
```

Methods inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
loadSidebar
```

Methods inherited from class java.lang.Object

```
clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()
```

Constructor Details

ShopController

```
public ShopController()
```

no arg constructor.

ShopController

```
protected ShopController(ShopModel model,  
                         UpgradeTileGroup players,  
                         UpgradeTileGroup shopItems,  
                         Logger logger)
```

protected constructor for unit testing with mock model injection.

Method Details

initialize

```
public void initialize()
```

FXML initialise function called once when the .fxml is loaded on application launch.

onSceneChangedToThis

```
public void onSceneChangedToThis()
```

Description copied from class: GameScreenController

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

Specified by:

onSceneChangedToThis in class GameScreenController

onUpgradeClicked

```
protected void onUpgradeClicked(UpgradeTileController controller)
```

Parameters:

controller - upgrade tile ui element clicked on.

onNextLevelPressed

```
protected void onNextLevelPressed()
```


Module com.example.project

Package com.example.project

package com.example.project

Related Packages

Package

Description

[com.example.project.controllers](#)

[com.example.project.models](#)

[com.example.project.services](#)

Classes

Class

Description

Application

The entry point of the application.

Hierarchy For Package com.example.project

Package Hierarchies:

All Packages

Class Hierarchy

- [java.lang.Object](#) ↗
 - [javafx.application.Application](#)
 - [com.example.project.Application](#)

Uses of Package com.example.project

No usage of com.example.project

Copyright © 2025. All rights reserved.

Module com.example.project
Package com.example.project.services

Class FXMLPageLoader

java.lang.Object²
 com.example.project.services.FXMLPageLoader

All Implemented Interfaces:

PageLoader

```
public class FXMLPageLoader
extends Object2
implements PageLoader
```

FXML Loader wrapper class for the project to load the game screen FXML pages.

Constructor Summary

Constructors

Constructor

Description

FXMLPageLoader()

constructor.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

<T> T

getController()

Get the .fxml pages controller

javafx.scene.Parent

load(String² fxmlPath)

Load method to load fxml page.

Methods inherited from class java.lang.Object²

clone², equals², finalize², getClass², hashCode², notify², notifyAll², toString², wait², wait², wait²

Constructor Details

FXMLPageLoader

```
public FXMLPageLoader()
constructor.
```

Method Details

load

```
public javafx.scene.Parent load(String2 fxmlPath)
```

```
throws IOException
```

Description copied from interface: PageLoader

Load method to load fxml page.

Specified by:

[load](#) in interface PageLoader

Parameters:

FXMLPath - path to .fxml mfile.

Returns:

returns the fxml file root node.

Throws:

IOException - exception on failing.

getController

```
public <T> T getController()
```

Description copied from interface: PageLoader

Get the .fxml pages controller

Specified by:

[getController](#) in interface PageLoader

Type Parameters:

T - controller type.

Returns:

page's controller.

Module com.example.project

Package com.example.project.services

Enum Class GameScenes

java.lang.Object ↗
 java.lang.Enum ↗<GameScenes>
 com.example.project.services.GameScenes

All Implemented Interfaces:

Serializable ↗, Comparable ↗<GameScenes>, Constable ↗

```
public enum GameScenes  
extends Enum<GameScenes>
```

Game Scenes enum.

Nested Class Summary

Nested classes/interfaces inherited from class java.lang.Enum

```
Enum.EnumDesc<E> extends Enum<E>>
```

Enum Constant Summary

Enum Constants

Enum Constant

Description

DAILY_REWARD

Daily Reward Spinner Screen.

LEVEL

level Screen

LOGIN

Login Screen.

MAINMENU

Main Menu Screen.

SHOP

Shop screen.

Method Summary

All Methods

Static Methods

Concrete Methods

Modifier and Type

Method

Description

```
static GameScenes
```

```
valueOf(String name)
```

Returns the enum constant of this class with the specified name.

```
static GameScenes[]
```

```
values()
```

Returns an array containing the constants of this enum class, in the order they are declared.

Methods inherited from class java.lang.Enum

clone², compareTo², describeConstable², equals², finalize², getDeclaringClass², hashCode², name², ordinal²,
toString², valueOf²

Methods inherited from class java.lang.Object²

getClass², notify², notifyAll², wait², wait², wait²

Enum Constant Details

LOGIN

public static final GameScenes LOGIN

Login Screen.

MAINMENU

public static final GameScenes MAINMENU

Main Menu Screen.

DAILY_REWARD

public static final GameScenes DAILY_REWARD

Daily Reward Spinner Screen.

LEVEL

public static final GameScenes LEVEL

level Screen

SHOP

public static final GameScenes SHOP

Shop screen.

Method Details

values

public static GameScenes[] values()

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

public static GameScenes valueOf(String² name)

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

IllegalArgumentException² - if this enum class has no constant with the specified name

[NullPointerException](#) - if the argument is null

Module com.example.project
Package com.example.project.services

Class Logger

java.lang.Object[✉]
 com.example.project.services.Logger

```
public class Logger  
extends Object✉
```

com.example.project.services.Logger for Application and to show up in test and build CI workflow.

Constructor Summary

Constructors

Modifier

Constructor

Description

Logger()

Default constructor writes to console does not capture.

Logger(ByteArrayOutputStream[✉] capturedErrStream, ByteArrayOutputStream[✉] capturedOutStream)

Constructor for unit tests.

protected

Logger(ByteArrayOutputStream[✉] capturedErrStream, ByteArrayOutputStream[✉] capturedOutStream, PrintStream[✉] mockRealErrOutput, PrintStream[✉] mockRealStdOutput)

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

clearLogs()

Clears captured logs use in tests teardown.

String[✉]

getErrorLogs()

String[✉]

getLogs()

void

logError(String[✉] message)

Logs an error message to standard error.

void

logMessage(String[✉] formattedMessage)

Log message to System.out.

```
void  
setPrintToConsole(boolean value)
```

Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructor Details

Logger

```
public Logger()
```

Default constructor writes to console does not capture. For the project files. Use below for unit tests.

Logger

```
public Logger(ByteArrayOutputStream capturedErrStream,  
             ByteArrayOutputStream capturedOutStream)
```

Constructor for unit tests. Logger with constructor to input the byte array output stream to write to. (for mocking a log to check get methods.)

Parameters:

`capturedErrStream` - byte array to store error logs.

`capturedOutStream` - byte array to store standard output logs.

Logger

```
protected Logger(ByteArrayOutputStream capturedErrStream,  
                 ByteArrayOutputStream capturedOutStream,  
                 PrintStream mockRealErrOutput,  
                 PrintStream mockRealStdOutput)
```

Method Details

setPrintToConsole

```
public void setPrintToConsole(boolean value)
```

Parameters:

`value` - if this logger will also print to the console.

getErrorLogs

```
public String getErrorLogs()
```

Returns:

Gets the error log messages.

getLogs

```
public String getLogs()
```

Returns:

returns the standard log messages.

logError

```
public void logError(String2 message)
```

Logs an error message to standard error. And adds a newline.

The message can include format specifiers like in `String.format(String, Object...)`.

Parameters:

message - the error message format string (e.g., "Failed to connect to %s")

clearLogs

```
public void clearLogs()
```

Clears captured logs use in tests teardown.

logMessage

```
public void logMessage(String2 formattedMessage)
```

Log message to System.out.

Parameters:

formattedMessage - message.

Module com.example.project
Package com.example.project.services

Interface PageLoader

All Known Implementing Classes:

FXMLPageLoader

public interface PageLoader

Interface for page loading.

Method Summary

[All Methods](#) [Instance Methods](#) [Abstract Methods](#)

Modifier and Type

Method

Description

<T> T

getController()

Get the .fxml pages controller

javafx.scene.Parent

load(String[✉] fxmlPath)

Load method to load fxml page.

Method Details

load

```
javafx.scene.Parent load(String✉ fxmlPath)
    throws IOException
```

Load method to load fxml page.

Parameters:

fxmlPath - path to .fxml mfile.

Returns:

returns the fxml file root node.

Throws:

IOException[✉] - exception on failing.

getController

<T> T getController()

Get the .fxml pages controller

Type Parameters:

T - controller type.

Returns:

page's controller.

Module com.example.project
Package com.example.project.services

Class PasswordHasher

java.lang.Object
 com.example.project.services.PasswordHasher

```
public class PasswordHasher  
extends Object
```

Hashes passwords.

Constructor Summary

Constructors

Modifier

Constructor

Description

`PasswordEncoder()`

public constructor.

protected

`PasswordEncoder(Logger logger)`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

boolean

`doesPasswordMatch(String candidate, String hashed)`

Verifies a candidate password against a hashed password.

`String`

`hashPassword(String rawPassword)`

Hashes a raw password using BCrypt.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Details

PasswordEncoder

```
public PasswordHasher()
```

public constructor.

PasswordEncoder

```
protected PasswordHasher(Logger logger)
```

Method Details

hashPassword

```
public String2 hashPassword(String2 rawPassword)
```

Hashes a raw password using BCrypt.

Parameters:

rawPassword - the plain text password

Returns:

the hashed password string

doesPasswordMatch

```
public boolean doesPasswordMatch(String2 candidate,  
                                String2 hashed)
```

Verifies a candidate password against a hashed password.

Parameters:

candidate - the plain text password entered by the user

hashed - the hashed password stored in the database

Returns:

true if the password matches, false otherwise

Module com.example.project
Package com.example.project.services

Class PopupLoader

java.lang.Object
com.example.project.services.PopupLoader

```
public class PopupLoader  
extends Object
```

class to load the popup and initialize it with a controller

Constructor Summary

Constructors

Modifier

Constructor

Description

`PopupLoader()`

Constructor.

protected

`PopupLoader(FXMLLoader loader)`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

<C extends PopupController<P>, P extends PopupModel>

C

`createPopupController(P popupModel)`

create popup controller.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Details

PopupLoader

`protected PopupLoader(FXMLLoader loader)`

PopupLoader

`public PopupLoader()`

Constructor.

Method Details

createPopupController

```
public <C extends PopupController<P>,
      P extends PopupModel>
C createPopupController(P popupModel)
```

create popup controller.

Type Parameters:

C - class of popup controller.

P - class of popup.

Parameters:

popupModel - popup object.

Returns:

returns controller of the tile.

Module com.example.project
Package com.example.project.services

Class SVGIcons

java.lang.Object[✉]
 com.example.project.services.SVGIcons

```
public class SVGIcons  
extends Object✉
```

a static class to hold some icons for the application.

Constructor Summary

Constructors

Constructor

Description

SVGIcons()

Method Summary

All Methods

Static Methods

Concrete Methods

Modifier and Type

Method

Description

static javafx.scene.shape.SVGPath

getCogIcon()

gets a cog icon.

Methods inherited from class java.lang.Object[✉]

clone[✉], equals[✉], finalize[✉], getClass[✉], hashCode[✉], notify[✉], notifyAll[✉], toString[✉], wait[✉], wait[✉], wait[✉]

Constructor Details

SVGIcons

```
public SVGIcons()
```

Method Details

getCogIcon

```
public static javafx.scene.shape.SVGPath getCogIcon()
```

gets a cog icon.

Returns:

icon SVG.

Module com.example.project

Package com.example.project.controllers.gameScreens

Class SidebarController

java.lang.Object
com.example.project.controllers.gameScreens.SidebarController

```
public class SidebarController  
extends Object
```

The sidebar on shop and level with the current round info.

Constructor Summary

Constructors

Constructor

Description

SidebarController()

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

bindPersistentInfo()

Binds things used in multiple screens, money, redraws plays.

javafx.scene.control.Label

getComboLabel()

Returns combo label.

javafx.scene.control.Label

getCurrentScoreLabel()

current score label.

javafx.scene.control.Label

getMultiplierLabel()

word score multiplier label.

javafx.scene.control.Label

getRawPointsLabel()

raw points label to be multiplied by multiplier.

void

onlyShopShopInfo()

Only show things relevant to upgrades or the shop.

void

setupProperties(LevelModel levelModel)

Setup sync able properties.

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructor Details

SidebarController

```
public SidebarController()
```

Method Details

bindPersistentInfo

```
public void bindPersistentInfo()
```

Binds things used in multiple screens, money, redraws plays.

onlyShopShopInfo

```
public void onlyShopShopInfo()
```

Only show things relevant to upgrades or the shop. Money, redraws, plays.

getComboLabel

```
public javafx.scene.control.Label getComboLabel()
```

Returns combo label.

Returns:

combo label.

setupProperties

```
public void setupProperties(LevelModel levelModel)
```

Setup sync able properties.

Parameters:

levelModel - level model.

getRawPointsLabel

```
public javafx.scene.control.Label getRawPointsLabel()
```

raw points label to be multiplied by multiplier.

Returns:

label.

getCurrentScoreLabel

```
public javafx.scene.control.Label getCurrentScoreLabel()
```

current score label.

Returns:

label.

getmultiplierLabel

```
public javafx.scene.control.Label getmultiplierLabel()
```

word score multiplier label.

Returns:

label.

Module com.example.project
Package com.example.project.services

Class SceneManager

java.lang.Object[↳]
 com.example.project.services.SceneManager

```
public class SceneManager  
extends Object↳
```

Represents the scene manager class.

Constructor Summary

Constructors

Modifier

Constructor

Description

SceneManager(SceneManager newInstance)

Constructor to inject an instance.

protected

SceneManager(SceneManager newInstance, RootLayoutController newRootController, Map<GameScenes, GameScreenController> controllersToUse, Map<GameScenes, javafx.scene.Parent> pagesToUse)

Constructor with injection for tests

Method Summary

All Methods

Static Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

static SceneManager

getInstance()

void

initialise(RootLayoutController theRootController, PageLoader loader)

loads the fxml of all the scenes on launch to switch to via scene manaager.

void

switchScene(GameScenes type)

Switch between scenes specifiy scene type of type from GameScenes.

Methods inherited from class java.lang.Object[↳]

clone[↳], equals[↳], finalize[↳], getClass[↳], hashCode[↳], notify[↳], notifyAll[↳], toString[↳], wait[↳], wait[↳], wait[↳]

Constructor Details

SceneManager

public SceneManager(SceneManager newInstance)

Constructor to inject an instance.

Parameters:

newInstance - new instance.

SceneManager

```
protected SceneManager(SceneManager newInstance,  
                      RootLayoutController newRootController,  
                      Map<GameScenes, GameScreenController> controllersToUse,  
                      Map<GameScenes, javafx.scene.Parent> pagesToUse)
```

Constructor with injection for tests

Parameters:

newInstance - instance

newRootController - root controller

controllersToUse - controllers

pagesToUse - pages

Method Details

getInstance

```
public static SceneManager getInstance()
```

Returns:

Gets the programs Scene Manager instance.

initialise

```
public void initialise(RootLayoutController theRootController,  
                      PageLoader loader)
```

loads the fxml of all the scenes on launch to switch to via scene manager.

Parameters:

theRootController - the root Controller for the rootLayout scene.

loader - FXMLLoader

switchScene

```
public void switchScene(GameScenes type)
```

Switch between scenes specify scene type of type from GameScenes.

Parameters:

type - scene.

Module com.example.project
Package com.example.project.services

Class Session

java.lang.Object[↳]
 com.example.project.services.Session

```
public class Session  
extends Object↳
```

Game Session. holds info of the current session.

Constructor Summary

Constructors

Modifier

Constructor

Description

Session()

Default constructor.

protected

**Session(int newHandSize, int newWordViewSize, int newRedrawWindowSize,
javafx.collections.ObservableList<UpgradeTileModel> newUpgrades, User newUser, int newMoney,
int newLevelsBeaten, int currentLevelRequirement, int newFirstLevelsRequirement, int newInitialMoney)**

Constructor for injecting values in for unit test.

Method Summary

All Methods

Static Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

addMoney(int amount)

Adds money to the player's balance.

void

addUpgrade(UpgradeTileModel upgrade)

Adds an upgrade tile to the player's collection.

javafx.beans.property.ReadOnlyIntegerWrapper

getCurrentPlays()

gets the current plays.

javafx.beans.property.ReadOnlyIntegerWrapper

getCurrentRedraws()

gets the redraws property.

int

getHandSize()

gets hand size.

static Session

getInstance()

Gets session.

LocalDate²

getLastRewardDate()

Gets the last date the player claimed their daily reward.

LevelModel

getLevelModel()

javafx.beans.property.ReadOnlyIntegerWrapper

getLevelRequirement()

protected int

getLevelsBeaten()

javafx.beans.property.IntegerProperty

getMoneyProperty()

Returns the read-only money property for binding to UI components.

Integer²

getRedrawWindowSize()

gets redraw window size (number of slots)

javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel>

getUpgradeTilesProperty()

gets upgrade tile property

int

getWordWindowSize()

gets word size.

boolean

hasClaimedRewardToday()

Checks if the player already claimed today's reward.

void

resetGame()

Resets the current session when you lose

void

resetMoney()

Resets the player's money to the initial state (e.g.

void

resetPlaysRedraws()

Reset the plays and redraws.

void

setLastRewardDate(LocalDate² date)

Sets the date the daily reward was last claimed.

void

setLevelModel(LevelModel levelModel)

sets the session's level model

void

setUser(User newUser)

set new user.

boolean

spendMoney(int amount)

This attempts to spend the specified amount of money from the player's account.

void

updateLevelInfo()

Increments how many points are required to beat the level.

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructor Details

Session

```
protected Session(int newHandSize,  
                 int newWordViewSize,  
                 int newRedrawWindowSize,  
                 javafx.collections.ObservableList<UpgradeTileModel> newUpgrades,  
                 User newUser,  
                 int newMoney,  
                 int newLevelsBeaten,  
                 int currentLevelRequirement,  
                 int newFirstLevelsRequirement,  
                 int newInitialMoney)
```

Constructor for injecting values in for unit test.

Parameters:

newHandSize - hand size.

newWordViewSize - word length allowed.

newRedrawWindowSize - redraw window size.

newUpgrades - upgrade tiles.

newUser - user.

newMoney - money.

newLevelsBeaten - levels beaten.

currentLevelRequirement - current level requirement.

newFirstLevelsRequirement - first level requirement.

Session

```
public Session()
```

Default constructor.

Method Details

getLastRewardDate

```
public LocalDate getLastRewardDate()
```

Gets the last date the player claimed their daily reward.

Returns:

the date the reward was last claimed, or null if never claimed

getInstance

```
public static Session getInstance()
```

Gets session.

Returns:

session instance.

getLevelRequirement

```
public javafx.beans.property.ReadOnlyIntegerWrapper getLevelRequirement()
```

Returns:

points required for the play to score at least to beat the level.

getLevelsBeaten

```
protected int getLevelsBeaten()
```

setLevelModel

```
public void setLevelModel(LevelModel levelModel)
```

sets the session's level model

Parameters:

levelModel - the current level model

getLevelModel

```
public LevelModel getLevelModel()
```

Returns:

the current level model

getMoneyProperty

```
public javafx.beans.property.IntegerProperty getMoneyProperty()
```

Returns the read-only money property for binding to UI components. This allows UI elements to automatically update when the players money changes.

Returns:

ReadOnlyIntegerProperty representing the player's current money amount

addUpgrade

```
public void addUpgrade(UpgradeTileModel upgrade)
```

Adds an upgrade tile to the player's collection. This will automatically update all UI displays bound to the upgrades property.

Parameters:

upgrade - this upgrades the tile to add it to the players collection

spendMoney

```
public boolean spendMoney(int amount)
```

This attempts to spend the specified amount of money from the player's account. This operation should only succeed if the player has enough money.

Parameters:

amount - the amount of money to spend (cannot be negative)

Returns:

true if the transaction was successful (player had enough money), false if the player is a brokey

Throws:

IllegalArgumentException⁴ - if the amount is negative

setUser

```
public void setUser(User newUser)
```

set new user.

Parameters:

newUser - user that logged in.

getHandSize

```
public int getHandSize()
```

gets hand size.

Returns:

returns number of tiles allowed in hand.

getWordWindowSize

```
public int getWordWindowSize()
```

gets word size.

Returns:

return int word size.

getUpgradeTilesProperty

```
public javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> getUpgradeTilesProperty()
```

gets upgrade tile property

Returns:

upgrade tiles model list

updateLevelInfo

```
public void updateLevelInfo()
```

Increments how many points are required to beat the level.

resetGame

```
public void resetGame()
```

Resets the current session when you lose

getRedrawWindowSize

```
public Integer5 getRedrawWindowSize()
```

gets redraw window size (number of slots)

Returns:

return int redraw window size.

getCurrentPlays

```
public javafx.beans.property.ReadOnlyIntegerWrapper getCurrentPlays()
```

gets the current plays.

Returns:

current plays remaining.

getCurrentRedraws

```
public javafx.beans.property.ReadOnlyIntegerWrapper getCurrentRedraws()  
gets the redraws property.
```

Returns:

the current redraws.

resetPlaysRedraws

```
public void resetPlaysRedraws()  
Reset the plays and redraws.
```

addMoney

```
public void addMoney(int amount)  
Adds money to the player's balance.
```

Parameters:

amount - amount to add

setLastRewardDate

```
public void setLastRewardDate(LocalDate2 date)  
Sets the date the daily reward was last claimed.
```

Parameters:

date - LocalDate of the reward claim

hasClaimedRewardToday

```
public boolean hasClaimedRewardToday()  
Checks if the player already claimed today's reward.  
  
Returns:  
true if already claimed today
```

resetMoney

```
public void resetMoney()  
Resets the player's money to the initial state (e.g. 0).
```

Uses of Class com.example.project.services.FXMLPageLoader

Packages that use FXMLPageLoader

Package

Description

com.example.project.controllers.tiles

com.example.project.services

Uses of FXMLPageLoader in com.example.project.controllers.tiles

Constructors in com.example.project.controllers.tiles with parameters of type FXMLPageLoader

Modifier

Constructor

Description

protected

`TileControllerFactory(FXMLPageLoader loader)`

Uses of FXMLPageLoader in com.example.project.services

Constructors in com.example.project.services with parameters of type FXMLPageLoader

Modifier

Constructor

Description

protected

`PopupLoader(FXMLPageLoader loader)`

Uses of Enum Class

com.example.project.services.GameScenes

Packages that use GameScenes

Package

Description

com.example.project.services

Uses of GameScenes in com.example.project.services

Methods in com.example.project.services that return GameScenes

Modifier and Type

Method

Description

static GameScenes

GameScenes.valueOf(String² name)

Returns the enum constant of this class with the specified name.

static GameScenes[]

GameScenes.values()

Returns an array containing the constants of this enum class, in the order they are declared.

Methods in com.example.project.services with parameters of type GameScenes

Modifier and Type

Method

Description

void

SceneManager.switchScene(GameScenes type)

Switch between scenes specify scene type of type from GameScenes.

Constructor parameters in com.example.project.services with type arguments of type GameScenes

Modifier

Constructor

Description

protected

SceneManager(SceneManager newInstance, RootLayoutController newRootController, Map²<GameScenes, GameScreenController> controllersToUse, Map²<GameScenes, javafx.scene.Parent> pagesToUse)

Constructor with injection for tests

Uses of Class com.example.project.services.Logger

Packages that use Logger

Package

Description

com.example.project.controllers.gameScreens

com.example.project.models.gameScreens

com.example.project.services

com.example.project.services.sound

com.example.project.services.sqlite.dAOs

Uses of Logger in com.example.project.controllers.gameScreens

Fields in com.example.project.controllers.gameScreens declared as Logger

Modifier and Type

Field

Description

protected `Logger`

`GameScreenController.logger`

Constructors in com.example.project.controllers.gameScreens with parameters of type Logger

Modifier

Constructor

Description

protected

`ShopController(ShopModel model, UpgradeTileGroup players, UpgradeTileGroup shopItems, Logger logger)`

protected constructor for unit testing with mock model injection.

Uses of Logger in com.example.project.models.gameScreens

Fields in com.example.project.models.gameScreens declared as Logger

Modifier and Type

Field

Description

protected `Logger`

`GameScreenModel.logger`

Constructors in com.example.project.models.gameScreens with parameters of type Logger

Modifier

Constructor

Description

protected
`LevelModel(Session session, Logger logger)`

protected
`ShopModel(Session session, Logger logger)`
Constructor for tests.

Uses of `Logger` in `com.example.project.services`

Constructors in `com.example.project.services` with parameters of type `Logger`

Modifier

Constructor

Description

protected
`PasswordHasher(Logger logger)`

Uses of `Logger` in `com.example.project.services.sound`

Constructors in `com.example.project.services.sound` with parameters of type `Logger`

Modifier

Constructor

Description

protected
`GameSoundPlayer(String filePath, Logger logger)`

protected
`GameSoundPlayer(String filePath, Logger logger, float gainAmount)`

Uses of `Logger` in `com.example.project.services.sqlite.dAOs`

Constructors in `com.example.project.services.sqlite.dAOs` with parameters of type `Logger`

Modifier

Constructor

Description

`DictionaryDAO(Connection connection, Logger logger)`
constructor with injection for tests.

protected
`UsersDAO(PasswordHasher hasher, Connection connection, Logger logger)`

`UsersDAO(Connection connection, Logger logger)`
Constructor with injection for unit tests.

Uses of Interface com.example.project.services.PageLoader

Packages that use PageLoader

Package

Description

com.example.project.services

Uses of PageLoader in com.example.project.services

Classes in com.example.project.services that implement PageLoader

Modifier and Type

Class

Description

class

FXMLPageLoader

FXML Loader wrapper class for the project to load the game screen FXML pages.

Methods in com.example.project.services with parameters of type PageLoader

Modifier and Type

Method

Description

void

SceneManager.initialise(RootLayoutController theRootController, PageLoader loader)

loads the fxml of all the scenes on launch to switch to via scene manaager.

Uses of Class com.example.project.services.PasswordHasher

Packages that use PasswordHasher

Package

Description

com.example.project.models.gameScreens

com.example.project.services.sqlite.dAOs

Uses of PasswordHasher in com.example.project.models.gameScreens

Constructors in com.example.project.models.gameScreens with parameters of type PasswordHasher

Modifier

Constructor

Description

`LoginModel(Session session, UsersDAO dao, PasswordHasher passwordHasher)`

constructor.

Uses of PasswordHasher in com.example.project.services.sqlite.dAOs

Constructors in com.example.project.services.sqlite.dAOs with parameters of type PasswordHasher

Modifier

Constructor

Description

protected

`UsersDAO(PasswordHasher hasher, Connection✉ connection, Logger logger)`

Uses of Class com.example.project.services.PopupLoader

No usage of com.example.project.services.PopupLoader

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.services.SVGIcons

No usage of com.example.project.services.SVGIcons

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.services.SceneManager

Packages that use SceneManager

Package

Description

com.example.project.services

Uses of SceneManager in com.example.project.services

Methods in com.example.project.services that return SceneManager

Modifier and Type

Method

Description

static SceneManager

SceneManager.getInstance()

Constructors in com.example.project.services with parameters of type SceneManager

Modifier

Constructor

Description

SceneManager(SceneManager newInstance)

Constructor to inject an instance.

protected

SceneManager(SceneManager newInstance, RootLayoutController newRootController, Map<GameScenes, GameScreenController> controllersToUse, Map<GameScenes, javafx.scene.Parent> pagesToUse)

Constructor with injection for tests

Module com.example.project

Package com.example.project.controllers.gameScreens.animations

Class AnimationWrapper

java.lang.Object[↳]
com.example.project.controllers.gameScreens.animations.AnimationWrapper

Direct Known Subclasses:

LevelScoreSequence, TextEmphasisAnimation

```
public abstract class AnimationWrapper  
extends Object↳
```

Animation wrapper class for our projects animations that get used.

Field Summary

Fields

Modifier and Type

Field

Description

protected final javafx.animation.SequentialTransition

sequentialAnimation

Constructor Summary

Constructors

Modifier

Constructor

Description

protected

AnimationWrapper()

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

javafx.collections.ObservableList<javafx.animation.Animation>

getChildren()

returns animations children.

void

play()

play.

void

setOnFinished(javafx.event.EventHandler<javafx.event.ActionEvent> handler)

Set on finished.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Details

sequentialAnimation

```
protected final javafx.animation.SequentialTransition sequentialAnimation
```

Constructor Details

AnimationWrapper

```
protected AnimationWrapper()
```

Method Details

play

```
public void play()
```

play.

setOnFinished

```
public void setOnFinished(javafx.event.EventHandler<javafx.event.ActionEvent> handler)
```

Set on finished.

Parameters:

handler - actions to do.

getChildren

```
public javafx.collections.ObservableList<javafx.animation.Animation> getChildren()
```

returns animations children.

Returns:

list of animations.

Uses of Class com.example.project.services.Session

Packages that use Session

Package

Description

com.example.project.models.gameScreens

com.example.project.services

Uses of Session in com.example.project.models.gameScreens

Fields in com.example.project.models.gameScreens declared as Session

Modifier and Type

Field

Description

protected final Session

GameScreenModel.session

Constructors in com.example.project.models.gameScreens with parameters of type Session

Modifier

Constructor

Description

protected

GameScreenModel(Session session)

LevelModel(Session session)

Default constructor.

protected

LevelModel(Session session, Logger logger)

LoginModel(Session session, UsersDAO dao, PasswordHasher passwordHasher)

constructor.

MainMenuModel(Session session)

constructor.

ShopModel(Session session)

Constructor

protected

ShopModel(Session session, Logger logger)

Constructor for tests.

Uses of Session in com.example.project.services

Methods in com.example.project.services that return Session

Modifier and Type

Method

Description

static Session

Session.getInstance()

Gets session.

Package com.example.project.services

package com.example.project.services

Related Packages

Package

Description

[com.example.project](#)

[com.example.project.services.shopItems](#)

[com.example.project.services.sound](#)

[com.example.project.services.sqlite](#)

[com.example.project.controllers](#)

[com.example.project.models](#)

All Classes and Interfaces

Interfaces

Classes

Enum Classes

Class

Description

FXMLPageLoader

FXML Loader wrapper class for the project to load the game screen FXML pages.

GameScenes

Game Scenes enum.

Logger

com.example.project.services.Logger for Application and to show up in test and build CI workflow.

PageLoader

Interface for page loading.

PasswordHasher

Hashes passwords.

PopupLoader

class to load the popup and initialize it with a controller

SceneManager

Represents the scene manager class.

Session

Game Session.

SVGIcons

a static class to hold some icons for the application.

Hierarchy For Package com.example.project.services

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#) ↗
 - [com.example.project.services.FXMLPageLoader](#) (implements [com.example.project.services.PageLoader](#))
 - [com.example.project.services.Logger](#)
 - [com.example.project.services.PasswordHasher](#)
 - [com.example.project.services.PopupLoader](#)
 - [com.example.project.services.SceneManager](#)
 - [com.example.project.services.Session](#)
 - [com.example.project.services.SVGIcons](#)

Interface Hierarchy

- [com.example.project.services.PageLoader](#)

Enum Class Hierarchy

- [java.lang.Object](#) ↗
 - [java.lang.Enum](#) ↗<E> (implements [java.lang.Comparable](#) ↗<T>, [java.lang.constant.Constable](#) ↗, [java.io.Serializable](#) ↗)
 - [com.example.project.services.GameScenes](#)

Uses of Package com.example.project.services

Packages that use com.example.project.services

Package	Description
com.example.project.controllers.gameScreens	
com.example.project.controllers.tiles	
com.example.project.models.gameScreens	
com.example.project.services	
com.example.project.services.sound	
com.example.project.services.sqlite.dAOs	

Classes in com.example.project.services used by com.example.project.controllers.gameScreens

Class	Description
Logger	com.example.project.services.Logger for Application and to show up in test and build CI workflow.

Classes in com.example.project.services used by com.example.project.controllers.tiles

Class	Description
FXMLPageLoader	FXML Loader wrapper class for the project to load the game screen FXML pages.

Classes in com.example.project.services used by com.example.project.models.gameScreens

Class	Description
Logger	com.example.project.services.Logger for Application and to show up in test and build CI workflow.
PasswordHasher	Hashes passwords.
Session	Game Session.

Classes in com.example.project.services used by com.example.project.services

Class	Description
FXMLPageLoader	FXML Loader wrapper class for the project to load the game screen FXML pages.
GameScenes	

Game Scenes enum.

Logger

com.example.project.services.Logger for Application and to show up in test and build CI workflow.

PageLoader

Interface for page loading.

SceneManager

Represents the scene manager class.

Session

Game Session.

Classes in com.example.project.services used by com.example.project.services.sound

Class

Description

Logger

com.example.project.services.Logger for Application and to show up in test and build CI workflow.

Classes in com.example.project.services used by com.example.project.services.sqlite.dAOs

Class

Description

Logger

com.example.project.services.Logger for Application and to show up in test and build CI workflow.

PasswordHasher

Hashes passwords.

Module com.example.project
Package com.example.project.services.shopItems

Class UpgradeTiles

java.lang.Object
 com.example.project.services.shopItems.UpgradeTiles

```
public class UpgradeTiles  
extends Object
```

Static class to store all the possible upgrade tiles available in the game.

Constructor Summary

Constructors

Constructor

Description

UpgradeTiles()

Method Summary

All Methods

Static Methods

Concrete Methods

Modifier and Type

Method

Description

static UpgradeTileModel

getRandomUpgradeTile()

Gets random upgrade tile.

static UpgradeTileModel

getTile(int index)

Gets the upgrade tile at index.

Methods inherited from class java.lang.Object

clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()

Constructor Details

UpgradeTiles

```
public UpgradeTiles()
```

Method Details

getRandomUpgradeTile

```
public static UpgradeTileModel getRandomUpgradeTile()
```

Gets random upgrade tile.

Returns:

returns upgrade tile.

getTile

```
public static UpgradeTileModel getTile(int index)
```

Gets the upgrade tile at index.

Parameters:

index - tile to get.

Returns:

an upgrade tile model.

Uses of Class com.example.project.services.shopItems.UpgradeTiles

No usage of com.example.project.services.shopItems.UpgradeTiles

Copyright © 2025. All rights reserved.

Module com.example.project

Package com.example.project.services.shopItems

package com.example.project.services.shopItems

Related Packages

Package

Description

[com.example.project.services](#)

[com.example.project.services.sound](#)

[com.example.project.services.sqlite](#)

Classes

Class

Description

[UpgradeTiles](#)

Static class to store all the possible upgrade tiles available in the game.

Copyright © 2025. All rights reserved.

Hierarchy For Package com.example.project.services.shopItems

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#) ↗
 - [com.example.project.services.shopItems.UpgradeTiles](#)

Copyright © 2025. All rights reserved.

Uses of Package com.example.project.services.shopItems

No usage of com.example.project.services.shopItems

Copyright © 2025. All rights reserved.

Module com.example.project
Package com.example.project.services.sound

Class GameMusicPlayer

```
java.lang.Object
  com.example.project.services.sound.GameSoundPlayer
    com.example.project.services.sound.GameMusicPlayer
```

```
public class GameMusicPlayer
extends GameSoundPlayer
```

Plays the game music track on repeat.

Field Summary

Fields inherited from class com.example.project.services.sound.GameSoundPlayer

clip

Constructor Summary

Constructors

Constructor

Description

[GameMusicPlayer\(\)](#)

Create new instance of game music player.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

[playGameMusicLoop\(\)](#)

play game music loop continuously.

Methods inherited from class com.example.project.services.sound.GameSoundPlayer

[mute](#), [replay](#), [unMute](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructor Details

GameMusicPlayer

```
public GameMusicPlayer()
```

Create new instance of game music player.

Method Details

playGameMusicLoop

```
public void playGameMusicLoop()
```

play game music loop continuously.

Module com.example.project

Package com.example.project.controllers.gameScreens.animations

Class InfiniteFloatingAnimation

java.lang.Object
com.example.project.controllers.gameScreens.animations.InfiniteFloatingAnimation

```
public class InfiniteFloatingAnimation  
extends Object
```

Balatro style floating tile animation.

Constructor Summary

Constructors

Constructor

Description

`InfiniteFloatingAnimation()`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

`void`

`apply(javafx.scene.Node node, double intervalSeconds)`

apply to node.

Methods inherited from class java.lang.Object

`clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()`

Constructor Details

InfiniteFloatingAnimation

```
public InfiniteFloatingAnimation()
```

Method Details

apply

```
public void apply(javafx.scene.Node node,  
                  double intervalSeconds)
```

apply to node.

Parameters:

node - node.

intervalSeconds - time between changing directions.

Module com.example.project
Package com.example.project.services.sound

Class GameSoundPlayer

java.lang.Object
com.example.project.services.sound.GameSoundPlayer

Direct Known Subclasses:

GameMusicPlayer

```
public class GameSoundPlayer  
extends Object
```

plays an audio clip as a sound effect for the game.

Field Summary

Fields

Modifier and Type

Field

Description

```
protected final Clip
```

clip

Constructor Summary

Constructors

Modifier

Constructor

Description

```
GameSoundPlayer(String filePath)
```

creates a new instance of GameSoundPlayer

```
GameSoundPlayer(String filePath, float gainAmount)
```

creates a new instance of GameSoundPlayer

protected

```
GameSoundPlayer(String filePath, Logger logger)
```

protected

```
GameSoundPlayer(String filePath, Logger logger, float gainAmount)
```

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

```
mute()
```

set clip volume to mute.

```
void
```

```
replay()
```

Reset clip and then play.

```
void
```

```
unMute()
```

Set clip to its default volume.

Methods inherited from class `java.lang.Object`

```
clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()
```

Field Details

clip

```
protected final Clip clip
```

Constructor Details

GameSoundPlayer

```
public GameSoundPlayer(String filePath)
```

creates a new instance of GameSoundPlayer

Parameters:

filePath - filepath to sound.

GameSoundPlayer

```
protected GameSoundPlayer(String filePath,  
                           Logger logger)
```

GameSoundPlayer

```
protected GameSoundPlayer(String filePath,  
                           Logger logger,  
                           float gainAmount)
```

GameSoundPlayer

```
public GameSoundPlayer(String filePath,  
                           float gainAmount)
```

creates a new instance of GameSoundPlayer

Parameters:

filePath - filepath to sound.

gainAmount - volume to set the clip at

Method Details

replay

```
public void replay()
```

Reset clip and then play.

mute

```
public void mute()
```

set clip volume to mute.

unMute

```
public void unMute()
```

Set clip to its default volume.

Uses of Class com.example.project.services.sound.GameMusicPlayer

No usage of com.example.project.services.sound.GameMusicPlayer

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.services.sound.GameSoundPlayer

Packages that use GameSoundPlayer

Package

Description

com.example.project.models.popups

com.example.project.models.tiles

com.example.project.services.sound

Uses of GameSoundPlayer in com.example.project.models.popups

Fields in com.example.project.models.popups declared as GameSoundPlayer

Modifier and Type

Field

Description

protected final GameSoundPlayer

PopupModel.paperSoundPlayer

protected final GameSoundPlayer

PopupModel.reversePaperSoundPlayer

Methods in com.example.project.models.popups that return GameSoundPlayer

Modifier and Type

Method

Description

GameSoundPlayer

PopupModel.getPaperSoundPlayer()

gets paper sound player

GameSoundPlayer

PopupModel.getReversePaperSoundPlayer()

gets reversed paper sound player

Uses of GameSoundPlayer in com.example.project.models.tiles

Fields in com.example.project.models.tiles declared as GameSoundPlayer

Modifier and Type

Field

Description

protected final GameSoundPlayer

TileModel.clackSoundPlayer

protected final GameSoundPlayer

TileModel.hoverSoundPlayer

Methods in com.example.project.models.tiles that return GameSoundPlayer

Modifier and Type

Method

Description

GameSoundPlayer

TileModel.getClickSoundPlayer()

gets the sound player that plays the click sound.

GameSoundPlayer

TileModel.getHoverSoundPlayer()

gets the hover sound player

Uses of GameSoundPlayer in com.example.project.services.sound

Subclasses of GameSoundPlayer in com.example.project.services.sound

Modifier and Type

Class

Description

class

GameMusicPlayer

Plays the game music track on repeat.

Module com.example.project

Package com.example.project.services.sound

package com.example.project.services.sound

Related Packages

Package

Description

[com.example.project.services](#)

[com.example.project.services.shopItems](#)

[com.example.project.services.sqlite](#)

Classes

Class

Description

[GameMusicPlayer](#)

Plays the game music track on repeat.

[GameSoundPlayer](#)

plays an audio clip as a sound effect for the game.

Copyright © 2025. All rights reserved.

Hierarchy For Package com.example.project.services.sound

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#) ↗
 - [com.example.project.services.sound.GameSoundPlayer](#)
 - [com.example.project.services.sound.GameMusicPlayer](#)

Uses of Package com.example.project.services.sound

Packages that use com.example.project.services.sound

Package

Description

com.example.project.models.popups

com.example.project.models.tiles

com.example.project.services.sound

Classes in com.example.project.services.sound used by com.example.project.models.popups

Class

Description

GameSoundPlayer

plays an audio clip as a sound effect for the game.

Classes in com.example.project.services.sound used by com.example.project.models.tiles

Class

Description

GameSoundPlayer

plays an audio clip as a sound effect for the game.

Classes in com.example.project.services.sound used by com.example.project.services.sound

Class

Description

GameSoundPlayer

plays an audio clip as a sound effect for the game.

Module com.example.project
Package com.example.project.services.sqlite

Class SQLiteConnection

`java.lang.Object`
com.example.project.services.sqlite.SQLiteConnection

Direct Known Subclasses:

SQLiteDictionaryConnection, SQLiteUsersConnection

```
public abstract class SQLiteConnection
extends Object
```

Abstract SQLiteConnection class.

Constructor Summary

Constructors

Constructor

Description

`SQLiteConnection()`

Method Summary

All Methods

Instance Methods

Abstract Methods

Concrete Methods

Modifier and Type

Method

Description

`protected abstract String`

`getDatabasePath()`

Each subclass provides its database path.

`Connection`

`getInstance()`

Gets the database connection from an existing readonly resource .db

`protected abstract Connection`

`getSQLiteInstance()`

`protected abstract void`

`setSQLiteInstance(Connection newInstance)`

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Details

SQLiteConnection

`public SQLiteConnection()`

Method Details

getSQLLiteInstance

```
protected abstract Connection2 getSQLLiteInstance()
```

setSQLLiteInstance

```
protected abstract void setSQLLiteInstance(Connection2 newInstance)
```

getDatabasePath

```
protected abstract String2 getDatabasePath()
```

Each subclass provides its database path.

getInstance

```
public Connection2 getInstance()
```

Gets the database connection from an existing readonly resource .db

Returns:

returns the connection is already made or creates new one.

Module com.example.project
Package com.example.project.services.sqlite

Class SQLiteDictionaryConnection

java.lang.Object
 com.example.project.services.sqlite.SQLiteConnection
 com.example.project.services.sqlite.SQLiteDictionaryConnection

public class **SQLiteDictionaryConnection**
extends **SQLiteConnection**

Connection to the dictionary.db

Constructor Summary

Constructors

Constructor

Description

SQLiteDictionaryConnection()

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

protected String [getDatabasePath\(\)](#)

getSQLiteInstance()

Each subclass provides its database path.

protected Connection [getSQLiteInstance\(\)](#)

setSQLiteInstance(Connection newInstance)

Methods inherited from class com.example.project.services.sqlite.SQLiteConnection

getInstance()

Methods inherited from class java.lang.Object

clone(), **equals()**, **finalize()**, **getClass()**, **hashCode()**, **notify()**, **notifyAll()**, **toString()**, **wait()**, **wait()**, **wait()**

Constructor Details

SQLiteDictionaryConnection

public SQLiteDictionaryConnection()

Method Details

getSQLiteInstance

```
protected Connection2 getSQLiteInstance()
```

Specified by:

getSQLiteInstance in class [SQLiteConnection](#)

setSQLiteInstance

```
protected void setSQLiteInstance(Connection2 newInstance)
```

Specified by:

setSQLiteInstance in class [SQLiteConnection](#)

getDatabasePath

```
protected String2 getDatabasePath()
```

Description copied from class: [SQLiteConnection](#)

Each subclass provides its database path.

Specified by:

getDatabasePath in class [SQLiteConnection](#)

Module com.example.project

Package com.example.project.services.sqlite

Class SQLiteUsersConnection

```
java.lang.Object
    com.example.project.services.sqlite.SQLiteConnection
        com.example.project.services.sqlite.SQLiteUsersConnection
```

```
public class SQLiteUsersConnection
extends SQLiteConnection
```

Connection to the users.db

Constructor Summary

Constructors

Constructor

Description

`SQLiteUsersConnection()`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

`protected String`

`getDatabasePath()`

Each subclass provides its database path.

`protected Connection`

`getSQLiteInstance()`

`protected void`

`setSQLiteInstance(Connection`

Methods inherited from class com.example.project.services.sqlite.SQLiteConnection

`getInstance`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Details

SQLiteUsersConnection

```
public SQLiteUsersConnection()
```

Method Details

getSQLLiteInstance

```
protected Connection2 getSQLLiteInstance()
```

Specified by:

[getSQLLiteInstance](#) in class [SQLiteConnection](#)

setSQLLiteInstance

```
protected void setSQLLiteInstance(Connection2 newInstance)
```

Specified by:

[setSQLLiteInstance](#) in class [SQLiteConnection](#)

getDatabasePath

```
protected String2 getDatabasePath()
```

Description copied from class: [SQLiteConnection](#)

Each subclass provides its database path.

Specified by:

[getDatabasePath](#) in class [SQLiteConnection](#)

Uses of Class com.example.project.services.sqlite.SQLiteConnection

Packages that use `SQLiteConnection`

Package

Description

[com.example.project.services.sqlite](#)

Uses of `SQLiteConnection` in com.example.project.services.sqlite

Subclasses of `SQLiteConnection` in com.example.project.services.sqlite

Modifier and Type

Class

Description

class

[SQLiteDictionaryConnection](#)

Connection to the dictionary.db

class

[SQLiteUsersConnection](#)

Connection to the users.db

Module com.example.project

Package com.example.project.controllers.gameScreens.animations

Class LevelScoreSequence

```
java.lang.Object
    com.example.project.controllers.gameScreens.animations.AnimationWrapper
        com.example.project.controllers.gameScreens.animations.LevelScoreSequence
```

```
public class LevelScoreSequence
extends AnimationWrapper
```

Animates each level tile popping up and the score text increasing for every tile in the word row.

Field Summary

Fields inherited from

class com.example.project.controllers.gameScreens.animations.AnimationWrapper

sequentialAnimation

Constructor Summary

Constructors

Constructor

Description

LevelScoreSequence(List<LetterTileController> wordTileControllers, **LevelModel** levelModel, javafx.scene.control.Label comboCountLabel, javafx.scene.control.Label multiplierLabel)

Constructor.

Method Summary

Methods inherited from

class com.example.project.controllers.gameScreens.animations.AnimationWrapper

getChildren, play, setOnFinished

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

LevelScoreSequence

```
public LevelScoreSequence(List<LetterTileController> wordTileControllers,
                           LevelModel levelModel,
                           javafx.scene.control.Label comboCountLabel,
                           javafx.scene.control.Label multiplierLabel)
```

Constructor.

Parameters:

wordTileControllers - tiles to animate.

levelModel - level model.

comboCountLabel - the text label to add the sum to.

multiplierLabel - the text label to add the multi to.

Uses of Class

com.example.project.services.sqlite.SQLiteDictionaryConnection

No usage of com.example.project.services.sqlite.SQLiteDictionaryConnection

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.services.sqlite.SQLiteUsersConnection

No usage of com.example.project.services.sqlite.SQLiteUsersConnection

Copyright © 2025. All rights reserved.

Module com.example.project
Package com.example.project.services.sqlite.dAOs

Class DictionaryDAO

java.lang.Object
 com.example.project.services.sqlite.dAOs.DictionaryDAO

```
public class DictionaryDAO  
extends Object
```

The SQLite Dictionary. The connection returned from SQLiteDictionaryConnection().getInstance() is always the same.

Constructor Summary

Constructors

Constructor

Description

DictionaryDAO()

Constructor for this class SQLLiteDictionary.

DictionaryDAO(Connection² connection, Logger logger)

constructor with injection for tests.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

String²

getWordDefinition(String² wordToFind)

gets the words definition.

boolean

isWordInDictionary(String² wordToCheck)

gets if word is in dictionary.

Methods inherited from class java.lang.Object²

clone², equals², finalize², getClass², hashCode², notify², notifyAll², toString², wait², wait², wait²

Constructor Details

DictionaryDAO

```
public DictionaryDAO()
```

Constructor for this class SQLLiteDictionary.

DictionaryDAO

```
public DictionaryDAO(Connection2 connection,  
                      Logger logger)
```

constructor with injection for tests.

Parameters:

connection - mock connection.

logger - a mock logger.

Method Details

getWordDefinition

```
public String2 getWordDefinition(String2 wordToFind)
```

gets the words definition.

Parameters:

wordToFind - Word to get definition of.

Returns:

Returns the definition.

isWordInDictionary

```
public boolean isWordInDictionary(String2 wordToCheck)
```

gets if word is in dictionary.

Parameters:

wordToCheck - Word to check.

Returns:

returns the boolean value indicating whether the word exists in our database.

Module com.example.project
Package com.example.project.services.sqlite.dAOs

Class UsersDAO

java.lang.Object
 com.example.project.services.sqlite.dAOs.UsersDAO

```
public class UsersDAO  
extends Object
```

SQLite Users database. with a table `users` 2 columns. 'username', 'password'. Which are both defined as unique not null Strings in sqlite.

Constructor Summary

Constructors

Modifier

Constructor

Description

UsersDAO()

Constructor for this class SQLLiteDictionary.

protected

UsersDAO(PasswordHasher hasher, Connection connection, Logger logger)

UsersDAO(Connection connection, Logger logger)

Constructor with injection for unit tests.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

addUser(User user)

Adds user to the user.db.

boolean

doesUserExist(String username)

User

getUser(String username)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait

Constructor Details

UsersDAO

```
public UsersDAO()
```

Constructor for this class SQLiteDictionary.

UsersDAO

```
protected UsersDAO(PasswordHasher hasher,  
                  Connection✉ connection,  
                  Logger logger)
```

UsersDAO

```
public UsersDAO(Connection✉ connection,  
                  Logger logger)
```

Constructor with injection for unit tests.

Parameters:

connection - Connection

logger - logger.

Method Details

addUser

```
public void addUser(User user)
```

Adds user to the user.db. password will be hashed before storing to ensure greater security (no plain text passwords)

Parameters:

user - user to add.

doesUserExist

```
public boolean doesUserExist(String✉ username)
```

Parameters:

username - username

Returns:

returns bool indicating whether use is in database already.

getUser

```
public User getUser(String✉ username)
```

Parameters:

username - username.

Returns:

returns user with matching username.

Uses of Class

com.example.project.services.sqlite.dAOs.DictionaryDAO

No usage of com.example.project.services.sqlite.dAOs.DictionaryDAO

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.services.sqlite.dAOs.UsersDAO

Packages that use UsersDAO

Package

Description

com.example.project.models.gameScreens

Uses of UsersDAO in com.example.project.models.gameScreens

Constructors in com.example.project.models.gameScreens with parameters of type UsersDAO

Modifier

Constructor

Description

`LoginModel(Session session, UsersDAO dao, PasswordHasher passwordHasher)`

constructor.

Module com.example.project

Package com.example.project.services.sqlite.dAOs

package com.example.project.services.sqlite.dAOs

Related Packages

Package

Description

com.example.project.services.sqlite

Classes

Class

Description

DictionaryDAO

The SQLite Dictionary.

UsersDAO

SQLite Users database.

Hierarchy For Package com.example.project.services.sqlite.dAOs

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#)
 - [com.example.project.services.sqlite.dAOs.DictionaryDAO](#)
 - [com.example.project.services.sqlite.dAOs.UsersDAO](#)

Uses of Package `com.example.project.services.sqlite.dAOs`

Packages that use `com.example.project.services.sqlite.dAOs`

Package

Description

`com.example.project.models.gameScreens`

Classes in `com.example.project.services.sqlite.dAOs` used by `com.example.project.models.gameScreens`

Class

Description

`UsersDAO`

SQLite Users database.

Module com.example.project

Package com.example.project.services.sqlite

package com.example.project.services.sqlite

Related Packages

Package

Description

[com.example.project.services](#)

[com.example.project.services.sqlite.dAOs](#)

[com.example.project.services.shopItems](#)

[com.example.project.services.sound](#)

Classes

Class

Description

[SQLiteConnection](#)

Abstract SQLiteConnection class.

[SQLiteDictionaryConnection](#)

Connection to the dictionary.db

[SQLiteUsersConnection](#)

Connection to the users.db

Copyright © 2025. All rights reserved.

Module com.example.project

Package com.example.project.controllers.gameScreens.animations

Class ScoreTimeline

java.lang.Object
com.example.project.controllers.gameScreens.animations.ScoreTimeline

```
public class ScoreTimeline  
extends Object
```

Class for total score counter animation

Constructor Summary

Constructors

Constructor

Description

`ScoreTimeline()`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

`javafx.animation.Timeline`

`animateTotalScore(int startScore, int endScore, javafx.scene.control.Label currentScoreLabel,
long totalDurationMillis)`

Methods inherited from class java.lang.Object

`clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()`

Constructor Details

ScoreTimeline

```
public ScoreTimeline()
```

Method Details

animateTotalScore

```
public javafx.animation.Timeline animateTotalScore(int startScore,  
                                                 int endScore,  
                                                 javafx.scene.control.Label currentScoreLabel,  
                                                 long totalDurationMillis)
```

Parameters:

`startScore` - int from current total score

`endScore` - int from calculated current score

`currentScoreLabel` - Label for total score

`totalDurationMillis` - total duration

Returns:

timeline of total score counter

Hierarchy For Package com.example.project.services.sqlite

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#)
- [com.example.project.services.sqlite.SQLiteConnection](#)
 - [com.example.project.services.sqlite.SQLiteDictionaryConnection](#)
 - [com.example.project.services.sqlite.SQLiteUsersConnection](#)

Uses of Package com.example.project.services.sqlite

Packages that use com.example.project.services.sqlite

Package

Description

com.example.project.services.sqlite

Classes in com.example.project.services.sqlite used by com.example.project.services.sqlite

Class

Description

SQLiteDatabase

Abstract SQLiteDatabase class.

Module com.example.project

module com.example.project

project dependencies.

Packages

Exports

Package

Description

[com.example.project](#)

[com.example.project.controllers](#)

[com.example.project.controllers.gameScreens](#)

[com.example.project.controllers.gameScreens.animations](#)

[com.example.project.controllers.popupControllers](#)

[com.example.project.controllers.tiles](#)

[com.example.project.models](#)

[com.example.project.models.gameScreens](#)

[com.example.project.models.popups](#)

[com.example.project.models.tileGroups](#)

[com.example.project.models.tiles](#)

[com.example.project.services](#)

[com.example.project.services.shopItems](#)

[com.example.project.services.sound](#)

[com.example.project.services.sqlite](#)

[com.example.project.services.sqlite.dAOs](#)

Constant Field Values

Contents

com.example.*

com.example.*

com.example.project.Application

Modifier and Type

Constant Field

Value

public static final int

HEIGHT

700

public static final String

TITLE

"WordPlay"

public static final int

WIDTH

1300

com.example.project.models.tiles.TileModel

Modifier and Type

Constant Field

Value

public static final int

CORNER_RADIUS

20

JavaDoc Help

- Navigation:
 - Search
- Kinds of Pages:
 - Module
 - Package
 - Class or Interface
 - Other Files
 - Use
 - Tree (Class Hierarchy)
 - Constant Field Values
 - All Packages
 - All Classes and Interfaces
 - Index

Navigation

Starting from the [Overview](#) page, you can browse the documentation using the links in each page, and in the navigation bar at the top of each page. The [Index](#) and [Search](#) box allow you to navigate to specific declarations and summary pages, including: [All Packages](#), [All Classes and Interfaces](#)

Search

You can search for definitions of modules, packages, types, fields, methods, system properties and other terms defined in the API. These items can be searched using part or all of the name, optionally using "camelCase" abbreviations, or multiple search terms separated by whitespace. Some examples:

- "j.l.obj" matches "java.lang.Object"
- "InpStr" matches "java.io.InputStream"
- "math exact long" matches "java.lang.Math.absExact(long)"

Refer to the [Javadoc Search Specification](#) for a full description of search features.

Kinds of Pages

The following sections describe the different kinds of pages in this collection.

Module

Each module has a page that contains a list of its packages, dependencies on other modules, and services, with a summary for each. These pages may contain the following categories:

- Packages
- Modules
- Services

Package

Each package has a page that contains a list of its classes and interfaces, with a summary for each. These pages may contain the following categories:

- Interfaces
- Classes
- Enum Classes
- Exception Classes
- Annotation Interfaces

Class or Interface

Each class, interface, nested class and nested interface has its own separate page. Each of these pages has three sections consisting of a declaration and description, member summary tables, and detailed member descriptions. Entries in each of these sections are omitted if they are empty or not applicable.

- Class Inheritance Diagram
- Direct Subclasses
- All Known Subinterfaces
- All Known Implementing Classes
- Class or Interface Declaration
- Class or Interface Description

- Nested Class Summary
- Enum Constant Summary
- Field Summary
- Property Summary
- Constructor Summary
- Method Summary
- Required Element Summary
- Optional Element Summary

- Enum Constant Details
- Field Details
- Property Details
- Constructor Details
- Method Details
- Element Details

Note: Annotation interfaces have required and optional elements, but not methods. Only enum classes have enum constants. The components of a record class are displayed as part of the declaration of the record class. Properties are a feature of JavaFX.

The summary entries are alphabetical, while the detailed descriptions are in the order they appear in the source code. This preserves the logical groupings established by the programmer.

Other Files

Packages and modules may contain pages with additional information related to the declarations nearby.

Use

Each documented package, class and interface has its own Use page. This page describes what packages, classes, methods, constructors and fields use any part of the given class or package. Given a class or interface A, its Use page includes subclasses of A, fields declared as A, methods that return A, and methods and constructors with parameters of type A. You can access this page by first going to the package, class or interface, then clicking on the USE link in the navigation bar.

Tree (Class Hierarchy)

There is a [Class Hierarchy](#) page for all packages, plus a hierarchy for each package. Each hierarchy page contains a list of classes and a list of interfaces. Classes are organized by inheritance structure starting with `java.lang.Object`. Interfaces do not inherit from `java.lang.Object`.

- When viewing the Overview page, clicking on TREE displays the hierarchy for all packages.
- When viewing a particular package, class or interface page, clicking on TREE displays the hierarchy for only that package.

Constant Field Values

The [Constant Field Values](#) page lists the static final fields and their values.

All Packages

The [All Packages](#) page contains an alphabetic index of all packages contained in the documentation.

All Classes and Interfaces

The [All Classes and Interfaces](#) page contains an alphabetic index of all classes and interfaces contained in the documentation, including annotation interfaces, enum classes, and record classes.

Index

The [Index](#) contains an alphabetic index of all classes, interfaces, constructors, methods, and fields in the documentation, as well as summary pages such as [All Packages](#), [All Classes and Interfaces](#).

This help file applies to API documentation generated by the standard doclet.

Index

A B C D E F G H I L M N O P R S T U V W

All Classes and Interfaces | All Packages | Constant Field Values

A

addMoney(int) - Method in class com.example.project.services.Session
 Adds money to the player's balance.

addTileToRack(LetterTileModel) - Method in class com.example.project.models.gameScreens.LevelModel

addTileToRedrawWindow(LetterTileModel) - Method in class com.example.project.models.gameScreens.LevelModel

addTileToWordWindow(LetterTileModel) - Method in class com.example.project.models.gameScreens.LevelModel

addToCombo(LetterTileModel) - Method in class com.example.project.models.gameScreens.LevelModel
 add combo sum and multiCombo

addUpgrade(UpgradeTileModel) - Method in class com.example.project.services.Session
 Adds an upgrade tile to the player's collection.

addUser(User) - Method in class com.example.project.services.sqlite.dAOs.UsersDAO
 Adds user to the user.db.

animateTotalScore(int, int, Label, long) - Method in class com.example.project.controllers.gameScreens.animations.ScoreTimeline

AnimationWrapper - Class in com.example.project.controllers.gameScreens.animations
 Animation wrapper class for our projects animations that get used.

AnimationWrapper() - Constructor for class com.example.project.controllers.gameScreens.animations.AnimationWrapper

Application - Class in com.example.project
 The entry point of the application.

Application() - Constructor for class com.example.project.Application

apply(Node, double) - Method in class com.example.project.controllers.gameScreens.animations.InfiniteFloatingAnimation
 apply to node.

applyReward(DailyRewardType) - Static method in class com.example.project.models.gameScreens.DailyRewardModel
 Applies the effect of the given reward to the session and marks it as claimed.

B

bind(EmptyTileSlotModel) - Method in class com.example.project.controllers.tiles.EmptyTileSlotController

bind(LetterTileModel) - Method in class com.example.project.controllers.tiles.LetterTileController

bind(UpgradeTileModel) - Method in class com.example.project.controllers.tiles.UpgradeTileController

bind(T) - Method in class com.example.project.controllers.tiles.TileController
 Binds tile to the controller as its model.

bindPersistentInfo() - Method in class com.example.project.controllers.gameScreens.SidebarController
 Binds things used in multiple screens, money, redraws plays.

braceletEffect() - Static method in class com.example.project.models.tiles.UpgradeEffects
 Add +1 to score multiplier for every consecutive letter alphabetical order.

build() - Method in class com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder
 build upgrade

buttonEffect() - Static method in class com.example.project.models.tiles.UpgradeEffects
 adds 5 to the word score for every x in the tile rack.

C

calcTotalWordScore() - Method in class com.example.project.models.gameScreens.LevelModel

canPurchase(UpgradeTileModel) - Method in class com.example.project.models.gameScreens.ShopModel
 Determines whether the player can afford to purchase the specified upgrade tile.

ClackSoundPlayer - Variable in class com.example.project.models.tiles.TileModel

clearLogs() - Method in class com.example.project.services.Logger
 Clears captured logs use in tests teardown.

clip - Variable in class com.example.project.services.sound.GameSoundPlayer

coinEffect() - Static method in class com.example.project.models.tiles.UpgradeEffects
 20% Chance the total word score is doubled

com.example.project - module com.example.project
 project dependencies.

com.example.project - package com.example.project

com.example.project.controllers - package com.example.project.controllers

com.example.project.controllers.gameScreens - package com.example.project.controllers.gameScreens
com.example.project.controllers.gameScreens.animations - package com.example.project.controllers.gameScreens.animations
com.example.project.controllers.popupControllers - package com.example.project.controllers.popupControllers
com.example.project.controllers.tiles - package com.example.project.controllers.tiles
com.example.project.models - package com.example.project.models
com.example.project.models.gameScreens - package com.example.project.models.gameScreens
com.example.project.models.popups - package com.example.project.models.popups
com.example.project.models.tileGroups - package com.example.project.models.tileGroups
com.example.project.models.tiles - package com.example.project.models.tiles
com.example.project.services - package com.example.project.services
com.example.project.services.shopItems - package com.example.project.services.shopItems
com.example.project.services.sound - package com.example.project.services.sound
com.example.project.services.sqlite - package com.example.project.services.sqlite
com.example.project.services.sqlite.dAOs - package com.example.project.services.sqlite.dAOs

container - Variable in class com.example.project.models.tileGroups.TileGroup

controller() - Method in record class com.example.project.controllers.gameScreens.GameScreenController.SidebarLoaded
Returns the value of the controller record component.

CORNER_RADIUS - Static variable in class com.example.project.models.tiles.TileModel
corner radius (rounded corners).

cost(double) - Method in class com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder
upgrade cost builder

createLetterTileController(LetterTileModel) - Method in class com.example.project.controllers.tiles.TileControllerFactory

createPopupController(P) - Method in class com.example.project.services.PopupLoader
create popup controller.

createTileController(T, Class<C>) - Method in class com.example.project.controllers.tiles.TileControllerFactory
Returns controller of type.

currentShopItemsProperty() - Method in class com.example.project.models.gameScreens.ShopModel
Current items in the shop row that you can buy.

D

DAILY_REWARD - Enum constant in enum class com.example.project.services.GameScenes
Daily Reward Spinner Screen.

Daily_Reward_Won_1Dollar - Enum constant in enum class com.example.project.models.gameScreens.DailyRewardType
Player wins \$1

Daily_Reward_Won_5Dollars - Enum constant in enum class com.example.project.models.gameScreens.DailyRewardType
Player wins \$5

Daily_Reward_Won_NOTHING - Enum constant in enum class com.example.project.models.gameScreens.DailyRewardType
Player wins nothing

DailyRewardController - Class in com.example.project.controllers.gameScreens
Controller for the daily reward popup screen.

DailyRewardController() - Constructor for class com.example.project.controllers.gameScreens.DailyRewardController

DailyRewardModel - Class in com.example.project.models.gameScreens
Model for handling daily reward logic and state.

DailyRewardModel() - Constructor for class com.example.project.models.gameScreens.DailyRewardModel

DailyRewardType - Enum Class in com.example.project.models.gameScreens
Enum representing the possible daily reward outcomes.

DefinitionController - Class in com.example.project.controllers.popupControllers
Controller for definition popup

DefinitionController() - Constructor for class com.example.project.controllers.popupControllers.DefinitionController

DefinitionPopup - Class in com.example.project.models.popups
Represents Definition window called when a word is played

DefinitionPopup() - Constructor for class com.example.project.models.popups.DefinitionPopup

definitionProperty() - Method in class com.example.project.models.popups.DefinitionPopup

description(String) - Method in class com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder
upgrade description builder

diceEffect() - Static method in class com.example.project.models.tiles.UpgradeEffects
Value is doubled for a random letter in the played word

DictionaryDAO - Class in com.example.project.services.sqlite.dAOs

The SQLite Dictionary.

DictionaryDAO() - Constructor for class com.example.project.services.sqlite.dAOs.DictionaryDAO

Constructor for this class SQLLiteDictionary.

DictionaryDAO(Connection, Logger) - Constructor for class com.example.project.services.sqlite.dAOs.DictionaryDAO

constructor with injection for tests.

doesPasswordMatch(String, String) - Method in class com.example.project.services.PasswordHasher

Verifies a candidate password against a hashed password.

doesUserExist(String) - Method in class com.example.project.services.sqlite.dAOs.UsersDAO

drawRandomTile() - Method in class com.example.project.models.tiles.ScrabbleTileProvider

E

EmptyTileSlotController - Class in com.example.project.controllers.tiles

Empty Tile controller for EmptyTile view.

EmptyTileSlotController() - Constructor for class com.example.project.controllers.tiles.EmptyTileSlotController

EmptyTileSlotModel - Class in com.example.project.models.tiles

An empty tile slot model.

EmptyTileSlotModel() - Constructor for class com.example.project.models.tiles.EmptyTileSlotModel

equals(Object) - Method in record class com.example.project.controllers.gameScreens.GameScreenController SidebarLoaded

Indicates whether some other object is "equal to" this one.

equals(Object) - Method in record class com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData

Indicates whether some other object is "equal to" this one.

F

frequency() - Method in record class com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData

Returns the value of the frequency record component.

FXMLPageLoader - Class in com.example.project.services

FXML Loader wrapper class for the project to load the game screen FXML pages.

FXMLPageLoader() - Constructor for class com.example.project.services.FXMLPageLoader

constructor.

G

GameMusicPlayer - Class in com.example.project.services.sound

Plays the game music track on repeat.

GameMusicPlayer() - Constructor for class com.example.project.services.sound.GameMusicPlayer

Create new instance of game music player.

GameScenes - Enum Class in com.example.project.services

Game Scenes enum.

GameScreenController - Class in com.example.project.controllers.gameScreens

Game screen controller that has some startup on screen thing todo.

GameScreenController() - Constructor for class com.example.project.controllers.gameScreens.GameScreenController

GameScreenController.SidebarLoaded - Record Class in com.example.project.controllers.gameScreens

GameScreenModel - Class in com.example.project.models.gameScreens

Game Screen Model.

GameScreenModel(Session) - Constructor for class com.example.project.models.gameScreens.GameScreenModel

GameSoundPlayer - Class in com.example.project.services.sound

plays an audio clip as a sound effect for the game.

GameSoundPlayer(String) - Constructor for class com.example.project.services.sound.GameSoundPlayer

creates a new instance of GameSoundPlayer

GameSoundPlayer(String, float) - Constructor for class com.example.project.services.sound.GameSoundPlayer

creates a new instance of GameSoundPlayer

GameSoundPlayer(String, Logger) - Constructor for class com.example.project.services.sound.GameSoundPlayer

GameSoundPlayer(String, Logger, float) - Constructor for class com.example.project.services.sound.GameSoundPlayer

getAbilityImagePath() - Method in class com.example.project.models.tiles.UpgradeTileModel

gets upgrade tile image path.

getChildren() - Method in class com.example.project.controllers.gameScreens.animations.AnimationWrapper

returns animations children.

getClickSoundPlayer() - Method in class com.example.project.models.tiles.TileModel

gets the sound player that plays the click sound.

getCogIcon() - Static method in class com.example.project.services.SVGIcons

gets a cog icon.

getComboLabel() - Method in class com.example.project.controllers.gameScreens.SidebarController

Returns combo label.

getController() - Method in class com.example.project.services.FXMLPageLoader

getController() - Method in interface com.example.project.services.PageLoader
Get the .fxml pages controller

getControllers() - Method in class com.example.project.models.tileGroups.TileGroup
Gets the groups tile controllers.

getCost() - Method in class com.example.project.models.tiles.UpgradeTileModel
gets the cost

getCurrentPlays() - Method in class com.example.project.services.Session
gets the current plays.

getCurrentRedraws() - Method in class com.example.project.services.Session
gets the redraws property.

getCurrentScoreLabel() - Method in class com.example.project.controllers.gameScreens.SidebarController
current score label.

getCurrentWord() - Method in class com.example.project.models.gameScreens.LevelModel
Gets the current word formed by tiles in the word area

getDatabasePath() - Method in class com.example.project.services.sqlite.SQLiteConnection
Each subclass provides its database path.

getDatabasePath() - Method in class com.example.project.services.sqlite.SQLiteDictionaryConnection

getDatabasePath() - Method in class com.example.project.services.sqlite.SQLiteUsersConnection

getDescription() - Method in class com.example.project.models.tiles.UpgradeTileModel
gets the description.

getErrorLogs() - Method in class com.example.project.services.Logger

getFXMLPath() - Method in class com.example.project.models.popups.DefinitionPopup

getFXMLPath() - Method in class com.example.project.models.popups.PopupModel
gets FXML path

getFXMLPath() - Method in class com.example.project.models.tiles.EmptyTileSlotModel

getFXMLPath() - Method in class com.example.project.models.tiles.LetterTileModel

getFXMLPath() - Method in class com.example.project.models.tiles.TileModel
gets the fxml path.

getFXMLPath() - Method in class com.example.project.models.tiles.UpgradeTileModel

getHandSize() - Method in class com.example.project.services.Session
gets hand size.

getHighscore() - Method in class com.example.project.models.User
get highscore.

getHoverSoundPlayer() - Method in class com.example.project.models.tiles.TileModel
gets the hover sound player

getInstance() - Static method in class com.example.project.services.SceneManager

getInstance() - Static method in class com.example.project.services.Session
Gets session.

getInstance() - Method in class com.example.project.services.sqlite.SQLiteConnection
Gets the database connection from an existing readonly resource .db

getIsDefinitionActive() - Method in class com.example.project.models.popups.DefinitionPopup

getIsRedrawActive() - Method in class com.example.project.models.gameScreens.LevelModel
gets the redraw property.

getLastRewardDate() - Method in class com.example.project.services.Session
Gets the last date the player claimed their daily reward.

getLetter() - Method in class com.example.project.models.tiles.LetterTileModel

getLevelModel() - Method in class com.example.project.services.Session

getLevelRequirement() - Method in class com.example.project.services.Session

getLevelsBeaten() - Method in class com.example.project.services.Session

getLogs() - Method in class com.example.project.services.Logger

getModel() - Method in class com.example.project.controllers.popupControllers.DefinitionController

getModel() - Method in class com.example.project.controllers.popupControllers.PopupController
gets the popup model.

getModel() - Method in class com.example.project.controllers.tiles.LetterTileController

getModel() - Method in class com.example.project.controllers.tiles.TileController
gets the tile model.

getMoneyProperty() - Method in class com.example.project.services.Session
Returns the read-only money property for binding to UI components.

getMultiplierLabel() - Method in class com.example.project.controllers.gameScreens.SidebarController
word score multiplier label.

getName() - Method in class com.example.project.models.tiles.UpgradeTileModel

gets the name.

getPaperSoundPlayer() - Method in class com.example.project.models.popups.PopupModel

 gets paper sound player

getPassword() - Method in class com.example.project.models.User

 get password.

getPlayersCurrentPoints() - Method in class com.example.project.models.gameScreens.LevelModel

getPlayersTotalPoints() - Method in class com.example.project.models.gameScreens.LevelModel

getRandomUpgradeTile() - Static method in class com.example.project.services.shopItems.UpgradeTiles

 Gets random upgrade tile.

getRawPointsLabel() - Method in class com.example.project.controllers.gameScreens.SidebarController

 raw points label to be multiplied by multiplier.

getRedrawWindowSize() - Method in class com.example.project.services.Session

 gets redraw window size (number of slots)

getRedrawWindowTilesProperty() - Method in class com.example.project.models.gameScreens.LevelModel

getReversePaperSoundPlayer() - Method in class com.example.project.models.popups.PopupModel

 gets reversed paper sound player

getRoot() - Method in class com.example.project.controllers.tiles.EmptyTileSlotController

getRoot() - Method in class com.example.project.controllers.tiles.LetterTileController

getRoot() - Method in class com.example.project.controllers.tiles.TileController

 root ui node.

getRoot() - Method in class com.example.project.controllers.tiles.UpgradeTileController

getSQLiteInstance() - Method in class com.example.project.services.sqlite.SQLiteConnection

getSQLiteInstance() - Method in class com.example.project.services.sqlite.SQLiteDictionaryConnection

getSQLiteInstance() - Method in class com.example.project.services.sqlite.SQLiteUsersConnection

getStack() - Method in class com.example.project.controllers.popupControllers.DefinitionController

getStack() - Method in class com.example.project.controllers.popupControllers.PopupController

 root ui node.

getTile() - Method in class com.example.project.models.tiles.EmptyTileSlotModel

 get letter tile in slot.

getTile(int) - Static method in class com.example.project.services.shopItems.UpgradeTiles

 Gets the upgrade tile at index.

getTileRackTilesProperty() - Method in class com.example.project.models.gameScreens.LevelModel

getTileScoreSoundPlayer() - Method in class com.example.project.models.gameScreens.LevelModel

 Gets the tile score sound effect player.

getUpgradeEffect() - Method in class com.example.project.models.tiles.UpgradeTileModel

 gets the effect for this tile.

getUpgradeTilesProperty() - Method in class com.example.project.services.Session

 gets upgrade tile property

getUser(String) - Method in class com.example.project.services.sqlite.dAOs.UsersDAO

getUsername() - Method in class com.example.project.models.User

 get username.

getValue() - Method in class com.example.project.models.tiles.LetterTileModel

getValue(Character) - Method in class com.example.project.models.tiles.ScrabbleTileProvider

 Returns Integer of the letter according to scrabble

getWelcomeTextProperty() - Method in class com.example.project.models.gameScreens.LoginModel

 Gets the info text property.

getWordDefinition(String) - Method in class com.example.project.services.sqlite.dAOs.DictionaryDAO

 gets the words definition.

getWordWindowSize() - Method in class com.example.project.services.Session

 gets word size.

getWordWindowTilesProperty() - Method in class com.example.project.models.gameScreens.LevelModel

glassesEffect() - Static method in class com.example.project.models.tiles.UpgradeEffects

 Adds +2 to the score multiplier for every identical pair of letters next to each other

H

hasClaimedRewardToday() - Method in class com.example.project.services.Session

 Checks if the player already claimed today's reward.

hashCode() - Method in record class com.example.project.controllers.gameScreens.GameScreenController SidebarLoaded

 Returns a hash code value for this object.

hashCode() - Method in record class com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData

 Returns a hash code value for this object.

hashPassword(String) - Method in class com.example.project.services.PasswordHasher

Hashes a raw password using BCrypt.

hasLost() - Method in class com.example.project.models.gameScreens.LevelModel
true if player has lost

hasWon() - Method in class com.example.project.models.gameScreens.LevelModel
returns true if player has won.

HEIGHT - Static variable in class com.example.project.Application

hoverSoundPlayer - Variable in class com.example.project.models.tiles.TileModel

I

imagePath(String) - Method in class com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder
upgrade image path builder

imageView - Variable in class com.example.project.controllers.tiles.UpgradeTileController

InfiniteFloatingAnimation - Class in com.example.project.controllers.gameScreens.animations
Balatro style floating tile animation.

InfiniteFloatingAnimation() - Constructor for class
com.example.project.controllers.gameScreens.animations.InfiniteFloatingAnimation

initialise(RootLayoutController, PageLoader) - Method in class com.example.project.services.SceneManager
loads the fxml of all the scenes on launch to switch to via scene manager.

initialize() - Method in class com.example.project.controllers.gameScreens.DailyRewardController
Initialises the daily reward view by resetting the reward label.

initialize() - Method in class com.example.project.controllers.gameScreens.LevelController

initialize() - Method in class com.example.project.controllers.gameScreens.LoginController
FXML initialise function called once when the .fxml is loaded on application launch.

initialize() - Method in class com.example.project.controllers.gameScreens.MainMenuController
FXML initialise function called once when the .fxml is loaded.

initialize() - Method in class com.example.project.controllers.gameScreens.ShopController
FXML initialise function called once when the .fxml is loaded on application launch.

initialize(DefinitionPopup) - Method in class com.example.project.controllers.popupControllers.DefinitionController

initialize(P) - Method in class com.example.project.controllers.popupControllers.PopupController
sets elements of the ui

isCurrentWordValid() - Method in class com.example.project.models.gameScreens.LevelModel
returns true if word is in dictionary.

isWordInDictionary(String) - Method in class com.example.project.services.sqlite.dAOs.DictionaryDAO
gets if word is in dictionary.

L

LetterTileController - Class in com.example.project.controllers.tiles
Controls the layout of the letterUIModel.

LetterTileController() - Constructor for class com.example.project.controllers.tiles.LetterTileController

LetterTileGroup - Class in com.example.project.models.tileGroups
tile group that observes an observable list and updates the ui Tile Controller's nodes into their EmptyTileSlotController nodes.

LetterTileGroup(int, Pane, ReadOnlyListProperty<LetterTileModel>, Consumer<LetterTileController>) - Constructor for
class com.example.project.models.tileGroups.LetterTileGroup
Constructor

LetterTileGroup(int, Pane, ReadOnlyListProperty<LetterTileModel>, Consumer<LetterTileController>, List<Runnable>) -
Constructor for class com.example.project.models.tileGroups.LetterTileGroup
Constructor

LetterTileGroup(int, Pane, ReadOnlyListProperty<LetterTileModel>, Consumer<LetterTileController>, List<Runnable>, TileControllerFactory) - Constructor for class com.example.project.models.tileGroups.LetterTileGroup

LetterTileModel - Class in com.example.project.models.tiles
Represents the letter tiles the player plays holds, redraws.

LetterTileModel(Character) - Constructor for class com.example.project.models.tiles.LetterTileModel

LEVEL - Enum constant in enum class com.example.project.services.GameScenes
level Screen

LevelController - Class in com.example.project.controllers.gameScreens
Controller for the level screen.

LevelController() - Constructor for class com.example.project.controllers.gameScreens.LevelController
Constructor only called once each time application opened.

LevelController(LevelModel) - Constructor for class com.example.project.controllers.gameScreens.LevelController

LevelModel - Class in com.example.project.models.gameScreens
Represents the level model.

LevelModel(Session) - Constructor for class com.example.project.models.gameScreens.LevelModel
Default constructor.

LevelModel(Session, Logger) - Constructor for class com.example.project.models.gameScreens.LevelModel

LevelScoreSequence - Class in com.example.project.controllers.gameScreens.animations

Animates each level tile popping up and the score text increasing for every tile in the word row.

LevelScoreSequence(List<LetterTileController>, LevelModel, Label, Label) - Constructor for class com.example.project.controllers.gameScreens.animations.LevelScoreSequence
Constructor.

load(String) - Method in class com.example.project.services.FXMLPageLoader

load(String) - Method in interface com.example.project.services.PageLoader

Load method to load fxml page.

loadSidebar() - Method in class com.example.project.controllers.gameScreens.GameScreenController

logError(String) - Method in class com.example.project.services.Logger

Logs an error message to standard error.

logger - Variable in class com.example.project.controllers.gameScreens.GameScreenController

logger - Variable in class com.example.project.models.gameScreens.GameScreenModel

Logger - Class in com.example.project.services

com.example.project.services.Logger for Application and to show up in test and build CI workflow.

Logger() - Constructor for class com.example.project.services.Logger
Default constructor writes to console does not capture.

Logger(ByteArrayOutputStream, ByteArrayOutputStream) - Constructor for class com.example.project.services.Logger
Constructor for unit tests.

Logger(ByteArrayOutputStream, ByteArrayOutputStream, PrintStream, PrintStream) - Constructor for class com.example.project.services.Logger
Constructor for unit tests.

LOGIN - Enum constant in enum class com.example.project.services.GameScenes
Login Screen.

LoginController - Class in com.example.project.controllers.gameScreens
Controller for the login scene.

LoginController() - Constructor for class com.example.project.controllers.gameScreens.LoginController
No arg constructor.

LoginModel - Class in com.example.project.models.gameScreens
Login model class.

LoginModel(Session, UsersDAO, PasswordHasher) - Constructor for class com.example.project.models.gameScreens.LoginModel
constructor.

logMessage(String) - Method in class com.example.project.services.Logger
Log message to System.out.

M

main(String[]) - Static method in class com.example.project.Application

MAINMENU - Enum constant in enum class com.example.project.services.GameScenes
Main Menu Screen.

MainMenuController - Class in com.example.project.controllers.gameScreens
controller for the main menu.

MainMenuController() - Constructor for class com.example.project.controllers.gameScreens.MainMenuController
No arg constructor.

MainMenuModel - Class in com.example.project.models.gameScreens
main menu model class

MainMenuModel(Session) - Constructor for class com.example.project.models.gameScreens.MainMenuModel
constructor.

mirrorEffect() - Static method in class com.example.project.models.tiles.UpgradeEffects
If played word is a palindrome, doubles word score.

model - Variable in class com.example.project.controllers.popupControllers.PopupController

model - Variable in class com.example.project.controllers.tiles.TileController

mute() - Method in class com.example.project.services.sound.GameSoundPlayer
set clip volume to mute.

N

name(String) - Method in class com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder
upgrade name builder

node() - Method in record class com.example.project.controllers.gameScreens.GameScreenController.SidebarLoaded
Returns the value of the node record component.

O

onClickAction - Variable in class com.example.project.models.tileGroups.TileGroup

onConfirmRedrawButton() - Method in class com.example.project.controllers.gameScreens.LevelController
Handle redraw confirm button.

onDailyRewardClicked() - Method in class com.example.project.controllers.gameScreens.MainMenuController

onFastForwardClick() - Method in class com.example.project.controllers.gameScreens.MainMenuController

onLoginButtonClick() - Method in class com.example.project.controllers.gameScreens.LoginController

onLoginClicked(String, String) - Method in class com.example.project.models.gameScreens.LoginModel

onLogoutButtonClick() - Method in class com.example.project.controllers.gameScreens.MainMenuController

onLogoutClicked() - Method in class com.example.project.models.gameScreens.MainMenuModel
switches to the login screen

onLostLevel() - Method in class com.example.project.models.gameScreens.LevelModel
Called when the level has been lost.

onlyShopShopInfo() - Method in class com.example.project.controllers.gameScreens.SidebarController
Only show things relevant to upgrades or the shop.

onNextLevelPressed() - Method in class com.example.project.controllers.gameScreens.ShopController

onNextLevelPressed() - Method in class com.example.project.models.gameScreens.ShopModel
exists shop and increments level requirement for the next level.

onPlayButton() - Method in class com.example.project.controllers.gameScreens.LevelController
Handle play button

onRedrawButton() - Method in class com.example.project.controllers.gameScreens.LevelController
redraw button opens or cancels the redraw.

onSceneChangedToThis() - Method in class com.example.project.controllers.gameScreens.DailyRewardController

onSceneChangedToThis() - Method in class com.example.project.controllers.gameScreens.GameScreenController
Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

onSceneChangedToThis() - Method in class com.example.project.controllers.gameScreens.LevelController

onSceneChangedToThis() - Method in class com.example.project.controllers.gameScreens.LoginController

onSceneChangedToThis() - Method in class com.example.project.controllers.gameScreens.MainMenuController

onSceneChangedToThis() - Method in class com.example.project.controllers.gameScreens.ShopController

onSignupButtonClick() - Method in class com.example.project.controllers.gameScreens.LoginController

onSignUpClicked(String, String) - Method in class com.example.project.models.gameScreens.LoginModel
Adds user to database.

onSkipButton() - Method in class com.example.project.controllers.gameScreens.LevelController

onStartButtonClick() - Method in class com.example.project.controllers.gameScreens.MainMenuController

onStartClicked() - Method in class com.example.project.models.gameScreens.MainMenuModel
switches to the level screen

onUpgradeClicked(UpgradeTileController) - Method in class com.example.project.controllers.gameScreens.ShopController

onWonLevel() - Method in class com.example.project.models.gameScreens.LevelModel
Called when level has been won.

P

PageLoader - Interface in com.example.project.services
Interface for page loading.

paperSoundPlayer - Variable in class com.example.project.models.popups.PopupModel

PasswordHasher - Class in com.example.project.services
Hashes passwords.

PasswordHasher() - Constructor for class com.example.project.services.PasswordHasher
public constructor.

PasswordHasher(Logger) - Constructor for class com.example.project.services.PasswordHasher

play() - Method in class com.example.project.controllers.gameScreens.animations.AnimationWrapper
play.

playersUpgradesProperty() - Method in class com.example.project.models.gameScreens.ShopModel
get what upgrades the player currently has.

playGameMusicLoop() - Method in class com.example.project.services.sound.GameMusicPlayer
play game music loop continuously.

playNextNote() - Method in class com.example.project.models.gameScreens.ScoreChimePlayer
plays the note then increments the int index.

playTiles() - Method in class com.example.project.models.gameScreens.LevelModel
clears the word row tiles.

PopupController<P> - Class in com.example.project.controllers.popupControllers
Parent class for PopupControllers

PopupController() - Constructor for class com.example.project.controllers.popupControllers.PopupController

PopupLoader - Class in com.example.project.services
class to load the popup and initialize it with a controller

PopupLoader() - Constructor for class com.example.project.services.PopupLoader
Constructor.

PopupLoader(FXMLLoader) - Constructor for class com.example.project.services.PopupLoader

PopupModel - Class in com.example.project.models.popups

Parent class for popup windows

PopupModel() - Constructor for class com.example.project.models.popups.PopupModel

purchase(UpgradeTileModel) - Method in class com.example.project.models.gameScreens.ShopModel

This should attempt to purchase an upgrade tile from the shop.

R

redrawTiles() - Method in class com.example.project.models.gameScreens.LevelModel

Redraws tiles into the tile rack and removes from redraw window.

regenerateShopItems() - Method in class com.example.project.models.gameScreens.ShopModel

Create new shop items.

replay() - Method in class com.example.project.services.sound.GameSoundPlayer

Reset clip and then play.

reset() - Method in class com.example.project.models.gameScreens.ScoreChimePlayer

Resets back to 0.

resetCombo() - Method in class com.example.project.models.gameScreens.LevelModel

Resets counts for sum and multi in combo

resetGame() - Method in class com.example.project.services.Session

Resets the current session when you lose

resetMoney() - Method in class com.example.project.services.Session

Resets the player's money to the initial state (e.g.

resetPlaysRedraws() - Method in class com.example.project.services.Session

Reset the plays and redraws.

returnRedrawTilesToTheRack() - Method in class com.example.project.models.gameScreens.LevelModel

Sends the selected redraw tiles back to the rack

reversePaperSoundPlayer - Variable in class com.example.project.models.popups.PopupModel

rollReward() - Static method in class com.example.project.models.gameScreens.DailyRewardModel

Randomly selects a daily reward.

root - Variable in class com.example.project.controllers.tiles.EmptyTileSlotController

root - Variable in class com.example.project.controllers.tiles.UpgradeTileController

RootLayoutController - Class in com.example.project.controllers

Root layout that remains the root scene of the application to switch scenes within.

RootLayoutController() - Constructor for class com.example.project.controllers.RootLayoutController

S

SceneManager - Class in com.example.project.services

Represents the scene manager class.

SceneManager(SceneManager) - Constructor for class com.example.project.services.SceneManager

Constructor to inject an instance.

SceneManager(SceneManager, RootLayoutController, Map<GameScenes, GameScreenController>, Map<GameScenes, Parent>) - Constructor for class com.example.project.services.SceneManager

Constructor with injection for tests

ScoreChimePlayer - Class in com.example.project.models.gameScreens

Plays a note from the F major scale ascending in pitch each time for a nice score combo sound.

ScoreChimePlayer() - Constructor for class com.example.project.models.gameScreens.ScoreChimePlayer

ScoreTimeline - Class in com.example.project.controllers.gameScreens.animations

Class for total score counter animation

ScoreTimeline() - Constructor for class com.example.project.controllers.gameScreens.animations.ScoreTimeline

ScrabbleTileData(int, int) - Constructor for record class com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData

Creates an instance of a ScrabbleTileData record class.

ScrabbleTileProvider - Class in com.example.project.models.tiles

Static class to store the scrabble base letter value.

ScrabbleTileProvider() - Constructor for class com.example.project.models.tiles.ScrabbleTileProvider

Constructor.

ScrabbleTileProvider.ScrabbleTileData - Record Class in com.example.project.models.tiles

seedRandomNumberGenerator(long) - Static method in class com.example.project.models.tiles.ScrabbleTileProvider

sequentialAnimation - Variable in class com.example.project.controllers.gameScreens.animations.AnimationWrapper

session - Variable in class com.example.project.models.gameScreens.GameScreenModel

Session - Class in com.example.project.services

Game Session.

Session() - Constructor for class com.example.project.services.Session

Default constructor.

Session(int, int, int, ObservableList<UpgradeTileModel>, User, int, int, int, int, int) - Constructor for class com.example.project.services.Session

Constructor for injecting values in for unit test.

setContent(Parent) - Method in class com.example.project.controllers.RootLayoutController

setIsDefinitionActive(boolean) - Method in class com.example.project.models.popups.DefinitionPopup
toggle isDefinitionActive

setIsRedrawActive(boolean) - Method in class com.example.project.models.gameScreens.LevelModel
set redraw active.

setLastRewardDate(LocalDate) - Method in class com.example.project.services.Session
Sets the date the daily reward was last claimed.

setLetter(LetterTileController) - Method in class com.example.project.controllers.tiles.EmptyTileSlotController
updates the tile slot with a new letter tile controller.

setLevelModel(LevelModel) - Method in class com.example.project.services.Session
sets the session's level model

setModel(T) - Method in class com.example.project.controllers.tiles.TileController
Set the model this controller will observe.

setOnFinished(EventHandler<ActionEvent>) - Method in class com.example.project.controllers.gameScreens.animations.AnimationWrapper
Set on finished.

setPlayersScore(int) - Method in class com.example.project.models.gameScreens.LevelModel

setPopup(String) - Method in class com.example.project.models.popups.DefinitionPopup

setPrintToConsole(boolean) - Method in class com.example.project.services.Logger

setSQLiteInstance(Connection) - Method in class com.example.project.services.sqlite.SQLiteConnection

setSQLiteInstance(Connection) - Method in class com.example.project.services.sqlite.SQLiteDictionaryConnection

setSQLiteInstance(Connection) - Method in class com.example.project.services.sqlite.SQLiteUsersConnection

setTile(LetterTileModel) - Method in class com.example.project.models.tiles.EmptyTileSlotModel
Set a new tile.

setTotalScore(int) - Method in class com.example.project.models.gameScreens.LevelModel

setupNewLevel() - Method in class com.example.project.models.gameScreens.LevelModel
Initialise new level.

setupProperties(LevelModel) - Method in class com.example.project.controllers.gameScreens.SidebarController
Setup sync able properties.

setUser(User) - Method in class com.example.project.services.Session
set new user.

setWordMulti(int) - Method in class com.example.project.models.gameScreens.LevelModel
sets the current word multiplier

setWordPoints(int) - Method in class com.example.project.models.gameScreens.LevelModel
sets the current word points before multipliers

SHOP - Enum constant in enum class com.example.project.services.GameScenes
Shop screen.

ShopController - Class in com.example.project.controllers.gameScreens
Shop view controller.

ShopController() - Constructor for class com.example.project.controllers.gameScreens.ShopController
no arg constructor.

ShopController(ShopModel, UpgradeTileGroup, UpgradeTileGroup, Logger) - Constructor for class com.example.project.controllers.gameScreens.ShopController
protected constructor for unit testing with mock model injection.

ShopModel - Class in com.example.project.models.gameScreens
Shop Model.

ShopModel(Session) - Constructor for class com.example.project.models.gameScreens.ShopModel
Constructor

ShopModel(Session, Logger) - Constructor for class com.example.project.models.gameScreens.ShopModel
Constructor for tests.

SidebarController - Class in com.example.project.controllers.gameScreens
The sidebar on shop and level with the current round info.

SidebarController() - Constructor for class com.example.project.controllers.gameScreens.SidebarController

SidebarLoaded(Parent, SidebarController) - Constructor for record class com.example.project.controllers.gameScreens.GameScreenController.SideBarLoaded
Creates an instance of a SidebarLoaded record class.

slotForLetterTile - Variable in class com.example.project.controllers.tiles.EmptyTileSlotController

spendMoney(int) - Method in class com.example.project.services.Session
This attempts to spend the specified amount of money from the player's account.

SQLiteConnection - Class in com.example.project.services.sqlite
Abstract SQLiteConnection class.

SQLiteConnection() - Constructor for class com.example.project.services.sqlite.SQLiteConnection

SQLiteDictionaryConnection - Class in com.example.project.services.sqlite

Connection to the dictionary.db

SQLiteDictionaryConnection() - Constructor for class com.example.project.services.sqlite.SQLiteDictionaryConnection

SQLiteUsersConnection - Class in com.example.project.services.sqlite

Connection to the users.db

SQLiteUsersConnection() - Constructor for class com.example.project.services.sqlite.SQLiteUsersConnection

start(Stage) - Method in class com.example.project.Application

SVGIcons - Class in com.example.project.services

a static class to hold some icons for the application.

SVGIcons() - Constructor for class com.example.project.services.SVGIcons

switchScene(GameScenes) - Method in class com.example.project.services.SceneManager

Switch between scenes specify scene type of type from GameScenes.

syncTiles() - Method in class com.example.project.models.tileGroups.TileGroup

Sync tiles in this tile groups controller.

T

TextEmphasisAnimation - Class in com.example.project.controllers.gameScreens.animations

An animation to quickly enlarge text and then return it to its original scale.

TextEmphasisAnimation(Label, Paint, Paint, Duration) - Constructor for class

com.example.project.controllers.gameScreens.animations.TextEmphasisAnimation

create the animations for text growing then shrinking

TileController<T> - Class in com.example.project.controllers.tiles

Parent class of TileControllers.

TileController() - Constructor for class com.example.project.controllers.tiles.TileController

tileControllerFactory - Variable in class com.example.project.models.tileGroups.TileGroup

TileControllerFactory - Class in com.example.project.controllers.tiles

class to load the tile model controller for that tile model type.

TileControllerFactory() - Constructor for class com.example.project.controllers.tiles.TileControllerFactory

Creates instance of TileControllerFactory.

TileControllerFactory(FXMLLoaderPageLoader) - Constructor for class com.example.project.controllers.tiles.TileControllerFactory

tileControllers - Variable in class com.example.project.models.tileGroups.TileGroup

TileGroup<modelType,controllerType> - Class in com.example.project.models.tileGroups

Tile Group abstract class holds a row or column of tiles.

TileModel - Class in com.example.project.models.tiles

Parent tile class for objects in the scene that are tiles.

TileModel() - Constructor for class com.example.project.models.tiles.TileModel

TITLE - Static variable in class com.example.project.Application

toString() - Method in record class com.example.project.controllers.gameScreens.GameScreenController SidebarLoaded

Returns a string representation of this record class.

toString() - Method in record class com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData

Returns a string representation of this record class.

tryMoveTile(LetterTileModel) - Method in class com.example.project.models.gameScreens.LevelModel

determines where tile should go and moves it

U

unMute() - Method in class com.example.project.services.sound.GameSoundPlayer

Set clip to its default volume.

updateLevelInfo() - Method in class com.example.project.services.Session

Increments how many points are required to beat the level.

updateVisuals() - Method in class com.example.project.models.tileGroups.LetterTileGroup

updateVisuals() - Method in class com.example.project.models.tileGroups.TileGroup

updateVisuals() - Method in class com.example.project.models.tileGroups.UpgradeTileGroup

UpgradeBuilder() - Constructor for class com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder

upgradeEffect(Runnable) - Method in class com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder

upgrade effect builder

UpgradeEffects - Class in com.example.project.models.tiles

upgrade effect methods

UpgradeEffects() - Constructor for class com.example.project.models.tiles.UpgradeEffects

UpgradeTileController - Class in com.example.project.controllers.tiles

Controls the upgrade tile view fxml file.

UpgradeTileController() - Constructor for class com.example.project.controllers.tiles.UpgradeTileController

UpgradeTileGroup - Class in com.example.project.models.tileGroups

tile group that observes an observable list and updates the ui nodes for some game tiles.

UpgradeTileGroup(Pane, ReadOnlyListProperty<UpgradeTileModel>) - Constructor for class

com.example.project.models.tileGroups.UpgradeTileGroup

Constructor with no additional sync action parameter.

UpgradeTileGroup(Pane, ReadOnlyListProperty<UpgradeTileModel>, Consumer<UpgradeTileController>) - Constructor for

class com.example.project.models.tileGroups.UpgradeTileGroup

Constructor.

UpgradeTileModel - Class in com.example.project.models.tiles

Represents the upgrade tiles sold at the shop.

UpgradeTileModel(UpgradeTileModel.UpgradeBuilder) - Constructor for class

com.example.project.models.tiles.UpgradeTileModel

public upgrade constructor.

UpgradeTileModel.UpgradeBuilder - Class in com.example.project.models.tiles

builder class for the upgrades

UpgradeTiles - Class in com.example.project.services.shopItems

Static class to store all the possible upgrade tiles available in the game.

UpgradeTiles() - Constructor for class com.example.project.services.shopItems.UpgradeTiles**User** - Class in com.example.project.models

Represents a user in the application that can log in.

User(String, String, int) - Constructor for class com.example.project.models.User

Constructor.

UsersDAO - Class in com.example.project.services.sqlite.dAOs

SQLite Users database.

UsersDAO() - Constructor for class com.example.project.services.sqlite.dAOs.UsersDAO

Constructor for this class SQLiteDictionary.

UsersDAO(PasswordHasher, Connection, Logger) - Constructor for class com.example.project.services.sqlite.dAOs.UsersDAO**UsersDAO(Connection, Logger)** - Constructor for class com.example.project.services.sqlite.dAOs.UsersDAO

Constructor with injection for unit tests.

V**value()** - Method in record class com.example.project.models.tiles.ScrabbleTileProvider.ScrabbleTileData

Returns the value of the value record component.

valueOf(String) - Static method in enum class com.example.project.models.gameScreens.DailyRewardType

Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class com.example.project.services.GameScenes

Returns the enum constant of this class with the specified name.

values() - Static method in enum class com.example.project.models.gameScreens.DailyRewardType

Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class com.example.project.services.GameScenes

Returns an array containing the constants of this enum class, in the order they are declared.

W**WIDTH** - Static variable in class com.example.project.Application**wordMultiProperty()** - Method in class com.example.project.models.gameScreens.LevelModel

word multiplier.

wordPointsProperty() - Method in class com.example.project.models.gameScreens.LevelModel**wordProperty()** - Method in class com.example.project.models.popups.DefinitionPopup

A B C D E F G H I L M N O P R S T U V W

All Classes and Interfaces | All Packages | Constant Field Values

Module com.example.project

module com.example.project

project dependencies.

Packages

Exports

Package

Description

[com.example.project](#)

[com.example.project.controllers](#)

[com.example.project.controllers.gameScreens](#)

[com.example.project.controllers.gameScreens.animations](#)

[com.example.project.controllers.popupControllers](#)

[com.example.project.controllers.tiles](#)

[com.example.project.models](#)

[com.example.project.models.gameScreens](#)

[com.example.project.models.popups](#)

[com.example.project.models.tileGroups](#)

[com.example.project.models.tiles](#)

[com.example.project.services](#)

[com.example.project.services.shopItems](#)

[com.example.project.services.sound](#)

[com.example.project.services.sqlite](#)

[com.example.project.services.sqlite.dAOs](#)

Hierarchy For All Packages

Package Hierarchies:

com.example.project, com.example.project.controllers, com.example.project.controllers.gameScreens, com.example.project.controllers.gameScreens.animations, com.example.project.controllers.popupControllers, com.example.project.controllers.tiles, com.example.project.models, com.example.project.models.gameScreens, com.example.project.models.popups, com.example.project.models.tileGroups, com.example.project.models.tiles, com.example.project.services, com.example.project.services.shopItems, com.example.project.services.sound, com.example.project.services.sqlite, com.example.project.services.sqlite.dAOs

Class Hierarchy

- java.lang.Object²
 - com.example.project.controllers.gameScreens.animations.AnimationWrapper
 - com.example.project.controllers.gameScreens.animations.LevelScoreSequence
 - com.example.project.controllers.gameScreens.animations.TextEmphasisAnimation
 - javafx.application.Application
 - com.example.project.Application
 - com.example.project.models.gameScreens.DailyRewardModel
 - com.example.project.services.sqlite.dAOs.DictionaryDAO
 - com.example.project.services.FXMLPageLoader (implements com.example.project.services.PageLoader)
 - com.example.project.controllers.gameScreens.GameScreenController
 - com.example.project.controllers.gameScreens.DailyRewardController
 - com.example.project.controllers.gameScreens.LevelController
 - com.example.project.controllers.gameScreens.LoginController
 - com.example.project.controllers.gameScreens.MainMenuController
 - com.example.project.controllers.gameScreens.ShopController
 - com.example.project.models.gameScreens.GameScreenModel
 - com.example.project.models.gameScreens.LevelModel
 - com.example.project.models.gameScreens.LoginModel
 - com.example.project.models.gameScreens.MainMenuModel
 - com.example.project.models.gameScreens.ShopModel
 - com.example.project.services.GameSoundPlayer
 - com.example.project.services.sound.GameMusicPlayer
 - com.example.project.controllers.gameScreens.animations.InfiniteFloatingAnimation
 - com.example.project.services.Logger
 - com.example.project.services.PasswordHasher
 - com.example.project.controllers.popupControllers.PopupController<P>
 - com.example.project.controllers.popupControllers.DefinitionController
 - com.example.project.services.PopupLoader
 - com.example.project.models.popups.PopupModel
 - com.example.project.models.popups.DefinitionPopup
 - com.example.project.controllers.RootLayoutController
 - com.example.project.services.SceneManager
 - com.example.project.models.gameScreens.ScoreChimePlayer
 - com.example.project.controllers.gameScreens.animations.ScoreTimeline
 - com.example.project.models.tiles.ScrabbleTileProvider
 - com.example.project.services.Session
 - com.example.project.controllers.gameScreens SidebarController
 - com.example.project.services.sqlite.SQLiteConnection
 - com.example.project.services.sqlite.SQLiteDictionaryConnection
 - com.example.project.services.sqlite.SQLiteUsersConnection
 - com.example.project.services.SVGIcons
 - com.example.project.controllers.tiles.TileController<T>
 - com.example.project.controllers.tiles.EmptyTileSlotController
 - com.example.project.controllers.tiles.LetterTileController
 - com.example.project.controllers.tiles.UpgradeTileController
 - com.example.project.controllers.tiles.TileControllerFactory
 - com.example.project.models.tileGroups.TileGroup<modelType, controllerType>
 - com.example.project.models.tileGroups.LetterTileGroup
 - com.example.project.models.tileGroups.UpgradeTileGroup
 - com.example.project.models.tiles.TileModel
 - com.example.project.models.tiles.EmptyTileSlotModel
 - com.example.project.models.tiles.LetterTileModel
 - com.example.project.models.tiles.UpgradeTileModel
 - com.example.project.models.tiles.UpgradeEffects
 - com.example.project.models.tiles.UpgradeTileModel.UpgradeBuilder
 - com.example.project.services.shopItems.UpgradeTiles
 - com.example.project.models.User
 - com.example.project.services.sqlite.dAOs.UsersDAO

Interface Hierarchy

- com.example.project.services.PageLoader

Enum Class Hierarchy

- java.lang.Object²
 - java.lang.Enum²<E> (implements java.lang.Comparable²<T>, java.lang.constant.Constable², java.io.Serializable²)

- com.example.project.models.gameScreens.**DailyRewardType**
- com.example.project.services.**GameScenes**

Record Class Hierarchy

- java.lang.**Object**²
 - java.lang.**Record**³
 - com.example.project.controllers.gameScreens.**GameScreenController.SidebarLoaded**
 - com.example.project.models.tiles.**ScrabbleTileProvider.ScrabbleTileData**

Copyright © 2025. All rights reserved.

Search

Reset

► Additional resources

Loading search index...

Copyright © 2025. All rights reserved.

Module com.example.project

Package com.example.project.controllers.gameScreens.animations

Class TextEmphasisAnimation

```
java.lang.Object
    com.example.project.controllers.gameScreens.animations.AnimationWrapper
        com.example.project.controllers.gameScreens.animations.TextEmphasisAnimation
```

```
public class TextEmphasisAnimation
extends AnimationWrapper
```

An animation to quickly enlarge text and then return it to its original scale.

Field Summary

Fields inherited from

class com.example.project.controllers.gameScreens.animations.AnimationWrapper

sequentialAnimation

Constructor Summary

Constructors

Constructor

Description

TextEmphasisAnimation(javafx.scene.control.Label textToAnimate, javafx.scene.paint.Paint colorAtStart, javafx.scene.paint.Paint changeColourAtEnd, javafx.util.Duration timePauseAfterAnim)

create the animations for text growing then shrinking

Method Summary

Methods inherited from

class com.example.project.controllers.gameScreens.animations.AnimationWrapper

getChildren, play, setOnFinished

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

TextEmphasisAnimation

```
public TextEmphasisAnimation(javafx.scene.control.Label textToAnimate,
                            javafx.scene.paint.Paint colorAtStart,
                            javafx.scene.paint.Paint changeColourAtEnd,
                            javafx.util.Duration timePauseAfterAnim)
```

create the animations for text growing then shrinking

Parameters:

textToAnimate - Label.

colorAtStart - initial colour change.

changeColourAtEnd - colour change after finished.

timePauseAfterAnim - time delay after animation until animation finished.

Uses of Class

com.example.project.controllers.gameScreens.animations.AnimationWrapper

Packages that use AnimationWrapper

Package

Description

[com.example.project.controllers.gameScreens.animations](#)

Uses of AnimationWrapper in com.example.project.controllers.gameScreens.animations

Subclasses of AnimationWrapper in com.example.project.controllers.gameScreens.animations

Modifier and Type

Class

Description

class

LevelScoreSequence

Animates each level tile popping up and the score text increasing for every tile in the word row.

class

TextEmphasisAnimation

An animation to quickly enlarge text and then return it to its original scale.

Module com.example.project

Package com.example.project

Class Application

```
java.lang.Object
    javafx.application.Application
        com.example.project.Application
```

```
public class Application
extends javafx.application.Application
```

The entry point of the application.

Nested Class Summary

Nested classes/interfaces inherited from class javafx.application.Application

```
javafx.application.Application.Parameters
```

Field Summary

Fields

Modifier and Type

Field

Description

```
static final int
```

HEIGHT

```
static final String
```

TITLE

```
static final int
```

WIDTH

Fields inherited from class javafx.application.Application

```
STYLESSHEET_CASPIAN, STYLESSHEET_MODENA
```

Constructor Summary

Constructors

Constructor

Description

Application()

Method Summary

All Methods

Static Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

```
static void
main(String[] args)

void
start(javafx.stage.Stage stage)
```

Methods inherited from class javafx.application.Application

getHostServices, getParameters, getUserAgentStylesheet, init, launch, launch, notifyPreloader, setUserAgentStylesheet, stop

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Details

TITLE

public static final String TITLE

See Also:

Constant Field Values

WIDTH

public static final int WIDTH

See Also:

Constant Field Values

HEIGHT

public static final int HEIGHT

See Also:

Constant Field Values

Constructor Details

Application

public Application()

Method Details

start

public void start(javafx.stage.Stage stage)
throws IOException

Specified by:

start in class javafx.application.Application

Throws:

IOException

main

```
public static void main(String[] args)
```

Parameters:

args - the command-line arguments passed to your program when it starts.

Uses of Class

com.example.project.controllers.gameScreens.animations.InfiniteFloatingAnimation

No usage of com.example.project.controllers.gameScreens.animations.InfiniteFloatingAnimation

Copyright © 2025. All rights reserved.

Uses of Class

com.example.project.controllers.gameScreens.animations.LevelScoreSequence

No usage of com.example.project.controllers.gameScreens.animations.LevelScoreSequence

Copyright © 2025. All rights reserved.

Uses of Class

com.example.project.controllers.gameScreens.animations.ScoreTimeline

No usage of com.example.project.controllers.gameScreens.animations.ScoreTimeline

Copyright © 2025. All rights reserved.

Uses of Class

com.example.project.controllers.gameScreens.animations.TextEmphasisAnimation

No usage of com.example.project.controllers.gameScreens.animations.TextEmphasisAnimation

Copyright © 2025. All rights reserved.

Module com.example.project

Package com.example.project.controllers.gameScreens.animations

package com.example.project.controllers.gameScreens.animations

Related Packages

Package

Description

com.example.project.controllers.gameScreens

Classes

Class

Description

AnimationWrapper

Animation wrapper class for our projects animations that get used.

InfiniteFloatingAnimation

Balatro style floating tile animation.

LevelScoreSequence

Animates each level tile popping up and the score text increasing for every tile in the word row.

ScoreTimeline

Class for total score counter animation

TextEmphasisAnimation

An animation to quickly enlarge text and then return it to its original scale.

Copyright © 2025. All rights reserved.

Hierarchy For Package com.example.project.controllers.gameScreens.animations

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#)
- [com.example.project.controllers.gameScreens.animations.AnimationWrapper](#)
 - [com.example.project.controllers.gameScreens.animations.LevelScoreSequence](#)
 - [com.example.project.controllers.gameScreens.animations.TextEmphasisAnimation](#)
- [com.example.project.controllers.gameScreens.animations.InfiniteFloatingAnimation](#)
- [com.example.project.controllers.gameScreens.animations.ScoreTimeline](#)

Uses of Package `com.example.project.controllers.gameScreens.animations`

Packages that use `com.example.project.controllers.gameScreens.animations`

Package

Description

`com.example.project.controllers.gameScreens.animations`

Classes in `com.example.project.controllers.gameScreens.animations` used by `com.example.project.controllers.gameScreens.animations`

Class

Description

`AnimationWrapper`

Animation wrapper class for our projects animations that get used.

Uses of Class

com.example.project.controllers.gameScreens.DailyRewardController

No usage of com.example.project.controllers.gameScreens.DailyRewardController

Copyright © 2025. All rights reserved.

Uses of Record Class

[com.example.project.controllers.gameScreens.GameScreenController.SidebarLoaded](#)

Packages that use GameScreenController.SidebarLoaded

Package

Description

[com.example.project.controllers.gameScreens](#)

Uses of GameScreenController.SidebarLoaded in com.example.project.controllers.gameScreens

Methods in com.example.project.controllers.gameScreens that return GameScreenController.SidebarLoaded

Modifier and Type

Method

Description

protected [GameScreenController.SidebarLoaded](#)

[GameScreenController.loadSidebar\(\)](#)

Uses of Class com.example.project.controllers.gameScreens.GameScreenController

Packages that use GameScreenController

Package

Description

com.example.project.controllers.gameScreens

com.example.project.services

Uses of GameScreenController in com.example.project.controllers.gameScreens

Subclasses of GameScreenController in com.example.project.controllers.gameScreens

Modifier and Type

Class

Description

class

DailyRewardController

Controller for the daily reward popup screen.

class

LevelController

Controller for the level screen.

class

LoginController

Controller for the login scene.

class

MainMenuController

controller for the main menu.

class

ShopController

Shop view controller.

Uses of GameScreenController in com.example.project.services

Constructor parameters in com.example.project.services with type arguments of type GameScreenController

Modifier

Constructor

Description

protected

`SceneManager(SceneManager newInstance, RootLayoutController newRootController, Map<GameScenes, GameScreenController> controllersToUse, Map<GameScenes, javafx.scene.Parent> pagesToUse)`

Constructor with injection for tests

Uses of Class com.example.project.Application

No usage of com.example.project.Application

Copyright © 2025. All rights reserved.

Uses of Class

com.example.project.controllers.gameScreens.LevelController

No usage of com.example.project.controllers.gameScreens.LevelController

Copyright © 2025. All rights reserved.

Uses of Class

com.example.project.controllers.gameScreens.LoginController

No usage of com.example.project.controllers.gameScreens.LoginController

Copyright © 2025. All rights reserved.

Uses of Class

com.example.project.controllers.gameScreens.MainMenuController

No usage of com.example.project.controllers.gameScreens.MainMenuController

Copyright © 2025. All rights reserved.

Uses of Class

com.example.project.controllers.gameScreens.ShopController

No usage of com.example.project.controllers.gameScreens.ShopController

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.controllers.gameScreens.SidebarController

Packages that use SidebarController

Package

Description

com.example.project.controllers.gameScreens

Uses of SidebarController in com.example.project.controllers.gameScreens

Methods in com.example.project.controllers.gameScreens that return SidebarController

Modifier and Type

Method

Description

SidebarController

GameScreenController.SidebarLoaded.controller()

Returns the value of the controller record component.

Constructors in com.example.project.controllers.gameScreens with parameters of type SidebarController

Modifier

Constructor

Description

protected

SidebarLoaded(javafx.scene.Parent node, SidebarController controller)

Creates an instance of a SidebarLoaded record class.

Package com.example.project.controllers.gameScreens

package com.example.project.controllers.gameScreens

Related Packages

Package

Description

[com.example.project.controllers](#)

[com.example.project.controllers.gameScreens.animations](#)

[com.example.project.controllers.popupControllers](#)

[com.example.project.controllers.tiles](#)

All Classes and Interfaces

Classes

Record Classes

Class

Description

DailyRewardController

Controller for the daily reward popup screen.

GameScreenController

Game screen controller that has some startup on screen thing todo.

GameScreenController.SidebarLoaded

LevelController

Controller for the level screen.

LoginController

Controller for the login scene.

MainMenuController

controller for the main menu.

ShopController

Shop view controller.

SidebarController

The sidebar on shop and level with the current round info.

Hierarchy For Package com.example.project.controllers.gameScreens

Package Hierarchies:

All Packages

Class Hierarchy

- [java.lang.Object](#)
 - [com.example.project.controllers.gameScreens.GameScreenController](#)
 - [com.example.project.controllers.gameScreens.DailyRewardController](#)
 - [com.example.project.controllers.gameScreens.LevelController](#)
 - [com.example.project.controllers.gameScreens.LoginController](#)
 - [com.example.project.controllers.gameScreens.MainMenuController](#)
 - [com.example.project.controllers.gameScreens.ShopController](#)
 - [com.example.project.controllers.gameScreens.SidebarController](#)

Record Class Hierarchy

- [java.lang.Object](#)
 - [java.lang.Record](#)
 - [com.example.project.controllers.gameScreens.GameScreenController.SidebarLoaded](#)

Copyright © 2025. All rights reserved.

Uses of Package com.example.project.controllers.gameScreens

Packages that use com.example.project.controllers.gameScreens

Package

Description

com.example.project.controllers.gameScreens

com.example.project.services

Classes in com.example.project.controllers.gameScreens used by com.example.project.controllers.gameScreens

Class

Description

GameScreenController

Game screen controller that has some startup on screen thing todo.

GameScreenController.SidebarLoaded

SidebarController

The sidebar on shop and level with the current round info.

Classes in com.example.project.controllers.gameScreens used by com.example.project.services

Class

Description

GameScreenController

Game screen controller that has some startup on screen thing todo.

Module com.example.project

Package com.example.project.controllers

package com.example.project.controllers

Related Packages

Package

Description

[com.example.project](#)

[com.example.project.controllers.gameScreens](#)

[com.example.project.controllers.popupControllers](#)

[com.example.project.controllers.tiles](#)

[com.example.project.models](#)

[com.example.project.services](#)

Classes

Class

Description

[RootLayoutController](#)

Root layout that remains the root scene of the application to switch scenes within.

Hierarchy For Package com.example.project.controllers

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#) ↗
 - [com.example.project.controllers.RootLayoutController](#)

Copyright © 2025. All rights reserved.

Module com.example.project
Package com.example.project.controllers

Class RootLayoutController

java.lang.Object
 com.example.project.controllers.RootLayoutController

```
public class RootLayoutController  
extends Object
```

Root layout that remains the root scene of the application to switch scenes within.

Constructor Summary

Constructors

Constructor

Description

RootLayoutController()

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

setContent(javafx.scene.Parent page)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

RootLayoutController

```
public RootLayoutController()
```

Method Details

setContent

```
public void setContent(javafx.scene.Parent page)
```

Parameters:

page - Set page content to a game scene.

Uses of Package com.example.project.controllers

Packages that use com.example.project.controllers

Package

Description

com.example.project.services

Classes in com.example.project.controllers used by com.example.project.services

Class

Description

[RootLayoutController](#)

Root layout that remains the root scene of the application to switch scenes within.

Module com.example.project

Package com.example.project.controllers.popupControllers

Class DefinitionController

```
java.lang.Object
  com.example.project.controllers.popupControllers.PopupController<DefinitionPopup>
    com.example.project.controllers.popupControllers.DefinitionController
```

```
public class DefinitionController
extends PopupController<DefinitionPopup>
```

Controller for definition popup

Field Summary

Fields inherited from class com.example.project.controllers.popupControllers.PopupController

model

Constructor Summary

Constructors

Constructor

Description

DefinitionController()

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

DefinitionPopup

getModel()

gets the popup model.

javafx.scene.Node

getStack()

root ui node.

void

initialize(DefinitionPopup model)

sets elements of the ui

Methods inherited from class java.lang.Object

clone[✉], equals[✉], finalize[✉], getClass[✉], hashCode[✉], notify[✉], notifyAll[✉], toString[✉], wait[✉], wait[✉], wait[✉]

Constructor Details

DefinitionController

```
public DefinitionController()
```

Method Details

getStack

```
public javafx.scene.Node getStack()
```

Description copied from class: PopupController

root ui node.

Specified by:

[getStack](#) in class [PopupController<DefinitionPopup>](#)

Returns:

returns Node

getModel

```
public DefinitionPopup getModel()
```

Description copied from class: PopupController

gets the popup model.

Overrides:

[getModel](#) in class [PopupController<DefinitionPopup>](#)

Returns:

model.

initialize

```
public void initialize(DefinitionPopup model)
```

Description copied from class: PopupController

sets elements of the ui

Specified by:

[initialize](#) in class [PopupController<DefinitionPopup>](#)

Parameters:

model - popup to initialize

Module com.example.project

Package com.example.project.controllers.popupControllers

Class PopupController<P extends PopupModel>

java.lang.Object
com.example.project.controllers.PopupController<P>

Type Parameters:

P - Popup model type

Direct Known Subclasses:

DefinitionController

```
public abstract class PopupController<P extends PopupModel>
extends Object
```

Parent class for PopupControllers

Field Summary

Fields

Modifier and Type

Field

Description

protected P

model

Constructor Summary

Constructors

Constructor

Description

PopupController()

Method Summary

All Methods

Instance Methods

Abstract Methods

Concrete Methods

Modifier and Type

Method

Description

P

getModel()

gets the popup model.

abstract javafx.scene.Node

getStack()

root ui node.

abstract void

initialize(P popup)

sets elements of the ui

Methods inherited from class java.lang.Object

```
clone2, equals2, finalize2, getClass2, hashCode2, notify2, notifyAll2, toString2, wait2, wait2, wait2
```

Field Details

model

```
protected P extends PopupModel model
```

Constructor Details

PopupController

```
public PopupController()
```

Method Details

getStack

```
public abstract javafx.scene.Node getStack()
```

root ui node.

Returns:

root ui Node

initialize

```
public abstract void initialize(P popup)
```

sets elements of the ui

Parameters:

popup - popup to initialize

getModel

```
public P getModel()
```

gets the popup model.

Returns:

model.

Uses of Class

com.example.project.controllers.popupControllers.DefinitionController

No usage of com.example.project.controllers.popupControllers.DefinitionController

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.controllers.popupControllers.PopupController

Packages that use PopupController

Package

Description

com.example.project.controllers.popupControllers

com.example.project.services

Uses of PopupController in com.example.project.controllers.popupControllers

Subclasses of PopupController in com.example.project.controllers.popupControllers

Modifier and Type

Class

Description

class

DefinitionController

Controller for definition popup

Uses of PopupController in com.example.project.services

Methods in com.example.project.services with type parameters of type PopupController

Modifier and Type

Method

Description

<C extends PopupController<P>, P extends PopupModel>

C

PopupLoader.createPopupController(P popupModel)

create popup controller.

Module com.example.project

Package com.example.project.controllers.popupControllers

package com.example.project.controllers.popupControllers

Related Packages

Package

Description

[com.example.project.controllers](#)

[com.example.project.controllers.gameScreens](#)

[com.example.project.controllers.tiles](#)

Classes

Class

Description

[DefinitionController](#)

Controller for definition popup

[PopupController<P extends PopupModel>](#)

Parent class for PopupControllers

Hierarchy For Package com.example.project.controllers.popupControllers

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#)
- [com.example.project.controllers.popupControllers.PopupController<P>](#)
 - [com.example.project.controllers.DefinitionController](#)

Uses of Package com.example.project.controllers.popupControllers

Packages that use com.example.project.controllers.popupControllers

Package	Description
com.example.project.controllers.popupControllers	
com.example.project.services	

Classes in com.example.project.controllers.popupControllers used by com.example.project.controllers.popupController

Class	Description
PopupController	Parent class for PopupControllers

Classes in com.example.project.controllers.popupControllers used by com.example.project.services

Class	Description
PopupController	Parent class for PopupControllers

Module com.example.project
Package com.example.project.controllers.tiles

Class EmptyTileSlotController

java.lang.Object
 com.example.project.controllers.tiles.TileController<EmptyTileSlotModel>
 com.example.project.controllers.tiles.EmptyTileSlotController

```
public class EmptyTileSlotController  
extends TileController<EmptyTileSlotModel>
```

Empty Tile controller for EmptyTile view.

Field Summary

Fields

Modifier and Type

Field

Description

protected javafx.scene.layout.StackPane
root

protected javafx.scene.layout.StackPane
slotForLetterTile

Fields inherited from class com.example.project.controllers.tiles.TileController

model

Constructor Summary

Constructors

Constructor

Description

EmptyTileSlotController()

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

bind(EmptyTileSlotModel modelToUse)

Binds tile to the controller as its model.

javafx.scene.Node

getRoot()

root ui node.

void

setLetter(LetterTileController letterController)

updates the tile slot with a new letter tile controller.

Methods inherited from class com.example.project.controllers.tiles.TileController

getModel, setModel

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Details

root

protected javafx.scene.layout.StackPane root

slotForLetterTile

protected javafx.scene.layout.StackPane slotForLetterTile

Constructor Details

EmptyTileSlotController

public EmptyTileSlotController()

Method Details

bind

public void bind(EmptyTileSlotModel modelToUse)

Description copied from class: TileController

Binds tile to the controller as its model.

Specified by:

bind in class TileController<EmptyTileSlotModel>

Parameters:

modelToUse - tile to bind.

getRoot

public javafx.scene.Node getRoot()

Description copied from class: TileController

root ui node.

Specified by:

getRoot in class TileController<EmptyTileSlotModel>

Returns:

root ui Node

setLetter

public void setLetter(LetterTileController letterController)

updates the tile slot with a new letter tile controller.

Parameters:

letterController - the letter tiles controller.

Copyright © 2025. All rights reserved.

Module com.example.project
Package com.example.project.controllers.tiles

Class LetterTileController

java.lang.Object ↗
 com.example.project.controllers.tiles.TileController<LetterTileModel>
 com.example.project.controllers.tiles.LetterTileController

```
public class LetterTileController  
extends TileController<LetterTileModel>
```

Controls the layout of the letterUIModel. Which is a letter tile.

Field Summary

Fields inherited from class com.example.project.controllers.tiles.TileController

model

Constructor Summary

Constructors

Constructor

Description

`LetterTileController()`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

`bind(LetterTileModel tile)`

Binds tile to the controller as its model.

`LetterTileModel`

`getModel()`

gets the tile model.

`javafx.scene.Node`

`getRoot()`

root ui node.

Methods inherited from class com.example.project.controllers.tiles.TileController

`setModel`

Methods inherited from class java.lang.Object ↗

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Details

LetterTileController

```
public LetterTileController()
```

Method Details

getRoot

```
public javafx.scene.Node getRoot()
```

Description copied from class: [TileController](#)

root ui node.

Specified by:

[getRoot](#) in class [TileController<LetterTileModel>](#)

Returns:

root ui Node

getModel

```
public LetterTileModel getModel()
```

Description copied from class: [TileController](#)

gets the tile model.

Overrides:

[getModel](#) in class [TileController<LetterTileModel>](#)

Returns:

model.

bind

```
public void bind(LetterTileModel tile)
```

Description copied from class: [TileController](#)

Binds tile to the controller as its model.

Specified by:

[bind](#) in class [TileController<LetterTileModel>](#)

Parameters:

tile - tile to bind.

Uses of Class com.example.project.controllers.RootLayoutController

Packages that use RootLayoutController

Package

Description

com.example.project.services

Uses of RootLayoutController in com.example.project.services

Methods in com.example.project.services with parameters of type RootLayoutController

Modifier and Type

Method

Description

void

`SceneManager.initialise(RootLayoutController theRootController, PageLoader loader)`

loads the fxml of all the scenes on launch to switch to via scene manager.

Constructors in com.example.project.services with parameters of type RootLayoutController

Modifier

Constructor

Description

protected

`SceneManager(SceneManager newInstance, RootLayoutController newRootController, Map<GameScenes, GameScreenController> controllersToUse, Map<GameScenes, javafx.scene.Parent> pagesToUse)`

Constructor with injection for tests

Module com.example.project

Package com.example.project.controllers.tiles

Class TileController<T extends TileModel>

java.lang.Object ↗
com.example.project.controllers.tiles.TileController<T>

Type Parameters:

T - tile model type.

Direct Known Subclasses:

EmptyTileSlotController, LetterTileController, UpgradeTileController

```
public abstract class TileController<T extends TileModel>
extends Object ↗
```

Parent class of TileControllers.

Field Summary

Fields

Modifier and Type

Field

Description

protected T model

Constructor Summary

Constructors

Constructor

Description

TileController()

Method Summary

All Methods

Instance Methods

Abstract Methods

Concrete Methods

Modifier and Type

Method

Description

abstract void bind(T tile)

Binds tile to the controller as its model.

T

getModel()

gets the tile model.

abstract javafx.scene.Node

getRoot()

root ui node.

void

setModel(T tile)

Set the model this controller will observe.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Field Details

model

`protected T extends TileModel model`

Constructor Details

TileController

`public TileController()`

Method Details

getRoot

`public abstract javafx.scene.Node getRoot()`

root ui node.

Returns:

root ui Node

bind

`public abstract void bind(T tile)`

Binds tile to the controller as its model.

Parameters:

tile - tile to bind.

setModel

`public void setModel(T tile)`

Set the model this controller will observe.

Parameters:

tile - tile model class.

getModel

`public T getModel()`

gets the tile model.

Returns:

model.

Module com.example.project
Package com.example.project.controllers.tiles

Class TileControllerFactory

java.lang.Object
 com.example.project.controllers.tiles.TileControllerFactory

```
public class TileControllerFactory  
extends Object
```

class to load the tile model controller for that tile model type.

Constructor Summary

Constructors

Modifier

Constructor

Description

`TileControllerFactory()`

Creates instance of `TileControllerFactory`.

protected

`TileControllerFactory(FXMLLoader loader)`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

`LetterTileController`

`createLetterTileController(LetterTileModel lt)`

`<C extends TileController<T>, T extends TileModel>`
C

`createTileController(T tile, Class<?> controllerType)`

Returns controller of type.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Details

TileControllerFactory

`public TileControllerFactory()`

Creates instance of `TileControllerFactory`.

TileControllerFactory

`protected TileControllerFactory(FXMLLoader loader)`

Method Details

createTileController

```
public <C extends TileController<T>,
      T extends TileModel>
C createTileController(T tile,
                      Class<?> controllerType)
```

Returns controller of type.

Type Parameters:

C - controller type.

T - tile type.

Parameters:

tile - tile model.

controllerType - controller type.

Returns:

return controller.

createLetterTileController

```
public LetterTileController createLetterTileController(LetterTileModel lt)
```

Parameters:

lt - letter tile model.

Returns:

returns letter tile controller.

Module com.example.project
Package com.example.project.controllers.tiles

Class UpgradeTileController

```
java.lang.Object
    com.example.project.controllers.tiles.TileController<UpgradeTileModel>
        com.example.project.controllers.tiles.UpgradeTileController
```

```
public class UpgradeTileController
extends TileController<UpgradeTileModel>
```

Controls the upgrade tile view fxml file.

Field Summary

Fields

Modifier and Type

Field

Description

protected javafx.scene.image.ImageView
imageView

protected javafx.scene.layout.StackPane
root

Fields inherited from class com.example.project.controllers.tiles.TileController

model

Constructor Summary

Constructors

Constructor

Description

UpgradeTileController()

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

bind(UpgradeTileModel tileModel)

Binds tile to the controller as its model.

javafx.scene.Node

getRoot()

root ui node.

Methods inherited from class com.example.project.controllers.tiles.TileController

`getModel, setModel`

Methods inherited from class `java.lang.Object`

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Field Details

`root`

`protected javafx.scene.layout.StackPane root`

`imageView`

`protected javafx.scene.image.ImageView imageView`

Constructor Details

`UpgradeTileController`

`public UpgradeTileController()`

Method Details

`getRoot`

`public javafx.scene.Node getRoot()`

Description copied from class: `TileController`

root ui node.

Specified by:

`getRoot` in class `TileController<UpgradeTileModel>`

Returns:

root ui Node

`bind`

`public void bind(UpgradeTileModel tileModel)`

Description copied from class: `TileController`

Binds tile to the controller as its model.

Specified by:

`bind` in class `TileController<UpgradeTileModel>`

Parameters:

tileModel - tile to bind.

Uses of Class

com.example.project.controllers.tiles.EmptyTileSlotController

No usage of com.example.project.controllers.tiles.EmptyTileSlotController

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.controllers.tiles.LetterTileController

Packages that use LetterTileController

Package

Description

com.example.project.controllers.gameScreens.animations

com.example.project.controllers.tiles

com.example.project.models.tileGroups

Uses of LetterTileController in com.example.project.controllers.gameScreens.animations

Constructor parameters in com.example.project.controllers.gameScreens.animations with type arguments of type LetterTileController

Modifier

Constructor

Description

`LevelScoreSequence(List<LetterTileController> wordTileControllers, LevelModel levelModel, javafx.scene.control.Label comboCountLabel, javafx.scene.control.Label multiplierLabel)`

Constructor.

Uses of LetterTileController in com.example.project.controllers.tiles

Methods in com.example.project.controllers.tiles that return LetterTileController

Modifier and Type

Method

Description

`LetterTileController`

`TileControllerFactory.createLetterTileController(LetterTileModel lt)`

Methods in com.example.project.controllers.tiles with parameters of type LetterTileController

Modifier and Type

Method

Description

`void`

`EmptyTileSlotController.setLetter(LetterTileController letterController)`

updates the tile slot with a new letter tile controller.

Uses of LetterTileController in com.example.project.models.tileGroups

Constructor parameters in com.example.project.models.tileGroups with type arguments of type LetterTileController

Modifier

Constructor

Description

```
LetterTileGroup(int numberOfEmptyTileSlots, javafx.scene.layout.Pane container,  
javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<  
<LetterTileController> onClickAction)
```

Constructor

```
LetterTileGroup(int numberOfEmptyTileSlots, javafx.scene.layout.Pane container,  
javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<  
<LetterTileController> onClickHandler, List<Runnable> afterSyncActions)
```

Constructor

protected

```
LetterTileGroup(int numberOfEmptyTileSlots, javafx.scene.layout.Pane container,  
javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<  
<LetterTileController> onClickHandler, List<Runnable> afterSyncActions, TileControllerFactory factory)
```

Uses of Class com.example.project.controllers.tiles.TileController

Packages that use TileController

Package

Description

com.example.project.controllers.tiles

com.example.project.models.tileGroups

Uses of TileController in com.example.project.controllers.tiles

Subclasses of TileController in com.example.project.controllers.tiles

Modifier and Type

Class

Description

class

EmptyTileSlotController

Empty Tile controller for EmptyTile view.

class

LetterTileController

Controls the layout of the letterUIModel.

class

UpgradeTileController

Controls the upgrade tile view fxml file.

Methods in com.example.project.controllers.tiles with type parameters of type TileController

Modifier and Type

Method

Description

<C extends TileController<T>, T extends TileModel>

C

TileControllerFactory.createTileController(T tile, Class<?> controllerType)

Returns controller of type.

Uses of TileController in com.example.project.models.tileGroups

Classes in com.example.project.models.tileGroups with type parameters of type TileController

Modifier and Type

Class

Description

class

TileGroup<modelType extends TileModel, controllerType extends TileController<modelType>>

Tile Group abstract class holds a row or column of tiles.

Uses of Class com.example.project.controllers.tiles.TileControllerFactory

Packages that use TileControllerFactory

Package

Description

com.example.project.models.tileGroups

Uses of TileControllerFactory in com.example.project.models.tileGroups

Fields in com.example.project.models.tileGroups declared as TileControllerFactory

Modifier and Type

Field

Description

protected TileControllerFactory

TileGroup.tileControllerFactory

Constructors in com.example.project.models.tileGroups with parameters of type TileControllerFactory

Modifier

Constructor

Description

protected

LetterTileGroup(int numberEmptyTileSlots, javafx.scene.layout.Pane container, javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<LetterTileController> onClickHandler, List<Runnable> afterSyncActions, TileControllerFactory factory)

Uses of Class com.example.project.controllers.tiles.UpgradeTileController

Packages that use UpgradeTileController

Package

Description

com.example.project.controllers.gameScreens

com.example.project.models.tileGroups

Uses of UpgradeTileController in com.example.project.controllers.gameScreens

Methods in com.example.project.controllers.gameScreens with parameters of type UpgradeTileController

Modifier and Type

Method

Description

protected void

`ShopController.onUpgradeClicked(UpgradeTileController controller)`

Uses of UpgradeTileController in com.example.project.models.tileGroups

Constructor parameters in com.example.project.models.tileGroups with type arguments of type UpgradeTileController

Modifier

Constructor

Description

`UpgradeTileGroup(javafx.scene.layout.Pane container,
javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> observedList, Consumer<
<UpgradeTileController> onClickAction)`

Constructor.

Module com.example.project

Package com.example.project.controllers.tiles

package com.example.project.controllers.tiles

Related Packages

Package

Description

[com.example.project.controllers](#)

[com.example.project.controllers.gameScreens](#)

[com.example.project.controllers.popupControllers](#)

Classes

Class

Description

[EmptyTileSlotController](#)

Empty Tile controller for EmptyTile view.

[LetterTileController](#)

Controls the layout of the letterUIModel.

[TileController<T extends TileModel>](#)

Parent class of TileControllers.

[TileControllerFactory](#)

class to load the tile model controller for that tile model type.

[UpgradeTileController](#)

Controls the upgrade tile view fxml file.

Copyright © 2025. All rights reserved.

Hierarchy For Package com.example.project.controllers.tiles

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#)
- [com.example.project.controllers.tiles.TileController<T>](#)
 - [com.example.project.controllers.tiles.EmptyTileSlotController](#)
 - [com.example.project.controllers.tiles.LetterTileController](#)
 - [com.example.project.controllers.tiles.UpgradeTileController](#)
- [com.example.project.controllers.tiles.TileControllerFactory](#)

Module com.example.project

Package com.example.project.controllers.gameScreens

Class DailyRewardController

java.lang.Object ↗
 com.example.project.controllers.gameScreens.GameScreenController
 com.example.project.controllers.gameScreens.DailyRewardController

```
public class DailyRewardController  
extends GameScreenController
```

Controller for the daily reward popup screen.

Nested Class Summary

Nested classes/interfaces inherited from class com.example.project.controllers.gameScreens.GameScreenController

GameScreenController.SidebarLoaded

Field Summary

Fields inherited from class com.example.project.controllers.gameScreens.GameScreenController

logger

Constructor Summary

Constructors

Constructor

Description

DailyRewardController()

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

initialize()

Initialises the daily reward view by resetting the reward label.

void

onSceneChangedToThis()

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

Methods inherited from class com.example.project.controllers.gameScreens.GameScreenController

loadSidebar

Methods inherited from class java.lang.Object ↗

clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()

Constructor Details

DailyRewardController

```
public DailyRewardController()
```

Method Details

initialize

```
public void initialize()
```

Initialises the daily reward view by resetting the reward label.

onSceneChangedToThis

```
public void onSceneChangedToThis()
```

Description copied from class: [GameScreenController](#)

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

Specified by:

onSceneChangedToThis in class GameScreenController

Uses of Package com.example.project.controllers.tiles

Packages that use com.example.project.controllers.tiles

Package	Description
com.example.project.controllers.gameScreens	

com.example.project.controllers.gameScreens.animations
--

com.example.project.controllers.tiles

com.example.project.models.tileGroups

Classes in com.example.project.controllers.tiles used by com.example.project.controllers.gameScreens

Class	Description
UpgradeTileController	
Controls the upgrade tile view fxml file.	

Classes in com.example.project.controllers.tiles used by com.example.project.controllers.gameScreens.animations

Class	Description
LetterTileController	
Controls the layout of the letterUIModel.	

Classes in com.example.project.controllers.tiles used by com.example.project.controllers.tiles

Class	Description
LetterTileController	
Controls the layout of the letterUIModel.	

Classes in com.example.project.controllers.tiles used by com.example.project.models.tileGroups

Class	Description
LetterTileController	
Controls the layout of the letterUIModel.	
TileController	
Parent class of TileControllers.	
TileControllerFactory	
class to load the tile model controller for that tile model type.	
UpgradeTileController	
Controls the upgrade tile view fxml file.	

Module com.example.project
Package com.example.project.models

Class User

java.lang.Object[✉]
 com.example.project.models.User

```
public class User  
extends Object✉
```

Represents a user in the application that can log in.

Constructor Summary

Constructors

Constructor

Description

User(String[✉] username, String[✉] password, int highscore)

Constructor.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

int

getHighscore()

get highscore.

String[✉]

getPassword()

get password.

String[✉]

getUsername()

get username.

Methods inherited from class java.lang.Object[✉]

clone[✉], equals[✉], finalize[✉], getClass[✉], hashCode[✉], notify[✉], notifyAll[✉], toString[✉], wait[✉], wait[✉], wait[✉]

Constructor Details

User

```
public User(String✉ username,  
          String✉ password,  
          int highscore)
```

Constructor.

Parameters:

username - username.

password - password.

highscore - highscore.

Method Details

getUsername

```
public String¶ getUsername()
```

get username.

Returns:

username.

getPassword

```
public String¶ getPassword()
```

get password.

Returns:

password.

getHighscore

```
public int getHighscore()
```

get highscore.

Returns:

returns highscore.

Uses of Class com.example.project.models.User

Packages that use User

Package

Description

com.example.project.services

com.example.project.services.sqlite.dAOs

Uses of User in com.example.project.services

Methods in com.example.project.services with parameters of type User

Modifier and Type

Method

Description

void

Session.setUser(User newUser)

set new user.

Constructors in com.example.project.services with parameters of type User

Modifier

Constructor

Description

protected

**Session(int newHandSize, int newWordViewSize, int newRedrawWindowSize,
javafx.collections.ObservableList<UpgradeTileModel> newUpgrades, User newUser, int newMoney,
int newLevelsBeaten, int currentLevelRequirement, int newFirstLevelsRequirement, int newInitialMoney)**

Constructor for injecting values in for unit test.

Uses of User in com.example.project.services.sqlite.dAOs

Methods in com.example.project.services.sqlite.dAOs that return User

Modifier and Type

Method

Description

User

UsersDAO.getUser(String² username)

Methods in com.example.project.services.sqlite.dAOs with parameters of type User

Modifier and Type

Method

Description

void

UsersDAO.addUser(User user)

Adds user to the user.db.

Module com.example.project
Package com.example.project.models.gameScreens

Class DailyRewardModel

java.lang.Object
 com.example.project.models.gameScreens.DailyRewardModel

```
public class DailyRewardModel  
extends Object
```

Model for handling daily reward logic and state.

Constructor Summary

Constructors

Constructor

Description

DailyRewardModel()

Method Summary

All Methods

Static Methods

Concrete Methods

Modifier and Type

Method

Description

static void

applyReward(DailyRewardType reward)

Applies the effect of the given reward to the session and marks it as claimed.

static DailyRewardType

rollReward()

Randomly selects a daily reward.

Methods inherited from class java.lang.Object

clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()

Constructor Details

DailyRewardModel

```
public DailyRewardModel()
```

Method Details

rollReward

```
public static DailyRewardType rollReward()
```

Randomly selects a daily reward.

Returns:

a randomly selected reward

applyReward

```
public static void applyReward(DailyRewardType reward)
```

Applies the effect of the given reward to the session and marks it as claimed.

Parameters:

reward - the reward to apply

Module com.example.project
Package com.example.project.models.gameScreens

Enum Class DailyRewardType

java.lang.Object
 java.lang.Enum<DailyRewardType>
 com.example.project.models.gameScreens.DailyRewardType

All Implemented Interfaces:

Serializable, Comparable<DailyRewardType>, Constable

```
public enum DailyRewardType  
extends Enum<DailyRewardType>
```

Enum representing the possible daily reward outcomes.

Nested Class Summary

Nested classes/interfaces inherited from class java.lang.Enum

Enum.EnumDesc<E> extends Enum<E>>

Enum Constant Summary

Enum Constants

Enum Constant

Description

Daily_Reward_Won_1Dollar

Player wins \$1

Daily_Reward_Won_5Dollars

Player wins \$5

Daily_Reward_Won_NOTHING

Player wins nothing

Method Summary

All Methods

Static Methods

Concrete Methods

Modifier and Type

Method

Description

static DailyRewardType

valueOf(String name)

Returns the enum constant of this class with the specified name.

static DailyRewardType[]

values()

Returns an array containing the constants of this enum class, in the order they are declared.

Methods inherited from class java.lang.Enum

clone, compareTo, describeConstable, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Enum Constant Details

Daily_Reward_Won_1Dollar

```
public static final DailyRewardType Daily_Reward_Won_1Dollar
```

Player wins \$1

Daily_Reward_Won_5Dollars

```
public static final DailyRewardType Daily_Reward_Won_5Dollars
```

Player wins \$5

Daily_Reward_Won_NOTHING

```
public static final DailyRewardType Daily_Reward_Won_NOTHING
```

Player wins nothing

Method Details

values

```
public static DailyRewardType[] values()
```

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

```
public static DailyRewardType valueOf(String¶ name)
```

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

IllegalArgumentException[¶] - if this enum class has no constant with the specified name

NullPointerException[¶] - if the argument is null

Module com.example.project
Package com.example.project.models.gameScreens

Class GameScreenModel

java.lang.Object[↳]
 com.example.project.models.gameScreens.GameScreenModel

Direct Known Subclasses:

LevelModel, LoginModel, MainMenuModel, ShopModel

```
public abstract class GameScreenModel
extends Object↳
```

Game Screen Model. extended by loginModel, shopModel, levelModel.

Field Summary

Fields

Modifier and Type

Field

Description

protected Logger

logger

protected final Session

session

Constructor Summary

Constructors

Modifier

Constructor

Description

protected

GameScreenModel(Session session)

Method Summary

Methods inherited from class java.lang.Object[↳]

clone[↳], equals[↳], finalize[↳], getClass[↳], hashCode[↳], notify[↳], notifyAll[↳], toString[↳], wait[↳], wait[↳], wait[↳]

Field Details

logger

protected Logger logger

session

protected final Session session

Constructor Details

GameScreenModel

```
protected GameScreenModel(Session session)
```

Module com.example.project

Package com.example.project.models.gameScreens

Class LevelModel

```
java.lang.Object
  com.example.project.models.gameScreens.GameScreenModel
    com.example.project.models.gameScreens.LevelModel
```

```
public class LevelModel
extends GameScreenModel
```

Represents the level model.

Property Summary

Properties

Type

Property

Description

```
javafx.beans.property.ReadOnlyIntegerProperty
```

wordMulti

word multiplier.

```
javafx.beans.property.ReadOnlyIntegerProperty
```

wordPoints

Field Summary

Fields inherited from class com.example.project.models.gameScreens.GameScreenModel

```
logger, session
```

Constructor Summary

Constructors

Modifier

Constructor

Description

```
LevelModel(Session session)
```

Default constructor.

protected

```
LevelModel(Session session, Logger logger)
```

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

```
protected void
addTileToRack(LetterTileModel tile)

protected void
addTileToRedrawWindow(LetterTileModel tile)

protected void
addTileToWordWindow(LetterTileModel tile)

void
addToCombo(LetterTileModel tile)
add combo sum and multiCombo

int
calcTotalWordScore()

String
getCurrentWord()
Gets the current word formed by tiles in the word area

javafx.beans.property.ReadOnlyBooleanProperty
getIsRedrawActive()
gets the redraw property.

javafx.beans.property.ReadOnlyIntegerProperty
getPlayersCurrentPoints()

javafx.beans.property.ReadOnlyIntegerProperty
getPlayersTotalPoints()

javafx.beans.property.ReadOnlyListProperty<LetterTileModel>
getRedrawWindowTilesProperty()

javafx.beans.property.ReadOnlyListProperty<LetterTileModel>
getTileRackTilesProperty()

ScoreChimePlayer
getTileScoreSoundPlayer()
Gets the tile score sound effect player.

javafx.beans.property.ReadOnlyListProperty<LetterTileModel>
getWordWindowTilesProperty()

boolean
hasLost()
true if player has lost

boolean
hasWon()
returns true if player has won.

boolean
```

isCurrentWordValid()

returns true if word is in dictionary.

void

onLostLevel()

Called when the level has been lost.

void

onWonLevel()

Called when level has been won.

void

playTiles()

clears the word row tiles.

void

redrawTiles()

redraws tiles into the tile rack and removes from redraw window.

void

resetCombo()

resets counts for sum and multi in combo

void

returnRedrawTilesToTheRack()

sends the selected redraw tiles back to the rack

void

setIsRedrawActive(boolean newValue)

set redraw active.

protected void

setPlayersScore(int newValue)

void

setTotalScore(int totalScore)

void

setupNewLevel()

Initialise new level.

void

setWordMulti(int newMulti)

sets the current word multiplier

void

setWordPoints(int newWordPoints)

sets the current word points before multipliers

boolean

tryMoveTile(LetterTileModel tile)

determines where tile should go and moves it

javafx.beans.property.ReadOnlyIntegerProperty

wordMultiProperty()

word multiplier.

javafx.beans.property.ReadOnlyIntegerProperty

```
wordPointsProperty()
```

Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Property Details

wordPoints

```
public javafx.beans.property.ReadOnlyIntegerProperty wordPointsProperty
```

See Also:

```
setWordPoints(int), wordPointsProperty()
```

wordMulti

```
public javafx.beans.property.ReadOnlyIntegerProperty wordMultiProperty
```

word multiplier.

See Also:

```
setWordMulti(int), wordMultiProperty()
```

Constructor Details

LevelModel

```
protected LevelModel(Session session,  
                    Logger logger)
```

LevelModel

```
public LevelModel(Session session)
```

Default constructor.

Parameters:

session - session

Method Details

getTileScoreSoundPlayer

```
public ScoreChimePlayer getTileScoreSoundPlayer()
```

Gets the tile score sound effect player.

Returns:

LevelTileScoreSoundPlayer.

getWordWindowTilesProperty

```
public javafx.beans.property.ReadOnlyListProperty<LetterTileModel> getWordWindowTilesProperty()
```

Returns:

Read-only list of tiles currently in the word area

getTileRackTilesProperty

```
public javafx.beans.property.ReadOnlyListProperty<LetterTileModel> getTileRackTilesProperty()
```

Returns:

Read-only list of tiles currently in the rack

getRedrawWindowTilesProperty

```
public javafx.beans.property.ReadOnlyListProperty<LetterTileModel> getRedrawWindowTilesProperty()
```

Returns:

Read-only list of tiles currently in the redraw window.

getPlayersTotalPoints

```
public javafx.beans.property.ReadOnlyIntegerProperty getPlayersTotalPoints()
```

Returns:

the total points property to observe.

wordPointsProperty

```
public javafx.beans.property.ReadOnlyIntegerProperty wordPointsProperty()
```

Returns:

the sum combo points property to observe.

See Also:

[setWordPoints\(int\)](#)

getPlayersCurrentPoints

```
public javafx.beans.property.ReadOnlyIntegerProperty getPlayersCurrentPoints()
```

Returns:

the players current level points property to observe.

wordMultiProperty

```
public javafx.beans.property.ReadOnlyIntegerProperty wordMultiProperty()
```

word multiplier.

Returns:

multiplier.

See Also:

[setWordMulti\(int\)](#)

getIsRedrawActive

```
public javafx.beans.property.ReadOnlyBooleanProperty getIsRedrawActive()
```

gets the redraw property.

Returns:

returns indication if redraw active.

setIsRedrawActive

```
public void setIsRedrawActive(boolean newValue)
```

set redraw active.

Parameters:

`newValue` - get if redraw window is on screen.

setPlayersScore

```
protected void setPlayersScore(int newValue)
```

addTileToWordWindow

```
protected void addTileToWordWindow(LetterTileModel tile)
```

addTileToRack

```
protected void addTileToRack(LetterTileModel tile)
```

addTileToRedrawWindow

```
protected void addTileToRedrawWindow(LetterTileModel tile)
```

onLostLevel

```
public void onLostLevel()
```

Called when the level has been lost. resets the players session info and logs back out to the login screen.

onWonLevel

```
public void onWonLevel()
```

Called when level has been won. reset the per level info: redraws plays. Goes to shop window.

hasWon

```
public boolean hasWon()
```

returns true if player has won.

Returns:

value indicating if player has won.

hasLost

```
public boolean hasLost()
```

true if player has lost

Returns:

value indicating if player has lost.

tryMoveTile

```
public boolean tryMoveTile(LetterTileModel tile)
```

determines where tile should go and moves it

Parameters:

`tile` - The tile to move

Returns:

true if move was successful, false otherwise

getCurrentWord

```
public String2 getCurrentWord()
```

Gets the current word formed by tiles in the word area

Returns:

returns current word string.

isCurrentWordValid

```
public boolean isCurrentWordValid()
```

returns true if word is in dictionary.

Returns:

value indicating if word is valid.

redrawTiles

```
public void redrawTiles()
```

redraws tiles into the tile rack and removes from redraw window.

addToCombo

```
public void addToCombo(LetterTileModel tile)
```

add combo sum and multiCombo

Parameters:

tile - tile.

calcTotalWordScore

```
public int calcTotalWordScore()
```

Returns:

total score int

setWordPoints

```
public void setWordPoints(int newWordPoints)
```

sets the current word points before multipliers

Parameters:

newWordPoints - the new word points value

setWordMulti

```
public void setWordMulti(int newMulti)
```

sets the current word multiplier

Parameters:

newMulti - the new multiplier value

setTotalScore

```
public void setTotalScore(int totalScore)
```

Parameters:

totalScore - from calcTotalScore sets Total Score

playTiles

```
public void playTiles()
```

clears the word row tiles. and refills the tile rack. and decreases the plays left.

returnRedrawTilesToTheRack

`public void returnRedrawTilesToTheRack()`

sends the selected redraw tiles back to the rack

setupNewLevel

`public void setupNewLevel()`

Initialise new level. Clears word row, redraw rack. draws new tiles for the player's tile rack.

resetCombo

`public void resetCombo()`

resets counts for sum and multi in combo

Module com.example.project

Package com.example.project.models.gameScreens

Class LoginModel

java.lang.Object[↳]
 com.example.project.models.gameScreens.GameScreenModel
 com.example.project.models.gameScreens.LoginModel

```
public class LoginModel  
extends GameScreenModel
```

Login model class.

Field Summary

Fields inherited from class com.example.project.models.gameScreens.GameScreenModel

logger, session

Constructor Summary

Constructors

Constructor

Description

`LoginModel(Session session, UsersDAO dao, PasswordHasher passwordHasher)`

constructor.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

`javafx.beans.property.ReadOnlyStringProperty`

`getWelcomeTextProperty()`

Gets the info text property.

`void`

`onLoginClicked(String✉ username, String✉ password)`

`void`

`onSignUpClicked(String✉ username, String✉ password)`

Adds user to database.

Methods inherited from class java.lang.Object[↳]

`clone✉, equals✉, finalize✉, getClass✉, hashCode✉, notify✉, notifyAll✉, toString✉, wait✉, wait✉, wait✉`

Constructor Details

LoginModel

```
public LoginModel(Session session,  
                  UsersDAO dao,  
                  PasswordHasher passwordHasher)
```

constructor.

Parameters:

session - session to use for the game.
dao - users database implementation.
passwordHasher - password hasher for this login

Method Details

getWelcomeTextProperty

```
public javafx.beans.property.ReadOnlyStringProperty getWelcomeTextProperty()
```

Gets the info text property.

Returns:

ReadonlyStringProperty.

onLoginClicked

```
public void onLoginClicked(String username,  
                           String password)
```

Parameters:

username - username.

password - password.

onSignUpClicked

```
public void onSignUpClicked(String username,  
                           String password)
```

Adds user to database.

Parameters:

username - username

password - password

Module com.example.project
Package com.example.project.models.gameScreens

MainMenuModel

java.lang.Object
 com.example.project.models.gameScreens.GameScreenModel
 com.example.project.models.gameScreens.MainMenuModel

```
public class MainMenuModel  
extends GameScreenModel
```

main menu model class

Field Summary

Fields inherited from class com.example.project.models.gameScreens.GameScreenModel

logger, session

Constructor Summary

Constructors

Constructor

Description

MainMenuModel(Session session)

constructor.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

void

onLogoutClicked()

switches to the login screen

void

onStartClicked()

switches to the level screen

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

MainMenuModel

```
public MainMenuModel(Session session)
```

constructor.

Parameters:

session - session to use for the game.

Method Details

onStartClicked

```
public void onStartClicked()
```

switches to the level screen

onLogoutClicked

```
public void onLogoutClicked()
```

switches to the login screen

Module com.example.project
Package com.example.project.models.gameScreens

Class ScoreChimePlayer

java.lang.Object
 com.example.project.models.gameScreens.ScoreChimePlayer

```
public class ScoreChimePlayer  
extends Object
```

plays a note from the F major scale ascending in pitch each time for a nice score combo sound.

Constructor Summary

Constructors

Constructor

Description

`ScoreChimePlayer()`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

`void`

`playNextNote()`

plays the note then increments the int index.

`void`

`reset()`

resets back to 0.

Methods inherited from class java.lang.Object

`clone()`, `equals()`, `finalize()`, `getClass()`, `hashCode()`, `notify()`, `notifyAll()`, `toString()`, `wait()`, `wait()`, `wait()`

Constructor Details

ScoreChimePlayer

```
public ScoreChimePlayer()
```

Method Details

reset

```
public void reset()
```

resets back to 0.

playNextNote

```
public void playNextNote()
```

```
plays the note then increments the int index.
```

Copyright © 2025. All rights reserved.

Module com.example.project

Package com.example.project.controllers.gameScreens

Record Class GameScreenController.SidebarLoaded

java.lang.Object[✉]
 java.lang.Record[✉]
 com.example.project.controllers.gameScreens.GameScreenController.SidebarLoaded

Enclosing class:

GameScreenController

```
protected static record GameScreenController.SidebarLoaded(javafx.scene.Parent node,  
SidebarController controller)  
extends Record✉
```

Constructor Summary

Constructors

Modifier

Constructor

Description

protected

SidebarLoaded(javafx.scene.Parent node, SidebarController controller)

Creates an instance of a SidebarLoaded record class.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

SidebarController

controller()

Returns the value of the controller record component.

final boolean

equals(Object[✉] o)

Indicates whether some other object is "equal to" this one.

final int

hashCode()

Returns a hash code value for this object.

javafx.scene.Parent

node()

Returns the value of the node record component.

final String[✉]

toString()

Returns a string representation of this record class.

Methods inherited from class java.lang.Object[✉]

clone[✉], finalize[✉], getClass[✉], hashCode[✉], notify[✉], notifyAll[✉], wait[✉], wait[✉], wait[✉]

Constructor Details

SidebarLoaded

```
protected SidebarLoaded(javafx.scene.Parent node,  
                      SidebarController controller)
```

Creates an instance of a SidebarLoaded record class.

Parameters:

node - the value for the node record component

controller - the value for the controller record component

Method Details

toString

```
public final String toString()
```

Returns a string representation of this record class. The representation contains the name of the class, followed by the name and value of each of the record components.

Specified by:

[toString](#) in class [Record](#)

Returns:

a string representation of this object

hashCode

```
public final int hashCode()
```

Returns a hash code value for this object. The value is derived from the hash code of each of the record components.

Specified by:

[hashCode](#) in class [Record](#)

Returns:

a hash code value for this object

equals

```
public final boolean equals(Object o)
```

Indicates whether some other object is "equal to" this one. The objects are equal if the other object is of the same class and if all the record components are equal. All components in this record class are compared with [Objects::equals\(Object, Object\)](#).

Specified by:

[equals](#) in class [Record](#)

Parameters:

o - the object with which to compare

Returns:

true if this object is the same as the o argument; false otherwise.

node

```
public javafx.scene.Parent node()
```

Returns the value of the node record component.

Returns:

the value of the node record component

controller

```
public SidebarController controller()
```

Returns the value of the controller record component.

Returns:

the value of the controller record component

Module com.example.project

Package com.example.project.models.gameScreens

Class ShopModel

java.lang.Object
 com.example.project.models.gameScreens.GameScreenModel
 com.example.project.models.gameScreens.ShopModel

public class **ShopModel**
extends [GameScreenModel](#)

Shop Model.

Property Summary

Properties

Type

Property

Description

`javafx.beans.property.ListProperty<UpgradeTileModel>`

currentShopItems

Current items in the shop row that you can buy.

`javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel>`

playersUpgrades

get what upgrades the player currently has.

Field Summary

Fields inherited from class com.example.project.models.gameScreens.GameScreenModel

`logger, session`

Constructor Summary

Constructors

Modifier

Constructor

Description

ShopModel(Session session)

Constructor

protected

ShopModel(Session session, Logger logger)

Constructor for tests.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

```
boolean  
canPurchase(UpgradeTileModel tile)
```

Determines whether the player can afford to purchase the specified upgrade tile.

```
javafx.beans.property.ListProperty<UpgradeTileModel>  
currentShopItemsProperty()
```

Current items in the shop row that you can buy.

```
void  
onNextLevelPressed()
```

exists shop and increments level requirement for the next level.

```
javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel>  
playersUpgradesProperty()
```

get what upgrades the player currently has.

```
void  
purchase(UpgradeTileModel tileClickedOn)
```

This should attempt to purchase an upgrade tile from the shop.

```
void  
regenerateShopItems()  
create new shop items.
```

Methods inherited from class java.lang.Object

```
clone(), equals(), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(), wait()
```

Property Details

currentShopItems

```
public javafx.beans.property.ListProperty<UpgradeTileModel> currentShopItemsProperty
```

Current items in the shop row that you can buy.

See Also:

[currentShopItemsProperty\(\)](#)

playersUpgrades

```
public javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> playersUpgradesProperty
```

get what upgrades the player currently has.

See Also:

[playersUpgradesProperty\(\)](#)

Constructor Details

ShopModel

```
protected ShopModel(Session session,  
                   Logger logger)
```

Constructor for tests.

Parameters:

session - session.

logger - logger to use.

ShopModel

```
public ShopModel(Session session)
```

Constructor

Parameters:

session - game session.

Method Details

currentShopItemsProperty

```
public javafx.beans.property.ListProperty<UpgradeTileModel> currentShopItemsProperty()
```

Current items in the shop row that you can buy.

Returns:

shop items.

regenerateShopItems

```
public void regenerateShopItems()
```

create new shop items.

playersUpgradesProperty

```
public javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> playersUpgradesProperty()
```

get what upgrades the player currently has.

Returns:

returns the list of upgrades.

purchase

```
public void purchase(UpgradeTileModel tileClickedOn)
```

This should attempt to purchase an upgrade tile from the shop. Verifies the player has sufficient funds, deducts the cost, removes the item from the shop, and logs the transaction.

Parameters:

tileClickedOn - the upgrade tile the player is trying to purchase

Throws:

IllegalArgumentException[¶] - if tileClickedOn is empty (null)

See Also:

to check affordability before calling this method,
for the payment mechanism,
for adding to player's collection

canPurchase

```
public boolean canPurchase(UpgradeTileModel tile)
```

Determines whether the player can afford to purchase the specified upgrade tile. Compares the player's current money against the tile's cost.

Parameters:

tile - the upgrade tile the player wants to buy thus check affordability for

Returns:

true if the player has enough money to purchase the tile, false if the player is broke and can't

Throws:

IllegalArgumentException[¶] - if tile is empty

See Also:

[for tile pricing](#)

onNextLevelPressed

`public void onNextLevelPressed()`

exists shop and increments level requirement for the next level.

Uses of Class

com.example.project.models.gameScreens.DailyRewardModel

No usage of com.example.project.models.gameScreens.DailyRewardModel

Copyright © 2025. All rights reserved.

Uses of Enum Class

com.example.project.models.gameScreens.DailyRewardType

Packages that use DailyRewardType

Package

Description

com.example.project.models.gameScreens

Uses of DailyRewardType in com.example.project.models.gameScreens

Methods in com.example.project.models.gameScreens that return DailyRewardType

Modifier and Type

Method

Description

static DailyRewardType

DailyRewardModel.rollReward()

Randomly selects a daily reward.

static DailyRewardType

DailyRewardType.valueOf(String[?] name)

Returns the enum constant of this class with the specified name.

static DailyRewardType[]

DailyRewardType.values()

Returns an array containing the constants of this enum class, in the order they are declared.

Methods in com.example.project.models.gameScreens with parameters of type DailyRewardType

Modifier and Type

Method

Description

static void

DailyRewardModel.applyReward(DailyRewardType reward)

Applies the effect of the given reward to the session and marks it as claimed.

Uses of Class com.example.project.models.gameScreens.GameScreenModel

Packages that use GameScreenModel

Package

Description

com.example.project.models.gameScreens

Uses of GameScreenModel in com.example.project.models.gameScreens

Subclasses of GameScreenModel in com.example.project.models.gameScreens

Modifier and Type

Class

Description

class

LevelModel

Represents the level model.

class

LoginModel

Login model class.

class

MainMenuModel

main menu model class

class

ShopModel

Shop Model.

Uses of Class com.example.project.models.gameScreens.LevelModel

Packages that use LevelModel

Package

Description

com.example.project.controllers.gameScreens

com.example.project.controllers.gameScreens.animations

com.example.project.services

Uses of LevelModel in com.example.project.controllers.gameScreens

Methods in com.example.project.controllers.gameScreens with parameters of type LevelModel

Modifier and Type

Method

Description

void

`SidebarController.setupProperties(LevelModel levelModel)`

Setup sync able properties.

Constructors in com.example.project.controllers.gameScreens with parameters of type LevelModel

Modifier

Constructor

Description

protected

`LevelController(LevelModel model)`

Uses of LevelModel in com.example.project.controllers.gameScreens.animations

Constructors in com.example.project.controllers.gameScreens.animations with parameters of type LevelModel

Modifier

Constructor

Description

`LevelScoreSequence(List<LetterTileController> wordTileControllers, LevelModel levelModel, javafx.scene.control.Label comboCountLabel, javafx.scene.control.Label multiplierLabel)`

Constructor.

Uses of LevelModel in com.example.project.services

Methods in com.example.project.services that return LevelModel

Modifier and Type

Method

Description

LevelModel

`Session.getLevelModel()`

Methods in com.example.project.services with parameters of type LevelModel

Modifier and Type

Method

Description

void

`Session.setLevelModel(LevelModel levelModel)`

sets the session's level model

Uses of Class com.example.project.models.gameScreens.LoginModel

No usage of com.example.project.models.gameScreens.LoginModel

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.models.gameScreens.MainMenuModel

No usage of com.example.project.models.gameScreens.MainMenuModel

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.models.gameScreens.ScoreChimePlayer

Packages that use ScoreChimePlayer

Package

Description

com.example.project.models.gameScreens

Uses of ScoreChimePlayer in com.example.project.models.gameScreens

Methods in com.example.project.models.gameScreens that return ScoreChimePlayer

Modifier and Type

Method

Description

ScoreChimePlayer

LevelModel.getTileScoreSoundPlayer()

Gets the tile score sound effect player.

Uses of Class com.example.project.models.gameScreens.ShopModel

Packages that use ShopModel

Package

Description

com.example.project.controllers.gameScreens

Uses of ShopModel in com.example.project.controllers.gameScreens

Constructors in com.example.project.controllers.gameScreens with parameters of type ShopModel

Modifier

Constructor

Description

protected

`ShopController(ShopModel model, UpgradeTileGroup players, UpgradeTileGroup shopItems, Logger logger)`

protected constructor for unit testing with mock model injection.

Package com.example.project.models.gameScreens

package com.example.project.models.gameScreens

Related Packages

Package

Description

[com.example.project.models](#)

[com.example.project.models.popups](#)

[com.example.project.models.tileGroups](#)

[com.example.project.models.tiles](#)

All Classes and Interfaces

Classes

Enum Classes

Class

Description

DailyRewardModel

Model for handling daily reward logic and state.

DailyRewardType

Enum representing the possible daily reward outcomes.

GameScreenModel

Game Screen Model.

LevelModel

Represents the level model.

LoginModel

Login model class.

MainMenuModel

main menu model class

ScoreChimePlayer

plays a note from the F major scale ascending in pitch each time for a nice score combo sound.

ShopModel

Shop Model.

Module com.example.project

Package com.example.project.controllers.gameScreens

Class GameScreenController

java.lang.Object
com.example.project.controllers.gameScreens.GameScreenController

Direct Known Subclasses:

DailyRewardController, LevelController, LoginController, MainMenuController, ShopController

```
public abstract class GameScreenController  
extends Object
```

Game screen controller that has some startup on screen thing todo. Level, shop controllers.

Nested Class Summary

Nested Classes

Modifier and Type

Class

Description

protected static final record

GameScreenController.SidebarLoaded

Field Summary

Fields

Modifier and Type

Field

Description

protected Logger

logger

Constructor Summary

Constructors

Modifier

Constructor

Description

protected

GameScreenController()

Method Summary

All Methods

Instance Methods

Abstract Methods

Concrete Methods

Modifier and Type

Method

Description

protected GameScreenController.SidebarLoaded

```
loadSidebar()
```

```
abstract void
```

```
onSceneChangedToThis()
```

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

Methods inherited from class java.lang.Object

```
clone✉, equals✉, finalize✉, getClass✉, hashCode✉, notify✉, notifyAll✉, toString✉, wait✉, wait✉, wait✉
```

Field Details

logger

```
protected Logger logger
```

Constructor Details

GameScreenController

```
protected GameScreenController()
```

Method Details

onSceneChangedToThis

```
public abstract void onSceneChangedToThis()
```

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

loadSidebar

```
protected GameScreenController.SidebarLoaded loadSidebar()
```

Hierarchy For Package com.example.project.models.gameScreens

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#)
 - [com.example.project.models.gameScreens.DailyRewardModel](#)
 - [com.example.project.models.gameScreens.GameScreenModel](#)
 - [com.example.project.models.gameScreens.LevelModel](#)
 - [com.example.project.models.gameScreens.LoginModel](#)
 - [com.example.project.models.gameScreens.MainMenuModel](#)
 - [com.example.project.models.gameScreens.ShopModel](#)
 - [com.example.project.models.gameScreens.ScoreChimePlayer](#)

Enum Class Hierarchy

- [java.lang.Object](#)
 - [java.lang.Enum](#) (implements [java.lang.Comparable](#), [java.lang.constant.Constable](#), [java.io.Serializable](#))
 - [com.example.project.models.gameScreens.DailyRewardType](#)

Copyright © 2025. All rights reserved.

Uses of Package com.example.project.models.gameScreens

Packages that use com.example.project.models.gameScreens

Package

Description

com.example.project.controllers.gameScreens

com.example.project.controllers.gameScreens.animations

com.example.project.models.gameScreens

com.example.project.services

Classes in com.example.project.models.gameScreens used by com.example.project.controllers.gameScreens

Class

Description

LevelModel

Represents the level model.

ShopModel

Shop Model.

Classes in com.example.project.models.gameScreens used by com.example.project.controllers.gameScreens.animation

Class

Description

LevelModel

Represents the level model.

Classes in com.example.project.models.gameScreens used by com.example.project.models.gameScreens

Class

Description

DailyRewardType

Enum representing the possible daily reward outcomes.

GameScreenModel

Game Screen Model.

ScoreChimePlayer

plays a note from the F major scale ascending in pitch each time for a nice score combo sound.

Classes in com.example.project.models.gameScreens used by com.example.project.services

Class

Description

LevelModel

Represents the level model.

Module com.example.project

Package com.example.project.models

package com.example.project.models

Related Packages

Package

Description

[com.example.project](#)

[com.example.project.models.gameScreens](#)

[com.example.project.models.popups](#)

[com.example.project.models.tileGroups](#)

[com.example.project.models.tiles](#)

[com.example.project.controllers](#)

[com.example.project.services](#)

Classes

Class

Description

User

Represents a user in the application that can log in.

Hierarchy For Package com.example.project.models

Package Hierarchies:

All Packages

Class Hierarchy

- [java.lang.Object](#) ↗
 - [com.example.project.models.User](#)

Copyright © 2025. All rights reserved.

Uses of Package com.example.project.models

Packages that use com.example.project.models

Package

Description

com.example.project.services

com.example.project.services.sqlite.dAOs

Classes in com.example.project.models used by com.example.project.services

Class

Description

User

Represents a user in the application that can log in.

Classes in com.example.project.models used by com.example.project.services.sqlite.dAOs

Class

Description

User

Represents a user in the application that can log in.

Module com.example.project
Package com.example.project.models.popups

Class DefinitionPopup

java.lang.Object ↗
 com.example.project.models.popups.PopupModel
 com.example.project.models.popups.DefinitionPopup

```
public class DefinitionPopup  
extends PopupModel
```

Represents Definition window called when a word is played

Property Summary

Properties

Type

Property

Description

javafx.beans.property.ReadOnlyStringProperty

definition

javafx.beans.property.ReadOnlyStringProperty

word

Field Summary

Fields inherited from class com.example.project.models.popups.PopupModel

paperSoundPlayer, reversePaperSoundPlayer

Constructor Summary

Constructors

Constructor

Description

DefinitionPopup()

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

javafx.beans.property.ReadOnlyStringProperty

definitionProperty()

String ↗

getFXMLPath()

gets FXML path

```
javafx.beans.property.ReadOnlyBooleanProperty
```

```
getIsDefinitionActive()
```

```
void
```

```
setIsDefinitionActive(boolean newState)
```

```
toggle isDefinitionActive
```

```
void
```

```
setPopup(String currentWord)
```

```
javafx.beans.property.ReadOnlyStringProperty
```

```
wordProperty()
```

Methods inherited from class com.example.project.models.popups.PopupModel

```
getPaperSoundPlayer, getReversePaperSoundPlayer
```

Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Property Details

definition

```
public javafx.beans.property.ReadOnlyStringProperty definitionProperty
```

See Also:

```
definitionProperty()
```

word

```
public javafx.beans.property.ReadOnlyStringProperty wordProperty
```

See Also:

```
wordProperty()
```

Constructor Details

DefinitionPopup

```
public DefinitionPopup()
```

Method Details

definitionProperty

```
public javafx.beans.property.ReadOnlyStringProperty definitionProperty()
```

Returns:

```
returns property of definition
```

wordProperty

```
public javafx.beans.property.ReadOnlyStringProperty wordProperty()
```

Returns:

returns property of word

getIsDefinitionActive

```
public javafx.beans.property.ReadOnlyBooleanProperty getIsDefinitionActive()
```

Returns:

returns boolean

setIsDefinitionActive

```
public void setIsDefinitionActive(boolean newState)
```

toggle isDefinitionActive

Parameters:

newState - current state of definition window

setPopup

```
public void setPopup(String2 currentWord)
```

Parameters:

currentWord - Word, when OnPlayButton is passed

getFXMLPath

```
public String2 getFXMLPath()
```

Description copied from class: [PopupModel](#)

gets FXML path

Specified by:

[getFXMLPath](#) in class [PopupModel](#)

Returns:

string path

Module com.example.project

Package com.example.project.models.popups

Class PopupModel

java.lang.Object[✉]
com.example.project.models.popups.PopupModel

Direct Known Subclasses:

DefinitionPopup

```
public abstract class PopupModel  
extends Object✉
```

Parent class for popup windows

Field Summary

Fields

Modifier and Type

Field

Description

```
protected final GameSoundPlayer
```

paperSoundPlayer

```
protected final GameSoundPlayer
```

reversePaperSoundPlayer

Constructor Summary

Constructors

Constructor

Description

PopupModel()

Method Summary

All Methods

Instance Methods

Abstract Methods

Concrete Methods

Modifier and Type

Method

Description

```
abstract String✉
```

getFXMLPath()

gets FXML path

GameSoundPlayer

getPaperSoundPlayer()

gets paper sound player

GameSoundPlayer

getReversePaperSoundPlayer()

gets reversed paper sound player

Methods inherited from class java.lang.Object

clone[✉], equals[✉], finalize[✉], getClass[✉], hashCode[✉], notify[✉], notifyAll[✉], toString[✉], wait[✉], wait[✉], wait[✉]

Field Details

paperSoundPlayer

protected final GameSoundPlayer paperSoundPlayer

reversePaperSoundPlayer

protected final GameSoundPlayer reversePaperSoundPlayer

Constructor Details

PopupModel

public PopupModel()

Method Details

getFXMLPath

public abstract String[✉] getFXMLPath()

gets FXML path

Returns:

string path

getPaperSoundPlayer

public GameSoundPlayer getPaperSoundPlayer()

gets paper sound player

Returns:

sound player

getReversePaperSoundPlayer

public GameSoundPlayer getReversePaperSoundPlayer()

gets reversed paper sound player

Returns:

sound player

Uses of Class com.example.project.models.popups.DefinitionPopup

Packages that use DefinitionPopup

Package

Description

com.example.project.controllers.popupControllers

Uses of DefinitionPopup in com.example.project.controllers.popupControllers

Methods in com.example.project.controllers.popupControllers that return DefinitionPopup

Modifier and Type

Method

Description

DefinitionPopup

DefinitionController.getModel()

Methods in com.example.project.controllers.popupControllers with parameters of type DefinitionPopup

Modifier and Type

Method

Description

void

DefinitionController.initialize(DefinitionPopup model)

Uses of Class com.example.project.models.popups.PopupModel

Packages that use PopupModel

Package

Description

com.example.project.controllers.popupControllers

com.example.project.models.popups

com.example.project.services

Uses of PopupModel in com.example.project.controllers.popupControllers

Classes in com.example.project.controllers.popupControllers with type parameters of type PopupModel

Modifier and Type

Class

Description

class

PopupController<P extends PopupModel>

Parent class for PopupControllers

Fields in com.example.project.controllers.popupControllers declared as PopupModel

Modifier and Type

Field

Description

protected P

PopupController.model

Uses of PopupModel in com.example.project.models.popups

Subclasses of PopupModel in com.example.project.models.popups

Modifier and Type

Class

Description

class

DefinitionPopup

Represents Definition window called when a word is played

Uses of PopupModel in com.example.project.services

Methods in com.example.project.services with type parameters of type PopupModel

Modifier and Type

Method

Description

<C extends PopupController<P>, P extends PopupModel>

C

PopupLoader.createPopupController(P popupModel)

create popup controller.

Module com.example.project

Package com.example.project.models.popups

package com.example.project.models.popups

Related Packages

Package

Description

[com.example.project.models](#)

[com.example.project.models.gameScreens](#)

[com.example.project.models.tileGroups](#)

[com.example.project.models.tiles](#)

Classes

Class

Description

[DefinitionPopup](#)

Represents Definition window called when a word is played

[PopupModel](#)

Parent class for popup windows

Module com.example.project

Package com.example.project.controllers.gameScreens

Class LevelController

```
java.lang.Object
  com.example.project.controllers.gameScreens.GameScreenController
    com.example.project.controllers.gameScreens.LevelController
```

```
public class LevelController
extends GameScreenController
```

Controller for the level screen.

Nested Class Summary

Nested classes/interfaces inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
GameScreenController.SidebarLoaded
```

Field Summary

Fields inherited from class com.example.project.controllers.gameScreens.GameScreenController

```
logger
```

Constructor Summary

Constructors

Modifier

Constructor

Description

```
LevelController()
```

Constructor only called once each time application opened.

protected

```
LevelController(LevelModel model)
```

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

```
void
```

```
initialize()
```

```
protected void
```

```
onConfirmRedrawButton()
```

Handle redraw confirm button.

```
protected void
```

onPlayButton()

Handle play button

protected void onRedrawButton()

redraw button opens or cancels the redraw.

void

onSceneChangedToThis()

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

protected void onSkipButton()

Methods inherited from class com.example.project.controllers.gameScreens.GameScreenController

loadSidebar

Methods inherited from class java.lang.Object

clone[✉], equals[✉], finalize[✉], getClass[✉], hashCode[✉], notify[✉], notifyAll[✉], toString[✉], wait[✉], wait[✉], wait[✉]

Constructor Details

LevelController

public LevelController()

Constructor only called once each time application opened.

LevelController

protected LevelController(LevelModel model)

Method Details

initialize

public void initialize()

See Also:

for the money binding

onSceneChangedToThis

public void onSceneChangedToThis()

Description copied from class: GameScreenController

Called when the game scene is changed to one of the GameScenes Login, Level, Shop etc.

Specified by:

onSceneChangedToThis in class GameScreenController

onPlayButton

protected void onPlayButton()

Handle play button

onSkipButton

```
protected void onSkipButton()
```

onRedrawButton

```
protected void onRedrawButton()
```

redraw button opens or cancels the redraw.

onConfirmRedrawButton

```
protected void onConfirmRedrawButton()
```

Handle redraw confirm button.

Hierarchy For Package com.example.project.models.popups

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#) ↗
 - [com.example.project.models.popups.PopupModel](#)
 - [com.example.project.models.popups.DefinitionPopup](#)

Uses of Package com.example.project.models.popups

Packages that use com.example.project.models.popups

Package

Description

[com.example.project.controllers.popupControllers](#)

[com.example.project.models.popups](#)

[com.example.project.services](#)

Classes in com.example.project.models.popups used by com.example.project.controllers.popupControllers

Class

Description

[DefinitionPopup](#)

Represents Definition window called when a word is played

[PopupModel](#)

Parent class for popup windows

Classes in com.example.project.models.popups used by com.example.project.models.popups

Class

Description

[PopupModel](#)

Parent class for popup windows

Classes in com.example.project.models.popups used by com.example.project.services

Class

Description

[PopupModel](#)

Parent class for popup windows

Module com.example.project

Package com.example.project.models.tileGroups

Class LetterTileGroup

```
java.lang.Object
  com.example.project.models.tileGroups.TileGroup<LetterTileModel,LetterTileController>
    com.example.project.models.tileGroups.LetterTileGroup
```

```
public class LetterTileGroup
extends TileGroup<LetterTileModel,LetterTileController>
```

tile group that observes an observable list and updates the ui Tile Controller's nodes into their EmptyTileSlotController nodes.

Field Summary

Fields inherited from class com.example.project.models.tileGroups.TileGroup

container, onClickAction, tileControllerFactory, tileControllers

Constructor Summary

Constructors

Modifier

Constructor

Description

```
LetterTileGroup(int numberOfEmptyTileSlots, javafx.scene.layout.Pane container,
javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<?
<LetterTileController> onClickAction)
```

Constructor

```
LetterTileGroup(int numberOfEmptyTileSlots, javafx.scene.layout.Pane container,
javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<?
<LetterTileController> onClickHandler, List<?><Runnable> afterSyncActions)
```

Constructor

protected

```
LetterTileGroup(int numberOfEmptyTileSlots, javafx.scene.layout.Pane container,
javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList, Consumer<?
<LetterTileController> onClickHandler, List<?><Runnable> afterSyncActions, TileControllerFactory factory)
```

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

protected void

`updateVisuals()`

Methods inherited from class com.example.project.models.tileGroups.TileGroup

`getControllers`, `syncTiles`

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

LetterTileGroup

```
protected LetterTileGroup(int numberEmptyTileSlots,
                         javafx.scene.layout.Pane container,
                         javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList,
                         Consumer<LetterTileController> onClickHandler,
                         List<Runnable> afterSyncActions,
                         TileControllerFactory factory)
```

LetterTileGroup

```
public LetterTileGroup(int numberEmptyTileSlots,
                      javafx.scene.layout.Pane container,
                      javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList,
                      Consumer<LetterTileController> onClickHandler,
                      List<Runnable> afterSyncActions)
```

Constructor

Parameters:

numberEmptyTileSlots - number of max tiles in group (empty slots)

container - container to place all in.

observedList - the observed list.

onClickHandler - On tile click action.

afterSyncActions - additional synchronisation actions that need to happen when this observed list changes.

LetterTileGroup

```
public LetterTileGroup(int numberEmptyTileSlots,
                      javafx.scene.layout.Pane container,
                      javafx.beans.property.ReadOnlyListProperty<LetterTileModel> observedList,
                      Consumer<LetterTileController> onClickAction)
```

Constructor

Parameters:

numberEmptyTileSlots - number of max tiles in group (empty slots)

container - container to place all in.

observedList - the observed list.

onClickAction - On tile click action.

Method Details

updateVisuals

```
protected void updateVisuals()
```

Specified by:

[updateVisuals](#) in class [TileGroup<LetterTileModel,LetterTileController>](#)

Module com.example.project

Package com.example.project.models.tileGroups

Class TileGroup<modelType extends TileModel, controllerType extends TileController<modelType>>

java.lang.Object²
com.example.project.models.tileGroups.TileGroup<modelType,controllerType>

Type Parameters:

modelType - tile model type.

controllerType - controller type.

Direct Known Subclasses:

LetterTileGroup, UpgradeTileGroup

```
public abstract class TileGroup<modelType extends TileModel, controllerType extends TileController<modelType>>
extends Object2
```

Tile Group abstract class holds a row or column of tiles.

Field Summary

Fields

Modifier and Type

Field

Description

protected final javafx.scene.layout.Pane
container

protected Consumer²<controllerType>
onClickAction

protected TileControllerFactory
tileControllerFactory

protected final List²<controllerType>
tileControllers

Method Summary

All Methods

Instance Methods

Abstract Methods

Concrete Methods

Modifier and Type

Method

Description

List²<controllerType>

getControllers()

Gets the groups tile controllers.

void

syncTiles()

Sync tiles in this tile groups controller.

protected abstract void

```
updateVisuals()
```

Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Field Details

container

```
protected final javafx.scene.layout.Pane container
```

tileControllers

```
protected final List<controllerType extends TileController<modelType>> tileControllers
```

tileControllerFactory

```
protected TileControllerFactory tileControllerFactory
```

onClickAction

```
protected Consumer<controllerType extends TileController<modelType>> onClickAction
```

Method Details

updateVisuals

```
protected abstract void updateVisuals()
```

syncTiles

```
public void syncTiles()
```

Sync tiles in this tile groups controller.

getControllers

```
public List<controllerType> getControllers()
```

Gets the groups tile controllers.

Returns:

the letter tile groups controllers

Module com.example.project
Package com.example.project.models.tileGroups

Class UpgradeTileGroup

java.lang.Object
 com.example.project.models.tileGroups.TileGroup<UpgradeTileModel,UpgradeTileController>
 com.example.project.models.tileGroups.UpgradeTileGroup

```
public class UpgradeTileGroup  
extends TileGroup<UpgradeTileModel,UpgradeTileController>
```

tile group that observes an observable list and updates the ui nodes for some game tiles.

Field Summary

Fields inherited from class com.example.project.models.tileGroups.TileGroup

container, onClickAction, tileControllerFactory, tileControllers

Constructor Summary

Constructors

Constructor

Description

UpgradeTileGroup(javafx.scene.layout.Pane container,
javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> observedList)

Constructor with no additional sync action parameter.

UpgradeTileGroup(javafx.scene.layout.Pane container,
javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> observedList, Consumer<UpgradeTileController> onClickAction)

Constructor.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method

Description

protected void

updateVisuals()

Methods inherited from class com.example.project.models.tileGroups.TileGroup

getControllers, syncTiles

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

UpgradeTileGroup

```
public UpgradeTileGroup(javafx.scene.layout.Pane container,
                        javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> observedList,
                        Consumer<UpgradeTileController> onClickAction)
```

Constructor.

Parameters:

container - container all tiles are in.

observedList - the observed list that when changes this tile group will sync.

onClickAction - additional synchronisation actions that need to be called.

UpgradeTileGroup

```
public UpgradeTileGroup(javafx.scene.layout.Pane container,
                        javafx.beans.property.ReadOnlyListProperty<UpgradeTileModel> observedList)
```

Constructor with no additional sync action parameter.

Parameters:

container - container tiles are in.

observedList - the observed list that when changes this tile group will sync.

Method Details

updateVisuals

```
protected void updateVisuals()
```

Specified by:

`updateVisuals` in class `TileGroup<UpgradeTileModel, UpgradeTileController>`

Uses of Class **com.example.project.models.tileGroups.LetterTileGroup**

No usage of com.example.project.models.tileGroups.LetterTileGroup

Copyright © 2025. All rights reserved.

Uses of Class com.example.project.models.tileGroups.TileGroup

Packages that use TileGroup

Package

Description

com.example.project.models.tileGroups

Uses of TileGroup in com.example.project.models.tileGroups

Subclasses of TileGroup in com.example.project.models.tileGroups

Modifier and Type

Class

Description

class

LetterTileGroup

tile group that observes an observable list and updates the ui Tile Controller's nodes into their EmptyTileSlotController nodes.

class

UpgradeTileGroup

tile group that observes an observable list and updates the ui nodes for some game tiles.

Uses of Class com.example.project.models.tileGroups.UpgradeTileGroup

Packages that use UpgradeTileGroup

Package

Description

com.example.project.controllers.gameScreens

Uses of UpgradeTileGroup in com.example.project.controllers.gameScreens

Constructors in com.example.project.controllers.gameScreens with parameters of type UpgradeTileGroup

Modifier

Constructor

Description

protected

`ShopController(ShopModel model, UpgradeTileGroup players, UpgradeTileGroup shopItems, Logger logger)`

protected constructor for unit testing with mock model injection.

Module com.example.project

Package com.example.project.models.tileGroups

package com.example.project.models.tileGroups

Related Packages

Package

Description

[com.example.project.models](#)

[com.example.project.models.gameScreens](#)

[com.example.project.models.popups](#)

[com.example.project.models.tiles](#)

Classes

Class

Description

LetterTileGroup

tile group that observes an observable list and updates the ui Tile Controller's nodes into their EmptyTileSlotController nodes.

TileGroup<modelType extends TileModel, controllerType extends TileController<modelType>>

Tile Group abstract class holds a row or column of tiles.

UpgradeTileGroup

tile group that observes an observable list and updates the ui nodes for some game tiles.

Copyright © 2025. All rights reserved.

Hierarchy For Package com.example.project.models.tileGroups

Package Hierarchies:

[All Packages](#)

Class Hierarchy

- [java.lang.Object](#)
- [com.example.project.models.tileGroups.TileGroup<modelType,controllerType>](#)
 - [com.example.project.models.tileGroups.LetterTileGroup](#)
 - [com.example.project.models.tileGroups.UpgradeTileGroup](#)