

Dining layouts and table clearances


Dining layout starts with people and use scenarios. Compare table forms, map moving chairs and doors, and distinguish chair operation from a usable circulation route.

What you will accomplish

- Define users and table form
- Separate chair movement from circulation
- Calculate an explicit layout envelope

Define users and table form


Record daily and guest counts, actual chair models and access needs. Rectangular and round tables do not become interchangeable merely by seating the same number: legs, bases and chair widths affect usable positions. Draw actual chairs and check entry and knee space. For an extending table, prepare both closed and extended layouts.



Compare actual seating positions, bases and use states.

Separate chair movement from circulation


Draw the chair stored, occupied and pulled back for standing, then add the walking route and room/sideboard door swings. Empty space with a tucked chair does not prove passage when it is pulled out. Test credible simultaneous states. If serving blocks access, revise position, dimensions or service arrangement and record why.



Check passage in the relevant occupied and moving states.

Calculate an explicit layout envelope

Exercise only: a 900 mm wide top with an assumed total movement zone of 1000 mm measured from each side edge needs $1000 + 900 + 1000 = 2900$ mm. In a 3000 mm room, the arithmetic remainder is 100 mm. This is a geometric difference, not proof of comfort or accessibility. Verify the assumed zones against actual chairs, users, openings and project requirements.



2900 mm follows the exercise assumptions; it is not a universal clearance.

Worked case and decision

The 2900 mm exercise envelope fits within 3000 mm, but an open sideboard door intersects an occupied chair. Reject approval based on arithmetic alone; relocate the sideboard and retest chair movement and serving together.

Decision: resolve the door conflict, then repeat the movement check.

Check understanding

The arithmetic fits but a door hits a chair. What next?

- Revise and retest movement
- Approve the arithmetic alone
- Omit the door swing

Correct: Revise and retest movement. Dimensional fit does not prove conflict-free operation.

Lesson questions

Is the 1000 mm zone a universal rule?

No. It is an exercise assumption that must be checked against actual use and project requirements.

Practice

Submit daily/guest layouts, moving-chair and door envelopes, the exercise calculation and a conflict log.

Users and chair models

Layouts and movement

Calculation and decision

Review your work against the criteria. Saving it does not constitute technical project approval.

- Actual use defined
- Simultaneous states checked
- 2900 mm identified as an assumption