

Worktops, fronts, plinths and gaps


Coordinate worktops, fronts, plinths and joints through material, movement and maintenance requirements before fabrication.

What you will accomplish

- Document the top and cut-outs
- Coordinate fronts and gaps
- Review plinths, access and junctions

Document the top and cut-outs


Document material, build-up, support, edges and joints. Sink/appliance cut-outs follow the approved template and worktop fabricator's requirements, not a marketing size. Check sides, rails and underside fittings. A product change reopens cut-out and support review before cutting.



Coordinate product templates with worktop details.

Coordinate fronts and gaps


Draw front divisions, handles and the top/front junction. Give every gap a purpose, dimension and reference: motion, installation or appearance. Check that handles and top projections do not obstruct neighboring fronts or devices under the selected system.



Each defined gap needs a purpose and reference.

Review plinths, access and junctions

Show base, removable plinth and cleaning/service access. Do not conceal an airflow route required by the selected appliance. Record worktop/wall joints and joint materials with the relevant material supplier and identify inspection before concealing the detail.



The plinth is part of service coordination, not only appearance.

Worked case and decision

A replacement sink has the same marketed width, but its template and clips may differ. Hold cutting until the replacement template, rails, support and joint details are coordinated.

Decision: approve the coordinated template before cutting.

Check understanding

Does the same marketed size justify reusing the sink cut-out?

- No; review the replacement template
- Yes, without review
- Yes, if the colour matches

Correct: No; review the replacement template. Cut-out geometry and fixing details can differ by model.

Lesson questions

Should every gap be identical?

No. Function and the selected system may require documented differences.

Practice

Submit top/front/plinth sections, a cut-out/joint detail, references and hold points before cutting and concealment.

Document the top and cut-outs

Coordinate fronts and gaps

Review plinths, access and junctions

Review your work against the criteria. Saving it does not constitute technical project approval.

- Referenced model template
- Purposeful gaps
- Service access retained