Low-VOC UN-TACK Adhesive Remover and Cleaner



Overview

Carlisle's Low-VOC UN-TACK Adhesive Remover and Cleaner is designed to remove adhesives from a variety of surfaces including single-ply membranes, accessories, metal, plastic, rubber, and glass. Low-VOC UN-TACK is used to clean spray guns and hoses when an opened CAV-GRIP III cylinder is going to be stored for more than 30 days.

Features and Benefits

- Clears clogged spray guns and hoses
- Allows easy cleanup of excess adhesive and overspray
- VOC compliant in all 50 states

Coverage Rate

250 – 300 FT^2/(23-28 sq. m) surface area to be cleaned per Low-VOC UN-TACK cylinder.

Typical Properties and Characteristics

Physical Property	Typical Value
Color	Clear
Consistency	Aerosol Spray
Odor	Slight Solvent
VOC	33 g/l
Application Temperature	25°F to 100°F (-4°C to 38°C)
Packaging	#8 Aerosol Cylinder
Part Number	330793

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product. Carlisle's Low-VOC UN-TACK Adhesive Remover and Cleaner CANNOT be used to clean CAV-PRIME pressurized cylinders. *For application procedures and precautions please see the Low-VOC UN-TACK Adhesive Remover and Cleaner Product Data Sheet.

800-479-6832 | P.O. Box 7000 | Carlisle, PA 17013 | Fax: 717-245-7053 | **www.carlislesyntec.com**

06.14.24 © 2024 Carlisle.
REPRINT CODE: 610331 TPO-8517 - "CAV-GRIP III Adhesive/Primer Product Data Sheet"

Carlisle, CAV-GRIP, InsulBase, SecurShield, VapAir Seal, FAST, FleeceBACK and UN-TACK are trademarks of Carlisle. DensDeck is a registered trademark of Georgia-Pacific Gypsum LLC. The following trademarks used herein are owned by United States Gypsum Company or a related company: SECUROCK, USG, USG in stylized letters. LEED is a registered trademark of the U.S. Green Building Council.