

Comment	Description	Designator	Footprint	Quantity
MOC3043	Zero-Cross Triac Driver Output Optocoupler	A1	DIP762W46P254L889H508Q6B	1
B0505S		A2	B05_S-1WR3	1
1uF	Capacitor	C1, C2, C3, C8	C0402	4
100nF	Capacitor	C4, C5, C11	C0402	3
10uF/50V	Capacitor	C12, C19	C1206	2
100nF/50V	Capacitor	C16	C0402	1
22uF	Capacitor	C17, C18	C0603	2
ACST410-8BTR	TRIAC Alternistor - Snubberless, 600V, 4A DPAK	D1	TO229P994X240-3N (DPAK)	1
1N4148W	Diode	D2, D3, D4	SOD-123	3
0.8A	Fuse	F1	FUSE-SMD_L10.3-W3.2	1
GZ1608D601TF	Ferrite_Bead	FB1	0603	1
ME3116	60-V, 600-mA High Efficiency Wide Input Voltage Range Buck Converter	IC1	SOT95P280X110-6N (SOT23-6L)	1
FFC 0.5mm 10Pin 90°	FFC 0.5mm 10P Bottom Connection C262659	J1	TE_1-1734592-0	1
NLCV32T-100K-PF (10uH)	15uH	L1	L1210	1
KF142R-5.08-4P	KF142R-5.08-4P	P1	CONN-TH_4P-P5.08_KF142R-5.08-4P	1
KF2EDGR-3.81-5Pin	KF2EDGR-3.81-5Pin	P2	CONN-TH_5P-P3.81_KF2EDGR-3.81-5P	1
4 Pin male	4 Pin male	P7	TE_826647-4	1
AO3400A	30V N-Channel MOSFET	Q1	SOT23 Normal	1
IRLU024N	N-HEXFET Power MOSFET	Q3, Q4, Q5, Q6	TO228P680X240X837-3 (TO-251)	4
10	Resistor	R1, R2, R3, R7, R8, R9, R10, R17	0402	8
270	Resistor	R4	R0603	1
100	Resistor	R6	R0603	1
100k	Resistor	R12, R13, R14, R15, R19	0402	5
390	Resistor	R16	R0603	1
1k	Resistor	R18	0402	1
15k	Resistor	R20	0402	1
51k	Resistor	R46	R0603	1
10k	Resistor	R47	0402	1
UCC27517DBVR	4-A/4-A single-channel gate driver with 5-V UVLO and 13-ns prop delay in SOT-23 package	U1, U2, U3, U4	SOT23-5	4
pi160M30	n160M30	U5	SOIC127P600X180-16N SOP-16	1