

STAT 447 Assignment 3

Caden Hewlett

2024-01-23

Question 1 : Functions on the Unit Interval

For this question, use Simple Monte Carlo. The main twist compared to week one is that you will use a continuous random variable.

Part 1

Write a function called `mc_estimate` that takes a function $f : [0, 1] \rightarrow \mathbb{R}$ and outputs the Monte Carlo estimator of $\int_0^1 f(x)dx$ using $n = 100,000$ independent samples from $\text{unif}(0, 1)$.

NOTE: Because my computer could handle it, I used $M = 100,000$ rather than $M = 10,000$ just for fun. The results are similar (but obviously more precise for larger M .)

The function is created using the code below:

```
mc_estimate <- function(f){  
  # declare the number of iterations  
  M <- 100000  
  # randomly generate M total observations in [0, 1]  
  m_vals <- runif(M)  
  # then, for all m in random generations, evaluate f(m)  
  G_m <- f(m_vals)  
  # then compute the average  
  G_hat_m <- (1/M)*sum(G_m)  
  # and return  
  return(G_hat_m)  
}
```

Part 2

Consider the function $f : [0, 1] \rightarrow [0, \infty)$ given by:

$$f(x) = \frac{1}{\sqrt[3]{x^2(1-x)}}$$

Note, importantly, that

$$\mathcal{I}_1 = \int_0^1 f(x)dx = \frac{\pi}{\sin\left(\frac{\pi}{3}\right)}$$

Test your implementation of `mc_estimate` by checking that it produces an answer close to the value above. We'll start by computing the actual result:

```
expected = pi / (sin(pi/3))
expected
```

```
## [1] 3.627599
```

Now, we implement `mc_estimate`.

```
# Apollo 11 moon landing, as an integer
set.seed(19690720)

f <- function(x){
  1 / ( ((x^2)*(1 - x))^(1/3) )
}

observed <- mc_estimate(f)
observed
```

```
## [1] 3.629373
```

It seems we got pretty close! Let's calculate the percent difference.

```
(abs(observed - expected) / expected)*100
```

```
## [1] 0.04892034
```

It looks like there's about a 0.05% difference between \hat{G}_M for $M = 100,000$.

For completeness, I also ran the code with $M = 10,000$ and observed approximately a 2.52% difference.

Part 3

The following integral, known as the sine integral, does not admit a closed-form expression.

$$\mathcal{I}_2 = \int_0^1 \frac{\sin(t)}{t} dt$$

It does not admit a closed-form expression. Estimate its value using `mc_estimate(f)`.

To test our Monte Carlo Approximation, we will evaluate $\text{Si}(1)$ using the `pracma` package.

```
Si(1)
```

```
## [1] 0.9460831
```

Now, we can see how close our `mc_estimate` gets. We let $g(x) = \frac{\sin(x)}{x}$.

```
set.seed(19690720)

g <- function(x){
  sin(x) / x
}
observed = mc_estimate(g)
observed
```

```
## [1] 0.9464033
```

It looks like we got really close! Let's find the percent difference:

```
expected = Si(1)
# we overwrite our old variables for convenience (and memory)
(abs(observed - expected) / expected)*100
```

```
## [1] 0.03384555
```

It looks like there's about a 0.03% difference between \hat{G}_M for $M = 100,000$.

For completeness, I also ran the code with $M = 10,000$ and observed approximately a 0.09% difference.

Question 2 : Implementing SNIS for simPPLe

Part 1

First, install the package `distr`.

Since this is a `.Rmd` file, all packages are loaded at the beginning in a hidden cell with suppressed warnings.

```
"distr" %in% installed.packages()
```

```
## [1] TRUE
```

Part 2

Read this short tutorial on `distr`. Nothing to submit for this item.

For completeness, I will work through the tutorial on my own and place the results here.

```
# Commented out to avoid spamming outputs
# distPoisson <- Pois(lambda = 3.2)
#
# d(distPoisson)(2)
#
# sum(r(distPoisson)(10))
#
# d(sqrt(distPoisson))(2)
```

Part 3

Read the “scaffold code”, and use `distr` and two of the functions in the example to create a fair coin, flip it, and to compute the probability of that flip:

Part 4

Complete the implementation of the function `posterior`:

```
posterior = function(ppl_function, number_of_iterations) {  
  numerator = 0.0  
  denominator = 0.0  
  for (i in 1:number_of_iterations) {  
    weight <- 1.0  
    # update numerator and denominator  
  }  
  return(numerator/denominator)  
}
```

Part 5

Test your program by checking that you can approximate the posterior probability of the fair coin obtained in exercise 1, Q.2.