

1)

```
mysql> SELECT * FROM t1;
+-----+-----+
| id    | pattern |
+-----+-----+
| 1     | A       |
| 2     | B       |
| 3     | C       |
+-----+-----+
3 rows in set (0.00 sec)
```

2)

```
mysql> SELECT * FROM t2;
+-----+-----+
| id    | pattern |
+-----+-----+
| 10    | A       |
| 20    | B       |
| 30    | C       |
+-----+-----+
3 rows in set (0.00 sec)
```

JOINS:

CROSS JOIN:

```
mysql> SELECT t1.id, t2.id  
-> FROM t1  
-> CROSS JOIN t2;
```

id	id
3	10
2	10
1	10
3	20
2	20
1	20
3	30
2	30
1	30

```
9 rows in set (0.00 sec)
```

INNER JOIN:

```
mysql> SELECT t1.id, t2.id  
-> FROM t1  
-> INNER JOIN t2  
-> ON t1.pattern = t2.pattern;
```

id	id
1	10
2	20
3	30

```
3 rows in set (0.00 sec)
```

LEFT JOIN:

```
mysql> SELECT t1.id, t2.id
-> FROM t1
-> LEFT JOIN t2
-> ON t1.pattern = t2.pattern
-> ORDER BY t1.id;
```

id	id
1	10
2	20
3	30

3 rows in set (0.00 sec)

RIGHT JOIN:

```
mysql> SELECT t1.id, t2.id
-> FROM t1
-> RIGHT JOIN t2
-> ON t1.pattern = t2.pattern
-> ORDER BY t2.id;
```

id	id
1	10
2	20
3	30

3 rows in set (0.00 sec)