

PROCEDURES

```
mysql> CREATE TABLE Student (  
->     StudentID INT PRIMARY KEY,  
->     StudentName VARCHAR(50),  
->     Department VARCHAR(50),  
->     Marks INT  
-> );  
Query OK, 0 rows affected (0.11 sec)  
  
mysql> INSERT INTO Student VALUES  
-> (101, 'Indhu', 'CSE', 85),  
-> (102, 'Meghana', 'IT', 78),  
-> (103, 'Shalini', 'ECE', 92),  
-> (104, 'Teju', 'CSE', 67);  
Query OK, 4 rows affected (0.02 sec)  
Records: 4  Duplicates: 0  Warnings: 0
```

```
mysql> SELECT * FROM Student;  
+-----+-----+-----+-----+  
| StudentID | StudentName | Department | Marks |  
+-----+-----+-----+-----+  
|      101 | Indhu      | CSE       | 85    |  
|      102 | Meghana    | IT        | 78    |  
|      103 | Shalini    | ECE       | 92    |  
|      104 | Teju       | CSE       | 67    |  
+-----+-----+-----+-----+  
4 rows in set (0.04 sec)
```

PROCEDURES:

```
mysql> DELIMITER //
```

```
mysql>
```

```
mysql> CREATE PROCEDURE GetStudents()  
-> BEGIN  
->     SELECT * FROM Student;  
-> END //
```

```
Query OK, 0 rows affected (0.09 sec)
```

```
mysql>
```

```
mysql> DELIMITER ;
```

```
mysql> CALL GetStudents();
```

StudentID	StudentName	Department	Marks
101	Indhu	CSE	85
102	Meghana	IT	78
103	Shalini	ECE	92
104	Teju	CSE	67

```
4 rows in set (0.01 sec)
```

```
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> DELIMITER //
```

```
mysql>
```

```
mysql> CREATE PROCEDURE GetStudentsByDepartment(IN dept VARCHAR(50))  
-> BEGIN  
->     SELECT * FROM Student  
->     WHERE Department = dept;  
-> END //
```

```
Query OK, 0 rows affected (0.06 sec)
```

```
mysql>
```

```
mysql> DELIMITER ;
```

```
mysql> CALL GetStudentsByDepartment('CSE');
```

StudentID	StudentName	Department	Marks
101	Indhu	CSE	85
104	Teju	CSE	67

```
2 rows in set (0.05 sec)
```

```
Query OK, 0 rows affected (0.05 sec)
```

```
mysql> CALL GetStudentsByDepartment('IT');
+-----+-----+-----+-----+
| StudentID | StudentName | Department | Marks |
+-----+-----+-----+-----+
|          102 | Meghana      | IT         | 78     |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE GetStudentsAboveMarks(IN m INT)
-> BEGIN
->     SELECT StudentID, StudentName, Marks
->     FROM Student
->     WHERE Marks > m;
-> END //
Query OK, 0 rows affected (0.05 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL GetStudentsAboveMarks(80);
+-----+-----+-----+
| StudentID | StudentName | Marks |
+-----+-----+-----+
|          101 | Indhu        | 85     |
|          103 | Shalini      | 92     |
+-----+-----+-----+
2 rows in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)
```

```
mysql> SHOW PROCEDURE STATUS WHERE Db = 'ProcedureDB';
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Db      | Name                | Type      | Definer      | Modified      | Created      | Security_type | Comment | character_set_client | collation_connection | Database Collation |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| proceduredb | GetStudents          | PROCEDURE | root@localhost | 2026-08-11 11:19:01 | 2026-08-11 11:19:01 | DEFINER      |         | cp850                | cp850_general_ci    | utf8mb4_0900_ai_ci |
| proceduredb | GetStudentsAboveMarks | PROCEDURE | root@localhost | 2026-08-11 11:20:08 | 2026-08-11 11:20:08 | DEFINER      |         | cp850                | cp850_general_ci    | utf8mb4_0900_ai_ci |
| proceduredb | GetStudentsByDepartment | PROCEDURE | root@localhost | 2026-08-11 11:19:36 | 2026-08-11 11:19:36 | DEFINER      |         | cp850                | cp850_general_ci    | utf8mb4_0900_ai_ci |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
3 rows in set (0.06 sec)

mysql> DROP PROCEDURE GetStudents;
Query OK, 0 rows affected (0.05 sec)

mysql> DROP PROCEDURE GetStudentsByDepartment;
Query OK, 0 rows affected (0.06 sec)
```