

```

mysql> CREATE DATABASE 101exp;
Query OK, 1 row affected (0.01 sec)

mysql> USE 101exp;
Database changed
mysql> CREATE TABLE class (
    ->     name VARCHAR(20),
    ->     id INT
    -> );
Query OK, 0 rows affected (0.08 sec)

mysql> INSERT INTO class VALUES ('arun', 15);
Query OK, 1 row affected (0.05 sec)

mysql>
mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql> UPDATE class
    -> SET name = 'vijay'
    -> WHERE id = 15;
Query OK, 1 row affected (0.00 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> INSERT INTO class VALUES ('meena', 16);
Query OK, 1 row affected (0.00 sec)

mysql> SAVEPOINT B;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> INSERT INTO class VALUES ('kiran', 17);
Query OK, 1 row affected (0.00 sec)

mysql> SAVEPOINT C;
Query OK, 0 rows affected (0.00 sec)

mysql> SELECT * FROM class;
+-----+-----+
| name | id  |
+-----+-----+
| vijay | 15  |
| meena | 16  |
| kiran | 17  |
+-----+-----+
3 rows in set (0.00 sec)

```

```

mysql>
mysql> INSERT INTO class VALUES ('kiran', 17);
Query OK, 1 row affected (0.00 sec)

mysql> SAVEPOINT C;
Query OK, 0 rows affected (0.00 sec)

mysql> SELECT * FROM class;
+-----+-----+
| name  | id    |
+-----+-----+
| vijay | 15    |
| meena | 16    |
| kiran | 17    |
+-----+-----+
3 rows in set (0.00 sec)

mysql>
mysql> ROLLBACK TO B;
Query OK, 0 rows affected (0.01 sec)

mysql> SELECT * FROM class;
+-----+-----+
| name  | id    |
+-----+-----+
| vijay | 15    |
| meena | 16    |
+-----+-----+
2 rows in set (0.00 sec)

mysql> ROLLBACK TO A;
ERROR 1305 (42000): SAVEPOINT A does not exist
mysql> SELECT * FROM class;
+-----+-----+
| name  | id    |
+-----+-----+
| vijay | 15    |
| meena | 16    |
+-----+-----+
2 rows in set (0.00 sec)

```

N