

## Homework 7, CSE 232

**Due October 22** Note: On most of the problem sets through the semester, I'll put a horizontal line with "Optional" under it. Any problems below this section are encouraged - I think they're interesting and will help you learn the subject - but not necessary to complete in order to get credit for the homework.

### Problem 1

This week's problem is from the [Timus Online Judge #1210 - Kind Spirits](#). Here's the problem statement, slightly rewritten for clarity:

Ivanushka the Fool lives at the planet of 0th-level. It's very unpleasant to live there. An awful climate, 80 hours working week, bad food. He, as well as every inhabitant of his planet, dreams to get to a planet of N-th level. To the paradise.

At each of the i-th level planets there are several hyperspace transfers to some of the (i+1)-st level planets (but there are no reverse paths). Every transfer is guarded by a spirit. The spirits are usually evil: they demand many galactic bank-notes for each transfer. You know, everyone wants to go to a higher level planet, and one has to pay for the pleasure. More than Ivanushka can even imagine. However, extraordinary situations like a lack of a labor-force at one of the higher level planets sometimes happen, and then the spirits - the guards of the transfers — become kind. Sometimes they give galactic bank-notes themselves if only someone goes to their planets.

In order to embody his dream of visiting a heavenly planet Ivanushka has done two things. First of all, he has borrowed a complete map of the Universe. It's written on the map how much the spirits demand or give for a transfer from this or that planet to another one of the next higher level. Secondly, he has hired a staff of young talented programmers in order that they will help him to draw the way on the map from his planet to the one of Nth level to find the cheapest path possible, perhaps even earning some money along the way.

### Input


The first line contains an integer N ( $0 < N < 30$ ) — the number of levels of planets on Ivanushka's map. Following are N blocks of information that describe the interlevel transfers. More precisely, the ith informative block describes the scheme of transfers from (i-1)-st level planets to the ones of ith level. Those blocks are separated with a line that contains only the symbol “\*“.

Planets of each level are numbered with sequential positive integers starting from 1. Each level contains at most 30 planets. There is only one planet of 0th-level: the one that Ivanushka lives at. The first line of a block contains a number  $K_i$  — the number of planets of the ith level. Then follow  $K_i$  lines — one for each planet of the ith level. Every line consists of sequences of number pairs - the first number in the pair is the number of a planet of the previous (i-1)st level that has a transfer to the ( $K_i$ )th planet in the (i)th level and the second number is the corresponding fee for this transfer. The fee for each transfer is an integer number from -32768 to 32767; a negative fee means that the kind spirit is ready to pay for such a transfer. Each description line is ended by a zero.

### Output

The output should contain only a single integer — the minimum total fees that Ivanushka could pay to travel to any planet of the Nth level. The answer may be negative, which means that Ivanushka will not only get to a heavenly planet, but will earn some galactic bank-notes. It is known that there exists at least one way from Ivanushka's planet to one of the Nth level.

```
In [1]: from IPython.display import Image, display
        display(Image(filename='./week7_hwimg.png'))
```



- How can we represent the map of transfers between planets as a graph? What are the nodes of the graph? What are the edges of the graph? We talked about several different ways to classify graphs. Classify the graph of transfers between planets according to these distinctions. Is this graph directed or undirected, weighted or unweighted, simple or non-simple, and cyclic or acyclic?
- One way we might solve this problem is to use the shortest path algorithm (Dijkstra's) we learned about in class today starting from Ivan's home planet to calculate the shortest path to all other planets. How will this algorithm scale based on the number of planets and transfers in the map? How large will this be in the worst possible case?
- The graph of transfers has a particularly useful structure - transfers only occur between any level  $i$  and the next level  $i + 1$ . Suppose we performed a topological sort of the graph. What would be the first vertex in the sort? How would the levels of the planets be arranged in the topological sort?
- Suppose that we already know the cheapest way to reach each planet in level  $N - 1$ . Describe a function that takes as input these minimum costs for level  $N - 1$  and returns the minimum

*costs to reach each planet in level  $N$ . Which transfers do we have to examine to perform this calculation? All of them, or a particular subset?*

*e) Using the insight from part e, write an  $O(V+E)$  dynamic programming solution to the problem, test its correctness on the Timus Online Judge, and attach it to your homework.*

---

**Optional** No optional work this week.