

## Multiplayer Game Synchronization Protocol (PSJM)

### Status of This Memo

This document is not an Internet Standards Track specification; it is published for informational purposes.

This document is a product of EPITECH Network Programming course.  
It represents information that the author believes is valuable to share with the community.

### Abstract

This document specifies the Multiplayer Game Synchronization Protocol (PSJM), a simple UDP-based protocol for real-time multiplayer games. It facilitates player connections/disconnections, position synchronization, and game state updates.

### Table of Contents

1. Introduction .....	2
2. Packet Format .....	2
3. Packet Types .....	3
4. Packet Details .....	3
5. Communication Example .....	6
6. Technical Considerations .....	7
7. Map Format Protocol .....	7
8. References .....	8
9. Author's Address .....	8

### 1. Introduction

The Multiplayer Game Synchronization Protocol (PSJM) is a simple

UDP-based protocol for real-time multiplayer games. It supports:

- Player connections/disconnections
- Position synchronization
- Game state updates

## 2. Packet Format

All packets have a fixed 6-byte header:

```
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3  
+-----+-----+-----+-----+-----+-----+  
| Magic | ID | Sequence | Length |  
+-----+-----+-----+-----+-----+  
|       Payload        | End Flag |  
+-----+-----+-----+-----+-----+
```

### Fields:

- Magic Number
- Client ID
- Sequence Number
- Length of Payload
- Payload
- End flag (/r/n)

### Header:

- Magic Number
- Client ID
- Sequence Number
- Length

café-sur-cours Informational  
RFC Draft PSJM Protocol Specification

[Page 2]  
November 2025

### Body:

- Payload
- End flag

## 3. Packet Types

Client :

```
+-----+-----+  
| Value | Name   | Description          |  
+-----+-----+  
| 0x01 | CONNEXION | Client connection request |
```

0x03   DECONNEXION   End of connection or window close	
0x04   EVENT   Sent when event happens	

Server :

Value	Name	Description	
0x02   CONNEXION_ACC   Server response to connection			
0x05   GAME_STATE   Game state update			
0x06   SEND_MAP   Sends map state and elements			
0x07   END_MAP   Signals map has ended			
0x08   END_GAME   Signals a player victory			
0x09   CAN_START   Client ready to start movement			

## 4. Packet Details

### 4.1 Client Details

#### 4.1.1 CONNEXION (0x01) – Sent from client to server

Data:

- Player name (UTF-8, max 7 chars + null terminator)

café-sur-cours Informational

[Page 3]

RFC Draft PSJM Protocol Specification

November 2025

#### 4.1.2. DECONNEXION (0x03) – Client requests to disconnect to server

Data:

- Player ID (4 bytes)

#### 4.1.3. EVENT (0x04) – Client notifies input

Data:

- Player ID (4 bytes)
- Event type (1 byte, e.g., Up, Down, Left, Right, Space)

### 4.2 Server Details

#### 4.2.1 CONNEXION\_ACC (0x01) – Sent from Server to Client

Data:

- Player ID (4 bytes)

#### 4.2.2. GAME\_STATE (0x05) – Server sends games state to clients

Data:

- Player ID (4 bytes)
- State (position, velocity, state...)

#### 4.2.3. SEND\_MAP (0x06) – Server sends the map to the clients

Data:

- Player ID (4 bytes)
- Map Data (json)

#### 4.2.4. END\_MAP (0x07) – Server notify the end of the map

Data:

- Player ID (4 bytes)

#### 4.2.5. END\_GAME (0x08) – Server notify end of game and who won

Data:


- Player ID (4 bytes)
- Player ID who won (4 bytes)


#### 4.2.6. CAN\_START (0x09) – Server tells client game can start

Data:

- Player ID (4 bytes)

### 5. Communication Example





café-sur-cours Informational

[Page 5]

RFC Draft PSJM Protocol Specification

November 2025

## 6. Packet lost consideration

### 6.1 Tracking :

To avoid and track easier what was lost, each packet is numbered and assigned to a user so that the server can now when a package was lost.

### 6.2 Rollback :

The client will have an interpolation logic, so that if needed he can predict and advance until the server (the absolute truth), sends a new packet or starts reponding again.

## 7. Technical Considerations

- Encoding: UTF-8 text
- Number format: Network order (big-endian)
- Frequency: ?

## 8. Map Format Protocol

### 8.1. File Formatting

- File type :  
File containing the map must be a .json

### 8.2. Map Format

- Element type ?

### 8.3. Map Rendering

- One elem = ?x? pixel square

## 9. References

[RFC7322] Flanagan, H. and S. Ginoza, "RFC Style Guide", RFC 7322,  
DOI 10.17487/RFC7322, September 2014,  
<<https://www.rfc-editor.org/info/rfc7322>>.

## 10. Author's Address

Matisse Marsac  
EPITECH  
Email: [matisse.marsac@epitech.eu](mailto:matisse.marsac@epitech.eu)

Marin Lamy  
EPITECH  
Email: [Marin.lamy@epitech.eu](mailto:Marin.lamy@epitech.eu)

Elliott Tesnier  
EPITECH  
Email: [elliott.tesnier@epitech.eu](mailto:elliott.tesnier@epitech.eu)

Alban Roussee  
EPITECH  
Email: [alban.roussee@epitech.eu](mailto:alban.roussee@epitech.eu)