
a Train and collect

Architecture × initialization



V-scr 3 **V-IN** 2

R224-scr 2 **R224-IN** 2

Seed pair and reference panels

R32 3 + V-scr 3 runs; CIFAR-100 3 + 3




C10 7 CNNs **C100** 7 CNNs **IN-V2** 6 CNNs

PGD-10

b Measure transfer

Transfer matrix T

target-correct, PGD-10



CIFAR-10 20 models
CIFAR-100 15 models
ImageNetV2 14 models

Exact split per pair

$\log T = \log w + \log \tau + \tfrac{1}{2} r$

w vulnerability, τ symmetric similarity, r direction, per ordered pair

σ, ρ panel means; gradient cosine c, Mantel with log τ

tests

c Decide by rules

panel family: K-a, K-b, K-c (CIFAR-10)

two-by-two family: H1, H2, H3 (CIFAR-10)

attack side: best attack per source

masking check: AutoAttack

replication: K-a, K-b, K-c (CIFAR-100)

gradient family: Mantel tests (all three)

ImageNetV2 panel: descriptive, no decision

d Models in each transfer matrix

20 models, CIFAR-10 **15** models, CIFAR-100 **14** models, ImageNetV2

Protocol layer: conditioning sets nested, raw, target-correct, both-correct, successful-source; $h = -\log(1 - T)$ scale