Family	Test and quantity		Pre-registered values	Falsified if
			0 0.4 0.8	
CIFAR-10 panel	**K-a**	σ share of the gap, q	≥ 0.75	90% CI top < 0.5
	K-b	ρ(V-scr), log	±0.1	95% CI excludes 0, |mean| > 0.1
	K-c	Δw, own pair vs panel	≥ 0.3	90% CI top < 0.1
2 × 2 design	**H1**	Aσ scratch, ViT − ResNet	≤ −0.2	90% CI inside ±0.1
	H2	Iσ, init. × architecture	≥ 0.1	90% CI inside ±0.1
	H3	Aρ, architecture on ρ	±0.1	95% CI excludes 0, |est.| > 0.1
attack side	**B5**	retention, best / PGD	≥ 0.5	90% CI top < 0.5
masking check	**B6**	PGD-10 − AA, points	points scale > 10 pt	flagged models out, H1–H3 rerun
CIFAR-100	**K-a–c**	as the CIFAR-10 panel	as above	same rules
gradient	**H10**	Spearman(c, log τ)	0.5	est. ≤ 0.2 and p ≥ 0.2
	H10k	same, model effects out	0.3	est. ≤ 0.2 and p ≥ 0.2
ImageNetV2	**Aσ**	transformer − CNN	≤ −0.1	no decision
	Aσ Liu	Liu scratch pair	≤ −0.2	no decision

◆ predicted size ○ falsification threshold equivalence band ±δ, δ = 0.1 (log); Holm α = 0.05 per family