IEEE Access
Multidisciplinary ⋮ Rapid Review ⋮ Open Access Journal

Submitted for review.

Digital Object Identifier 10.1109/ACCESS.2026.0000000

Less a Weak Source than a Different One: Vulnerability, Similarity and Direction in CNN-ViT Adversarial Transfer under an Architecture-by-Initialization Design

ÇAĞRI ŞAHİN[1,2], AND ÖZAL YILDIRIM[2]
[1]Department of Software Engineering, Muş Alparslan University, 49250 Muş, Türkiye (e-mail: c.sahin@alparslan.edu.tr)
[2]Department of Software Engineering, Fırat University, 23119 Elazığ, Türkiye (e-mail: ozalyildirim@firat.edu.tr)

Corresponding author: Çağrı Şahin (e-mail: c.sahin@alparslan.edu.tr).

ABSTRACT Adversarially trained ViTs look like weak transfer sources against CNNs, but two models cannot split this asymmetry between source and target. We factor log target-correct transfer rates into target vulnerability, symmetric similarity and directional residual, averaged over a fixed panel of seven robust ResNet-family CNNs, testing registered predictions with two or three runs per cell (brackets: 90% intervals over training runs, conditional on test images and panel). On CIFAR-10, 0.936 [0.925, 0.948] of ViT-Tiny's panel source gap to ResNet-18 is symmetric, and the ViT's directional term ($+0.012$) is equivalent to zero within ± 0.10. In an architecture-by-initialization design on a matched pipeline, the scratch-trained ViT is less similar to the panel than the ResNet (-0.364 [-0.415, -0.314]), a contrast confounded with its lower clean accuracy. ImageNet initialization narrows it more for the ViT ($+0.260$); averaged over initialization, architecture leaves the log directional term within ± 0.10 ($+0.003$). The gap is retained under the best of PGD-10, momentum PGD and adapted token gradient regularization (0.960), and AutoAttack flags no new model for masking. On CIFAR-100 the symmetric share (0.840) replicates, but equivalence of the ViT's directional term is refuted ($+0.143$): there the ViT is also a directionally weaker source. A small directional term holds only on CIFAR-10, the log scale and a CNN panel; on the logit scale it is strongly negative. On ImageNetV2, transformers in two same-recipe pairs are descriptively less similar to the panel (-0.142), and input-gradient cosine tracks similarity on three datasets (Spearman 0.893–0.944 net of additive model effects).

INDEX TERMS Adversarial robustness, transfer attacks, transferability, Vision Transformer, convolutional neural networks, pre-registration, evaluation methodology

I. INTRODUCTION

Deep neural networks are vulnerable to adversarial examples, carefully crafted perturbations that cause confident misclassification while remaining bounded by a small norm budget [1], [2]. As Vision Transformers (ViTs) [3], [4] joined convolutional neural networks (CNNs) [5] as a dominant architecture family, a natural question followed: which family is more robust, and why?

The literature answers this question inconsistently. Under matched training recipes transformers do not surpass CNNs [6], whereas Benz et al. [7] find standardly trained ViTs more robust. Transfer studies disagree as well: several report that attacks move more easily from ViTs to CNNs than the reverse [7]–[9], Naseer et al. [10] find that perturbations crafted on ViTs transfer poorly under conventional attacks, and the direction measured in this paper is the opposite of the first group's, a point Section V returns to.

In our adversarially trained pair, examples crafted on the ViT fool the CNN less often than the reverse, and the ViT looks like a weak transfer source. Two different situations produce this pattern. The ViT may craft examples that carry less of what misleads other models, which would be a property of the source. Alternatively, the ViT and the CNNs may simply be dissimilar, so that transfer is low in both directions and the asymmetry within the pair is left to target vulnerability and a pair-specific residual. We call a model a weak source when its examples transfer poorly to third models, a quantity distinct from the asymmetry within the pair. A study with

one CNN and one ViT cannot separate the two situations, because its transfer matrix holds a single asymmetry and an additive split of it into source and target terms is not identified (Proposition 1). Separating them requires models outside the pair.

We train ResNet-18 and ViT-Tiny adversarially on CIFAR-10 [11], three runs each with a validation split fixed before training and per-sample logging over the full test set, and measure both against a fixed panel of seven robust CNNs from RobustBench [12]. Each log target-correct transfer rate is split into the target's white-box vulnerability w_j, a symmetric pairwise similarity $\bar{\tau}_{ij}$ and a directional residual r_{ij}, and the last two are averaged over the panel into a model's similarity σ and direction ρ (Section III-E). Six new runs, two per cell, complete a two-by-two design that crosses architecture with initialization, random or ImageNet, at a matched input pipeline and training recipe (Section III-D). Further blocks test the attack side with attacks selected per source, check for gradient masking with AutoAttack, replicate the panel tests on CIFAR-100, describe the same quantities for independently trained ImageNet models evaluated on ImageNetV2 [13], and ask whether input-gradient alignment [14] predicts pairwise similarity. Predictions, tests and decision rules for these blocks were registered before they were run. Those for the new two-by-two cells, the CIFAR-100 replication, the ImageNetV2 panel and the gradient tests are out of sample, whereas the CIFAR-10 panel tests extend a first seed that had been seen (Section III-J).

The first contribution is an identifiability result. In a two-model design the asymmetry identifies only a difference of potentials, and in a family with a single ViT an additive source-plus-target fit loads the within-family similarity of the CNNs onto the ViT's source and target terms at once, so a source effect read from such a fit may be a similarity effect under another name. A fixed external panel combined with a multiplicative decomposition makes vulnerability, similarity and direction identifiable for each model (Proposition 1 and Section IV-B).

The decomposition and the sizes it measures form the second contribution. The relation $\log T_{ij} = \log w_j + \log \bar{\tau}_{ij} + \frac{1}{2} r_{ij}$ is an accounting identity, related to the quasi-symmetry model of Caussinus [15] and to the role Demontis et al. [16] give to target vulnerability, and its content lies in the values its terms take. On CIFAR-10 a share of 0.936 of ViT-Tiny's panel source gap relative to ResNet-18 is symmetric, against one half for a pure source effect (Proposition 1), the ViT's directional term $\rho = +0.012$ lies within the registered equivalence bound of ± 0.10, and ViT seeds resemble each other more than they resemble the panel ($\Delta_{\text{seed}} = +0.566$). On CIFAR-100 the symmetric share is 0.840 and the seed similarity replicates, while the ViT's directional term rises to $+0.143$ and the registered equivalence is refuted, so that there the ViT is also a directionally weaker source (Section IV-C).

The third contribution is an intervention on the pair itself. Trained from scratch on the same input pipeline, the ViT is less similar to the panel than the ResNet ($A^{\sigma}_{\text{scr}} = -0.364$), ImageNet initialization raises the ViT's panel similarity more than the ResNet's (interaction $I^{\sigma} = +0.260$), and, averaged over the two initializations, the effect of architecture on the directional term is equivalent to zero ($A^{\rho} = +0.003$), which does not imply a small directional term in every cell. All three registered tests are supported after Holm correction (Section IV-D). When each source uses the best of PGD-10, momentum PGD and our adaptation of token gradient regularization [17], which transferred worse than PGD-10 from every ViT source, a fraction of 0.960 of the gap is retained (Section IV-E), and the registered AutoAttack rule flags none of the new models.

The fourth contribution concerns the measurement layer underneath. The conditioning protocol, that is, which samples enter the denominator of a transfer rate, moves the asymmetry of the same models from $+4.36$ to $+19.37$ points across four protocols (Section IV-I). Unconditioned and target-correct rates are linked by the law of total probability through the probability p that a sample the target already misclassifies stays misclassified, which is at least 0.989 on our adversarially trained targets. On the scale $h = -\log(1 - T)$ the two protocols then differ only in the target potentials, up to an adjustment term no larger than 0.0044 in our model pool, so source terms and pairwise similarity on that scale do not depend on the choice between them (Proposition 2).

These results hold within a definite boundary. The small directional term is a finding on the log scale, against a CNN panel and on CIFAR-10: on the logit scale the ViT's directional term is large and negative, on CIFAR-100 the equivalence is refuted, and against a single transformer reference the scratch-trained ViT is a directionally weaker source. The architecture contrast compares whole packages, patch stem, attention and parameter count together, and in the scratch row it moves with a lower clean accuracy of the ViT, which this design cannot separate from architecture. The ImageNetV2 panel is descriptive, and its only scratch-trained pair gives an uncertain estimate. Input-gradient alignment, measured at a single clean point, is associated with similarity as a gradient-alignment account requires, but it is not evidence of a mechanism, and one ImageNet pair shows that a near-zero cosine can coexist with above-median similarity (Sections IV-G and V-D).

Absolute robustness favors the CNN under every attack, with AutoAttack accuracies of 37.93% and 29.14% (Table 1). Three behavioral readings that such comparisons readily suggest, about gradient locality, attention under attack and transformer-specific attacks, do not hold under direct measurement (Appendix A).

A preliminary version of this study was submitted to ATEEC 2026 [18]. That version reports the conditional decomposition, the four-protocol comparison and the gradient and drift measurements on CIFAR-10 alone. The present paper adds the vulnerability-similarity-direction decomposition with its fixed panel, the architecture-by-initialization design, the CIFAR-100 and ImageNetV2 panels, the gradient-alignment test, the protocol identity with its measured

premise, and predictions registered before measurement. It also corrects one claim of the earlier version: the direction of the asymmetry is not stable once the architectures are matched in clean accuracy (Section IV-I, Table 2).

II. RELATED WORK

A. CNN AND VIT ROBUSTNESS

Adversarial training [19] remains the reference empirical defense, and the RobustBench leaderboard [12] tracks it across architectures, with wide residual networks at the top of its CIFAR-10 ranking. Within CNNs, skip connections are known to affect transferability [20], and adversarial training at scale induces batch-normalization statistics distinct from those of clean training [21].

Vision Transformers [3], built on self-attention [4], form internal representations that differ measurably from those of CNNs [22]. Whether this makes them more robust has been answered both ways. Bhojanapalli et al. [23] found ViTs at least as robust as ResNets when pre-trained on enough data, and Shao et al. [9] found them more robust in white-box and transfer settings, with features that carry less high-frequency content; Benz et al. [7] tied an early comparison of the same kind to frequency preferences. Bai et al. [6] trained both families under matched recipes and found transformers no more adversarially robust than CNNs, although more robust under distribution shift.

Much of the disagreement concerns training. Mo et al. [24] report that adversarial training of ViTs depends on pre-training, which makes a ViT trained adversarially from scratch a known weak point, and Debenedetti et al. [25] give a lighter recipe for robust XCiT models. On ImageNet, Singh et al. [26] show that a convolutional stem and the training scheme change ViT robustness considerably and release ViT and ConvNeXt models trained with the same recipe, which we use as matched pairs. Jain et al. [27] trace a form of gradient masking in ViTs to softmax underflow in attention, a caveat for PGD-only evaluations, and with diffusion-augmented adversarial training ViTs have been reported to surpass wide ResNets on small datasets [28]. Comparisons that hold the recipe fixed have also been urged on general grounds [29]. A recent study in this journal compares ViT and CNN adversarial robustness directly [30]; the comparison here differs in that it asks how the two families behave as sources and targets of transfer against a fixed panel, with architecture and initialization varied separately.

B. WHAT MAKES A SOURCE AND A TARGET

Adversarial examples transfer between models, which makes black-box attacks possible [31]. Demontis et al. [16] trace transferability to the intrinsic vulnerability of the target, a term that does not depend on the surrogate, and to the alignment between the input gradients of surrogate and target, a term that is symmetric in the two models, alongside the complexity of the surrogate. Adam et al. [32] attribute the asymmetry between two models of the same architecture to the difference in their gradient norms. Zhang et al. [14] define gradient similarity between two models on the same input and explain transferability as a trade-off between that similarity and model smoothness, which accounts for the observation that slightly robust surrogates transfer well [33]. Awad et al. [34] report, for a zoo of 36 CNNs and ViTs evaluated on ImageNet, that adversarially trained surrogates transfer better than standard ones in all four directions between the families.

A second line asks whether ViT sources are weak because of the attack. Naseer et al. [10] argue that the poor transfer of conventional attacks crafted on ViTs comes from suboptimal attack procedures and improve it with self-ensembles and token refinement; Wei et al. [35] bypass attention gradients, Token Gradient Regularization (TGR) [17] suppresses extreme token gradients, Momentum Integrated Gradients [36] improves transfer across both families, and Chen et al. [37] exploit the different inductive biases of CNNs and ViTs. On the measurement side, Mahmood et al. [8] report low transfer between CNNs and ViTs under a both-correct protocol, Shao et al. [9] find ImageNet-21k pre-trained ViTs to be strong sources against CNNs, Liu et al. [38] give a source-by-target heat map among adversarially trained ImageNet models, and PubDef [39] records transfer across 24 source models. Each of these reports transfer rates or their aggregates. In a search of the transfer literature from 2017 to October 2026 we did not find a study that separates a transfer rate into the target's white-box vulnerability, a similarity shared by both directions and a directional remainder, which is the separation this paper makes. That separation is a parameter-free identity on measured rates whose target term is fixed at a measured value, and a surrogate-complexity term has no separate slot in it: a source main effect enters the directional remainder as a potential and the shared similarity with half weight (Proposition 1).

C. ASYMMETRIC MATRICES AND THEIR DECOMPOSITIONS

A transfer matrix is a square table of rates indexed by source and target, and the statistics of such tables is old. Caussinus [15] introduced the quasi-symmetry model for square contingency tables, $\pi_{ij} = a_i b_j \psi_{ij}$ with ψ symmetric. The form used in Section III-E, $T_{ij} = w_j \bar{\tau}_{ij}$ before the directional residual is added, is that model with the row effect fixed at one and the column effect replaced by a measured quantity, the target's white-box vulnerability. The antisymmetric part of a pairwise matrix splits orthogonally into a potential, a difference of model scores, and a circulation; this is the combinatorial Hodge decomposition behind HodgeRank [40], and Balduzzi et al. [41] use it to show when Elo-type ratings are adequate for machine-learning evaluation matrices. Its degree-of-freedom count is what makes a two-model asymmetry uninformative about sources and targets (Proposition 1). Correspondence between two distance matrices over the same objects is tested with the Mantel permutation test [42], and Smouse et al. [43] extend it to partial correlation given further matrices, the idea behind the residual statistic for gradient alignment in Section III-H.

D. EVALUATION PROTOCOLS FOR TRANSFER

How robustness is measured often decides what is concluded. Carlini et al. [44] catalog the failure modes of robustness evaluation, from gradient masking to attacks that are not run to convergence, the concern that the Carlini–Wagner attack [45] and AutoAttack [46] address from the attack side, and Tramèr et al. [47] show that defenses judged robust under fixed attacks fall to adaptive ones. Those works concern attack strength. A second choice, the set of samples a transfer rate is conditioned on, has received less attention. Foundational transfer studies already restrict evaluation to correctly classified samples [48], attack papers condition their success rates likewise [49], and systematic re-evaluations of transfer attacks restrict the pool to samples every model classifies correctly [50]; Mahmood et al. [8] and Ravikumar et al. [51] condition on samples both models classify correctly to remove differences in clean accuracy. Each study states its set and proceeds with it. TA-Bench [52] fixes the scoring rule and varies the attack and the model pool, Yu et al. [53] vary how an outcome over several targets is aggregated and show that transferability is overestimated when it is measured within one architecture family, and Waseda et al. [54] separate transfers that reproduce the source's error from those that fail differently. The protocol layer of this paper varies the conditioning set on fixed models instead. Over a single model, the relation between the unconditioned and the conditioned rate is the natural-plus-boundary decomposition of TRADES [55]; in transfer its premise becomes an empirical quantity, which Section III-G defines.

III. METHODOLOGY

The study centers on one adversarially trained pair, a ResNet-18 and a ViT-Tiny with three seeds each, whose transfer rates are factored against a fixed panel of robust CNNs that contains neither model. A two-by-two design crosses architecture with ImageNet initialization, and every decision rule was registered before the runs it concerns (Figure 1).

A. THREAT MODEL AND MODELS

All attacks are untargeted and bounded in L_∞ norm, $\mathcal{B}_\epsilon(x) = \{x' : \|x' - x\|_\infty \le \epsilon\}$, with $\epsilon = 8/255$ on CIFAR-10 and CIFAR-100 [11] and $\epsilon = 4/255$ on ImageNetV2.

Figure 1(a) places the trained models in the design. The CIFAR ResNet-18 [5], called R32 here, has a 3×3 stem, 11.2M parameters and 32×32 inputs. ViT-Tiny (`timm` [56]; 5.5M parameters, 16×16 patches, 12 blocks of width 192 with 3 heads) and R224, the `timm` `resnet18` with its 7×7 stem, read inputs upsampled bilinearly from 32 to 224 pixels. ImageNet weights come from `deit_tiny_patch16_224.fb_in1k` [57] and `resnet18.a1_in1k` [58]. CIFAR models read raw pixels in $[0, 1]$; ImageNet-initialized ones apply ImageNet normalization inside the model.

B. ATTACK METHODS

PGD [19] takes ten signed-gradient steps on the cross-entropy, of size $\alpha = 2/255$ ($1/255$ on ImageNetV2), from a uniform random start, projecting onto $\mathcal{B}_\epsilon(x)$ after each step. This PGD-10 is used for training, white-box evaluation and every transfer matrix. AutoAttack [46] is the standard ensemble of APGD-CE, APGD-T, FAB-T and Square. Two further source attacks probe the dependence on the attack: momentum PGD-10 after MI-FGSM [49] ($\mu = 1.0$, $\alpha = \epsilon/10$) and, on ViT sources only, TGR [17] (Section II-B) with momentum 1.0, $\alpha = 2/255$ and $\gamma = 0.5$. Our TGR applies one γ to the attention, QKV and MLP paths and zeroes one maximum and one minimum entry per sample and channel across tokens, so its results speak for this adaptation only.

Each source's best attack is the permitted one whose examples transfer best to the panel, chosen on even-indexed images and scored on odd-indexed ones and vice versa, and the source gap is recomputed under that choice (Section III-E). Step sizes differ between attacks and are not tuned.

C. ADVERSARIAL TRAINING

All models minimize $\frac{1}{2}\mathcal{L}_{\mathrm{CE}}(f_\theta(x), y) + \frac{1}{2}\mathcal{L}_{\mathrm{CE}}(f_\theta(x_{adv}), y)$, with x_{adv} generated by PGD-10 in training mode as in the reference implementation of Rice et al. [59]. Half of the loss is clean and training starts from clean checkpoints, so this mixed-loss PGD adversarial fine-tuning is not the PGD adversarial training of Madry et al. [19], and its robust accuracies should not be read against reference results for that method. One recipe serves every cell so that architecture is not confounded with the defense.

Clean training of R32 and ViT-Tiny uses cosine annealing [60], with SGD (weight decay 5×10^{-4}) for the CNN and AdamW [61] (weight decay 0.05) for the ViT, and adversarial fine-tuning follows with a cosine schedule; the epochs, learning rates, batch sizes and seeds of every run are given in Figure 2. Fine-tuning clips gradients at L_2 norm 10, skips non-finite batches and uses random crops with 4-pixel padding and horizontal flips. Selection and early stopping (patience 20, threshold 0.1 points) use PGD-10 accuracy on a fixed 2,000-image validation split, drawn once with seed 777 and excluded from both training stages of every model. Seeds are paired by index, and tables give means and standard deviations over runs.

An earlier pair of checkpoints, selected on a validation split that clean pre-training had already seen, gave the same absolute ordering; it predates the leakage-free protocol, and none of its numbers enters this paper.

D. ARCHITECTURE-BY-INITIALIZATION DESIGN

A ViT-Tiny trained from scratch differs from R32 in architecture, in input pipeline and possibly in training adequacy, since adversarial training of ViTs is known to depend on pre-training [24]. The design of Figure 2 separates these factors. R224-scr shares the input pipeline and clean-phase command of the ViT-Tiny runs (V-scr), so the scratch row differs in the architecture package and, for V-scr, in training campaign




FIGURE 1. **Study overview as one scene. (a) Trained models: the two-by-two design, one slice per run, beside the R32 bridge; (b) Reference panels, decks of robust CNNs, sliced into (c) their PGD-10 matrices; (d) Registered before measurement gives the test families; (e) Exact split and contrasts factors each log rate. Depth runs from inputs (back) to the derived split (front).**

and adversarial-epoch cap, and the ImageNet row starts both architectures from ImageNet weights. Initialization bundles the weights, a shorter AdamW clean phase and in-model normalization. The bundle is the same for both architectures, so it cancels from the interaction contrast only if its effect does not depend on architecture, and the separate effect of normalization is not identified.

Each ImageNet-initialized run had to beat, after its first clean epoch, the mean first-epoch validation accuracy of the random-initialized runs of its architecture by 5 points, a check on loading and normalization. A validation PGD accuracy below 15% at the fifth adversarial epoch would have lowered the learning rate of the ImageNet row, a run selected within five epochs of the cap is flagged as possibly truncated, and no run is excluded on its results. The registered contrasts use the cell means of σ and ρ (Equation (5)):

$$\begin{aligned} A^{\sigma}_{\text{scr}} &= \sigma(\text{V-scr}) - \sigma(\text{R224-scr}), \\ I^{\sigma} &= [\sigma(\text{V-IN}) - \sigma(\text{V-scr})] \\ &\quad - [\sigma(\text{R224-IN}) - \sigma(\text{R224-scr})], \\ A^{\rho} &= \tfrac{1}{2}\{[\rho(\text{V-scr}) - \rho(\text{R224-scr})] \\ &\quad + [\rho(\text{V-IN}) - \rho(\text{R224-IN})]\}. \end{aligned}$$

E. VULNERABILITY, SIMILARITY AND DIRECTION

Robust accuracy counts clean-misclassified images as non-robust, so it factorizes exactly as clean accuracy times conditioned survival; the complement of the latter is the white-box conditioned fooling rate w_j of model j. For transfer from source i to target j, the *target-correct* rate is the fraction of images that j classifies correctly and misclassifies on the example crafted on i,

$$T_{ij} = \frac{\sum_x \mathbf{1}[f_j(x) = y]\,\mathbf{1}[f_j(x^{(i)}_{adv}) \neq y]}{\sum_x \mathbf{1}[f_j(x) = y]}, \tag{1}$$

so that $w_j = T_{jj}$.

For two models with target-correct rates T_{ij}, T_{ji} and white-box rates w_i, w_j, define

$$\log \bar{\tau}_{ij} = \tfrac{1}{2}\left[\log(T_{ij}T_{ji}) - \log(w_i w_j)\right], \tag{2}$$

$$r_{ij} = \log(T_{ij}/T_{ji}) - \log(w_j/w_i). \tag{3}$$

Then, exactly,

$$\log T_{ij} = \log w_j + \log \bar{\tau}_{ij} + \tfrac{1}{2} r_{ij}, \tag{4}$$

where the similarity $\bar{\tau}_{ij} = \bar{\tau}_{ji}$ is shared by both directions and the directional residual $r_{ij} = -r_{ji}$ is the log asymmetry left after the vulnerability ratio is removed. Equation (4) is an accounting identity; its content lies in the measured sizes of the terms and in how they respond to the design. Without r,




FIGURE 2. **Architecture-by-initialization design as a card cabinet. On CIFAR-10 the drawer rows ViT-Tiny and ResNet-18 cross the columns scratch (random init.) and ImageNet init.; each drawer gives its clean stage (epochs, learning rate) and seeds, one index card per run. The R32 bridge drawer keeps its own recipe; the sign on top is the AT recipe of the four cells.**




FIGURE 3. **Decomposition used throughout, in three tiers. Top to bottom, the arrows per pair (i, j), panel mean and R minus V mark three steps: the log transfer rate splits exactly into vulnerability, similarity and half a directional residual; panel averages give σ and ρ; the source gap G splits into symmetric and directional parts. Tiers recede with the aggregation level.**

$T_{ij} = w_j \bar{\tau}_{ij}$ is the quasi-symmetry model of Caussinus [15] (Section II-C) with the column effect fixed at a measured value, close to two of the three factors of Demontis et al. [16], target vulnerability and gradient alignment; their third, surrogate complexity, is absorbed as Proposition 1(d) describes (Figure 3).

Model-level quantities average over a fixed panel P of external models,

$$\sigma_m = \frac{1}{|P|}\sum_{c\in P} \log \bar{\tau}_{mc}, \qquad \rho_m = \frac{1}{|P|}\sum_{c\in P} r_{cm}, \qquad \omega_m = \log w_m. \tag{5}$$

A high σ_m means that m shares adversarial directions with the panel; a positive ρ_m means that m receives more from the panel than it sends beyond what vulnerability explains, that is, m is a directionally weak source. Rates enter the logarithm in percent, so ω and L_k below carry an additive constant $\log 100$ that cancels from every contrast, and σ_m also takes up half of any model main effect not captured by w. For models R and V the panel source gap

$$G = \frac{1}{|P|}\sum_{c\in P} [\log T_{Rc} - \log T_{Vc}] = (\sigma_R - \sigma_V) - \tfrac{1}{2}(\rho_R - \rho_V)$$

measures how much weaker a source V is than R against third models. Its symmetric share is $q = (\sigma_R - \sigma_V)/G$, written q_s for seed pair s and q for the mean over pairs, and the panel's own vulnerabilities cancel from it. A pure source effect gives $q = 1/2$, the null value of K-a, so a larger q measures dissimilarity beyond a source effect. For source attack k, $L_k(m) = |P|^{-1}\sum_{c\in P} \log T_k(m \to c)$ is the panel-mean log transfer of source m, so that $G = L_{\mathrm{PGD}}(R) - L_{\mathrm{PGD}}(V)$; G_k is the same difference under attack k for the R32 and ViT-Tiny runs, and the retained fraction $G_{\mathrm{best}}/G_{\mathrm{PGD}}$ asks whether the gap survives each source's best attack (Section III-B). Within-family similarity Δ_{seed} is the mean $\log \bar{\tau}$ over pairs of ViT seeds minus the mean of their σ.

Proposition 1 (Identifiability): Let $\ell_{ij} = \log T_{ij}$ for $i \neq j$. (a) With two models, the antisymmetric part of ℓ is the single number $\ell_{12} - \ell_{21}$, and an additive fit $\ell_{ij} = \mu + \alpha_i + \beta_j + s_{ij}$

with symmetric s identifies only $(\alpha_1-\alpha_2)-(\beta_1-\beta_2)$, not its split between source and target. (b) If ℓ_{ij} contains a family term $\gamma\,\mathbf{1}[i,j\in C]$ and the design has a single model $V\notin C$, the additive fit absorbs the term into the source and target effects of V with equal weight $-\gamma$, leaving the asymmetry unchanged. (c) Any symmetric term in ℓ_{ij}, the family term included, cancels from r_{ij} and enters $\log\bar{\tau}_{ij}$ in full; over a fixed panel it moves σ_m and leaves ρ_m unchanged. (d) A source main effect α_i in ℓ_{ij} enters r_{ij} as the potential difference $\alpha_i-\alpha_j$ and $\log\bar{\tau}_{ij}$ as $\frac{1}{2}(\alpha_i+\alpha_j)$; with no symmetric difference between R and V it gives $q=1/2$.

Part (a) is the degree-of-freedom count of the Hodge decomposition, $K-1$ potential and $(K-1)(K-2)/2$ circulation degrees of freedom for K models [40]; (b) follows from $\mathbf{1}[i,j\in C]=1-\mathbf{1}[i=V]-\mathbf{1}[j=V]$ for $i\neq j$, and (c) from substitution into Equations (2) and (3); (d) follows by the same substitution. With one ViT, an additive source effect of the ViT is thus indistinguishable from its dissimilarity to the CNNs, which the decomposition assigns to σ.

Estimates are split-half (Figure 1(e)): w comes from the even-indexed test images and T from the odd-indexed ones and vice versa, and the halves are averaged, so a diagonal and an off-diagonal cell never share images; ω uses the full-sample w. A panel member's own σ and ρ leave that member out. The natural logarithm is primary; as sensitivities, the logit scale replaces $\log x$ by $\log[x/(1-x)]$, and the ratio scale uses the rates themselves.

F. REFERENCE PANELS

Panel members come from RobustBench [12], each panel was frozen before its transfer cells were computed, and Figure 4 lists every member by identifier; the CIFAR members come from [25], [59], [62]–[72]. On CIFAR-10 the primary panel P holds seven L_∞-robust CNNs of the ResNet family, four of them (PreAct) ResNet-18 variants, trained without ImageNet pre-training, and the ImageNet pre-trained XCiT-S12 is a secondary panel (Figure 1(b)). With the pair and the design cells the CIFAR-10 matrix has 20 models (Figure 1(c)).

The CIFAR-100 panel is as close to P as RobustBench allows: seven CNNs, with XCiT-S12 and the model of Hendrycks et al. as a secondary panel. Its pair is the CIFAR-100 ResNet-18 and ViT-Tiny with three seeds each, selected under the single-split rule used when they were trained, which differs from the CIFAR-10 rule; the matrix has 15 models.

On ImageNet the panel holds six CNNs [63], [73]–[75]. Two CNN-transformer pairs adversarially trained with a shared recipe from clean-trained models, ConvNeXt-T with ViT-S and ConvNeXt-B with ViT-B, all with convolutional stems [26], form the ImageNet-initialized row. For pair k we write A_k^σ, A_k^ρ and A_k^ω for the transformer-minus-CNN differences in σ, ρ and ω, and $\bar{A}_{\mathrm{IN}}^\sigma$ for the mean of A_k^σ over these two pairs. ConvNeXt-B and Swin-B of Liu et al. [38] give the scratch row, though only indirectly, since their shared configuration lacks a pre-training flag; their contrast is written $A_{\mathrm{scr,Liu}}^\sigma$ to keep it apart from the CIFAR-10 contrast A_{scr}^σ. Mo et al.'s ViT-B [24] enters unpaired and XCiT-S12




FIGURE 4. Reference panel members on two catalogue cards. The front card, CIFAR-10 and CIFAR-100, gives each RobustBench identifier its role in the C10 and C100 columns and marks ResNet-18 variants in the R18 column. The back card, ImageNetV2, holds the CNN panel and the secondary XCiT-S12, the transformer pairs and the unpaired ViT-B of Mo et al.

as a secondary member, for 14 models, evaluated on 2,000 ImageNetV2 MatchedFrequency images [13], the first two files of each class. One preprocessing pipeline (bicubic resize to 256, center crop to 224) serves all models, so a source's adversarial tensor reaches every target in the same pixel space; normalization stays as each RobustBench model applies it, and scoring uses all 1,000 logits. Each model's clean accuracy on its own pipeline had to reach 25% and 0.6 times its RobustBench value, within 5 points of the common pipeline. This panel is descriptive and does not replicate the two-by-two design: initialization there means clean pre-training on the same dataset, and the architectures differ.

G. CONDITIONING PROTOCOLS

The decomposition uses the target-correct rate throughout, because its diagonal is conditioned in the same way. Conditioning on correctly classified images is established practice (Section II-D), yet the conditioning set is a protocol choice, and the protocol layer of Section IV-I scores three alternatives on the same per-sample records, with masks drawn there in

the terraced top part of Figure 14: the unconditioned rate, the *both-correct* rate [8], [51] and the *successful-source* rate of Ravikumar et al. [51], read strictly so that white-box success presupposes a clean-correct source; a loose reading without that condition is a sensitivity analysis only. The unconditioned and both-correct masks use the same samples in both directions of a pair, and the target-correct and successful-source masks do not. Rates use full test sets with per-sample outcomes logged; intervals for fixed checkpoints come from a percentile bootstrap over images with 10,000 resamples.

Write e for the target's clean error, r_{raw} and r_{cond} for the unconditioned and target-correct rates of a direction ($r_{\text{cond}} = T_{ij}$), and p for the probability that a sample the target misclassifies on clean input is also misclassified on the source-crafted input. By the law of total probability,

$$r_{\text{raw}} = e\,p + r_{\text{cond}}\,(1 - e), \tag{6}$$

and, when $p = 1$,

$$r_{\text{raw}} - r_{\text{cond}} = e\,(1 - r_{\text{cond}}). \tag{7}$$

Over a single model $p = 1$ holds by definition, but in transfer a fixed perturbation can return a misclassified sample to the correct class, so p must be measured. Equation (6) is an accounting identity whose only empirical content is p; where $p < 1$, Equation (7) overstates the deviation by $e\,(1 - p)$. On the scale $h = -\log(1 - T)$ the identity also says which conclusions the protocol can change.

Proposition 2 (Protocol gauge on the h scale): For every direction $i \to j$, $h_{ij}^{\text{raw}} - h_{ij}^{\text{tc}} = -\log(1 - e_j) + g_{ij}$ with $g_{ij} = -\log\big(1+e_j(1-p_{ij})/[(1-e_j)(1-T_{ij})]\big)$, which vanishes at $p_{ij} = 1$. Source effects, pairwise symmetric terms and circulation of an additive decomposition of the h matrix are therefore the same under the raw and target-correct protocols up to g, and only the target effects shift, by the known amount $-\log(1 - e_j)$.

This follows from rearranging Equation (6) as $1 - r_{\text{raw}} = (1 - e)(1 - r_{\text{cond}}) + e(1 - p)$. The both-correct protocol is no such gauge, since its mask depends on the source's clean accuracy.

H. INPUT-GRADIENT ALIGNMENT

To ask whether the symmetric term reflects something measured without transfer or attack, we compute for every model pair the mean cosine between input gradients on clean images,

$$c_{ij} = \frac{1}{n} \sum_{x} \cos\left(\nabla_x \mathcal{L}_i(x, y),\ \nabla_x \mathcal{L}_j(x, y)\right), \tag{8}$$

with $\mathcal{L}_m$ the cross-entropy of model m, gradients in $[0, 1]$ pixel space through any in-model normalization, models in evaluation mode, and the images of the corresponding transfer matrix. This is the image average of the gradient similarity of Zhang et al. [14], and alignment is the symmetric factor of Demontis et al. [16].

The raw statistic is the Spearman correlation r_{S} between c_{ij} and $\log \bar{\tau}_{ij}$ over unordered pairs. The residual statistic correlates the residuals of a least-squares fit $X_{ij} = \mu + a_i + a_j + e_{ij}$ to each matrix, which removes every model-level property that adds to both members of a pair, such as robustness, gradient norm or clean accuracy, in the spirit of the partial Mantel test [43], with all model main effects removed at once. Significance comes from the Mantel test [42], permuting model labels jointly over the rows and columns of c with $\log \bar{\tau}$ fixed, 9,999 times, for a one-sided p with floor 10^{-4}. The additive fit leaves in place multiplicative or interacting model effects and the block structure of the CNN and transformer families.

I. STATISTICAL INFERENCE

The unit of inference is the training run, with images as repeated measurements shared by all models, so intervals over runs are conditional on the fixed test images and panel members; image sampling enters only the bootstraps that resample images. Two-by-two contrasts use run-level cell means and a pooled-variance t interval with 5 degrees of freedom. Tests form the registered families of Figure 1(d), with Holm correction at $\alpha = 0.05$ within each family (Figure 5). Equivalence is tested by two one-sided tests (TOST) with margin $\delta = 0.10$ log units, roughly a ten percent relative change in a rate; it is registered for log quantities, so logit and ratio comparisons against the same band are descriptive. The margin came from the root-mean-square directional residual among the adversarially trained models seen before registration; that set includes the ViT, so the margin is loose, and every equivalence is repeated at $\delta = 0.06$, the value for CNN pairs alone. For the σ contrasts (H1, H2, K-c) the same margin is a convention without a separate empirical basis.

Support is read from Holm-adjusted $p < 0.05$; refutation, and the equivalence arms of H1 and H2, from raw intervals; equivalence support for K-b and H3 from Holm-adjusted TOST p, with refutation checked first, so a significant effect whose interval lies within $\pm\delta$ counts as negligible. K-a is undecided if any seed pair has $G_s \le \delta$; the retained fraction is undecided if $G_{\text{PGD}} \le \delta$, supported if its 90% lower bound reaches 0.5 and refuted if its upper bound falls below it; H2 support also needs a positive logit estimate. A test that cannot be computed counts as $p = 1$, and predicted sizes are reported without being criteria. A headline was written in advance for every combination of H1 to H3 outcomes, and the masking rule applies after the region is chosen. In region O1, where H1 and H2 are supported and H3 is equivalent, the registered headline, which the results below narrow, here also because the design does not separate architecture from convergence in the scratch row, attributes the ViT's weak-source appearance to a symmetric, architectural dissimilarity that ImageNet initialization reduces more for the ViT, with the asymmetry carried by target vulnerability and a small directional term independent of architecture. Secondary analyses S1 to S7 are exploratory and uncorrected, and protocol equivalence is tested by TOST at ± 1 and ± 3 points.




FIGURE 5. Registered tests and decision rules as a staircase. Each step is one family, numbered in registration order and set behind the previous one; rows give test and quantity, place the predicted size (diamond) and falsification threshold (circle) on a number line with the ±0.1 band, and state the falsifying rule. Holm correction is per family; ImageNetV2 rows are descriptive.

J. PRE-REGISTRATION

The main registration (panel tests, two-by-two design, attack side, masking) was frozen on 29 October 2026 before any of these runs, and an addendum (CIFAR-100, ImageNetV2, gradient alignment) on 30 October 2026 before any of its matrices or gradients was computed (Figure 6). The registered tests ran through the frozen analysis script or, for the addendum, through a wrapper around it and a gradient script whose digests were recorded before their first run; the SHA-256 digests of the frozen script (`4bce2c983ace...`), of the addendum scripts, of the cell tables and of both registration texts match the records written at freezing or before the first run and those stored in the analysis outputs. The main registration has one implementation deviation: the frozen script had no code for its hierarchical-bootstrap sensitivity of K-a and K-b, which a separate script, loading the frozen functions unchanged, computed on both CIFAR datasets after the results and an internal review had been seen (Section IV-C). The addendum has none; its exploratory S10-3, a partial Mantel test with family indicators, was specified at that point.

Data seen before registration are not tests; besides the matrices in Figure 6, they include desk analyses on the pool matrix, a mock run of the two-by-two code on real pair matrices, and small-sample smoke matrices and clean accuracies. The mock run and the desk analysis had already shown the σ gap between the pair's ViT and its 32-pixel ResNet, and the H1 prediction was written with that gap known; what H1 tests beyond it is whether a 224-pixel ResNet-18 on the ViT's input pipeline reproduces the ResNet side of the gap. No full-recipe run of a new cell had been seen, so the CIFAR-10 panel predictions extend the first seed to two further seeds and a seven-member panel. Two rules changed after data had been seen. The refutation criterion of K-b was widened to both signs, which makes refutation easier, although the CIFAR-100 refutation also follows from the original one-sided rule. The clean-phase check, a loading check, was moved to the first epoch, with a single R224-scr run as the R224-IN reference; no decision depended on it. Whether the attack-side prediction predates the momentum and TGR smoke matrices cannot be verified from the file history. The directional values of the CIFAR-10 panel table had been looked at before the addendum was frozen, and its predictions were copied from the frozen ones. During the CIFAR-100 matrix a launch script printed one source's log lines to the screen; the analysis is a single call that leaves no choices.

Several registered sensitivity and exploratory analyses were not produced, among them the both-correct and Hodge analyses of CIFAR-100, part of the ImageNetV2 and gradient

analyses, and the both-correct Mantel test. The ImageNet top-1 accuracy of the two initialization checkpoints was not recorded.

IV. EXPERIMENTS

Unless a protocol is named, every transfer rate below is the target-correct rate T_{ij}, factored by Equation (4); split-half log-scale estimates are primary, logit and ratio scales are sensitivities, and the decision rules are those of Figure 5.

A. ROBUSTNESS OF THE PAIR

The CNN holds the absolute advantage under every attack (Table 1). Under AutoAttack ResNet-18 AT keeps $37.93 \pm 0.14\%$ of the test set against $29.14 \pm 0.40\%$ for ViT-Tiny AT, and McNemar's test on the full test set, paired by image, favors the CNN in each of the three seed pairs ($p \leq 1.2 \times 10^{-84}$ under AutoAttack, $p \leq 1.9 \times 10^{-120}$ under PGD-10). Clean accuracy accounts for part of the gap. The rest is conditional: of the images each model classifies correctly, PGD-10 flips $48.58 \pm 0.80\%$ for the CNN and $55.53 \pm 0.50\%$ for the ViT, and the factorization is exact, $85.78 \times 0.442 = 37.93$ and $73.53 \times 0.396 = 29.14$ under AutoAttack. On the $7{,}061 \pm 68$ images that both models classify correctly the CNN retains $59.86 \pm 0.35\%$ under PGD-10 and the ViT $46.11 \pm 0.59\%$ (51.89 and 41.15% under AutoAttack).

The conditional PGD-10 column is the vulnerability w of the decomposition: as a target, the ViT is the more vulnerable model. The perturbation-budget sweep and the gradient, attention and feature-drift measurements of the pair are in Appendix A.

B. FROM AN ADDITIVE SPLIT TO A DECOMPOSITION

Under the target-correct protocol the pair's asymmetry, CNN→ViT minus ViT→CNN, is positive (Table 2), and an additive source-plus-target fit to the three-model matrices that include the WideResNet reference assigns $+5.13$ points of it to the source and -2.03 to the target. Proposition 1 shows why that split cannot be read as a source effect: with a single ViT among CNNs, the ViT's source term and its similarity to the CNN family enter the same contrast, and the additive fit loads family similarity onto both. Separating them requires a fixed external panel and the multiplicative decomposition used from here on.

The pair itself already separates two of the three terms (Table 2). Its log asymmetry, $\log(T_{RV}/T_{VR}) = +0.251$, is the sum of a potential component $\log(w_V/w_R) = +0.136$, which comes from the ViT being the more vulnerable target (w of 55.53 against 48.58%), and a directional residual $r_{RV} = +0.115$ with a run-to-run standard deviation of 0.010. The potential share is 0.541, so target vulnerability carries about half of the pair's direction on CIFAR-10. It carries less on CIFAR-100, where the share is 0.283 and r_{RV} rises to $+0.154$. The symmetric term, $\log \bar{\tau}_{RV} = -1.083$, enters both directions equally and cannot appear in a two-model asymmetry at all. For one seed pair an image bootstrap gives a standard deviation of 0.030 for r_{RV}, three times its run-to-run spread, a component that the run-level intervals below do not include.

A two-model asymmetry cannot say why the ViT looks like a weak source against CNNs in general, because that question concerns the ViT's relation to models outside the pair. Before the registration was frozen, a desk analysis of the eight-model CIFAR-10 pool (Table 3) took its four robust CNNs as a panel. Against that panel the ViT's source gap relative to ResNet-18 was 0.422 log units, of which 0.392 was symmetric and 0.030 directional, a symmetric share of 0.928; these values shaped the predictions and are not tests. At the model level, panel similarity σ puts ViT-Tiny far from every other model (-1.086 against -0.694 to -0.519 for the robust CNNs), while ρ stays between -0.096 and $+0.083$ for all seven models. The XCiT-S12, which mixes attention with convolutional components, sits among the CNNs on σ (-0.609), so the one other attention-based model in the pool does not share the low similarity.

C. PANEL TESTS ON CIFAR-10 AND CIFAR-100

The registered panel family on CIFAR-10 has three tests, all decided after Holm correction (Table 4). The first, K-a, asks what share of the ViT's source gap against the seven-member CNN panel is symmetric. In the three seed pairs the gap G_s is 0.391, 0.387 and 0.390 log units; its symmetric part is 0.368, 0.360 and 0.367 and its directional part 0.023, 0.028 and 0.023. The mean symmetric share is $q = 0.936$ with a 90% interval of $[0.925, 0.948]$, every seed clears the predicted 0.75, and K-a is supported (CIFAR-10 panel of Figure 7). In terms of the derived quantity $2q - 1$, the symmetric part exceeds the directional part by 0.873 of the gap ($[0.849, 0.896]$).

The second test, K-b, asks whether the ViT is a directionally weak source once similarity and vulnerability are removed. Its directional term is $\rho(\text{V-scr}) = +0.012$ (seeds $+0.025$, $+0.007$ and $+0.004$), with a 90% interval of $[-0.007, +0.031]$ well inside the ± 0.10 equivalence band, and equivalence is supported (TOST, Holm $p = 2.73 \times 10^{-3}$). On this panel, on CIFAR-10 and on the log scale, then, ViT-Tiny's weak-source appearance against CNNs is carried by its dissimilarity to them, which holds in both directions.

The third test, K-c, asks whether that dissimilarity belongs to the family or to individual seeds. The three ViT seeds are much more similar to one another than to the panel ($\Delta_{\text{seed}} = +0.566$, bootstrap 90% interval $[0.537, 0.604]$), and the test is supported. The mean pairwise $\log \bar{\tau}$ between ViT seeds is -0.443, against -0.489 between the three ResNet-18 seeds, so the ViT runs form a block as tight as the ResNet runs, away from the CNNs (Figure 8). A general weakness of the ViT as a source would have lowered this within-family similarity as well.

The same family was registered as a binding replication on CIFAR-100, with a seven-member CIFAR-100 panel. K-a and K-c are supported again ($q = 0.840$, $[0.795, 0.885]$; $\Delta_{\text{seed}} = +0.519$, $[0.469, 0.599]$), and the within-family values repeat (-0.487 between ViT seeds, -0.501 between ResNet seeds). K-b does not replicate. The directional term




FIGURE 6. Pre-registration chain as a time shelf. Seen beforehand lists the data looked at before registration; Main registration: B2-B6 and Supplement: B8-B10, the addendum of the text, give each block's models, images and cells. Cards recede in time; arrows carry the freeze dates (October 2026), commits and registration digest prefix; the strip Added after the fact names two post hoc analyses.

TABLE 1. Robustness of the ResNet-18 and ViT-Tiny pair on CIFAR-10 ($\epsilon = 8/255$, full test set), mean±SD over three independent training runs per architecture. The last two columns give the conditional fooling rate, the share of correctly classified test images that the attack flips; under PGD-10 this is the white-box vulnerability w used throughout.

Model	Defense	Params	Clean	FGSM	PGD-10	AA	Cond. PGD-10 (w)	Cond. AA
ResNet-18	None	11.2M	95.25±0.15	40.29±1.77	0.03±0.03	–	–	–
ResNet-18	AT	11.2M	85.78±0.36	53.46±0.08	44.11±0.50	37.93±0.14	48.58±0.80	55.78±0.23
WRN-28-10	AT†	36.5M	89.48	70.91	66.92	62.76	–	–
ViT-Tiny	None	5.5M	80.09±0.60	6.10±1.47	0.05±0.05	–	–	–
ViT-Tiny	AT	5.5M	73.53±0.55	36.31±0.42	32.69±0.22	29.14±0.40	55.53±0.50	60.37±0.33

†Robust checkpoint of Gowal et al. [65] via RobustBench [12], a single external checkpoint; clean, FGSM and PGD-10 are our full-test evaluations, AA is the RobustBench-reported figure.

TABLE 2. Log-scale decomposition of the target-correct asymmetry between ResNet-18 and ViT-Tiny. Upper block: the three seed pairs, mean (run-to-run standard deviation); the matrices are those of the separate three-model attack run, hence +4.41 here against +4.36 in Figure 14. Lower block: seed-matched pairs of the two-by-two design (secondary analysis S4, descriptive, full sample). The log ratio is exactly the potential component plus the directional residual; the potential share, their ratio, is undefined (–) when the log ratio is near zero.

Setting	Asymmetry (pts)	$\log(T_{RV}/T_{VR})$	$\log(w_V/w_R)$	r_{RV}	$\log \bar{\tau}_{RV}$	Potential share
CIFAR-10, selected checkpoint	+4.41 (0.45)	+0.251 (0.032)	+0.136 (0.023)	+0.115 (0.010)	−1.083 (0.022)	0.541 (0.029)
CIFAR-10, last checkpoint	+4.64 (0.56)	+0.273 (0.029)	+0.144 (0.034)	+0.129 (0.044)	−1.170 (0.021)	0.531 (0.134)
CIFAR-100, selected checkpoint	+4.96 (1.02)	+0.215 (0.048)	+0.061 (0.020)	+0.154 (0.041)	−1.138 (0.023)	0.283 (0.087)
Two-by-two design, seed-matched pairs (ResNet / ViT)						
R224-scr s1201 / V-scr s2001	+4.18	+0.248	+0.125	+0.123	−1.141	0.504
R224-scr s1202 / V-scr s2002	+4.43	+0.266	+0.142	+0.124	−1.142	0.534
R224-IN s1301 / V-IN s2101	−1.28	−0.056	−0.002	−0.054	−0.753	–
R224-IN s1302 / V-IN s2102	+0.78	+0.036	+0.068	−0.032	−0.825	–

Image-bootstrap standard deviation for seed pair 1 (CIFAR-10, selected; $B = 300$): r_{RV} 0.030, $\log \bar{\tau}_{RV}$ 0.016.

is $+0.143$ ($[+0.101, +0.184]$), the TOST p is 0.953, the 95% interval excludes zero and the estimate exceeds 0.10, so equivalence is refuted in the positive direction, and on CIFAR-100 the ViT is also a directionally weaker source. The directional parts of the source gap grow accordingly, to 0.059, 0.064 and 0.085 from 0.023 to 0.028 on CIFAR-10, which is why q falls while the symmetric parts stay of the same size. The directional term depends on the dataset: it is large on CIFAR-100, and on SVHN, where no panel was run, the pair's target-correct asymmetry itself changes sign at closely matched clean accuracy (Section IV-I).

On CIFAR-100, ViT-Tiny reaches only 41.94 to 44.06% clean accuracy, against 62.68 to 64.65% for ResNet-18 and 53.82 to 72.57% for the panel, so its w and its target-correct denominators rest on a much smaller and easier subset of images, and part of its directional term may reflect clean accuracy. The both-correct version of these tests, which would hold that subset fixed, has not been run.

A hierarchical bootstrap that resamples runs within cells and images shared by all models ($B = 2{,}000$) gives $[0.894, 0.981]$ for q and $[-0.021, +0.046]$ for ρ(V-scr) on CIFAR-10, wider than the t intervals, and $[0.800, 0.880]$ and

TABLE 3. The eight-model CIFAR-10 pool (PGD-10, $\epsilon = 8/255$, full test set). $p_{\min}$ is the smallest premise p of Equation (6) over directions into each target. σ and ρ are split-half log estimates against the four robust CNNs of the pool (desk analysis, seen before registration) and against the seven-member registered panel.

			4-CNN panel		7-member panel	
Model	Clean	$p_{\min}$	σ	ρ	σ	ρ
ResNet-18 AT (ours)	85.37	0.9911	−0.694	−0.018	−0.648	−0.022
ViT-Tiny AT (ours)	74.10	0.9919	−1.086	+0.043	−1.015	+0.025
Standard WRN-28-10	94.78	0.9330	–	–	–	–
Wong2020 PRN-18	83.34	0.9892	−0.656	−0.033	−0.576	−0.033
Engstrom2019 RN-50	87.03	0.9846	−0.566	−0.058	−0.508	−0.055
Carmon2019 WRN-28-10	89.69	0.9884	−0.519	+0.008	−0.472	−0.009
Gowal2020 WRN-28-10	89.48	0.9895	−0.521	+0.083	−0.467	+0.065
Debenedetti2022 XCiT-S12	90.06	0.9940	−0.609	−0.096	−0.561	−0.095

Over all 56 directions p lies in $[0.9330, 1.0000]$ and the $p = 1$ residual is at most 0.35 points.

$[+0.106, +0.178]$ on CIFAR-100, slightly narrower. With its intervals and p values in the frozen decision rules no decision changes on either dataset. The two intervals err in opposite directions: the t intervals omit image sampling, and a bootstrap over three runs per cell underestimates the run component. Bootstrap p values are bounded below by $1/(B+1)$ and reach that floor in every test except K-b on CIFAR-100.

D. ARCHITECTURE BY INITIALIZATION

The two-by-two design of Figure 2 asks which part of the dissimilarity is architecture and which is initialization, with the input pipeline and the adversarial training recipe held equal across cells. All six new runs passed the registered manipulation checks. Each ImageNet-initialized run exceeded the scratch reference at the first clean epoch by 48.40 to 69.38 points, none triggered the collapse rule, and every run stopped early, well before the 80-epoch cap (Section IV-J).

Across the runs of Table 5, only the scratch-trained ViT stands apart on clean accuracy (73.01 to 74.10% against 83.39 to 86.35% in the other cells) and on vulnerability (w of 55.12 to 55.91% against 47.73 to 51.11%). On panel similarity the two ResNet cells are nearly identical, and ImageNet initialization moves only the ViT (Figure 9).

Each test of the registered two-by-two family is supported (Table 6). With a matched input pipeline and training from scratch, the ViT is less similar to the CNN panel than the ResNet ($A^{\sigma}_{\mathrm{scr}} = -0.364$, 90% interval $[-0.415, -0.314]$, Holm $p = 4.09 \times 10^{-5}$), beyond the predicted size of -0.20 (H1). ImageNet initialization narrows that difference more for the ViT than for the ResNet ($I^{\sigma} = +0.260$, $[+0.186, +0.335]$, Holm $p = 9.0 \times 10^{-4}$), and the interaction stays positive on the logit scale ($+0.354$), as the support rule requires (H2). The architecture main effect on the directional term is equivalent to zero ($A^{\rho} = +0.003$, $[-0.020, +0.026]$; TOST Holm $p = 3.79 \times 10^{-4}$; H3). This combination is the registered outcome region O1 defined in Section III-I. The masking rule flags no model (Section IV-E), so the region stands after it, and the tighter margin $\delta = 0.06$ gives the same region.

The H1 estimate holds under every registered sensitivity. Panel jackknife moves it between -0.376 and -0.346, and the hierarchical bootstrap interval is $[-0.393, -0.335]$. Welch intervals, which drop the pooling across cells, are much wider because the new cells have two runs each ($[-0.569, -0.160]$ at 1.10 degrees of freedom), yet they still exclude zero for H1 and H2. In an exploratory three-member panel without the four ResNet-18 variants, all six CIFAR-10 tests keep their direction and decision and the outcome region stays O1, with similar magnitudes (Appendix D).

H3 needs a narrower reading than its decision suggests. It is an equivalence of the architecture main effect, averaged over the two initialization rows, and does not imply a small directional term in every cell. The ImageNet-initialized ViT has a cell mean of $\rho = -0.118$, outside the band, and initialization changes the ViT's directional term by -0.130 ($[-0.161, -0.099]$; secondary analysis S2, as predicted). Behind the main effect, the architecture simple effects on ρ are $+0.070$ from scratch and -0.064 with ImageNet initialization; their difference, -0.134, is negative on the log and the logit scale, and the two simple effects differ in sign only on the log scale (Table 12). On the logit scale H3 is -0.087: its 95% interval excludes zero while the estimate stays inside ± 0.10, so the registered rule would return neither support nor refutation on that scale. On the ratio scale the same contrast is -4.13 points.

The 32-pixel ResNet-18 of the pair and the 224-pixel ResNet-18 of the design relate to the panel in the same way: $\sigma(\text{R224-scr}) - \sigma(\text{R32}) = -0.0003$ ($[-0.035, +0.034]$) and the ρ difference is -0.021 ($[-0.064, +0.023]$), which is consistent with an unchanged bridge under pooled variances, though not under a Welch 90% interval ($[-0.120, +0.119]$ for σ; S1). This bridge, not the σ gap seen before registration (Section III-J), is what H1 tests. Initialization changes the ViT's log vulnerability by -0.114 ($[-0.151, -0.077]$) and the ResNet's by -0.018 (S3). Against the XCiT-S12 as a secondary panel both σ contrasts keep their signs (-0.284 and $+0.254$; S6). In the 20-model residual matrix a Hodge decomposition places 0.919 of the directional structure in model-level potentials, against 0.100 at random (S7). The seed-matched pairs (S4, Table 2) repeat the pair's potential share in the scratch row (0.504 and 0.534); in the ImageNet row the log ratio is close to zero and the share is undefined.

The design cannot separate one alternative explanation of H1. The scratch-trained ViT has both the lowest clean accuracy and the highest vulnerability, and the architecture contrast changes together with them by construction, so part of $A^{\sigma}_{\mathrm{scr}}$ may reflect a less converged solution. The ImageNet-initialized ViT comes close to the clean accuracy of the ResNet cells (83.39 and 83.47%), yet its panel similarity stays below that of R224-IN (-0.739 against -0.635). Derived after the results were seen, this contrast, $\sigma(\text{V-IN}) - \sigma(\text{R224-IN}) = -0.104$, has a pooled-variance 90% interval of $[-0.159, -0.049]$, while its Welch interval with two runs per cell, $[-0.318, +0.109]$, includes zero (Appendix D), so it points to a dissimilarity beyond accuracy only under pooled variances.

TABLE 4. Registered panel tests for ViT-Tiny against the seven-member CNN panel on CIFAR-10 and, as a binding replication, on CIFAR-100 (split-half, log scale; Holm within each dataset). K-a: symmetric share q; K-b: the ViT's directional term, TOST at ± 0.10; K-c: within-family similarity, hierarchical bootstrap. K-a and K-b use t intervals over three seeds, conditional on the fixed test images and panel; the K-c bootstrap and the hierarchical-bootstrap row also resample images.

	CIFAR-10					CIFAR-100				
Test	Estimate	90% CI	95% CI	Holm p	Decision	Estimate	90% CI	95% CI	Holm p	Decision
K-a, q	0.936	[0.925, 0.948]	[0.919, 0.953]	1.26×10^{-4}	support	0.840	[0.795, 0.885]	[0.773, 0.906]	2.05×10^{-3}	support
K-b, ρ(V-scr)	$+0.012$	$[-0.007, +0.031]$	$[-0.016, +0.040]$	2.73×10^{-3}	support	$+0.143$	$[+0.101, +0.184]$	$[+0.082, +0.203]$	0.953	refuted (+)
K-c, Δ_{seed}	$+0.566$	$[+0.537, +0.604]$	$[+0.533, +0.608]$	1.00×10^{-3}	support	$+0.519$	$[+0.469, +0.599]$	$[+0.463, +0.604]$	1.50×10^{-3}	support
Predicted size met	K-a ($q_s \geq 0.75$), K-b (90% CI in ± 0.10), K-c ($\Delta_{\text{seed}} \geq 0.30$): yes					K-a, K-c: yes; K-b (90% CI in ± 0.10): no				
Sensitivities										
$\delta = 0.06$	all three supported					K-a, K-c supported; K-b refuted (+)				
$2q - 1$, derived	$+0.873$ [$+0.849$, $+0.896$]					$+0.679$ [$+0.589$, $+0.769$]				
Full sample, log	q 0.937; ρ $+0.012$ [-0.007, $+0.031$]					q 0.840; ρ $+0.143$ [$+0.101$, $+0.184$]				
Logit scale	q 1.101; ρ -0.304 [-0.320, -0.289]					q 1.026; ρ -0.413 [-0.546, -0.280]				
Ratio scale	q 1.542; ρ -14.66 pts [-14.93, -14.39]					q 1.216; ρ -14.61 pts [-17.32, -11.89]				
Hier. bootstrap	90% CI: q [0.894, 0.981]; ρ [-0.021, $+0.046$]; same decisions					90% CI: q [0.800, 0.880]; ρ [$+0.106$, $+0.178$]; same decisions				
Panel jackknife	q 0.931 to 0.941; ρ $+0.001$ to $+0.022$					q 0.831 to 0.847; ρ $+0.127$ to $+0.150$				
Secondary panel	XCiT-S12: q_s 0.899, 0.825, 0.842; ρ $+0.198$, $+0.202$, $+0.204$					XCiT-S12, Hendrycks: q_s 0.799, 0.834, 0.771; ρ $+0.129$, $+0.136$, $+0.221$				

Hierarchical bootstrap: runs resampled within cells, images shared, $B = 2{,}000$, produced after registration (Section III-J). $2q - 1$ is a linear transform of K-a, not a test.




FIGURE 7. Source gap split into symmetric and directional parts, one slab per data set. Per seed pair on CIFAR-10 and CIFAR-100 and per same-recipe pair on ImageNetV2 (descriptive): olive symmetric part, lavender-grey directional part, diamond total G. Strips lie in the slab plane; the printed G and share q carry the values. A dashed part narrows the gap.

TABLE 5. Runs of the two-by-two design on CIFAR-10, with cell means. Clean accuracy and w (target-correct white-box PGD-10 fooling) on the full test set; $\omega = \log w$ with w in %; σ and ρ are split-half log estimates against the seven-member panel. The last three columns are the masking check on the first 1,000 test images (PGD-10 and AutoAttack robust accuracy and their difference; flag at 10 points), which covers the six new runs only; full-test AutoAttack for V-scr is in Table 1.

Cell	Seed	Clean (%)	w (%)	ω	σ	ρ	PGD-10, 1k (%)	AA, 1k (%)	PGD−AA (pts)
V-scr	2001	74.10	55.91	4.024	−1.015	+0.025	–	–	–
V-scr	2002	73.47	55.86	4.023	−1.000	+0.007	–	–	–
V-scr	2003	73.01	55.12	4.009	−1.011	+0.004	–	–	–
V-scr	mean ($n = 3$)	73.53	55.63	4.019	−1.009	+0.012			
V-IN	2101	83.39	48.24	3.876	−0.702	−0.131	43.30	40.10	3.20
V-IN	2102	83.47	51.11	3.934	−0.776	−0.105	42.20	38.80	3.40
V-IN	mean ($n = 2$)	83.43	49.68	3.905	−0.739	−0.118			
R224-scr	1201	86.35	49.33	3.899	−0.625	−0.038	43.90	39.50	4.40
R224-scr	1202	85.11	48.47	3.881	−0.664	−0.079	45.10	41.10	4.00
R224-scr	mean ($n = 2$)	85.73	48.90	3.890	−0.645	−0.058			
R224-IN	1301	85.76	48.34	3.878	−0.642	−0.056	45.80	38.40	7.40
R224-IN	1302	86.25	47.73	3.866	−0.628	−0.052	47.40	41.80	5.60
R224-IN	mean ($n = 2$)	86.00	48.04	3.872	−0.635	−0.054			




FIGURE 8. **Pairwise symmetric similarity on three plinths. log τ (split-half) for all models on CIFAR-10 (1), CIFAR-100 (2) and ImageNetV2 (3), in frozen group order; cell colour is one of five joint quintile bins, the dark diagonal undefined. Dark frames mark the groups; no height carries a value. Scratch-trained ViT-Tiny seeds form a block dissimilar to the CNN panel.**

TABLE 6. **Registered two-by-two family on CIFAR-10 (split-half, log scale; pooled variance over the four cells, 5 degrees of freedom; Holm correction). H1: $A^{\sigma}_{\mathrm{scr}} = \sigma$(V-scr) $- \sigma$(R224-scr), one-sided; H2: the interaction I^{σ}, two-sided; H3: the architecture main effect on ρ, TOST at ± 0.10. Outcome region O1, before and after the masking rule; no sensitivity below the rule changes a decision.**

	H1, $A^{\sigma}_{\mathrm{scr}}$	H2, I^{σ}	H3, A^{ρ}
Estimate	-0.364	$+0.260$	$+0.003$
90% CI	$[-0.415, -0.314]$	$[+0.186, +0.335]$	$[-0.020, +0.026]$
95% CI	$[-0.428, -0.300]$	$[+0.165, +0.355]$	$[-0.026, +0.033]$
t (df 5)	-14.60	$+7.03$	$+0.29$
Raw p	1.36×10^{-5}	9.00×10^{-4}	1.89×10^{-4} (TOST)
Holm p	4.09×10^{-5}	9.00×10^{-4}	3.79×10^{-4}
Decision	support	support	support (equiv.)
Predicted size met	yes (≤ -0.20)	yes ($\geq +0.10$)	–
Logit estimate	-0.498	$+0.354$	-0.087
90% CI	$[-0.570, -0.426]$	$[+0.247, +0.461]$	$[-0.110, -0.064]$
Ratio estimate (pts)	-8.50	$+5.85$	-4.13
90% CI	$[-9.85, -7.14]$	$[+3.83, +7.86]$	$[-4.90, -3.37]$
Welch 95% CI	$[-0.569, -0.160]$	$[+0.029, +0.491]$	$[-0.052, +0.059]$
Welch df	1.10	1.63	1.95
Panel jackknife	$-0.376, -0.346$	$+0.249, +0.266$	$+0.001, +0.006$
Hier. bootstrap 90%	$[-0.393, -0.335]$	$[+0.204, +0.316]$	$[-0.024, +0.031]$
$\delta = 0.06$, Holm p	4.09×10^{-5}	1.80×10^{-3}	2.13×10^{-3}
decision	support	support	support

Pooled SD: 0.0273 (σ contrasts), 0.0169 (A^{ρ}).

E. ATTACK SIDE AND GRADIENT MASKING

A source gap measured with one attack could reflect how well PGD-10 suits each source. For every source, cross-fitted split-half selection therefore picks the attack that transfers best to the panel among PGD-10, MI-PGD-10 and, for ViT sources, TGR (Section III-B), and the gap is recomputed under each source's chosen attack (Table 7). Under PGD-10 the gap between the 32-pixel ResNet-18 and the scratch-trained ViT is $G_{\mathrm{PGD}} = 0.389$ log units; under the chosen attacks it is $G_{\mathrm{best}} = 0.374$. The retained fraction is 0.960 (90% interval $[0.941, 0.976]$), far above the registered threshold of 0.5, and the test is supported. Momentum PGD was chosen for all three ViT sources and one of the three ResNet sources, and




FIGURE 9. **Two-by-two cells on CIFAR-10 as a three-floor tower. Floors Panel similarity σ, Direction ρ and Vulnerability ω share the posts at scratch and ImageNet; lines join cell means (split-half, log scale), open marks are runs, diamonds the R32 bridge. σ prints $A^{\sigma}_{\mathrm{scr}}$ (H1) and I^{σ} (H2); ρ carries the ± 0.10 band. Values are positions on each floor.**

TABLE 7. Attack-side test: source gap between the 32-pixel ResNet-18 and the scratch-trained ViT-Tiny under PGD-10 and under each source's best attack (log units, panel mean), with hierarchical-bootstrap intervals that repeat the selection in every copy; design pairs are descriptive.

Quantity	Value
G_{PGD} [90% CI]	0.3893 [0.370, 0.409]
G_{best}	0.3738
Retained fraction $G_{\mathrm{best}}/G_{\mathrm{PGD}}$	0.960
90% CI; 95% CI	[0.941, 0.976]; [0.937, 0.981]
Valid bootstrap copies	2000 / 2000
Decision (threshold 0.5)	support
Full-sample selection, ratio	0.960
R224-scr / V-scr: G_{PGD}, G_{best}, ratio	0.399, 0.383, 0.959
R224-IN / V-IN: G_{PGD}	0.072 (no ratio, $G_{\mathrm{PGD}} \leq 0.10$)

TGR was selected for 0 of 5 ViT sources.

it closes 0.0155 log units of the gap.

TGR was never selected, for any of the five ViT sources. It transfers worse than PGD-10 from every one of them, by −0.218 to −0.147 log units for the scratch-trained ViTs and by −0.217 to −0.168 for the ImageNet-initialized ones (Figure 10). Among the descriptive design pairs the scratch row retains 0.959 of its gap, while the ImageNet-row gap of 0.072 is below the 0.10 at which the fraction is defined. An earlier matched-budget TGR comparison on the pair is in Appendix A.

AutoAttack was run on the first 1,000 test images of the six new models to check for gradient masking (Table 5). PGD-10 exceeds AutoAttack accuracy by 3.20 to 7.40 points, below the registered 10-point flag, so no model is flagged and the two-by-two decisions are computed on all models as registered.




FIGURE 10. Transfer by attack, per source, on an abacus. Each wire is one source; beads sit at its panel-mean log transfer L(m) under PGD-10 (circle), momentum PGD (square) and, for ViT sources, TGR (triangle). Filled beads are the attacks chosen by cross-fitted selection; TGR is never chosen. The value is the bead's position on the beam scale.

F. A DESCRIPTIVE IMAGENETV2 PANEL

The two-by-two design is confined to CIFAR scale and small models. A registered but descriptive panel on ImageNetV2 [13] asks whether the initialized row has a counterpart among independently trained ImageNet models; it has no decision family and cannot confirm or refute the CIFAR tests. The fourteen models of Section III-F were attacked with PGD-10 through one common preprocessing pipeline (Table 8). Every candidate passed the registered preprocessing check, with a largest difference of 0.95 points between the common pipeline and a model's own among the fourteen models in the matrix (1.20 for an unused reserve), and the same image list, identified by its hash, entered the transfer matrix and the gradient run.

The initialized row is represented by two pairs from Singh et al. [26], a ConvNeXt and a ViT with convolutional stems trained with the same recipe from clean ImageNet checkpoints. In both pairs the transformer is less similar to the CNN panel ($A_1^\sigma = -0.167$, image-bootstrap 90% interval $[-0.234, -0.096]$; $A_2^\sigma = -0.118$, $[-0.202, -0.038]$). Their mean, $\bar{A}_{\mathrm{IN}}^\sigma = -0.142$ ($[-0.197, -0.090]$), meets the registered expectation of at most −0.10 with both pairs negative and carries the label "consistent with expectation". The result is the descriptive counterpart of the initialized row at natural scale and does not test the two-by-two design; with two pairs, its intervals cover image sampling only.

Unlike the CIFAR-100 pair, the Singh pairs are matched in clean accuracy and vulnerability. Within each pair clean accuracy and w differ by less than two points (Table 8) and the vulnerability contrast is +0.001 and +0.050 log units, so the lower similarity of these transformers cannot be read off accuracy or vulnerability.

The scratch row has one pair, a ConvNeXt-B and a Swin-B from Liu et al. [38] counted as trained from scratch on indirect evidence. Its contrast is $A_{\mathrm{scr,Liu}}^\sigma = -0.055$ ($[-0.137, +0.022]$), labeled "uncertain": at ImageNet scale the scratch-row estimate rests on one pair and is not determined, and the large scratch-row dissimilarity found on CIFAR should not be carried to this scale.

No transformer-specific direction appears. The four transformers have ρ of −0.211, −0.188, −0.049 and +0.024, but the Singh CNNs are negative as well (−0.122 and −0.298), and the within-pair contrasts A_1^ρ to A_3^ρ are −0.089, +0.110 and +0.091. A Hodge decomposition of the 14-model residual matrix places 0.890 of the directional structure in model

potentials, against 0.143 at random.[1]

G. INPUT-GRADIENT ALIGNMENT

The symmetric term is defined through transfer itself. A registered family therefore asked whether it tracks a quantity measured without any attack: the input-gradient cosine c_{ij} of Equation (8), averaged over clean test images. In every dataset the rank correlation between c_{ij} and $\log \bar{\tau}_{ij}$ over all model pairs is high, both raw (H10) and after additive model main effects are removed from both matrices (H10k; Table 9, Figure 11): $r_S = 0.943$ and 0.944 on CIFAR-10 (20 models), 0.981 and 0.912 on CIFAR-100 (15), and 0.694 and 0.893 on ImageNetV2 (14). Every one-sided Mantel p sits at the permutation floor of 10^{-4}, and each test exceeds its predicted size and is supported after Holm correction.

Two exploratory checks, outside the family, point the same way. Partial Mantel tests that control for both models' log vulnerability give 0.936, 0.954 and 0.532, and adding gradient norm gives 0.937, 0.941 and 0.597. By pair type (lower block of Table 9), alignment is highest between CNNs and lowest in mixed pairs on both CIFAR datasets. On ImageNetV2, descriptively, the transformer pairs are the more aligned ones (0.318 against 0.187 between CNNs).

Alignment measured at one clean point is associated with similar transfer but is not evidence of a mechanism: it is not measured along the attack path, and the residual statistic removes additive model effects only, leaving the block structure of the two families in place. Since mixed pairs are the least aligned on both CIFAR datasets, part of the association could reflect the split between CNNs and transformers. Exploratory analyses that remove or respect this split leave the association high. With pair-type indicators added to the additive fit (S10-3), r_S is 0.917, 0.882 and 0.878 on CIFAR-10, CIFAR-100 and ImageNetV2; the same adjustment on the rank scale gives 0.905, 0.892 and 0.888, and residuals restricted to CNN pairs give 0.963, 0.929 and 0.842. Permuting models only within their family, so that the null distribution keeps the blocks, leaves all six registered statistics at the permutation floor, with null means between -0.008 and $+0.461$. Seeds of one architecture are also close to replicates, which strains the exchangeability that the permutation test assumes. The ResNet-18 and ResNet-50 of Salman et al. [73] have the smallest cosine of the 91 ImageNetV2 pairs ($c = 0.0034$), yet their $\log \bar{\tau} = -0.936$ ranks 55th from the bottom; a recomputation on the GPU confirmed the value, with gradients aligned at low spatial frequencies and opposed in the highest band. For this measure a near-zero cosine does not rule out similar transfer.

H. DEPENDENCE ON SCALE, PANEL AND DATASET

The symmetric findings do not depend on the scale on which rates are compared (Figure 12). The symmetric share of the ViT's source gap is 1.101 on the logit scale and 1.542 on the ratio scale on CIFAR-10, and 1.026 and 1.216 on CIFAR-100; a share above one means that on that scale the directional part narrows the gap. H1 and H2 keep their signs on both scales (Table 6).

The directional term does depend on scale. On the logit scale the ViT's ρ is -0.304 ($[-0.320, -0.289]$) on CIFAR-10 and -0.413 ($[-0.546, -0.280]$) on CIFAR-100, and on the ratio scale -14.66 and -14.61 points. These values are large and negative on both datasets, which makes the ViT the directionally stronger source on the logit scale; on CIFAR-100 this reverses a positive log estimate. The log scale is primary because the quasi-symmetry form $T_{ij} = w_j \bar{\tau}_{ij}$ is additive on it and because the registration fixed it as primary before any of these runs.

The directional term also depends on the panel. Leaving out any one panel member moves ρ(V-scr) only between $+0.001$ and $+0.022$ on CIFAR-10, but against the XCiT-S12 as a single-member secondary panel it is $+0.198$ to $+0.204$, and on CIFAR-100 against the XCiT-S12 and the Hendrycks et al. model $+0.129$ to $+0.221$. Against a single transformer reference, without an interval, the ViT is a directionally weak source.

For this ViT-Tiny, then, the symmetric dissimilarity holds on both CIFAR datasets and on every scale and panel tested, whereas the directional term is small only on the log scale, against a CNN panel and on CIFAR-10.

I. THE CONDITIONING-PROTOCOL LAYER

Everything above uses one conditioning protocol, target-correct, whose rate $r_{\text{cond}} = T_{ij}$ is the quantity decomposed. Because outcomes are logged per image, the same attack runs can be scored under every protocol of Figure 14, and on the pair the choice alone moves the asymmetry from $+4.36 \pm 0.44$ points under target-correct to $+19.37 \pm 1.27$ under successful-source, a mean per-pair spread of 15.01 ± 0.84 points (Figures 13 and 14). The direction is positive under all four protocols in all three seed pairs, and also under MI-FGSM (CNN→ViT $19.07 \pm 0.33\%$ against ViT→CNN $15.42 \pm 0.52\%$, target-correct). The CIFAR-100 and L_2 rows of Figure 13 show the same spread and sign (CIFAR-100: 13.83 ± 1.30 points), and the predictions registered for them are evaluated in Appendix C.

Most of that range is arithmetic. Equation (7) writes the unconditioned rate as an identity in the target's clean error, the conditioned rate and the premise p, the probability that an attack leaves a clean error wrong. Over 36 off-diagonal directions on adversarially trained targets (two datasets, three seed pairs) the measured p is at least 0.989 (mean 0.997) against its upper bound of 1.000, and the $p = 1$ form reproduces every unconditioned rate to within 0.41 points. The premise weakens on standard-trained targets, where p falls to 0.877 and the $p = 1$ form misses by up to 1.58 points on the clean ViT-Tiny target, the one with the largest clean error; there the general form, Equation (6), with measured p applies.

[1]The frozen panel script, run on these matrices for completeness, returns a descriptive mean symmetric share of 0.864 ([0.126, 1.603]), with the denominator rule triggered by the Liu pair.

TABLE 8. ImageNetV2 panel, descriptive and exploratory, with no decision family (2,000 images, PGD-10, $\epsilon = 4/255$, common BicubicRes256Crop224 pipeline). Upper block: the fourteen models by RobustBench identifier; clean and PGD-10 robust accuracy in the common pipeline, w, and split-half log σ and ρ against the six-member CNN panel; the last two columns are reported by RobustBench. Lower block: CNN-transformer pairs k (Section III-F); intervals cover image sampling only (image bootstrap, $B = 2000$).

Model	Role	Family	Clean	PGD-10	w	σ	ρ	RB clean	RB AA
Singh2023Revisiting_ConvNeXt-T-ConvStem	pair 1, IN	CNN	60.90	39.85	34.56	−0.963	−0.122	72.72	49.46
Singh2023Revisiting_ViT-S-ConvStem	pair 1, IN	ViT	61.00	39.90	34.59	−1.130	−0.211	72.56	48.08
Singh2023Revisiting_ConvNeXt-B-ConvStem	pair 2, IN	CNN	63.20	44.05	30.30	−1.118	−0.298	75.90	56.14
Singh2023Revisiting_ViT-B-ConvStem	pair 2, IN	ViT	64.85	44.20	31.84	−1.237	−0.188	76.30	54.66
Liu2023Comprehensive_ConvNeXt-B	pair 3, scr	CNN	65.50	45.65	30.38	−1.148	−0.140	76.02	55.82
Liu2023Comprehensive_Swin-B	pair 3, scr	Swin	64.80	45.40	29.94	−1.203	−0.049	76.16	56.16
Mo2022When_ViT-B	unpaired	ViT	56.75	28.05	50.57	−1.184	+0.024	68.38	34.40
Salman2020Do_R18	panel	CNN	41.35	22.90	44.62	−1.070	+0.202	52.92	25.32
Salman2020Do_R50	panel	CNN	51.90	29.80	42.58	−0.819	+0.003	64.02	34.96
Salman2020Do_50_2	panel	CNN	56.75	31.30	44.85	−0.895	−0.120	68.46	38.14
Engstrom2019Robustness	panel	CNN	51.05	25.65	49.76	−0.890	−0.043	62.56	29.22
Chen2024Data_WRN_50_2	panel	CNN	57.60	35.90	37.67	−0.813	+0.025	68.76	40.60
Peng2023Robust	panel	CNN	60.45	40.45	33.09	−1.039	−0.067	73.44	48.94
Debenedetti2022Light_XCiT-S12	secondary	XCiT	60.35	35.60	41.01	−1.112	−0.194	72.34	41.78

Pair (row)	A_k^σ	90% CI	95% CI	A_k^σ logit	A_k^ρ; A_k^ω
1: ConvNeXt-T / ViT-S (IN)	−0.167	[−0.234, −0.096]	[−0.246, −0.084]	−0.193	−0.089; +0.001
2: ConvNeXt-B / ViT-B (IN)	−0.118	[−0.202, −0.038]	[−0.217, −0.023]	−0.147	+0.110; +0.050
3: ConvNeXt-B / Swin-B (scr)	−0.055	[−0.137, +0.022]	[−0.153, +0.034]	−0.061	+0.091; −0.015
$\bar{A}^\sigma_{\mathrm{IN}}$, pairs 1–2	−0.142	[−0.197, −0.090]	[−0.207, −0.081]	consistent with expectation	
$A^\sigma_{\mathrm{scr,Liu}}$, pair 3	−0.055	[−0.137, +0.022]	[−0.153, +0.034]	uncertain	




FIGURE 11. Input-gradient alignment against similarity on three steles. Cosine c between input gradients against log $\bar{\tau}$ for every model pair on CIFAR-10, CIFAR-100 and ImageNetV2; upper panels raw, lower panels residual below the ledge, with additive model main effects removed. Each panel prints the Spearman r and pair count n; values are positions on the flat faces.

Proposition 2 states when a protocol change is harmless for the decomposition: on the scale $h = -\log(1 - T)$, unconditioned and target-correct rates should differ only through a target-side potential. In the pool the test of that statement finds a largest calibration term of $|g| = 0.0044$ (smallest $p = 0.933$). The difference between unconditioned and target-correct source effects is 0.016 of the target-correct source standard deviation on the h scale, against 0.316 on the ratio scale and 1.655 on the logit scale, and the difference in target effects correlates at 1.000 with the target potential on

TABLE 9. Registered gradient family: Mantel tests of input-gradient cosine c_{ij} against log τ_{ij} (Spearman r_S, one-sided, 9,999 permutations; Holm over six tests). "Residual" removes additive model main effects from both matrices; raw rows are test H10 and residual rows test H10k of Figure 5. S10-3 adds pair-type indicators to the residual fit; it was registered as exploratory in the addendum, specified after the results were seen, and is outside the family. Every one-sided p equals the permutation floor of 10^{-4}. Lower block: mean c_{ij} by pair type (number of pairs), descriptive.

Data	Test	K / pairs	r_S	p	Holm p	Size met	Decision
CIFAR-10	raw	20 / 190	+0.943	10^{-4}	6×10^{-4}	yes ($\geq$0.50)	support
CIFAR-10	residual	20 / 190	+0.944	10^{-4}	6×10^{-4}	yes ($\geq$0.30)	support
CIFAR-100	raw	15 / 105	+0.981	10^{-4}	6×10^{-4}	yes	support
CIFAR-100	residual	15 / 105	+0.912	10^{-4}	6×10^{-4}	yes	support
ImageNetV2	raw	14 / 91	+0.694	10^{-4}	6×10^{-4}	yes	support
ImageNetV2	residual	14 / 91	+0.893	10^{-4}	6×10^{-4}	yes	support
CIFAR-10	S10-3	20 / 190	+0.917	10^{-4}	–	–	–
CIFAR-100	S10-3	15 / 105	+0.882	10^{-4}	–	–	–
ImageNetV2	S10-3	14 / 91	+0.878	10^{-4}	–	–	–

Data	All	CNN–CNN	Transf.–transf.	Mixed
CIFAR-10	0.460	0.543 (91)	0.464 (15)	0.370 (84)
CIFAR-100	0.376	0.462 (55)	0.359 (6)	0.271 (44)
ImageNetV2	0.218	0.187 (36)	0.318 (10)	0.221 (45)

the h scale. Choosing between these two protocols therefore moves target potentials only, provided rates are compared on the h scale.

The identity does not cover the successful-source and both-correct protocols. Images that the target solves on clean input but the source does not are three to four times more fragile than jointly solved ones ($41.2 \pm 0.8\%$ and $59.1 \pm 1.7\%$ fooling against 10.0 and 18.2%), and these marginal subsets differ five-fold in size ($1{,}517 \pm 102$ against 291 ± 16). Target-correct admits both subsets, whose unequal sizes pull the two directions together; both-correct excludes them, and the directional difference reappears 3.91 ± 0.32 points higher. Successful-source selects on the source's own robustness, which does not follow the clean-accuracy gap, so it contributes a second and partly opposing term.

Figure 15 places every measured pair on the clean-accuracy gap. The spread over the three protocols that the identity covers rises with the gap (slope $+0.796$, Pearson correlation $r_P = 0.957$ over 60 pairs) and equals the unconditioned-minus-target-correct difference at 57 of the 60 points, where the identity tracks it to within 1.09 points (mean 0.13). The four-protocol spread does not follow the gap (slope $+0.092$, $r_P = 0.053$). Within the eight-model pool of Table 3, over its 28 pairs, the three-protocol slope is $+0.872$ (model leave-out bootstrap 95% interval $[+0.534, +1.274]$, $r_P = 0.944$) and the four-protocol slope $+0.559$ ($[-0.205, +4.582]$, $r_P = 0.350$). Out of sample, the two-by-two pairs deviate from the line by -0.181 points on average ($[-0.500, +0.138]$), inside the registered ± 1.5-point band (S5). The checkpoint-selection rule moves the four-protocol spread by -2.16 ± 0.93 points without changing the direction (Appendix B).

SVHN shows what happens when the pair is matched in clean accuracy. With clean gaps of 1.94 and 1.74 points in the two seed pairs, the sign of the asymmetry becomes a property of the protocol: target-correct gives -1.16 and -0.85 points




FIGURE 12. Registered estimates carved into one tablet. Upper panel, Contrasts on panel similarity σ: H1, H2 and descriptive ImageNetV2 rows; lower panel, Directional terms: K-b and H3. Circles log, diamonds logit, open marks descriptive; thick and thin bars are 90% and 95% intervals. Values are positions on the flat panel floors; the ± 0.10 lines apply to log rows only.

and successful-source $+2.98$ and $+2.41$, while under both-correct the sign-flip permutation p is 0.105 and TOST accepts equivalence at margins of ± 1 to ± 3 points. Two seed pairs cannot bound run-to-run variation, so the equivalence rests on the within-run comparison and on the agreement of the two runs. Reported under one protocol only, this pair could crown either architecture as the stronger source.

J. COMPUTATIONAL DETAILS

The three CIFAR-10 training pairs of the original cell and their evaluations ran on an NVIDIA RTX 5060 Ti (16 GB). The CIFAR-100, SVHN and L_2 campaigns, the selection trajectories, the external pool and all registered blocks ran on an RTX 5090 (32 GB). Code ran in a container built on NVIDIA's PyTorch 25.01 image (PyTorch 2.6.0a0, CUDA 12.8) with timm 1.0.27, NumPy 1.26.4 and RobustBench commit `78fcc9e`, under deterministic cuDNN settings and seed 42. The registered CIFAR-100, ImageNetV2 and gra-




FIGURE 13. **Protocol by setting as four exploded boards. Transfer asymmetry (CNN to ViT minus ViT to CNN): boards 1-4 are the conditioning protocols, set back layer by layer; rows are settings, mean±SD over three seed pairs, pairs as small circles (SVHN two, no mean). Values are positions on each board's flat face; the spine prints the spread.**




FIGURE 14. **Conditioning sets and measured asymmetry. Conditioning sets: nested evaluation sets as terraces (schematic, not area-proportional; terrace height carries no value) with masks and mean N. Measured asymmetry: mean±SD of the within-pair difference, pairs as open circles, read as positions on the flat card and printed; the steps print the three decomposition terms.**

dient blocks reused existing checkpoints and trained no new model. They ran from a committed snapshot of the rebuilt container, with a forked copy of the transfer-matrix script that reproduced the original outputs exactly in a regression run.

AutoAttack used the standard configuration (APGD-CE, APGD-T, FAB-T, Square), on the full test set in seeded 1,000-image chunks for the original pair and on the first 1,000 test images for the six new models.

The three-seed training pipeline of the original pair took 21.7 GPU-hours. The six new runs took 17.79 hours for their clean and adversarial phases (block B3 in Figure 6), on a GPU at times shared with another process. Adversarial training stopped early in every run, after 36 to 58 epochs, with selected epochs between 16 and 38.

V. DISCUSSION

A. WHAT THE MEASUREMENTS SHOW

Against a fixed panel of robust ResNet-family CNNs, the adversarially trained ViT-Tiny looks like a weak source mostly because it is unlike the panel, and the unlikeness runs both ways: on CIFAR-10 and the log scale, once each target's white-box vulnerability is divided out, panel examples transfer into the ViT about as poorly as its own examples transfer out. The dissimilarity is present when both architectures are trained from scratch on a matched pipeline, and ImageNet initialization removes more of it for the ViT than for the ResNet. The directional term, the part that would make a model a weak source in its own right, is small and independent of architecture only on the log scale, against the CNN panel and on CIFAR-10. On CIFAR-100 its equivalence is refuted ($+0.143$) while the symmetric share replicates, and on the logit scale it is large and negative, which makes the ViT the directionally stronger source (Section IV-H).

The weak-source and dissimilarity readings make different predictions. A source that is weak for its own reasons should gain from a stronger or an architecture-specific attack, yet the gap between ResNet and ViT sources is retained under each source's best attack, and our adaptation of token




FIGURE 15. Protocol spread against the clean-accuracy gap on a deep stage. All 60 model pairs. Back card, Three-protocol spread: unconditioned, target-correct and both-correct, rings the identity prediction at p = 1; front card, Successful-source minus both-correct, the term left out. Values are positions on the flat cards; no line is fitted.

gradient regularization, not validated against its published gain, transfers worse than PGD-10 from every ViT source (Section IV-E). Similarity to the target family then accounts for most of a source's transfer deficit into it, in contrast to source-quality effects such as the better transfer of robust surrogates [34], which the directional term bounds on this panel. For a scratch-trained ViT-Tiny like ours, a black-box score measured with CNN surrogates therefore reflects dissimilarity along with vulnerability, and the surrogate family belongs in the report. The decomposition separates the target-vulnerability and alignment terms of Demontis et al. [16], while their surrogate-complexity term is split between r and $\log \bar{\tau}$ (Proposition 1(d)), and Section IV-G links the similarity term to input-gradient alignment as defined by Zhang et al. [14], an association that leaves the mechanism open.

Whether the scratch-trained dissimilarity persists at ImageNet scale is unknown. On ImageNetV2 the transformers of the two same-recipe pairs initialized from clean models are, descriptively, less similar to the panel, consistent with the registered expectation, while the single scratch-trained pair is uncertain (Section IV-F). Nor is it known which component carries the dissimilarity, since the contrast changes patch stem, attention and parameter count together. Three behavioral readings that such comparisons invite failed direct measurement (Appendix A), and Section V-E outlines designs for the open questions.

B. RELATION TO EARLIER REPORTS

An additive fit with the WideResNet reference places the pair's asymmetry on the source (Section IV-B). Proposition 1 explains why two models cannot support that reading. A two-model matrix carries no circulation, and with a single ViT among CNNs the within-family similarity loads onto the ViT's source and target effects, booking dissimilarity as a weak source. Part (b) holds on any additive scale, including the points scale of that fit. The split becomes identified only once the pair is crossed with a fixed panel and each rate is factored into w, $\bar{\tau}$ and r, and then most of the ViT's source deficit is symmetric. Within the pair, about half of the log asymmetry is the ViT's higher white-box vulnerability and the rest is a seed-stable directional residual of $+0.115$, above the margin, which belongs to this pair: against the panel the ViT's directional term is equivalent to zero on the log scale.

Mahmood et al. [8] report the opposite direction, as do Benz et al. [7] and Shao et al. [9]. The conditioning protocol does not explain the disagreement on CIFAR-10: rescored with Equation (7), their BiT-M-R50x1 and ViT-L-16 pair moves by -0.59 points under unconditioned scoring, against a both-correct asymmetry of -36.80. Their diagonal reports transfer to an independently trained copy of each model, so w is undefined and the decomposition cannot be applied. Our cells suggest one candidate for the reversal. Their models are pre-trained at scale, and in our design ImageNet initialization both moves the ViT toward the CNN panel and gives it a negative directional term on the log scale, in an exploratory secondary analysis. Whether pre-training, scale or both reverse the direction remains open.

C. REPORTING REQUIREMENTS

The four conditioning protocols estimate different quantities, so their distance measures the ambiguity a reader faces when a transfer number arrives without its conditioning set, and that set is the first thing to report (Section IV-I). Unconditioned rates should not serve as architecture comparisons, because their departure from the target-correct rate is the target's clean error entering through the law of total probability (Equation (7)). From published raw rates and clean errors, Equation (6) bounds the target-correct rate, and on the scale $h = -\log(1 - T)$ the two protocols differ only by a target potential (Proposition 2). A claim about direction needs the targets' white-box vulnerabilities and a fixed panel over which w, $\bar{\tau}$ and r can be separated, with the scale named, because the sign of the directional term depended on it here (Section V-A). Clean accuracies and the checkpoint-selection rule belong in the same report (Appendix B). Initialization has to be kept apart from architecture: by the interaction of Section IV-D, an ImageNet-initialized ViT set against a scratch-trained CNN mixes two effects.

Under the matched mixed-loss recipe the CNN gives the higher absolute robust accuracy under every attack we ran (Section IV-A), yet the WideResNet reference at 62.76% shows that a larger model trained on extra data with a stronger recipe [65] moves robustness further than the choice between these two families.

D. LIMITATIONS

Every architectural conclusion rests on two small models, a ResNet-18 and a ViT-Tiny on 32×32 images upsampled to 224×224, with three runs in the original ViT cell and two in each new cell. Welch intervals, at 1.10 to 1.95 degrees of freedom, still place H1 and H2 away from zero but do not support the equivalence of the bridge between the two ResNet-18 pipelines (S1). The binding panel intervals hold the test images fixed; a hierarchical bootstrap that also resamples images, produced after the results were seen, changes no decision, though over three runs per cell it understates the run component. ViT adversarial training depends on pretraining on small datasets [24], and robust transformers have been trained with dedicated recipes [25]. The scratch-trained ViT is also the least accurate and most vulnerable model of the design, so a less converged solution and an architectural dissimilarity cannot be told apart; the ImageNet-initialized ViT, close to the ResNet cells in clean accuracy, stays less similar to the panel only in an unregistered comparison (Section IV-D).

Beyond its dependence on scale and dataset, the directional term is about $+0.20$ for the scratch ViT against the secondary XCiT panel, and its mean of -0.118 in the ImageNet-initialized ViT cell lies outside the margin. Four of the seven CIFAR-10 panel members are ResNet-18 variants; without them no decision changes in an exploratory check (Section IV-D), but the panel stays within the ResNet family. The initialization factor bundles pretrained weights, clean-phase length and input normalization, whose separate effects, and their interaction with architecture, are not identified. On CIFAR-100 the ViT's quantities may be confounded with its clean accuracy, which lies below the panel's, and the both-correct sensitivity that would bound this was not produced. TGR ran with its original settings in adapted form, without a check that the adaptation reproduces its published gain on a standard ViT, and attacks with input diversity, more steps or the self-ensemble of Naseer et al. [10] were not run; step sizes also differ between attacks by design. The simplest law the decomposition suggests, log asymmetry equal to the log vulnerability ratio, failed along the training trajectories ($R^2 = 0.201$ at unit slope) and is not claimed.

Our training covers three datasets; ImageNetV2 enters only through independently trained checkpoints, and that panel is descriptive. Its initialized row rests on two pairs of Singh et al. [26] and its scratch row on one pair of Liu et al. [38], counted as scratch-trained on indirect evidence. The ViT-B of Mo et al. [24] has a short adversarial schedule and no partner, panel initializations were not verified, and the architectures (convolution-stem ViTs, ConvNeXt, Swin) differ from ours. The common preprocessing departs from some models' own pipeline by at most 0.95 points of clean accuracy for the models in the matrix, and the distribution shift of ImageNetV2 enters both w and T. The gradient cosine is measured at one clean point, and the registered partial statistic removes only additive main effects; the analyses that also control the family split were specified after the results were seen. An energy-weighted cosine can also hide alignment, as one ImageNet ResNet pair with above-median transfer similarity shows (Section IV-G). Every model is trained under L_∞ at $\epsilon = 8/255$, so the L_2 result probes the protocol and not L_2 robustness. The mechanism account of the protocol spread is incomplete: the composition of marginal subsets covers three of the four protocols, and the successful-source protocol adds a second driver tied to the source's own robustness. Our leakage ablation, finally, answers a weaker question than the one posed, since split identity and leakage are not separable in its design.


E. FUTURE DIRECTIONS

A two-by-two design at the next size, ViT-Small against ResNet-50 under one recipe, would show whether the dissimilarity and its response to initialization belong to the families or to these small models (costs in Section IV-J). At ImageNet scale, same-recipe pairs trained from scratch would replace the single indirect pair. A cell that applies ImageNet normalization to random weights would separate normalization from pretraining. Measuring gradient alignment along the PGD path and per frequency band would test whether the clean point stands in for the path the attack travels.

VI. CONCLUSION

We asked whether an adversarially trained ViT that looks like a weak transfer source against CNNs crafts weaker examples or is simply different from the models it attacks. Measured against a fixed panel of robust CNNs, with the vulnerability of each target taken out, most of ViT-Tiny's source gap on CIFAR-10 is symmetric: the ViT and the CNNs transfer poorly to each other in both directions, and the ViT seeds resemble one another more than they resemble the panel. Trained from scratch on a matched input pipeline and recipe, the ViT is less similar to the panel than the ResNet, a contrast that also carries the ViT's lower clean accuracy; ImageNet initialization removes more of the dissimilarity for the ViT than for the ResNet, and averaged over initialization, architecture leaves the log-scale directional term within the margin. Momentum PGD and our adapted token gradient regularization do not close the gap, and the registered AutoAttack rule flags none of the six new models.

The directional term is small only on the log scale, against a CNN panel and on CIFAR-10. On CIFAR-100 its equivalence is refuted and the ViT is also a directionally weaker source, and on the logit scale it is large and negative, so that there the ViT is the directionally stronger source; the evidence from ImageNet models is descriptive. Input-gradient alignment tracks pairwise similarity on CIFAR-10, CIFAR-100



	clean	2/255	4/255	8/255	16/255
▽WRN-28-10	89.5	85.4	80.0	66.9	47.4
□ResNet-18 AT	85.8	77.3	66.7	44.2	20.4
△ViT-Tiny AT	73.5	64.1	53.9	32.7	12.2

accuracy %, back to front; AT models: mean of 3 seed pairs, largest SD 0.59; WRN-28-10: one model

FIGURE 16. Robust accuracy under PGD-10 as cut-out profiles. Each card's top edge traces CIFAR-10 test accuracy over the budget ϵ, clean to 16/255, as height above its own base (back bases dashed; scale bar 25 points); the number rows print the same values, which carry the result (mean of three seed pairs; WRN-28-10 is one RobustBench model).

and ImageNetV2; we read it as an association a gradient-alignment account requires, not as a mechanism. Our training covers three datasets, CIFAR-10, CIFAR-100 and SVHN, with ResNet-18 and ViT-Tiny at CIFAR scale; ImageNetV2 enters only through independently trained checkpoints, so whether the pattern holds for larger models trained from scratch at ImageNet scale remains to be measured.

A cross-architecture transfer comparison becomes interpretable when it states its conditioning set, measures each target's vulnerability separately from the similarity between models, does so against models outside the compared pair, and names the scale on which direction is read; Section V-C turns these into reporting requirements.

APPENDIX A BEHAVIORAL MEASUREMENTS OF THE PAIR

The CNN's margin over the ViT is widest at small perturbation budgets (77.30 against 64.10% at $2/255$) and narrows at $16/255$ (20.38 against 12.16%; Figure 16).

Input gradients of per-sample losses were measured on 500 test images per run. Sparsity is scored with Hoyer sparsity, the Gini coefficient and the fraction of components below 1% of the per-sample maximum, all scale-invariant [76], and spatial locality on the normalized channel-summed energy map (Table 11). CNN gradients are sparser on all three measures in every run (Table 10). Paired tests within runs reject the null (Holm $p \leq 2.2 \times 10^{-12}$), but at the run level, the unit an architectural claim needs, Holm correction leaves $p = 0.108$, so the ordering is reproducible without being significant.

TABLE 10. Gradient characteristics (n = 500 images per run; mean±SD over three runs). The native control is one CIFAR-native ViT checkpoint (4×4 patches) that predates the fixed-split protocol.

Metric	ResNet-18 AT	ViT-Tiny AT	ViT (native)
Hoyer sparsity	0.4928±0.0120	0.4561±0.0055	0.4046
Gini coefficient	0.6498±0.0089	0.6099±0.0051	0.5712
Fraction <1% of max	0.3477±0.0210	0.2682±0.0090	0.1785
Alignment (absolute)	0.0378±0.0009	0.0562±0.0004	0.0794
Alignment (signed)	0.0010±0.0003	0.0004±0.0001	–

TABLE 11. Spatial locality of input gradients (n = 500 per run; mean±SD over three runs). p: one-sample t-test on the three per-run paired differences, Holm-corrected over the four measures.

Measure	ResNet-18	ViT-Tiny	Diff. (R−V)	p (Holm)
Area for 50% energy	0.0378±0.0017	0.0397±0.0010	−0.0019±0.0027	0.54
Area for 90% energy	0.2345±0.0078	0.2570±0.0067	−0.0224±0.0133	0.40
Spatial entropy (nat)	5.2014±0.0387	5.2524±0.0197	−0.0509±0.0580	0.54
Moran's I	0.4141±0.0132	0.3941±0.0024	+0.0200±0.0156	0.47

Adversarial training produces it: clean-trained, the ViT is the sparser model (Hoyer 0.380 against 0.347), and a CIFAR-native ViT is less sparse than the upsampled one. The ViT has the higher absolute alignment (run-level $p = 0.0009$), while signed alignment stays at or below 0.0014 for both. No spatial descriptor differs at the run level (Holm p from 0.40 to 0.54), and two of them change sign across runs, so the sparser CNN gradients are not more localized.

Feature drift is the clean-to-adversarial cosine at each residual block output under the model's own PGD-10 attack ($n = 1{,}000$ per run). In the ViT it is gradual and leaves feature norms within 0.45%; in the CNN it concentrates in the first block of the last stage, with a cosine of 0.8777 against 0.9607 one block earlier and 0.9108 one block later, and a $-13.14 \pm 1.89\%$ norm change. The CLS token drifts about three times as far as the patch-token mean at their minima, which lie at blocks 11 and 9. The entropy of the head-averaged CLS attention does not change: the largest per-layer change is 0.0045 nats against clean values of 4.61 to 5.11, and run-level TOST at ±0.05 nats accepts equivalence in all 12 layers (left card of Figure 17). Attention displacement grows from 0.028 to 0.084 with depth, so the attack redirects attention without broadening it. Last-block drift does not separate flipped from unflipped images (run-level $p = 0.20$ for the ViT, 0.080 for the CNN).

An earlier matched-budget comparison on the pair agrees with Section IV-E: token gradient regularization [17] transferred worse than MI-FGSM [49] from the ViT (12.70 ± 0.41 against $15.71 \pm 0.60\%$ target-correct), in a run separate from the MI-FGSM check of Section IV-I ($15.42 \pm 0.52\%$).

APPENDIX B CHECKPOINT SELECTION AND SOURCES OF VARIANCE

Varying only how the final checkpoint is chosen from a fixed trajectory (validation split, patience and curve smoothing; eighteen combinations) moves PGD-10 accuracy by 2.62 to 2.85 points per seed for the ResNet and 1.58 to 2.09 for the




FIGURE 17. Feature degradation of ViT-Tiny under attack, block by block. The clean and PGD-10 image enter the spine, block 1 at the bottom; per block over three runs: CLS attention entropy change with 90% TOST intervals inside the ±0.05-nat band, attention displacement (TV), block-output cosine, mean±SD. Values are positions on the flat cards.

ViT. This dispersion is quoted in points and deliberately not as a ratio to seed-level dispersion, because that ratio runs from 0.67 to 3.38 (ResNet) and 0.63 to 7.38 (ViT) depending on the reference cell. Selection paths can be unstable while outcomes are not: on CIFAR-100 the selected epoch varies by 25 epochs across ResNet seeds, yet the test PGD-10 standard deviation is 0.32 points.

At their last checkpoints, twenty epochs after the selected ones, the three training pairs have a clean gap of 10.55 ± 0.59 instead of 12.26 ± 0.90 points and a four-protocol spread of 12.84 ± 0.34 points, with the CNN→ViT sign kept under every protocol and the identity premise intact ($p \geq 0.9915$).

The comparisons face four sources of variance. Over three attack seeds on the first 1,000 test images of one seed pair, robust accuracy has a standard deviation of 0.05 points for the CNN and 0.00 for the ViT. Training runs move accuracy by a standard deviation of at most 0.55 points and the transfer asymmetry by 0.23 to 1.27 points, depending on the protocol. Within a fixed seed pair the protocol moves the asymmetry by 15.01 ± 0.84 points, and the selection rule moves the spread by about two (Section IV-I). The ratio of protocol to run dispersion is not used as evidence, since with two degrees of freedom its χ^2 interval is very wide.

APPENDIX C REGISTERED PREDICTIONS FOR CIFAR-100 AND THE L_2 BUDGET

Three directional predictions and three endpoint bands were registered before any CIFAR-100 measurement. The predicted sign held in all twelve measurements. The predicted larger spread than on CIFAR-10 named the CIFAR-10 spread, then quoted as 10.45 points; the measured 13.83 exceeds that number but not the spread under the strict successful-source reading (15.01), and the prediction counts as failed. The third prediction, a deviation of unconditioned from conditioned rates growing with target clean error, gave a positive slope ($+0.656$, $r_P = 0.931$), but two of the three targets have almost equal clean errors (36.15 and 36.36%), so it is not testable in this design.

The clean-accuracy band for the ViT (33 to 40%) was missed at $43.17 \pm 1.10\%$, because the ViT kept 0.885 of its clean pre-training accuracy under adversarial training against 0.802 for the ResNet. Both adversarial endpoints fell inside their bands, by 0.22 points (AutoAttack) and 0.48 points (PGD-10), margins below the 0.18 to 1.83 points by which checkpoint selection moves PGD-10 accuracy on this dataset (Appendix B).

Under an L_2 budget of $\epsilon = 0.5$ on the same CIFAR-10 checkpoints, the protocol spread fell to 10.92 ± 0.82 points with the sign positive in all twelve measurements, so two of three registered predictions hold. The third cannot fail once Equation (7) holds: the fitted slope of $+0.914$ estimates $1 - r_{\text{cond}}$, and we report the slope rather than a correlation, because the eighteen directions take only seven distinct target-error values, and six of the directions share the fixed WideResNet target. The CNN keeps its absolute advantage (McNemar $p \leq 2.729 \times 10^{-58}$ per seed pair).

APPENDIX D EXPLORATORY RE-ANALYSES OF THE CIFAR-10 FAMILIES

Both analyses were specified after the results and an internal review had been seen, reuse the frozen functions unchanged and enter no decision family. Table 12 splits the two-by-two contrasts into simple effects. Table 13 drops the four panel members with the eight-block ResNet-18 layout; the three left are fewer than the registered minimum of five, so the frozen script was run with its optional three-member flag.

DATA AND CODE AVAILABILITY

The CIFAR-10 and CIFAR-100 [11], SVHN [77] and ImageNetV2 MatchedFrequency [13] datasets are public. Panel checkpoints come from RobustBench [12], and the ImageNet initializations are the public DeiT-Tiny [57] and ResNet-18 A1 [58] weights from timm. The analysis pipeline, the scripts behind every table and figure, the per-sample evaluation records, the validation-split indices and the seed lists are available at https://github.com/cagrisahin58/cnn-vit-robustness-protocols. The repository also holds the pre-registration documents with their freeze records, the frozen analysis script, the cell tables whose SHA-256 digests the analysis outputs record, and a machine-read copy of Tables 1 and 2 of Mahmood et al. [8] with the scripts that re-score them. The registration documents, the frozen analysis script and the cell tables are also time-stamped in the development repository (commits e32f2ce and 7325419).

TABLE 12. Simple effects of the two-by-two design on CIFAR-10 (split-half, log scale; exploratory): architecture (Arch.) is ViT minus ResNet within a row, initialization (Init.) ImageNet minus scratch within an architecture; registered counterparts in parentheses. Pooled intervals as in Table 6; Welch intervals use only the cells of the contrast.

Contrast	Estimate	Pooled 90% CI	Welch 90% CI	Logit
Panel similarity σ				
Arch., scratch (H1)	−0.364	[−0.415, −0.314]	[−0.472, −0.256]	−0.498
Arch., ImageNet	−0.104	[−0.159, −0.049]	[−0.318, +0.109]	−0.144
Init., ViT	+0.270	[+0.219, +0.320]	[+0.043, +0.496]	+0.372
Init., ResNet	+0.009	[−0.046, +0.065]	[−0.084, +0.102]	+0.018
Interaction (H2)	+0.260	[+0.186, +0.335]	[+0.113, +0.407]	+0.354
Arch. main effect	−0.234	[−0.271, −0.197]	[−0.308, −0.161]	−0.321
Directional term ρ				
Arch., scratch	+0.070	[+0.039, +0.101]	[−0.031, +0.172]	−0.061
Arch., ImageNet	−0.064	[−0.098, −0.030]	[−0.140, +0.013]	−0.112
Init., ViT (S2)	−0.130	[−0.161, −0.099]	[−0.182, −0.078]	−0.034
Init., ResNet	+0.004	[−0.030, +0.038]	[−0.122, +0.130]	+0.017
Interaction	−0.134	[−0.180, −0.088]	[−0.208, −0.060]	−0.051
Arch. main effect (H3)	+0.003	[−0.020, +0.026]	[−0.034, +0.041]	−0.087

TABLE 13. CIFAR-10 families with the registered panel and, exploratorily, without its ResNet-18 variants (Engstrom2019 RN-50, Carmon2019 and Gowal2020 WRN-28-10), under the frozen rules; intervals as in Tables 4 and 6. The H2 logit estimate stays positive (+0.390).

	Seven members		Three members		
Test	Estimate	90% CI	Estimate	90% CI	Decision
H1	−0.364	[−0.415, −0.314]	−0.412	[−0.465, −0.359]	support
H2	+0.260	[+0.186, +0.335]	+0.295	[+0.216, +0.373]	support
H3	+0.003	[−0.020, +0.026]	+0.004	[−0.021, +0.029]	equiv.
K-a	0.936	[0.925, 0.948]	0.921	[0.905, 0.936]	support
K-b	+0.012	[−0.007, +0.031]	+0.018	[−0.008, +0.044]	equiv.
K-c	+0.566	[+0.537, +0.604]	+0.673	[+0.641, +0.714]	support
Region	O1		O1		

Since every protocol and decomposition term is computed from these records, all reported numbers can be reproduced without retraining. Trained checkpoints are available from the authors on request.

ACKNOWLEDGMENT

The authors acknowledge the computational resources provided by the Department of Software Engineering, Fırat University.

The authors used Claude (Anthropic) during the preparation of this work. The tool assisted with drafting and revising the manuscript text in all sections, and with implementing the analysis and verification scripts released with the paper. The study design, the experimental protocol, and all conclusions are the authors', who verified every reported number against the released artifacts.

REFERENCES

[1] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus, "Intriguing properties of neural networks," in *Proc. International Conference on Learning Representations (ICLR)*, 2014.

[2] I. J. Goodfellow, J. Shlens, and C. Szegedy, "Explaining and harnessing adversarial examples," in *Proc. International Conference on Learning Representations (ICLR)*, 2015.

[3] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly *et al.*, "An image is worth 16x16 words: Transformers for image recognition at scale," in *Proc. International Conference on Learning Representations (ICLR)*, 2021.

[4] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 30, 2017.

[5] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 770–778.

[6] Y. Bai, J. Mei, A. L. Yuille, and C. Xie, "Are transformers more robust than CNNs?" in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 34, 2021, pp. 26 831–26 843.

[7] P. Benz, S. Ham, C. Zhang, A. Karjauv, and I. S. Kweon, "Adversarial robustness comparison of vision transformer and MLP-Mixer to CNNs," in *Proc. British Machine Vision Conference (BMVC)*, 2021.

[8] K. Mahmood, R. Mahmood, and M. van Dijk, "On the robustness of vision transformers to adversarial examples," in *Proc. IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021, pp. 7818–7827.

[9] R. Shao, Z. Shi, J. Yi, P.-Y. Chen, and C.-J. Hsieh, "On the adversarial robustness of vision transformers," *Transactions on Machine Learning Research*, 2022.

[10] M. Naseer, K. Ranasinghe, S. Khan, F. S. Khan, and F. Porikli, "On improving adversarial transferability of vision transformers," in *Proc. International Conference on Learning Representations (ICLR)*, 2022.

[11] A. Krizhevsky and G. Hinton, "Learning multiple layers of features from tiny images," University of Toronto, Tech. Rep., 2009.

[12] F. Croce, M. Andriushchenko, V. Sehwag, E. Debenedetti, N. Flammarion, M. Chiang, P. Mittal, and M. Hein, "RobustBench: a standardized adversarial robustness benchmark," in *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2021.

[13] B. Recht, R. Roelofs, L. Schmidt, and V. Shankar, "Do ImageNet classifiers generalize to ImageNet?" in *Proc. International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 97. PMLR, 2019, pp. 5389–5400.

[14] Y. Zhang, S. Hu, L. Y. Zhang, J. Shi, M. Li, X. Liu, W. Wan, and H. Jin, "Why does little robustness help? A further step towards understanding adversarial transferability," in *Proc. IEEE Symposium on Security and Privacy (S&P)*, 2024.

[15] H. Caussinus, "Contribution à l'analyse statistique des tableaux de corrélation," *Annales de la Faculté des sciences de Toulouse : Mathématiques*, vol. 29, pp. 77–183, 1965.

[16] A. Demontis, M. Melis, M. Pintor, M. Jagielski, B. Biggio, A. Oprea, C. Nita-Rotaru, and F. Roli, "Why do adversarial attacks transfer? Explaining transferability of evasion and poisoning attacks," in *Proc. 28th USENIX Security Symposium (USENIX Security 19)*, 2019, pp. 321–338.

[17] J. Zhang, Y. Huang, W. Wu, and M. R. Lyu, "Transferable adversarial attacks on vision transformers with token gradient regularization," in *Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023, pp. 16 415–16 424.

[18] Ç. Şahin and Ö. Yıldırım, "A behavioral comparison of adversarially trained ResNet-18 and ViT-Tiny on CIFAR-10: Transfer metrics, gradient structure, and block-wise feature drift," in *Proc. ATEEC 2026*, 2026, preliminary version of the present study; submitted.

[19] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu, "Towards deep learning models resistant to adversarial attacks," in *Proc. International Conference on Learning Representations (ICLR)*, 2018.

[20] D. Wu, Y. Wang, S.-T. Xia, J. Bailey, and X. Ma, "Skip connections matter: On the transferability of adversarial examples generated with ResNets," in *Proc. International Conference on Learning Representations (ICLR)*, 2020.

[21] C. Xie and A. Yuille, "Intriguing properties of adversarial training at scale," in *Proc. International Conference on Learning Representations (ICLR)*, 2020.

[22] M. Raghu, T. Unterthiner, S. Kornblith, C. Zhang, and A. Dosovitskiy, "Do vision transformers see like convolutional neural networks?" in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 34. Curran Associates, Inc., 2021, pp. 12 116–12 128.

[23] S. Bhojanapalli, A. Chakrabarti, D. Glasner, D. Li, T. Unterthiner, and A. Veit, "Understanding robustness of transformers for image classification," in *Proc. IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021, pp. 10 211–10 221.

[24] Y. Mo, D. Wu, Y. Wang, Y. Guo, and Y. Wang, "When adversarial training meets vision transformers: Recipes from training to architecture," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 35, 2022, pp. 18 599–18 611.

[25] E. Debenedetti, V. Sehwag, and P. Mittal, "A light recipe to train robust vision transformers," in *Proc. IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, 2023, pp. 225–253.

[26] N. D. Singh, F. Croce, and M. Hein, "Revisiting adversarial training for ImageNet: Architectures, training and generalization across threat models," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 36, 2023.

[27] S. Jain and T. Dutta, "Towards understanding and improving adversarial robustness of vision transformers," in *Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024, pp. 24 736–24 745.

[28] J. Wu, Z. Song, X. Zhang, S. Xie, L. Lin, and K. Wang, "Vision transformers beat WideResNets on small scale datasets adversarial robustness," in *Proc. AAAI Conference on Artificial Intelligence (AAAI)*, vol. 39, no. 1, 2025, pp. 886–894.

[29] F. Pinto, P. H. S. Torr, and P. K. Dokania, "An impartial take to the CNN vs Transformer robustness contest," in *Proc. European Conference on Computer Vision (ECCV)*, ser. Lecture Notes in Computer Science, vol. 13673. Cham: Springer, 2022, pp. 466–480.

[30] K. Ali, M. S. Bhatti, A. Saeed, A. Athar, M. A. Al Ghamdi, S. H. Almotiri, and S. Akram, "Adversarial robustness of vision transformers versus convolutional neural networks," *IEEE Access*, vol. 12, pp. 105 281–105 293, 2024.

[31] N. Papernot, P. McDaniel, and I. Goodfellow, "Transferability in machine learning: from phenomena to black-box attacks using adversarial samples," *arXiv preprint arXiv:1605.07277*, 2016.

[32] G. Adam, P. Smirnov, B. Haibe-Kains, and A. Goldenberg, "Reducing adversarial example transferability using gradient regularization," arXiv preprint arXiv:1904.07980, 2019.

[33] J. M. Springer, M. Mitchell, and G. T. Kenyon, "A little robustness goes a long way: Leveraging robust features for targeted transfer attacks," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 34, 2021.

[34] M. Awad, M. Akrm, and W. Gomaa, "Defense that attacks: How robust models become better attackers," arXiv preprint arXiv:2512.02830, 2025.

[35] Z. Wei, J. Chen, M. Goldblum, Z. Wu, T. Goldstein, and Y.-G. Jiang, "Towards transferable adversarial attacks on vision transformers," in *Proc. AAAI Conference on Artificial Intelligence (AAAI)*, vol. 36, no. 3, 2022, pp. 2668–2676.

[36] W. Ma, Y. Li, X. Jia, and W. Xu, "Transferable adversarial attack for both vision transformers and convolutional networks via momentum integrated gradients," in *Proc. IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023, pp. 4607–4616.

[37] Z. Chen, C. Xu, H. Lv, S. Liu, and Y. Ji, "Understanding and improving adversarial transferability of vision transformers and convolutional neural networks," *Information Sciences*, vol. 648, p. 119474, 2023.

[38] C. Liu, Y. Dong, W. Xiang, X. Yang, H. Su, J. Zhu, Y. Chen, Y. He, H. Xue, and S. Zheng, "A comprehensive study on robustness of image classification models: Benchmarking and rethinking," *International Journal of Computer Vision*, vol. 133, no. 2, pp. 567–589, 2025.

[39] C. Sitawarin, J. Chang, D. Huang, W. Altoyan, and D. Wagner, "PubDef: Defending against transfer attacks from public models," in *Proc. International Conference on Learning Representations (ICLR)*, 2024.

[40] X. Jiang, L.-H. Lim, Y. Yao, and Y. Ye, "Statistical ranking and combinatorial Hodge theory," *Mathematical Programming*, vol. 127, no. 1, pp. 203–244, 2011.

[41] D. Balduzzi, K. Tuyls, J. Pérolat, and T. Graepel, "Re-evaluating evaluation," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 31, 2018.

[42] N. Mantel, "The detection of disease clustering and a generalized regression approach," *Cancer Research*, vol. 27, no. 2, pp. 209–220, Feb. 1967.

[43] P. E. Smouse, J. C. Long, and R. R. Sokal, "Multiple regression and correlation extensions of the Mantel test of matrix correspondence," *Systematic Zoology*, vol. 35, no. 4, pp. 627–632, 1986.

[44] N. Carlini, A. Athalye, N. Papernot, W. Brendel, J. Rauber, D. Tsipras, I. Goodfellow, A. Madry, and A. Kurakin, "On evaluating adversarial robustness," *arXiv preprint arXiv:1902.06705*, 2019.

[45] N. Carlini and D. Wagner, "Towards evaluating the robustness of neural networks," in *Proc. IEEE Symposium on Security and Privacy (SP)*, 2017, pp. 39–57.

[46] F. Croce and M. Hein, "Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks," in *Proc. International Conference on Machine Learning (ICML)*, 2020, pp. 2206–2216.

[47] F. Tramèr, N. Carlini, W. Brendel, and A. Madry, "On adaptive attacks to adversarial example defenses," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 33, 2020.

[48] Y. Liu, X. Chen, C. Liu, and D. Song, "Delving into transferable adversarial examples and black-box attacks," in *Proceedings of the 5th International Conference on Learning Representations (ICLR)*, 2017.

[49] Y. Dong, F. Liao, T. Pang, H. Su, J. Zhu, X. Hu, and J. Li, "Boosting adversarial attacks with momentum," in *Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018, pp. 9185–9193.

[50] Z. Zhao, H. Zhang, R. Li, R. Sicre, L. Amsaleg, M. Backes, Q. Li, Q. Wang, and C. Shen, "Revisiting transferable adversarial images: Systemization, evaluation, and new insights," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 48, no. 1, pp. 765–780, 2026.

[51] D. Ravikumar, S. Kodge, I. Garg, and K. Roy, "TREND: Transferability-based robust ENsemble design," *IEEE Transactions on Artificial Intelligence*, vol. 4, no. 3, pp. 534–548, 2023.

[52] Q. Li, Y. Guo, W. Zuo, and H. Chen, "Towards evaluating transfer-based attacks systematically, practically, and fairly," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 36, 2023, pp. 41 707–41 726.

[53] W. Yu, J. Gu, Z. Li, and P. Torr, "Reliable evaluation of adversarial transferability," in *Proc. IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, 2025, pp. 797–810.

[54] F. Waseda, S. Nishikawa, T.-N. Le, H. H. Nguyen, and I. Echizen, "Closer look at the transferability of adversarial examples: How they fool different models differently," in *Proc. IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 2023, pp. 1360–1368.

[55] H. Zhang, Y. Yu, J. Jiao, E. Xing, L. El Ghaoui, and M. Jordan, "Theoretically principled trade-off between robustness and accuracy," in *Proc. International Conference on Machine Learning (ICML)*, 2019, pp. 7472–7482.

[56] R. Wightman, "PyTorch image models," https://github.com/huggingface/pytorch-image-models, 2019.

[57] H. Touvron, M. Cord, M. Douze, F. Massa, A. Sablayrolles, and H. Jégou, "Training data-efficient image transformers & distillation through attention," in *Proc. International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 139. PMLR, 2021, pp. 10 347–10 357.

[58] R. Wightman, H. Touvron, and H. Jégou, "ResNet strikes back: An improved training procedure in timm," arXiv preprint arXiv:2110.00476, 2021.

[59] L. Rice, E. Wong, and J. Z. Kolter, "Overfitting in adversarially robust deep learning," in *Proc. International Conference on Machine Learning (ICML)*, 2020, pp. 8093–8104.

[60] I. Loshchilov and F. Hutter, "SGDR: Stochastic gradient descent with warm restarts," in *Proc. International Conference on Learning Representations (ICLR)*, 2017.

[61] ——, "Decoupled weight decay regularization," in *Proc. International Conference on Learning Representations (ICLR)*, 2019.

[62] E. Wong, L. Rice, and J. Z. Kolter, "Fast is better than free: Revisiting adversarial training," in *Proc. International Conference on Learning Representations (ICLR)*, 2020.

[63] L. Engstrom, A. Ilyas, H. Salman, S. Santurkar, and D. Tsipras, "Robustness (Python library)," https://github.com/MadryLab/robustness, 2019.

[64] Y. Carmon, A. Raghunathan, L. Schmidt, P. Liang, and J. C. Duchi, "Unlabeled data improves adversarial robustness," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 32, 2019.

[65] S. Gowal, C. Qin, J. Uesato, T. Mann, and P. Kohli, "Uncovering the limits of adversarial training against norm-bounded adversarial examples," *arXiv preprint arXiv:2010.03593*, 2020.

[66] V. Sehwag, S. Mahloujifar, T. Handina, S. Dai, C. Xiang, M. Chiang, and P. Mittal, "Robust learning meets generative models: Can proxy distributions improve adversarial robustness?" in *Proc. International Conference on Learning Representations (ICLR)*, 2022.

[67] S. Addepalli, S. Jain, and R. V. Babu, "Efficient and effective augmentation strategy for adversarial training," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 35, 2022.

[68] R. Rade and S.-M. Moosavi-Dezfooli, "Reducing excessive margin to achieve a better accuracy vs. robustness trade-off," in *Proc. International Conference on Learning Representations (ICLR)*, 2022. [Online]. Available: https://openreview.net/forum?id=Azh9QBQ4tR7

[69] T. Pang, M. Lin, X. Yang, J. Zhu, and S. Yan, "Robustness and accuracy could be reconcilable by (proper) definition," in *Proc. International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 162. PMLR, 2022, pp. 17 258–17 277.

[70] Z. Wang, T. Pang, C. Du, M. Lin, W. Liu, and S. Yan, "Better diffusion models further improve adversarial training," in *Proc. International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 202. PMLR, 2023, pp. 36 246–36 263.
[71] X. Jia, Y. Zhang, B. Wu, K. Ma, J. Wang, and X. Cao, "LAS-AT: Adversarial training with learnable attack strategy," in *Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022, pp. 13 388–13 398.
[72] D. Hendrycks, K. Lee, and M. Mazeika, "Using pre-training can improve model robustness and uncertainty," in *Proc. International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 97. PMLR, 2019, pp. 2712–2721.
[73] H. Salman, A. Ilyas, L. Engstrom, A. Kapoor, and A. Madry, "Do adversarially robust ImageNet models transfer better?" in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 33, 2020.
[74] E.-C. Chen and C.-R. Lee, "Data filtering for efficient adversarial training," *Pattern Recognition*, vol. 151, p. 110394, 2024.
[75] S. Peng, W. Xu, C. Cornelius, M. Hull, K. Li, R. Duggal, M. Phute, J. Martin, and D. H. Chau, "Robust principles: Architectural design principles for adversarially robust CNNs," in *Proc. British Machine Vision Conference (BMVC)*, 2023.
[76] N. Hurley and S. Rickard, "Comparing measures of sparsity," *IEEE Transactions on Information Theory*, vol. 55, no. 10, pp. 4723–4741, Oct. 2009.
[77] Y. Netzer, T. Wang, A. Coates, A. Bissacco, B. Wu, and A. Y. Ng, "Reading digits in natural images with unsupervised feature learning," in *NIPS Workshop on Deep Learning and Unsupervised Feature Learning*, 2011.

ÇAĞRI ŞAHİN received the B.Sc. degree in software engineering from Fırat University, Elazığ, Türkiye. He is currently pursuing the Ph.D. degree with the Department of Software Engineering, Fırat University. His research interests include adversarial machine learning, deep learning security, and computer vision, with a focus on the robustness of neural network architectures against adversarial perturbations.

ÖZAL YILDIRIM is with the Department of Software Engineering, Fırat University, Elazığ, Türkiye. His research interests include deep learning, computer vision, and biomedical signal processing.