Unsure if you were informed already, but because this was a rush order the calibration is non-standard. Please use these Q factors and calculation method.

Read calibration data (factory calibrated) from PROM

Variable	Description /Equation	Recommender Variable Type	Size [Bit]	Value Min	Value Max
C0	Bridge Offset	Signed int 16	14	-8192	8191
C1	Gain	Signed int 16	14	-8192	8191
C2	Non-Linearity 2nd Order	Signed int 16	9	-256	255
C3	Temperature Coefficient, Bridge Offset 1st order	Signed int 16	10	-512	511
C4	Temperature Coefficient, Bridge Offset 2nd order	Signed int 16	9	-256	255
C5	Temperature Coefficient, Gain 1st order	Signed int 16	10	-512	511
C6	Temperature Coefficient, Gain 2nd order	Signed int 16	9	-256	255
Q0	Calculation Factor 0	Unsigned char 8	3	0	7
Q1	Calculation Factor 1	Unsigned char 8	3	0	7
Q2	Calculation Factor 2	Unsigned char 8	3	0	7
A0	Temperature Coefficient 0	Signed char 8	8	-128	127
A1	Temperature Coefficient 1	Signed char 8	8	-128	127
A2	Temperature Coefficient 2	Signed char 8	8	-128	127

Read digital pressure and temperature data

D1	Digital pressure value	Unsigned long	24	0	16777216
D2	Digital temperature	Unsigned long	24	0	16777216

Calculate temperature

TEMP	Actual Temperature(0-85 with 0.01C resolution) $TEMP=A0*10+A1*20*D2/2^{24}+A2*20*(D2/2^{24})^2$	Double	32			26.56 C

Calculate temperature compensated pressure

Y	$Y=(D1+C0*2^{(15-Q0)}+C3*2^{15}*D2/2^{24}+C4*2^{15}*(D2/2^{24})^2)/(C1*2^{(15-Q1)}+C5*2^{18}*D2/2^{24}+C6*2^{18}*(D2/2^{24})^2)$	Double	32		
P	$P=Y*(1-C2*2^{(15-Q2)}/2^{24})+C2*2^{(15-Q2)}/2^{24}*Y^2$	Double	32		
Pressure	$Pressure=((P-0.1)/0.8)*(P_{max}-P_{min})+P_{min}$	Double	32		

$$Y = \frac{D1 + \left(C0 \times 2^{(15-Q0)}\right) + \left(\frac{D2 \times C3 \times 2^{15}}{2^{24}}\right) + \left[C4 \times 2^{15} \times \left(\frac{D2}{2^{24}}\right)^2\right]}{(C1 \times 2^{15-Q2}) + \left(\frac{C5 \times 2^{18} \times D2}{2^{24}}\right) + \left(C6 \times 2^{18} \times \left(\frac{D2}{2^{24}}\right)^2\right)}$$

$$P = Y\left(1 - \frac{C2 \times 2^{15-Q2}}{2^{24}}\right) + Y^2\left(\frac{C2 \times 2^{(15 \times Q2)}}{2^{24}}\right)$$

$$Pressure = \left[\left(\frac{P - 0.1}{0.8}\right) \times (Pmax - Pmin)\right] + Pmin$$

$$Temp = (A0 \cdot 10) + \left(\frac{A1 \cdot 20 \cdot D2}{2^{24}}\right) + A2 \cdot 20 \cdot \left(\frac{D2}{2^{24}}\right)^2$$

Memory mapping

Address	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	16 bit reserved for manufacturer															
1	$C0_{13}$	$C0_{12}$	$C0_{11}$	$C0_{10}$	$C0_{09}$	$C0_{08}$	$C0_{07}$	$C0_{06}$	$C0_{05}$	$C0_{04}$	$C0_{03}$	$C0_{02}$	$C0_{01}$	$C0_{00}$	$C1_{13}$	$C1_{12}$
2	$C1_{11}$	$C1_{10}$	$C1_{09}$	$C1_{08}$	$C1_{07}$	$C1_{06}$	$C1_{05}$	$C1_{04}$	$C1_{03}$	$C1_{02}$	$C1_{01}$	$C1_{00}$	$C2_{08}$	$C2_{07}$	$C2_{06}$	$C2_{05}$
3	$C2_{04}$	$C2_{03}$	$C2_{02}$	$C2_{01}$	$C2_{00}$	$C3_{09}$	$C3_{08}$	$C3_{07}$	$C3_{06}$	$C3_{05}$	$C3_{04}$	$C3_{03}$	$C3_{02}$	$C3_{01}$	$C3_{00}$	$C4_{08}$
4	$C4_{07}$	$C4_{06}$	$C4_{05}$	$C4_{04}$	$C4_{03}$	$C4_{02}$	$C4_{01}$	$C4_{00}$	$C5_{09}$	$C5_{08}$	$C5_{07}$	$C5_{06}$	$C5_{05}$	$C5_{04}$	$C5_{03}$	$C5_{02}$
5	$C5_{01}$	$C5_{00}$	$C6_{08}$	$C6_{07}$	$C6_{06}$	$C6_{05}$	$C6_{04}$	$C6_{03}$	$C6_{02}$	$C6_{01}$	$C6_{00}$	$Q0_{02}$	$Q0_{01}$	$Q0_{00}$	$Q1_{02}$	$Q1_{01}$
6	$Q1_{00}$	$Q2_{02}$	$Q2_{01}$	$Q2_{00}$	$A0_{07}$	$A0_{06}$	$A0_{05}$	$A0_{04}$	$A0_{03}$	$A0_{02}$	$A0_{01}$	$A0_{00}$	$A1_{07}$	$A1_{06}$	$A1_{05}$	$A1_{04}$
7	$A1_{03}$	$A1_{02}$	$A1_{01}$	$A1_{00}$	$A2_{07}$	$A2_{06}$	$A2_{05}$	$A2_{04}$	$A2_{03}$	$A2_{02}$	$A2_{01}$	$A2_{00}$	CRC			

Vincent Wong
Office (510)-498-1570 ext 245
vincent.wong@meas-spec.com