

Modeling Recurrent Safety-critical Events among Commercial Truck Drivers: A Bayesian Hierarchical Jump Power Law Process

Miao Cai

Saint Louis University, Saint Louis, MO 63104

Qiong Hu

Auburn University, Auburn, AL 36849

Amir Mehdizadeh

Auburn University, Auburn, AL 36849

Mohammad Ali Alamdar Yazdi

Johns Hopkins University, Baltimore, MD 21202

Alexander Vinel

Auburn University, Auburn, AL 36849

Fadel M. Megahed

Miami University, Oxford, OH 45056

Karen C. Davis

Miami University, Oxford, OH 45056

Hong Xian

Saint Louis University, Saint Louis, MO 63104


Steven E. Rigdon

Saint Louis University, Saint Louis, MO 63104

May 22, 2020

Abstract

JUST COMMENT ON TARGET JOURNALS, NOT REAL ABSTRACT. The target of this manuscript will be statistical journal, so the writing will involve quite a bit of math and simulation. The target journals I have in mind include: a) Journal of the American Statistical Association (JASA, impact factor: 3.412, rank: 5/123), b) Journal of Computational and Graphical Statistics (impact factor: 1.882, rank: 28/123), c) Statistics in Medicine (impact factor: 1.847, rank: 29/123), d) Journal of Applied Statistics (impact factor: 0.767, rank: 84/123). This will be written once the paper is complete.



As a general rule, keep the ordering consistent ... inside \rightarrow out rsd

or outside-in dsr. If you have only a subset of these indices, you should maintain the order. For

example, if you use dsr then you would have τ_{ds} .

1. INTRODUCTION

The methods used in trucking safety is usually predictive model, while reliability models that account for multiple events are less used.

Traditional data use retrospective crash reports collected at certain road segments. In studies using these data, there are at most one crash in one shift and recurrent data models do not make sense in these scenarios. However, there can be multiple unsafe driving events in shift generated in NDS, which motivate the application of innovative recurrent event models in transportation safety modeling.

Literature review of recurrent event analyses application in transportation safety science. The most common recurrent event analysis model is probably Poisson regression, which assumes the events in a time interval is generated by a homogeneous Poisson process (Kim et al., 2013). (Chen and Guo, 2016; Li et al., 2017; Liu and Guo, 2019; Liu et al., 2019; Guo et al., 2019; Li et al., 2018).

2. DESCRIPTION OF DATA

[Figure 1 about here.]

Here are the notations for the data:

- Driver $d : 1, 2, \dots, D$,
- Shift $s, 1, 2, \dots, S_d$,
- Trip $r : 1, 2, \dots, R_{d,s}$,
- SCE $i : 1, 2, \dots, I_{d,s}$.
- $t_{i,d,s}$: time to the i -th SCE for driver d on shift s ,
- $n_{d,s,r}$: the number of SCEs for trip r within shift s for driver d ,
- $a_{d,s,r}$: the end time of trip r within shift s for driver d .

measured from the beginning of the shift.

3. MODELS

3.1 Non-homogeneous Poisson Process (NHPP) and Power Law Process

We assume the time to SCEs t follows a non-homogeneous Poisson process, whose intensity function $\lambda(t)$ is non-constant. The intensity function is assumed to have the following function form

$$\lambda_{PLP}(t) = \beta \theta^{-\beta} t^{\beta-1}, \quad (1)$$

where the shape parameter β indicates reliability improvement ($\beta < 1$), constant ($\beta = 1$), or deterioration ($\beta > 1$), and the scale parameter θ determines the rate of events. Here we assume the intensity function of a power law process because it has a flexible functional form, relatively simple statistical inference, and is a well-established model (Rigdon and Basu, 1989, 2000).

$$n_{ds} = \sum_{r=1}^{R_{ds}} n_{dsr} = \# \text{ SCEs in shift } s \text{ for driver } d.$$

$$\tau_{ds} = \text{length of time of shift } s \text{ for driver } d.$$

$$= a_{ds, R_{ds}}$$

Earlier the indices were i, d, s . Here they are d, s, i .

37 3.2 Bayesian Hierarchical Power Law Process (PLP)

The Bayesian hierarchical power law process is parameterized as:

$$t_{d,s,1}, t_{d,s,2}, \dots, t_{d,s,n_{d,s}}, \tau_{d,s} \sim \text{PLP}(\beta, \theta_{d,s})$$

$$\beta \sim \text{Gamma}(1, 1)$$

$$\log \theta_{d,s} = \gamma_{0d} + \gamma_1 x_{d,s,1} + \gamma_2 x_{d,s,2} + \dots + \gamma_k x_{d,s,k}$$

$$\kappa \sim \text{Uniform}(0, 1)$$

$$\gamma_{01}, \gamma_{02}, \dots, \gamma_{0D} \sim \text{i.i.d. } N(\mu_0, \sigma_0^2)$$

$$\gamma_1, \gamma_2, \dots, \gamma_k \sim \text{i.i.d. } N(0, 10^2)$$

$$\mu_0 \sim N(0, 5^2)$$

$$\sigma_0 \sim \text{Gamma}(1, 1),$$

What is k ? Is this the "jump" parameter? (2)

where $t_{d,s,i}$ is the time to the i -th event for driver d in shift s and $\tau_{d,s}$ is the shift length (truncation time) for driver d on shift s . The likelihood function of event times generated from a PLP for driver d in shift s is given in Rigdon and Basu (2000, Section 2.3.2, Page 60):

$$L_{s,d}(\beta, \gamma_{0d}, \gamma | \mathbf{X}_d, \mathbf{W}_s) = \left(\prod_{i=1}^{n_{d,s}} \lambda_{\text{PLP}}(t_i) \right) \exp \left(- \int_0^{\tau_{d,s}} \lambda(u) du \right)$$

$$= \begin{cases} \exp \left(- (\tau_{d,s}/\theta)^\beta \right), & \text{if } n_{d,s} = 0, \\ \left(\prod_{i=1}^{n_{d,s}} \beta \theta^{-\beta} t_i^{\beta-1} \right) \exp \left(- (\tau_{d,s}/\theta)^\beta \right), & \text{if } n_{d,s} > 0, \end{cases} \quad (3)$$

where $n_{d,s}$ is the total number of SCEs for driver d in shift s , \mathbf{X}_d indicates driver specific variables (e.g. driver age and gender), and \mathbf{W}_s represents shift specific variables (e.g. precipitation and traffic). The full likelihood function and log likelihood function for all drivers are:

$$\prod_{d=1}^D \prod_{s=1}^{S_d}$$

$$L = \prod_d \prod_{s \in d} L_{s,d} = \prod_d \prod_{s \in d} \left(\left(\prod_{i=1}^{n_{d,s}} \beta \theta^{-\beta} t_i^{\beta-1} \right) \exp \left(- (\tau_{d,s}/\theta)^\beta \right) \right),$$

$$\log L = \sum_{d=1}^D \sum_{s=1}^{S_d} \left(n_{d,s} \log \beta - n_{d,s} \beta \log \theta + (\beta - 1) \sum_{i=1}^{n_{d,s}} \log t_i - (\tau_{d,s}/\theta)^\beta \right), \quad (4)$$

where θ is a function of parameters $\gamma_{0d}, \gamma_1, \gamma_2, \dots, \gamma_k$ and variables $x_{d,s,1}, x_{d,s,2}, \dots, x_{d,s,k}$ given in the third line of equation (2).

39 3.3 Bayesian Hierarchical Jump Power Law Process (JPLP)

Since the Bayesian hierarchical PLP in Subsection 3.2 does not account for the rests ($r : 1, 2, \dots, R_{d,s}$) within shifts and associated potential reliability improvement. In this subsection, we propose a Bayesian hierarchical JPLP, with the following piecewise intensity function:

$$\lambda_{\text{JPLP}}(t|d, s, r, \beta, \gamma_{0d}, \gamma, \mathbf{X}_d, \mathbf{W}_s) = \begin{cases} \kappa^0 \lambda(t|\beta, \gamma_{0d}, \gamma, \mathbf{X}_d, \mathbf{W}_s), & 0 < t \leq a_{d,s,1}, \\ \kappa^1 \lambda(t|\beta, \gamma_{0d}, \gamma, \mathbf{X}_d, \mathbf{W}_s), & a_{d,s,1} < t \leq a_{d,s,2}, \\ \dots & \dots \\ \kappa^{R-1} \lambda(t|\beta, \gamma_{0d}, \gamma, \mathbf{X}_d, \mathbf{W}_s), & a_{d,s,R-1} < t \leq a_{d,s,R}, \\ \kappa^{r-1} \lambda(t|d, s, r, \kappa, \beta, \gamma_{0d}, \gamma, \mathbf{X}_d, \mathbf{W}_s), & a_{d,s,r-1} < t \leq a_{d,s,r}, \end{cases} \quad (5)$$

where the introduced parameter κ is the percent of intensity function recovery once the driver takes a break, and $a_{d,s,r}$ is the end time of trip r within shift s for driver d . By definition, the end time of the 0-th trip $a_{d,s,0} = 0$, and the end time of the last trip for the d -driver within s -shift $a_{d,s,R}$ equals the shift end time $\tau_{d,s}$. We assume that this κ is constant across drivers and shifts.

The Bayesian hierarchical JPLP model is parameterized as

$$\begin{aligned}
t_{d,s,1}, t_{d,s,2}, \dots, t_{d,s,n_{d,s}}, \tau_{d,s} &\sim \text{JPLP}(\beta, \theta_{d,s}, \kappa) \\
\beta &\sim \text{Gamma}(1, 1) \\
\log \theta_{d,s} &= \gamma_{0d} + \gamma_1 x_{d,s,1} + \gamma_2 x_{d,s,2} + \dots + \gamma_k x_{d,s,k} \\
\kappa &\sim \text{Uniform}(0, 1) \\
\gamma_{01}, \gamma_{02}, \dots, \gamma_{0D} &\sim \text{i.i.d. } N(\mu_0, \sigma_0^2) \\
\gamma_1, \gamma_2, \dots, \gamma_k &\sim \text{i.i.d. } N(0, 10^2) \\
\mu_0 &\sim N(0, 5^2) \\
\sigma_0 &\sim \text{Gamma}(1, 1),
\end{aligned} \tag{6}$$

The notations are identical with those in Equation 2 except for the extra κ parameter. The likelihood function of event times generated from a JPLP for driver d on shift s is

$$L_{s,d}^*(\kappa, \beta, \gamma_{0d}, \gamma | \mathbf{X}_d, \mathbf{W}_s) = \begin{cases} \exp \left(- \int_0^{a_{d,s,R}} \lambda_{\text{JPLP}}(u | d, s, r, k, \beta, \gamma_{0d}, \gamma, \mathbf{X}_d, \mathbf{W}_s) du \right), & \text{if } n_{d,s} = 0, \\ \left(\prod_{i=1}^{n_{d,s}} \lambda_{\text{JPLP}}(t_{i,d,s} | d, s, r, k, \beta, \gamma_{0d}, \gamma, \mathbf{X}_d, \mathbf{W}_s) \right) \\ \times \exp \left(- \int_0^{a_{d,s,R}} \lambda_{\text{JPLP}}(u | d, s, r, k, \beta, \gamma_{0d}, \gamma, \mathbf{X}_d, \mathbf{W}_s) du \right), & \text{if } n_{d,s} > 0, \end{cases} \tag{7}$$

where $t_{i,d,s}$ is the time to the i -th SCE for driver d on shift s , $n_{d,s}$ is the number of SCEs for driver d on shift s . Therefore, the overall likelihood function for drivers $d \in 1, 2, \dots, D$ and their corresponding shifts $s \in d$ is:

$$L^* = \prod_{d=1}^D \prod_{s \in d} L_{s,d}^*. \tag{8}$$

$S = 1, 2, \dots, S_d$
 $d \in \{1, 2, \dots, D\}$ or $d = 1, 2, \dots, D$. Latter is preferable.
 $d = 1, s = 1$
 $d \in \{1, 2, \dots, D\}$ or $d = 1, 2, \dots, D$. Latter is preferable.

Since λ_{JPLP} is a piecewise likelihood function that depends on event time and trip time, we will not spell out the details of the full likelihood or log likelihood.

[Figure 2 about here.]

4. SIMULATION STUDY

4.1 Simulation setting

We conducted a simulation study to evaluate the performance of our proposed JPLP. 1000 simulations were performed to each scenario with various number of drivers ($D = 25, 50, 75, 100$).

4.2 Simulation results

5. DATA ANALYSES

The hierarchical Bayesian PLP and JPLP were performance using the probabilistic programming language (Carpenter et al., 2017; Stan Development Team, 2018).

6. DISCUSSION

In this article we have proposed a Bayesian hierarchical jump power law process, which accounts for the characteristics of multiple rests within a shift among commercial truck drivers. The simulation results shows XXXX. In the application to a 496 truck driver NDS dataset, the results suggest that XXX.

REFERENCES

- Carpenter, B., Gelman, A., Hoffman, M. D., Lee, D., Goodrich, B., Betancourt, M., Brubaker, M., Guo, J., Li, P., and Riddell, A. “Stan: A Probabilistic Programming Language.” *Journal of Statistical Software*, 76(1) (2017).
- Chen, C. and Guo, F. “Evaluating the influence of crashes on driving risk using recurrent event models and Naturalistic Driving Study data.” *Journal of Applied Statistics*, 43(12):2225–2238 (2016).
- Guo, F., Kim, I., and Klauer, S. G. “Semiparametric Bayesian models for evaluating time-variant driving risk factors using naturalistic driving data and case-crossover approach.” *Statistics in Medicine*, 38(2):160–174 (2019).
- Kim, S., Chen, Z., Zhang, Z., Simons-Morton, B. G., and Albert, P. S. “Bayesian hierarchical Poisson regression models: an application to a driving study with kinematic events.” *Journal of the American Statistical Association*, 108(502):494–503 (2013).
- Li, Q., Guo, F., Kim, I., Klauer, S. G., and Simons-Morton, B. G. “A Bayesian finite mixture change-point model for assessing the risk of novice teenage drivers.” *Journal of Applied Statistics*, 45(4):604–625 (2018).
- Li, Q., Guo, F., Klauer, S. G., and Simons-Morton, B. G. “Evaluation of risk change-point for novice teenage drivers.” *Accident Analysis & Prevention*, 108:139–146 (2017).
- Liu, Y. and Guo, F. “A Bayesian Time-Varying Coefficient Model for Multitype Recurrent Events.” *Journal of Computational and Graphical Statistics*, 1–12 (2019).
- Liu, Y., Guo, F., and Hanowski, R. J. “Assessing the Impact of Sleep Time on Truck Driver Performance using a Recurrent Event Model.” *Statistics in Medicine*, 38(21):4096–4111 (2019).
- Rigdon, S. E. and Basu, A. P. “The Power Law Process: A model for the Reliability of Repairable Systems.” *Journal of Quality Technology*, 21(4):251–260 (1989).
- . *Statistical Methods for the Reliability of Repairable Systems*. Wiley New York (2000).
- Stan Development Team. “RStan: the R interface to Stan.” (2018). R package version 2.18.2. URL <http://mc-stan.org/>

87
88
89
90
91
92
93
94

List of Figures

1	NDS real-time ping data (colored points) and the aggregation process from pings to shifts and trips (colored arrows).	7
2	Simulated intensity function of power law process (left) and jump power law process. The x -axis shows time in hours since start and y -axis shows the intensity of SCEs. The red crosses mark the time to SCEs and the green vertical lines indicates the time of the rests. Parameter values for simulation: shape parameters $\beta = 1.2$, rate parameter $\theta = 2$, jump parameter $\kappa = 0.8$	8




Figure 1: NDS real-time ping data (colored points) and the aggregation process from pings to shifts and trips (colored arrows).




Figure 2: Simulated intensity function of power law process (left) and jump power law process. The x -axis shows time in hours since start and y -axis shows the intensity of SCEs. The red crosses mark the time to SCEs and the green vertical lines indicates the time of the rests. Parameter values for simulation: shape parameters $\beta = 1.2$, rate parameter $\theta = 2$, jump parameter $\kappa = 0.8$.