

# Notebook - Competitive Programming

## Contents

<b>1 Data structures</b>	<b>2</b>				
1.1 Int 128	2	4.11 Line Intersection	14	5.18 Prim	27
1.2 Lazy Segtree	2	4.12 Line Structure	14	5.19 Retrieve Path 2d	28
1.3 Matrix	3	4.13 Reduced Line Structure	14	5.20 Retrieve Path	28
1.4 Merge Sort Tree	4	4.14 Minimum Enclosing Circle (MEC)	15	5.21 Second Best MST	28
1.5 Minimal Excluded With Updates (MEX-U)	5	4.15 Point in Polygon	15	5.22 TopSort - Tarjan	28
1.6 Minimal Excluded (MEX)	5	4.16 Point Rotate	15		
1.7 Range Min Query (RMQ)	5	4.17 Point Structure	16	<b>6 Math</b>	<b>28</b>
1.8 Segment Tree (Parameterized OP)	6	4.18 Point To Segment	16	6.1 Binomial	28
1.9 Segment Tree 2D	6	4.19 Point Vector	16	6.2 Count Divisors Range	29
1.10 Segment Tree Lazy	6	4.20 Polygon	17	6.3 Count Divisors	29
1.11 Segtreelazy Generic	7	4.21 Polynominoes	18	6.4 Factorization With Sieve	29
1.12 Simple Int 128	8	4.22 Rectangle	19	6.5 Factorization	29
1.13 Union Find Disjoint Set (UFDS)	8	4.23 Segment Structure	19	6.6 Fast Doubling - Fibonacci	29
1.14 Wavelet Tree	8	4.24 Segment Intersection Exists	20	6.7 Fast Exp Iterative	30
		4.25 Sweep Line	21	6.8 Fast Exp	30
		4.26 Triangle	22	6.9 Fast Fourier Transform (FFT)	30
<b>2 Dynamic programming</b>	<b>9</b>	<b>5 Graphs</b>	<b>22</b>	6.10 GCD	30
2.1 Kadane	9	5.1 Articulation Points	22	6.11 Integer Mod	30
2.2 Longest Increasing Subsequence (LIS)	9	5.2 Bellman Ford	23	6.12 Is prime	31
		5.3 BFS 0/1	23	6.13 LCM	31
<b>3 Extras</b>	<b>9</b>	5.4 Binary Lifting	23	6.14 Euler phi $\varphi(n)$	31
3.1 cin/cout __int128_t	9	5.5 Bridges	23	6.15 Sieve	31
		5.6 Negative Cycle Bellman Ford	23	6.16 Sum Divisors	31
<b>4 Geometry</b>	<b>10</b>	5.7 Negative Cycle Floyd Warshall	24	6.17 Sum of difference	32
4.1 Andrew Convex Hull	10	5.8 Dijkstra	24		
4.2 Angle Between Segments	10	5.9 Dinic	24	<b>7 Problems</b>	<b>32</b>
4.3 Circle	10	5.10 Floyd Warshall	25	7.1 Kth Digit String (CSES)	32
4.4 Closest Points	11	5.11 Graph	25	7.2 Longest Common Substring (LONGCS - SPOJ)	32
4.5 Convex Hull Trick	12	5.12 TopSort - Kahn	25	7.3 Substring Order II (CSES)	32
4.6 Convex Hull	12	5.13 Kosaraju	26		
4.7 Distance between Point and Line	13	5.14 Kruskal	26		
4.8 Graham Convex Hull	13	5.15 Minimax	26		
4.9 Convex Hull Trick	13	5.16 MSF	27		
4.10 Line Closest Point	14	5.17 Minimum Spanning Graph (MSG)	27		

<b>8</b>	<b>Strings</b>	<b>33</b>	<b>10</b>	<b>Settings and macros</b>	<b>39</b>	11.8	Number of Different Substrings . . . . .	42
8.1	Aho-Corasick . . . . .	33	10.1	macro.cpp . . . . .	39	11.9	Exponent With Module . . . . .	42
8.2	Edit Distance . . . . .	34	10.2	short-macro.cpp . . . . .	40	11.10	Line Equations . . . . .	42
8.3	LCP with Suffix Array . . . . .	34	<b>11</b>	<b>Theoretical guide</b>	<b>40</b>	11.10.1	Reduced Equation . . . . .	42
8.4	Manacher . . . . .	34	11.1	Modular Multiplicative Inverse . . . . .	40	11.10.2	General Equation . . . . .	42
8.5	Rabin Karp . . . . .	34	11.2	Pick's Theorem . . . . .	40	11.11	Laws of Trigonometry for Triangles . . . . .	42
8.6	Suffix Array Optimized - $O(n)$ . . . . .	35	11.3	Side on which a point lies . . . . .	40	11.11.1	Law of Sines . . . . .	42
8.7	Suffix Array . . . . .	35	11.4	Triangle Formulas . . . . .	41	11.11.2	Law of Cosines . . . . .	42
8.8	Suffix Automaton . . . . .	36	11.4.1	Area of a Triangle . . . . .	41	11.12	Triangle Inequality . . . . .	42
8.9	Suffix Tree (CP Algo - freopen) . . . . .	37	11.4.2	Area using Heron's Formula . . . . .	41	11.12.1	Finding a third side . . . . .	42
8.10	Z Function . . . . .	37	11.4.3	Perimeter of a Triangle . . . . .	41	11.13	Common Geometric Shape Formulas . . . . .	42
<b>9</b>	<b>Trees</b>	<b>37</b>	11.4.4	Pythagorean Theorem (Right Triangle)	41	11.13.1	Area of a Trapezium . . . . .	42
9.1	LCA Binary Lifting (CP Algo) . . . . .	37	11.4.5	Height of a Triangle . . . . .	41	11.13.2	Area of a Regular Hexagon . . . . .	42
9.2	LCA SegTree (CP Algo) . . . . .	38	11.5	Trigonometry Formulas . . . . .	41	11.13.3	Area of a Parallelogram . . . . .	42
9.3	LCA Sparse Table . . . . .	38	11.6	Unit Circle . . . . .	41	11.13.4	Area of a Rhombus . . . . .	42
9.4	Tree Flatten . . . . .	39	11.7	String Matching with FFT . . . . .	41	11.13.5	Area of an Ellipse . . . . .	42
9.5	Tree Isomorph . . . . .	39	11.7.1	Wildcards . . . . .	42	11.13.6	Area of a Regular Pentagon . . . . .	43
						11.14	Notable Series . . . . .	43

# 1 Data structures

## 1.1 Int 128

```
using int128 = signed __int128;
using uint128 = unsigned __int128;

namespace int128_io {
inline auto char_to_digit(int chr) {
    return static_cast<int>(isalpha(chr) ? 10 + tolower(chr) - 'a' : chr - '0');
}

inline auto digit_to_char(int digit) {
    return static_cast<char>(digit > 9 ? 'a' + digit - 10 : '0' + digit);
}

template <class integer>
inline auto to_int(const std::string &str, size_t *idx = nullptr,
                  int base = 10) {
    size_t i = idx != nullptr ? *idx : 0;
    const auto n = str.size();
    const auto neg = str[i] == '-';
    integer num = 0;
    if (neg) ++i;
    while (i < n) num *= base, num += char_to_digit(str[i++]);
    if (idx != nullptr) *idx = i;
    return neg ? -num : num;
}

template <class integer>
inline auto to_string(integer num, int base = 10) {
    const auto neg = num < 0;
    std::string str;
    if (neg) num = -num;
    do str += digit_to_char(num % base), num /= base;
    while (num > 0);
    if (neg) str += '-';
    std::reverse(str.begin(), str.end());
    return str;
}

inline auto next_str(std::istream &stream) {
    std::string str;
    stream >> str;
    return str;
}

template <class integer>
inline auto &read(std::istream &stream, integer &num) {
    num = to_int<integer>(next_str(stream));
    return stream;
}

template <class integer>
inline auto &write(std::ostream &stream, integer num) {
    return stream << to_string(num);
}

} // namespace int128_io
```

```
using namespace std;

inline auto &operator>>(istream &stream, int128 &num) {
    return int128_io::read(stream, num);
}

inline auto &operator>>(istream &stream, uint128 &num) {
    return int128_io::read(stream, num);
}

inline auto &operator<<(ostream &stream, int128 num) {
    return int128_io::write(stream, num);
}

inline auto &operator<<(ostream &stream, uint128 num) {
    return int128_io::write(stream, num);
}

inline auto uint128_max() {
    uint128 ans = 0;
    for (uint128 pow = 1; pow > 0; pow <= 1) ans |= pow;
    return ans;
}
```

## 1.2 Lazy Segtree

```
const int N = 200002;
struct ST {
    vector<ll> t;
    vector<ll> lazy;
    ST() {
        t.assign(4 * N, 0);
        lazy.assign(4 * N, 0);
    }

    inline ll f(ll a, ll b) { return a + b; }

    void prop(int lx, int rx, int x) {
        if (lazy[x] != 0) {
            t[x] += lazy[x] * (rx - lx + 1);
            if (lx != rx) {
                lazy[2 * x] += lazy[x];
                lazy[2 * x + 1] += lazy[x];
            }
            lazy[x] = 0;
        }
    }

    ll query(int l, int r, int lx = 0, int rx = N - 1, int x = 1) {
        prop(lx, rx, x);
        if (r < lx or rx < l) return 0;
        if (l <= lx and rx <= r) return t[x];
        int mid = (lx + rx) / 2;
        return f(query(l, r, lx, mid, 2 * x), query(l, r, mid + 1, rx, 2 * x + 1));
    }

    void update(int l, int r, ll val, int lx = 0, int rx = N - 1, int x = 1) {
        prop(lx, rx, x);
        if (r < lx or rx < l) return;
        if (l <= lx and rx <= r) t[x] += val * (rx - lx + 1);
        else {
            int mid = (lx + rx) / 2;
            update(l, r, val, lx, mid, 2 * x);
            update(l, r, val, mid + 1, rx, 2 * x + 1);
        }
    }
};
```

```

if (l <= lx and rx <= r) {
    lazy[x] += val;
    prop(lx, rx, x);
    return;
}
int mid = (lx + rx) / 2;
update(l, r, val, lx, mid, 2 * x);
update(l, r, val, mid + 1, rx, 2 * x + 1);
t[x] = f(t[2 * x], t[2 * x + 1]);
}
};

```

### 1.3 Matrix

```

template <typename T>
struct Matrix {
    vector<vector<T>> d;

    Matrix() : Matrix(0) {}
    Matrix(int n) : Matrix(n, n) {}
    Matrix(int n, int m) : Matrix(vector<vector<T>>(n, vector<T>(m))) {}
    Matrix(const vector<vector<T>> &v) : d(v) {}

    constexpr int n() const { return (int)d.size(); }
    constexpr int m() const { return n() ? (int)d[0].size() : 0; }

    void rotate() { *this = rotated(); }

    Matrix<T> rotated() const {
        Matrix<T> res(m(), n());
        for (int i = 0; i < m(); i++) {
            for (int j = 0; j < n(); j++) {
                res[i][j] = d[n() - j - 1][i];
            }
        }
        return res;
    }

    Matrix<T> pow(int power) const {
        assert(n() == m());

        auto res = Matrix<T>::identity(n());
        auto b = *this;
        while (power) {
            if (power & 1) res *= b;
            b *= b;
            power >>= 1;
        }
        return res;
    }

    Matrix<T> submatrix(int start_i, int start_j, int rows = INT_MAX,
                        int cols = INT_MAX) const {
        rows = min(rows, n() - start_i);
        cols = min(cols, m() - start_j);
        if (rows <= 0 or cols <= 0) return {};

        Matrix<T> res(rows, cols);

```

```

        for (int i = 0; i < rows; i++)
            for (int j = 0; j < cols; j++) res[i][j] = d[i + start_i][j + start_j];
        return res;
    }

    Matrix<T> translated(int x, int y) const {
        Matrix<T> res(n(), m());
        for (int i = 0; i < n(); i++) {
            for (int j = 0; j < m(); j++) {
                if (i + x < 0 or i + x >= n() or j + y < 0 or j + y >= m()) continue;
                res[i + x][j + y] = d[i][j];
            }
        }
        return res;
    }

    static Matrix<T> identity(int n) {
        Matrix<T> res(n);
        for (int i = 0; i < n; i++) res[i][i] = 1;
        return res;
    }

    vector<T> &operator[](int i) { return d[i]; }
    const vector<T> &operator[](int i) const { return d[i]; }
    Matrix<T> &operator+=(T value) {
        for (auto &row : d) {
            for (auto &x : row) x += value;
        }
        return *this;
    }

    Matrix<T> operator+(T value) const {
        auto res = *this;
        for (auto &row : res) {
            for (auto &x : row) x = x + value;
        }
        return res;
    }

    Matrix<T> &operator-=(T value) {
        for (auto &row : d) {
            for (auto &x : row) x -= value;
        }
        return *this;
    }

    Matrix<T> operator-(T value) const {
        auto res = *this;
        for (auto &row : res) {
            for (auto &x : row) x = x - value;
        }
        return res;
    }

    Matrix<T> &operator*=(T value) {
        for (auto &row : d) {
            for (auto &x : row) x *= value;
        }
        return *this;
    }

    Matrix<T> operator*(T value) const {
        auto res = *this;

```

```

    for (auto &row : res) {
        for (auto &x : row) x = x * value;
    }
    return res;
}
Matrix<T> &operator/=(T value) {
    for (auto &row : d) {
        for (auto &x : row) x /= value;
    }
    return *this;
}
Matrix<T> operator/(T value) const {
    auto res = *this;
    for (auto &row : res) {
        for (auto &x : row) x = x / value;
    }
    return res;
}
Matrix<T> &operator+=(const Matrix<T> &o) {
    assert(n() == o.n() and m() == o.m());
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            d[i][j] += o[i][j];
        }
    }
    return *this;
}
Matrix<T> operator+(const Matrix<T> &o) const {
    assert(n() == o.n() and m() == o.m());
    auto res = *this;
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            res[i][j] = res[i][j] + o[i][j];
        }
    }
    return res;
}
Matrix<T> &operator-=(const Matrix<T> &o) {
    assert(n() == o.n() and m() == o.m());
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            d[i][j] -= o[i][j];
        }
    }
    return *this;
}
Matrix<T> operator-(const Matrix<T> &o) const {
    assert(n() == o.n() and m() == o.m());
    auto res = *this;
    for (int i = 0; i < n(); i++) {
        for (int j = 0; j < m(); j++) {
            res[i][j] = res[i][j] - o[i][j];
        }
    }
    return res;
}
Matrix<T> &operator*=(const Matrix<T> &o) {
    *this = *this * o;
}

```

```

    return *this;
}
Matrix<T> operator*(const Matrix<T> &o) const {
    assert(m() == o.n());
    Matrix<T> res(n(), o.m());
    for (int i = 0; i < res.n(); i++) {
        for (int j = 0; j < res.m(); j++) {
            auto &x = res[i][j];
            for (int k = 0; k < m(); k++) {
                x += (d[i][k] * o[k][j]);
            }
        }
    }
    return res;
}

friend istream &operator>>(istream &is, Matrix<T> &mat) {
    for (auto &row : mat)
        for (auto &x : row) is >> x;
    return is;
}

friend ostream &operator<<(ostream &os, const Matrix<T> &mat) {
    bool frow = 1;
    for (auto &row : mat) {
        if (not frow) os << '\n';
        bool first = 1;
        for (auto &x : row) {
            if (not first) os << ' ';
            os << x;
            first = 0;
        }

        frow = 0;
    }
    return os;
}

auto begin() { return d.begin(); }
auto end() { return d.end(); }
auto rbegin() { return d.rbegin(); }
auto rend() { return d.rend(); }

auto begin() const { return d.begin(); }
auto end() const { return d.end(); }
auto rbegin() const { return d.rbegin(); }
auto rend() const { return d.rend(); }
};

```

## 1.4 Merge Sort Tree

Like a segment tree but each node  $st_i$  stores a sorted subarray

- $inrange(l, r, a, b)$  : counts the number of elements  $x \in [l, r]$  such that  $a \leq x \leq b$ .

Memory:  $O(N \log N)$

Build:  $O(N \log N)$

$inrange$ :  $O(\log^2 N)$

```

template <class T>
struct MergeSortTree {

```

```

int n;
vector<vector<T>> st;
MergeSortTree(vector<T>& xs) : n(len(xs)), st(n << 1) {
    for (int i = 0; i < n; i++) st[i + n] = vector<T>({xs[i]});

    for (int i = n - 1; i > 0; i--) {
        st[i].resize(len(st[i << 1]) + len(st[i << 1 | 1]));
        merge(all(st[i << 1]), all(st[i << 1 | 1]), st[i].begin());
    }
}

int count(int i, T a, T b) {
    return upper_bound(all(st[i]), b) - lower_bound(all(st[i]), a);
}

int inrange(int l, int r, T a, T b) {
    int ans = 0;

    for (l += n, r += n + 1; l < r; l >>= 1, r >>= 1) {
        if (l & 1) ans += count(l++, a, b);
        if (r & 1) ans += count(--r, a, b);
    }

    return ans;
}
};

```

## 1.5 Minimal Excluded With Updates (MEX-U)

In the problem you need to change individual numbers in the array, and compute the new MEX of the array after each such update.

Pre-compute:  $O(N \log N)$

Update:  $O(\log N)$

Query:  $O(1)$

```

class Mex {
private:
    map<ll, ll> frequency;
    set<ll> missing_numbers;
    vl A;

public:
    Mex(vl const& A) : A(A) {
        for (ll i = 0; i <= A.size(); i++) missing_numbers.insert(i);

        for (ll x : A) {
            ++frequency[x];
            missing_numbers.erase(x);
        }
    }

    ll mex() { return *missing_numbers.begin(); }

    void update(ll idx, ll new_value) {
        if (--frequency[A[idx]] == 0) missing_numbers.insert(A[idx]);
        A[idx] = new_value;
        ++frequency[new_value];
        missing_numbers.erase(new_value);
    }
}

```

```

}
};

```

## 1.6 Minimal Excluded (MEX)

Given an array  $A$  of size  $N$ . You have to find the minimal non-negative element that is not present in the array. That number is commonly called the MEX (minimal excluded).

Time:  $O(N)$

```

ll mex(vl const& A) {
    static bool used[MAX + 111] = {0};

    for (ll x : A) {
        if (x <= MAX) used[x] = true;
    }

    ll result = 0;
    while (used[result]) ++result;

    for (ll x : A) {
        if (x <= MAX) used[x] = false;
    }

    return result;
}

```

## 1.7 Range Min Query (RMQ)

Build:  $O(N)$

Query:  $O(1)$

```

// @brunomaletta
template <typename T>
struct rmq {
    vector<T> v;
    int n;
    static const int b = 30;
    vector<int> mask, t;

    int op(int x, int y) { return v[x] <= v[y] ? x : y; }
    int msb(int x) { return __builtin_clz(1) - __builtin_clz(x); }
    int small(int r, int sz = b) { return r - msb(mask[r] & ((1 << sz) - 1)); }
    rmq() {}
    rmq(const vector<T>& v_) : v(v_), n(v.size()), mask(n), t(n) {
        for (int i = 0, at = 0; i < n; mask[i++] = at | = 1) {
            at = (at << 1) & ((1 << b) - 1);
            while (at and op(i - msb(at & -at), i) == i) at ^= at & -at;
        }
        for (int i = 0; i < n / b; i++) t[i] = small(b * i + b - 1);
        for (int j = 1; (1 << j) <= n / b; j++)
            for (int i = 0; i + (1 << j) <= n / b; i++)
                t[n / b * j + i] =
                    op(t[n / b * (j - 1) + i], t[n / b * (j - 1) + i + (1 << (j - 1))]);
    }

    int index_query(int l, int r) {
        if (r - l + 1 <= b) return small(r, r - l + 1);
        int x = l / b + 1, y = r / b - 1;
    }
}

```

```

    if (x > y) return op(small(l + b - 1), small(r));
    int j = msb(y - x + 1);
    int ans = op(small(l + b - 1),
        op(t[n / b * j + x], t[n / b * j + y - (1 << j) + 1]));
    return op(ans, small(r));
}
T query(int l, int r) { return v[index_query(l, r)]; }
};

```

## 1.8 Segment Tree (Parameterized OP)

Query:  $O(\log N)$

Update:  $O(\log N)$

```

template <typename T, auto op>
class SegTree {
private:
    T e;
    ll N;
    vector<T> seg;

public:
    SegTree(ll N, T e) : e(e), N(N), seg(N + N, e) {}

    void assign(ll i, T v) {
        i += N;
        seg[i] = v;
        for (i >= 1; i; i >>= 1) seg[i] = op(seg[2 * i], seg[2 * i + 1]);
    }

    T query(ll l, ll r) {
        T la = e, ra = e;
        l += N;
        r += N;

        while (l <= r) {
            if (l & 1) la = op(la, seg[l++]);
            if (~r & 1) ra = op(seg[r--], ra);
            l >>= 1;
            r >>= 1;
        }

        return op(la, ra);
    }
};

```

## 1.9 Segment Tree 2D

Query:  $O(\log N \cdot \log M)$

Update:  $O(\log N \cdot \log M)$

```

template <typename T, auto op>
class SegTree {
private:
    T e;
    ll n, m;
    vector<vector<T>> seg;

```

```

public:
    SegTree(ll n, ll m, T e)
        : e(e), n(n), m(m), seg(2 * n, vector<T>(2 * m, e)) {}

    void assign(ll x, ll y, T v) {
        ll ny = y += m;
        for (x += n; x; x >>= 1, y = ny) {
            if (x >= n)
                seg[x][y] = v;
            else
                seg[x][y] = op(seg[2 * x][y], seg[2 * x + 1][y]);

            while (y >>= 1) seg[x][y] = op(seg[x][2 * y], seg[x][2 * y + 1]);
        }
    }

    T query(ll lx, ll rx, ll ly, ll ry) {
        ll ans = e, nx = rx + n, my = ry + m;

        for (lx += n, ly += m; lx <= ly; ++lx >>= 1, --ly >>= 1)
            for (rx = nx, ry = my; rx <= ry; ++rx >>= 1, --ry >>= 1) {
                if (lx & 1 and rx & 1) ans = op(ans, seg[lx][rx]);
                if (lx & 1 and !(ry & 1)) ans = op(ans, seg[lx][ry]);
                if (!(ly & 1) and rx & 1) ans = op(ans, seg[ly][rx]);
                if (!(ly & 1) and !(ry & 1)) ans = op(ans, seg[ly][ry]);
            }

        return ans;
    }
};

```

## 1.10 Segment Tree Lazy

Query (Range Sum):  $O(\log N)$

Update (Sum Value):  $O(\log N)$

```

template <typename T>
class SegTreeLazy {
private:
    int N;
    vector<T> seg, lzy;

    void down(int k, int l, int r) {
        seg[k] += (r - l + 1) * lzy[k];
        if (l < r) {
            lzy[k << 1] += lzy[k];
            lzy[k << 1 | 1] += lzy[k];
        }
        lzy[k] = 0;
    }

    void update(int i, int j, int k, int l, int r, T v) {
        if (lzy[k]) down(k, l, r);
        if (i > r or j < l) return;
        if (i <= l and j >= r) {
            seg[k] += (r - l + 1) * v;
            if (l < r) {

```

```

        lzy[k << 1] += v;
        lzy[k << 1 | 1] += v;
    }
    return;
}

update(i, j, k << 1, 1, (1 + r) / 2, v);
update(i, j, k << 1 | 1, (1 + r) / 2 + 1, r, v);
seg[k] = seg[k << 1] + seg[k << 1 | 1];
}

T query(int i, int j, int k, int l, int r) {
    if (lzy[k]) down(k, l, r);
    if (i > r or j < l) return 0;
    if (i <= l and j >= r) return seg[k];

    T lft = query(i, j, k << 1, l, (1 + r) / 2);
    T rgt = query(i, j, k << 1 | 1, (1 + r) / 2 + 1, r);
    return lft + rgt;
}

public:
    SegTreeLazy(int N) : N(N), seg(N << 2, 0), lzy(N << 2, 0) {}

    void update(int i, int j, T v) { update(i, j, 1, 0, N - 1, v); }

    T query(int i, int j) { return query(i, j, 1, 0, N - 1); }
};

```

## 1.11 Segtreelazy Generic

```

using SegT = ll;

struct QueryT {
    SegT mx, mn;
    QueryT() : mx(numeric_limits<SegT>::min()), mn(numeric_limits<SegT>::max()) {}
    QueryT(SegT _v) : mx(_v), mn(_v) {}
};

inline QueryT combine(QueryT ln, QueryT rn, ii lr1, ii lr2) {
    ln.mx = max(ln.mx, rn.mx);
    ln.mn = min(ln.mn, rn.mn);
    return ln;
}

using LazyT = SegT;

inline QueryT applyLazyInQuery(QueryT q, LazyT l, ii lr) {
    if (q.mx == QueryT().mx) q.mx = SegT();
    if (q.mn == QueryT().mn) q.mn = SegT();
    q.mx += l, q.mn += l;
    return q;
}

inline LazyT applyLazyInLazy(LazyT a, LazyT b) { return a + b; }

```

```

using UpdateT = SegT;

inline QueryT applyUpdateInQuery(QueryT q, UpdateT u, ii lr) {
    if (q.mx == QueryT().mx) q.mx = SegT();
    if (q.mn == QueryT().mn) q.mn = SegT();
    q.mx += u, q.mn += u;
    return q;
}

inline LazyT applyUpdateInLazy(LazyT l, UpdateT u, ii lr) { return l + u; }

template <typename Qt = QueryT, typename Lt = LazyT, typename Ut = UpdateT,
          auto C = combine, auto ALQ = applyLazyInQuery,
          auto ALL = applyLazyInLazy, auto AUQ = applyUpdateInQuery,
          auto AUL = applyUpdateInLazy>
struct LazySegmentTree {
    int n, h;
    vector<Qt> ts;
    vector<Lt> ds;
    vector<ii> lrs;

    LazySegmentTree(int _n)
        : n(_n),
          h(sizeof(int) * 8 - __builtin_clz(n)),
          ts(n << 1),
          ds(n),
          lrs(n << 1) {
        for (int i = 0; i < n; i++) lrs[i + n] = {i, i};
        for (int i = n - 1; i > 0; i--) {
            lrs[i] = {lrs[i << 1].first, lrs[i << 1 | 1].second};
        }
    }

    LazySegmentTree(const vector<Qt> &xs) : LazySegmentTree(xs.size()) {
        copy(all(xs), ts.begin() + n);
        for (int i = 0; i < n; i++) lrs[i + n] = {i, i};
        for (int i = n - 1; i > 0; i--) {
            ts[i] = C(ts[i << 1], ts[i << 1 | 1], lrs[i << 1], lrs[i << 1 | 1]);
        }
    }

    void set(int p, Qt v) {
        ts[p + n] = v;
        build(p + n);
    }

    void upd(int l, int r, Ut v) {
        l += n, r += n + 1;
        int l0 = l, r0 = r;
        for (; l < r; l >>= 1, r >>= 1) {
            if (l & 1) apply(l++, v);
            if (r & 1) apply(--r, v);
        }
        build(l0), build(r0 - 1);
    }

    Qt qry(int l, int r) {
        l += n, r += n + 1;

```



```

push(l), push(r - 1);
Qt resl = Qt(), resr = Qt();
ii lr1 = {l, l}, lr2 = {r, r};
for (; l < r; l >>= 1, r >>= 1) {
    if (l & 1) resl = C(resl, ts[l], lr1, lrs[l]), l++;
    if (r & 1) resr = C(ts[r], resr, lrs[r], lr2);
}
return C(resl, resr, lr1, lr2);
}

void build(int p) {
    while (p > 1) {
        p >>= 1;
        ts[p] = ALQ(C(ts[p << 1], ts[p << 1 | 1], lrs[p << 1], lrs[p << 1 | 1]),
                    ds[p], lrs[p]);
    }
}

void push(int p) {
    for (int s = h; s > 0; s--) {
        int i = p >> s;
        if (ds[i] != Lt()) {
            apply(i << 1, ds[i]), apply(i << 1 | 1, ds[i]);
            ds[i] = Lt();
        }
    }
}

inline void apply(int p, Ut v) {
    ts[p] = AUQ(ts[p], v, lrs[p]);
    if (p < n) ds[p] = AUL(ds[p], v, lrs[p]);
}
};

```

## 1.12 Simple Int 128

```

__int128 read() {
    __int128 x = 0, f = 1;
    char ch = getchar();
    while (ch < '0' || ch > '9') {
        if (ch == '-') f = -1;
        ch = getchar();
    }
    while (ch >= '0' && ch <= '9') {
        x = x * 10 + ch - '0';
        ch = getchar();
    }
    return x * f;
}

void print(__int128 x) {
    if (x < 0) {
        putchar('-');
        x = -x;
    }
    if (x > 9) print(x / 10);
    putchar(x % 10 + '0');
}

```

```
bool cmp(__int128 x, __int128 y) { return x > y; }
```

## 1.13 Union Find Disjoint Set (UFDS)

Uncomment the lines to recover which element belong to each set.  
Time:  $\approx O(1)$  for everything.

```

class UFDS {
public:
    vi ps, size;
    // vector<unordered_set<int>> sts;

    UFDS(int N) : size(N + 1, 1), ps(N + 1), sts(N) {
        iota(ps.begin(), ps.end(), 0);
        // for (int i = 0; i < N; i++) sts[i].insert(i);
    }

    int find_set(int x) { return x == ps[x] ? x : (ps[x] = find_set(ps[x])); }

    bool same_set(int x, int y) { return find_set(x) == find_set(y); }

    void union_set(int x, int y) {
        if (same_set(x, y)) return;

        int px = find_set(x);
        int py = find_set(y);

        if (size[px] < size[py]) swap(px, py);

        ps[py] = px;
        size[px] += size[py];
        // sts[px].merge(sts[py]);
    }
};

```

## 1.14 Wavelet Tree

Build:  $O(N \cdot \log \sigma)$ .

Queries:  $O(\log \sigma)$ .

$\sigma$  = alphabet length

```

typedef vector<int>::iterator iter;

class WaveletTree {
public:
    int L, H;
    WaveletTree *l, *r;
    vector<int> frq;

    WaveletTree(iter fr, iter to, int x, int y) {
        L = x, H = y;
        if (fr >= to) return;

        int M = L + ((H - L) >> 1);
        auto F = [M](int x) { return x <= M; };

        frq.reserve(to - fr + 1);
    }

```

```

    frq.push_back(0);
    for (auto it = fr; it != to; it++) frq.push_back(frq.back() + F(*it));

    if (H == L) return;
    auto pv = stable_partition(fr, to, F);
    l = new WaveletTree(fr, pv, L, M);
    r = new WaveletTree(pv, to, M + 1, H);
}

// Find the k-th smallest element in positions [i,j]
int quantile(int l, int r, int k) {
    if (l > r) return 0;
    if (L == H) return L;
    int inLeft = frq[r] - frq[l - 1];
    int lb = frq[l - 1], rb = frq[r];
    if (k <= inLeft) return this->l->quantile(lb + 1, rb, k);
    return this->r->quantile(l - lb, r - rb, k - inLeft);
}

// Count occurrences of number c until position i -> [0, i].
int rank(int c, int i) { return until(c, min(i + 1, (int)frq.size() - 1)); }

int until(int c, int i) {
    if (c > H or c < L) return 0;
    if (L == H) return i;

    int M = L + ((H - L) >> 1);
    int r = frq[i];
    if (c <= M)
        return this->l->until(c, r);
    else
        return this->r->until(c, i - r);
}

// Count number of occurrences of numbers in the range [a, b]
int range(int i, int j, int a, int b) const {
    if (b < a or j < i) return 0;
    return range(i, j + 1, L, H, a, b);
}

int range(int i, int j, int a, int b, int L, int U) const {
    if (b < L or U < a) return 0;
    if (L <= a and b <= U) return j - i;
    int M = a + ((b - a) >> 1);
    int ri = frq[i], rj = frq[j];
    return this->l->range(ri, rj, a, M, L, U) +
        this->r->range(i - ri, j - rj, M + 1, b, L, U);
}

// Number of elements greater than or equal to k in [l, r];
// Can count distinct in a range with aux vector of next pos
int greater(int l, int r, int k) { return _greater(l + 1, r + 1, k); }

int _greater(int l, int r, int k) {
    if (l > r or k > H) return 0;
    if (L >= k) return r - l + 1;

    int ri = frq[l - 1], rj = frq[r];

```

```

        return this->l->_greater(ri + 1, rj, k) +
            this->r->_greater(l - ri, r - rj, k);
    }
};

```

## 2 Dynamic programming

### 2.1 Kadane

```

int kadane(const vi& xs) {
    vi s(xs.size());
    s[0] = xs[0];

    for (size_t i = 1; i < xs.size(); ++i) s[i] = max(xs[i], s[i - 1] + xs[i]);

    return *max_element(all(s));
}

```

### 2.2 Longest Increasing Subsequence (LIS)

Time:  $O(N \cdot \log N)$ .

```

int lis(vi const& a) {
    int n = a.size();
    const int INF = 1e9;
    vi d(n + 1, INF);
    d[0] = -INF;

    for (int i = 0; i < n; i++) {
        int l = upper_bound(d.begin(), d.end(), a[i]) - d.begin();
        if (d[l - 1] < a[i] && a[i] < d[l]) d[l] = a[i];
    }

    int ans = 0;
    for (int l = 0; l <= n; l++) {
        if (d[l] < INF) ans = l;
    }

    return ans;
}

```

## 3 Extras

### 3.1 cin/cout \_\_int128\_t

Allows standard reading and writing with cin/cout for 128-bit integers using `__int128_t` type.

```

ostream& operator<<(ostream& dest, __int128_t value) {
    ostream::sentry s(dest);
    if (s) {
        __uint128_t tmp = value < 0 ? -value : value;
        char buffer[128];
        char* d = end(buffer);
        do {
            --d;

```

```

    *d = "0123456789"[tmp % 10];
    tmp /= 10;
} while (tmp != 0);
if (value < 0) {
    --d;
    *d = '-';
}
int len = end(buffer) - d;
if (dest.rdbuf()->sputn(d, len) != len) dest.setstate(ios_base::badbit);
}
return dest;
}

istream& operator>>(istream& is, __int128_t& value) {
    string s;
    is >> s;

    __int128_t res = 0;
    size_t i = 0;

    bool neg = false;
    if (s[i] == '-') neg = 1, i++;
    for (; i < s.size(); ++i) (res *= 10) += (s[i] - '0');

    value = neg ? -res : res;
    return is;
}

```

## 4 Geometry

### 4.1 Andrew Convex Hull

Benefit of having lower hull and upper hull  
Complexity:  $O(n \log n)$

```

template <typename T>
vector<Point<T>> make_hull(const vector<Point<T>>& points,
                        vector<Point<T>>& hull) {
    for (const auto& p : points) {
        auto size = hull.size();

        while (size >= 2 and D(hull[size - 2], hull[size - 1], p) <= 0) {
            hull.pop_back();
            size = hull.size();
        }

        hull.push_back(p);
    }

    return hull;
}

template <typename T>
vector<Point<T>> monotone_chain(const vector<Point<T>>& points) {
    vector<Point<T>> P(points);

    sort(P.begin(), P.end());

```

```

vector<Point<T>> lower, upper;

lower = make_hull(P, lower);

reverse(P.begin(), P.end());

upper = make_hull(P, upper);

lower.pop_back();
lower.insert(lower.end(), upper.begin(), upper.end());

return lower;
}

```

### 4.2 Angle Between Segments

```

// Ângulo entre os segmentos de reta PQ e RS
template <typename T>
double angle(const Point<T>& P, const Point<T>& Q, const Point<T>& R,
            const Point<T>& S) {
    auto ux = P.x - Q.x;
    auto uy = P.y - Q.y;

    auto vx = R.x - S.x;
    auto vy = R.y - S.y;

    auto num = ux * vx + uy * vy;
    auto den = hypot(ux, uy) * hypot(vx, vy);

    // Caso especial: se den == 0, algum dos vetores é degenerado: os dois
    // pontos são iguais. Neste caso, o ângulo não está definido

    return acos(num / den);
}

```

### 4.3 Circle

```

enum PointPosition { IN, ON, OUT };

template <typename T>
struct Circle {
    Point<T> C;
    T r;

    PointPosition position(const Point<T>& P) const {
        auto d = dist(P, C);

        return equals(d, r) ? ON : (d < r ? IN : OUT);
    }

    bool contains(Point<T>& P) { return distance(C, P) <= r; }

    static std::optional<Circle> from_2_points_and_r(const Point<T>& P,
                                                    const Point<T>& Q, T r) {
        double d2 = (P.x - Q.x) * (P.x - Q.x) + (P.y - Q.y) * (P.y - Q.y);

```

```

double det = r * r / d2 - 0.25;

if (det < 0.0) return {};

double h = sqrt(det);

auto x = (P.x + Q.x) * 0.5 + (P.y - Q.y) * h;
auto y = (P.y + Q.y) * 0.5 + (Q.x - P.x) * h;

return Circle<T>{Point<T>(x, y), r};
}

static Circle<T> from_2_points(const Point<T>& P, const Point<T>& Q) {
    auto x = (P.x + Q.x) / 2;
    auto y = (P.y + Q.y) / 2;

    return Circle<T>{Point(x, y), distance(P, Q) / 2};
}

static std::optional<Circle> from_3_points(const Point<T>& P,
                                           const Point<T>& Q,
                                           const Point<T>& R) {

    auto a = 2 * (Q.x - P.x);
    auto b = 2 * (Q.y - P.y);
    auto c = 2 * (R.x - P.x);
    auto d = 2 * (R.y - P.y);

    auto det = a * d - b * c;

    // Pontos colineares
    if (equals(det, (T)0)) return {};

    auto k1 = (Q.x * Q.x + Q.y * Q.y) - (P.x * P.x + P.y * P.y);
    auto k2 = (R.x * R.x + R.y * R.y) - (P.x * P.x + P.y * P.y);

    // Solução do sistema por Regra de Cramer
    auto cx = (k1 * d - k2 * b) / det;
    auto cy = (a * k2 - c * k1) / det;

    Point<T> C{cx, cy};
    auto r = distance(P, C);

    return Circle<T>(C, r);
}

// Interseção entre o círculo c e a reta que passa por P e Q
static std::vector<Point<T>> intersection(const Circle<T>& c,
                                          const Point<T>& P,
                                          const Point<T>& Q) {

    auto a = pow(Q.x - P.x, 2.0) + pow(Q.y - P.y, 2.0);
    auto b = 2 * ((Q.x - P.x) * (P.x - c.C.x) + (Q.y - P.y) * (P.y - c.C.y));
    auto d = pow(c.C.x, 2.0) + pow(c.C.y, 2.0) + pow(P.x, 2.0) + pow(P.y, 2.0)
        +
        2 * (c.C.x * P.x + c.C.y * P.y);
    auto D = b * b - 4 * a * d;

    if (D < 0)
        return {};

```

```

    else if (equals(D, (T)0)) {
        auto u = -b / (2 * a);
        auto x = P.x + u * (Q.x - P.x);
        auto y = P.y + u * (Q.y - P.y);
        return {Point<T>(x, y)};
    }

    auto u = (-b + sqrt(D)) / (2 * a);

    auto x = P.x + u * (Q.x - P.x);
    auto y = P.y + u * (Q.y - P.y);

    auto P1 = Point<T>(x, y);

    u = (-b - sqrt(D)) / (2 * a);

    x = P.x + u * (Q.x - P.x);
    y = P.y + u * (Q.y - P.y);

    auto P2 = Point<T>(x, y);

    return {P1, P2};
}
};

```

## 4.4 Closest Points

```

template <typename T>
double dist(Point<T>& P, Point<T>& Q) {
    return hypot(P.x - Q.x, P.y - Q.y);
}

template <typename T>
pair<Point<T>, Point<T>> closest_pair(int N, vector<Point<T>>& ps) {
    using ii = pair<T, T>;

    sort(ps.begin(), ps.end());

    // Este código assume que N > 1
    auto d = dist(ps[0], ps[1]);
    auto closest = make_pair(ps[0], ps[1]);

    set<ii> S;
    S.insert(ii(ps[0].y, ps[0].x));
    S.insert(ii(ps[1].y, ps[1].x));

    for (int i = 2; i < N; ++i) {
        auto P = ps[i];
        auto it = S.lower_bound(ii(P.y - d, 0));

        while (it != S.end()) {
            auto Q = Point<T>(it->second, it->first);

            if (Q.x < P.x - d) {
                it = S.erase(it);
                continue;
            }

```

```

    if (Q.y > P.y + d) break;

    auto t = dist(P, Q);

    if (t < d) {
        d = t;
        closest = make_pair(P, Q);
    }

    ++it;
}

S.insert(ii(P.y, P.x));
}

return closest;
}

```

## 4.5 Convex Hull Trick

Add lines of the form  $y = ax + b$  to a set and query the maximum value of  $y$  at a given  $x$ . `add(a, b)`: add line  $y = ax + b$  `query(x)`: find the maximum value of  $y$  at  $x$   
Time:  $O(\log n)$  amortized for `add(a, b)` and  $O(\log n)$  for `query(x)`.

```

template <typename T = ll>
struct ConvexHullTrick {
    static constexpr T inf = numeric_limits<T>::max();

    struct Line {
        T a, b;
        mutable T x_inter;
        T eval(T x) const { return a * x + b; }
        bool operator<(const Line& rhs) const { return a < rhs.a; }
        bool operator<(T x) const { return x_inter < x; }
    };

    multiset<Line, less<>> ln;

    T query(T x) const {
        auto it = ln.lower_bound(x);
        if (it == ln.end()) return inf;
        return it->eval(x);
    }

    void add(T a, T b) {
        auto it = ln.insert({a, b, 0});
        while (overlap(it)) ln.erase(next(it)), update(it);
        if (it != ln.begin() and !overlap(prev(it))) it = prev(it), update(it);
        while (it != ln.begin() and overlap(prev(it)))
            it = prev(it), ln.erase(next(it)), update(it);
    }

private:
    void update(auto it) const {
        if (next(it) == ln.end())
            it->x_inter = inf;
        else if (it->a == next(it)->a)
            (it->x_inter = it->b >= next(it)->b ? inf : -inf);
        else {
            auto h = (it->b - next(it)->b);

```

```

        auto l = (next(it)->a - it->a);
        it->x_inter = h / l - ((h ^ l) < 0 && h % l);
    }
}

bool overlap(auto it) const {
    update(it);
    if (next(it) == ln.end()) return false;
    if (it->a == next(it)->a) return it->b >= next(it)->b;
    return it->x_inter >= next(it)->x_inter;
}

};

```

## 4.6 Convex Hull

Given a set of points find the smallest convex polygon that contains all the given points.

Time:  $O(N \cdot \log N)$

By default it removes the collinear points, set the boolean to true if you don't want that

```

struct pt {
    double x, y;
};

int orientation(pt a, pt b, pt c) {
    double v = a.x * (b.y - c.y) + b.x * (c.y - a.y) + c.x * (a.y - b.y);
    if (v < 0) return -1; // clockwise
    if (v > 0) return +1; // counter-clockwise
    return 0;
}

bool cw(pt a, pt b, pt c, bool include_collinear) {
    int o = orientation(a, b, c);
    return o < 0 || (include_collinear && o == 0);
}

bool collinear(pt a, pt b, pt c) { return orientation(a, b, c) == 0; }

void convex_hull(vector<pt>& a, bool include_collinear = false) {
    pt p0 = *min_element(a.begin(), a.end(), [](pt a, pt b) {
        return make_pair(a.y, a.x) < make_pair(b.y, b.x);
    });
    sort(a.begin(), a.end(), [&p0](const pt& a, const pt& b) {
        int o = orientation(p0, a, b);
        if (o == 0)
            return (p0.x - a.x) * (p0.x - a.x) + (p0.y - a.y) * (p0.y - a.y) <
                (p0.x - b.x) * (p0.x - b.x) + (p0.y - b.y) * (p0.y - b.y);
        return o < 0;
    });
    if (include_collinear) {
        int i = (int)a.size() - 1;
        while (i >= 0 && collinear(p0, a[i], a.back())) i--;
        reverse(a.begin() + i + 1, a.end());
    }

    vector<pt> st;
    for (int i = 0; i < (int)a.size(); i++) {
        while (st.size() > 1 &&
            !cw(st[st.size() - 2], st.back(), a[i], include_collinear))
            st.pop_back();
    }
}

```

```

    st.push_back(a[i]);
}

a = st;
}

```

## 4.7 Distance between Point and Line

It uses the implementation of the general equation of a line

```

template <typename T>
double distance(Point<T>& p, Line<T>& l) {
    return fabs(1.a * p.x + 1.b * p.y) / hypot(1.a, 1.b);
}

```

## 4.8 Graham Convex Hull

```

template <typename T>
class GrahamScan {
private:
    static Point<T> pivot(vector<Point<T>>& P) {
        size_t idx = 0;

        for (size_t i = 1; i < P.size(); ++i)
            if (P[i].y < P[idx].y or (equals(P[i].y, P[idx].y) and P[i].x > P[idx].x))
                idx = i;

        swap(P[0], P[idx]);

        return P[0];
    }

    static void sort_by_angle(vector<Point<T>>& P) {
        auto P0 = pivot(P);

        sort(P.begin() + 1, P.end(), [&](const Point<T>& A, const Point<T>& B) {
            // pontos colineares: escolhe-se o mais próximo do pivô
            if (equals(D(P0, A, B), 0)) return A.distance(P0) < B.distance(P0);

            auto alfa = atan2(A.y - P0.y, A.x - P0.x);
            auto beta = atan2(B.y - P0.y, B.x - P0.x);

            return alfa < beta;
        });
    }

public:
    static vector<Point<T>> convex_hull(const vector<Point<T>>& points) {
        vector<Point<T>> P(points);
        auto N = P.size();

        // Corner case: com 3 vértices ou menos, P é o próprio convex hull
        if (N <= 3) return P;

        sort_by_angle(P);
    }
}

```

```

vector<Point<T>> ch;
ch.push_back(P[N - 1]);
ch.push_back(P[0]);
ch.push_back(P[1]);

size_t i = 2;

while (i < N) {
    auto j = ch.size() - 1;

    if (D(ch[j - 1], ch[j], P[i]) > 0)
        ch.push_back(P[i++]);
    else
        ch.pop_back();
}

// O envoltório é um caminho fechado: o primeiro ponto é igual ao último
return ch;
}
};

```

## 4.9 Convex Hull Trick

Add lines  $ax + b$  and query maximum value at  $x$ . If you want to get minimum value, set `inf = numeric_limits<T>::max()`. In case of overflow, try to compress  $x$  values.  
Time:  $O(\log(HI - LO))$  for query,  $O(\log(HI - LO))$  for add,  $O(\log^2(HI - LO))$  for add segment.

```

template <typename T = ll, T LO = T(-1e9), T HI = T(1e9)>
struct LiChaoTree {
    // get max value at x by default
    // to get min value, set inf = numeric_limits<T>::max()
    static constexpr T inf = numeric_limits<T>::min();
    static constexpr bool compare(T a, T b) {
        if constexpr (inf == numeric_limits<T>::max()) {
            return a < b;
        } else {
            return a > b;
        }
    }

    static constexpr T best(T a, T b) { return (compare(a, b) ? a : b); }
    struct Line {
        T a, b;
        array<int, 2> ch;
        Line(T a_ = 0, T b_ = inf) : a(a_), b(b_), ch({-1, -1}) {}
        constexpr T eval(T x) const { return a * x + b; }
        constexpr bool is_leaf() const { return ch[0] == -1 and ch[1] == -1; }
    };
    vector<Line> ln;
    LiChaoTree() { ln.emplace_back(); }

    T query(T x, int v = 0, T l = LO, T r = HI) {
        auto m = l + (r - l) / 2, val = ln[v].eval(x);
        if (ln[v].is_leaf()) return val;
        if (x <= m)
            return best(val, query(x, ch(v, 0), l, m));
        else
            return best(val, query(x, ch(v, 1), m + 1, r));
    }
}

```

```

void add(T a, T b) { add({a, b}, 0, LO, HI); }
void add(Line s, int v, T l, T r) {
    auto m = l + (r - l) / 2;
    bool L = compare(s.eval(l), ln[v].eval(l));
    bool M = compare(s.eval(m), ln[v].eval(m));
    bool R = compare(s.eval(r), ln[v].eval(r));
    if (M) swap(ln[v], s), swap(ln[v].ch, s.ch);
    if (s.b == inf) return;
    if (L != M)
        add(s, ch(v, 0), l, m);
    else if (R != M)
        add(s, ch(v, 1), m + 1, r);
}

void add_segment(T a, T b, T l, T r) { add_segment({a, b}, l, r, 0, LO, HI);
}
void add_segment(Line s, T l, T r, int v, T L, T R) {
    if (l <= L and R <= r) return add(s, v, L, R);
    auto m = L + (R - L) / 2;
    if (l <= m) add_segment(s, l, r, ch(v, 0), L, m);
    if (r > m) add_segment(s, l, r, ch(v, 1), m + 1, R);
}

private:
int ch(int v, bool b) {
    if (ln[v].ch[b] == -1) {
        ln[v].ch[b] = (int)ln.size();
        ln.emplace_back();
    }
    return ln[v].ch[b];
}
};

```

## 4.10 Line Closest Point

Given a line using the general equation and an arbitrary point, returns the closest point of the line

```

template <typename T>
Point<T> closest(Point<T>& p, Line<T> l) {
    auto den = (l.a * l.a + l.b * l.b);

    auto x = (l.b * (l.b * p.x - l.a * p.y) - l.a * l.c) / den;
    auto y = (l.a * (-l.b * p.x + l.a * p.y) - l.b * l.c) / den;

    return Point<T>(x, y);
}

```

## 4.11 Line Intersection

```

const int oo{-1};

template <typename T>
std::pair<int, Point<T>> intersections(const Line<T>& r, const Line<T>& s) {
    auto det = r.a * s.b - r.b * s.a;

```

```

    if (equals(det, 0)) // Coincidentes ou paralelas
    {
        return {(r == s) ? oo : 0, {}};
    } else // Concorrentes
    {
        auto x = (-r.c * s.b + s.c * r.b) / det;
        auto y = (-s.c * r.a + r.c * s.a) / det;

        return {1, {x, y}};
    }
}

```

## 4.12 Line Structure

Line structure using the general equation

```

template <typename T>
struct Line {
    T a, b, c;

    Line(const Point<T>& P, const Point<T>& Q)
        : a(P.y - Q.y), b(Q.x - P.x), c(P.x * Q.y - Q.x * P.y) {}

    bool operator==(const Line<T>& r) const {
        auto k = a ? a : b;
        auto s = r.a ? r.a : r.b;

        return equals(a * s, r.a * k) && equals(b * s, r.b * k) &&
            equals(c * s, r.c * k);
    }

    bool parallel(const Line<T>& r) const {
        auto det = a * r.b - b * r.a;

        return det == 0 and !(*this == r);
    }

    bool orthogonal(const Line& r) const // Verdadeiro se perpendiculares
    {
        return equals(a * r.a + b * r.b, 0);
    }

    bool contains(const Point<T>& P) const {
        return equals(a * P.x + b * P.y + c, 0);
    }
};

```

## 4.13 Reduced Line Structure

Line structure using the reduced equation

```

template <typename T>
struct Line {
    bool vertical;
    T m, b;

    Line(const Point<T>& P, const Point<T>& Q) : vertical(false) {

```

```

    if (equals(P.x, Q.x)) {
        vertical = true;
        b = P.x;
    } else {
        m = (Q.y - P.y) / (Q.x - P.x);
        b = P.y - m * P.x;
    }
}

bool operator==(const Line<T>& r) const // Verdadeiro se coincidentes
{
    if (vertical != r.vertical || !equals(m, r.m)) return false;

    return equals(b, r.b);
}

bool parallel(const Line<T>& r) const // Verdadeiro se paralelas
{
    if (vertical && r.vertical) return b != r.b;
    if (vertical || r.vertical) return false;

    return equals(m, r.m) && !equals(b, r.b);
}

bool orthogonal(const Line& r) const // Verdadeiro se perpendiculares
{
    if (vertical and r.vertical) return false;

    if ((vertical && equals(r.m, 0)) || (equals(m, 0) && r.vertical))
        return true;

    if (vertical || r.vertical) return false;

    return equals(m * r.m, -1.0);
}
};

```

## 4.14 Minimum Enclosing Circle (MEC)

Given a vector of points, it returns a circle in which every point is contained in the circle.

Time Complexity:  $O(N)$

```

template <typename T>
Circle<T> welzl(vector<Point<T>> &points, vector<Point<T>> r, int n) {
    if (n == 0 || r.size() == 3) {
        if (r.size() == 0) return {{0, 0}, 0};
        if (r.size() == 1) return {r[0], 0};
        if (r.size() == 2) return Circle<T>::from_2_points(r[0], r[1]);
        return Circle<T>::from_3_points(r[0], r[1], r[2]);
    }

    Point<T> p = points[n - 1];
    Circle<T> d = welzl(points, r, n - 1);

    if (d.contains(p)) return d;

    r.push_back(p);
    return welzl(points, r, n - 1);
}

```

```

}

template <typename T>
Circle<T> minimum_enclosing_circle(vector<Point<T>> &points) {
    random_shuffle(points.begin(), points.end());
    return welzl(points, {}, points.size());
}

```

## 4.15 Point in Polygon

Given the vertices of a polygon, we want to determine if a point lies inside the polygon.

Time:  $O(\text{num\_vertices})$

**Note:** The points must be sorted in increasing order of x-coordinates.

```

const double EPS = 1e-9;
template <typename T>
bool point_in_polygon(Point<T> point, vector<Point<T>> polygon) {
    int num_vertices = polygon.size();
    T x = point.x, y = point.y;
    bool inside = false;
    Point<T> p1 = polygon[0], p2; // p1 is the first vertex
    for (int i = 1; i <= num_vertices; i++) {
        p2 = polygon[i % num_vertices]; // next vertex

        if (abs((p2.y - p1.y) * (x - p1.x) - (p2.x - p1.x) * (y - p1.y)) < EPS &&
            (x - p1.x) * (x - p2.x) <= 0 && (y - p1.y) * (y - p2.y) <= 0) {
            return true; // point is on the boundary
        }

        if (y > min(p1.y, p2.y)) {
            if (y <= max(p1.y, p2.y)) {
                if (p1.x == p2.x) {
                    if (x <= p1.x) {
                        inside = !inside;
                    }
                } else if (x <= max(p1.x, p2.x) &&
                    x <= (y - p1.y) * (p2.x - p1.x) / (p2.y - p1.y) + p1.x) {
                    inside = !inside;
                }
            }
        }
        p1 = p2;
    }
    return inside;
}

```

## 4.16 Point Rotate

```

const double PI = acos(-1.0);

template <typename T>
Point<T> rotate_point(Point<T> &P, double a) {
    return Point<T>(P.x * cos(a) - P.y * sin(a), P.x * sin(a) + P.y * cos(a));
}

double radians(double angle) { return (PI * angle) / 180.0; }

```



## 4.17 Point Structure

```
template <typename T>
bool equals(T a, T b) {
    constexpr double EPS{1e-9};

    return std::is_floating_point<T>::value ? fabs(a - b) < EPS : a == b;
}

template <typename T>
struct Point {
    T x = 0, y = 0;

    Point() {}
    Point(T _x, T _y) : x(_x), y(_y) {}

    bool operator==(const Point<T>& p) const noexcept {
        return equals(x, p.x) && equals(y, p.y);
    }

    bool operator<(const Point& p) const noexcept {
        return equals(x, p.x) ? y < p.y : x < p.x;
    }
};

// D = 0: R pertence a reta PQ
// D > 0: R à esquerda da reta PQ
// D < 0: R à direita da reta PQ
template <typename T>
T D(const Point<T>& P, const Point<T>& Q, const Point<T>& R) {
    return (P.x * Q.y + P.y * R.x + Q.x * R.y) -
        (R.x * Q.y + R.y * P.x + Q.x * P.y);
}
```

## 4.18 Point To Segment

```
typedef pair<double, double> pdb;

double pt2segment(pdb A, pdb B, pdb E) {
    pdb AB = {B.fst - A.fst, B.snd - A.snd};
    pdb BE = {E.fst - B.fst, E.snd - B.snd};
    pdb AE = {E.fst - A.fst, E.snd - A.snd};

    double AB_BE = AB.fst * BE.fst + AB.snd * BE.snd;
    double AB_AE = AB.fst * AE.fst + AB.snd * AE.snd;

    double ans;
    if (AB_BE > 0) {
        double y = E.snd - B.snd;
        double x = E.fst - B.fst;
        ans = hypot(x, y);
    } else if (AB_AE < 0) {
        double y = E.snd - A.snd;
        double x = E.fst - A.fst;
        ans = hypot(x, y);
    } else {
        auto [x1, y1] = AB;
        auto [x2, y2] = AE;
```

```
        double mod = hypot(x1, y1);
        ans = abs(x1 * y2 - y1 * x2) / mod;
    }

    return ans;
}
```

## 4.19 Point Vector

```
template <typename T>
struct Point {
    T x, y;

    Point(T x = 0, T y = 0) : x(x), y(y) {}

    inline Point operator+(const Point &p) const {
        return Point(x + p.x, y + p.y);
    }
    inline Point operator-(const Point &p) const {
        return Point(x - p.x, y - p.y);
    }
    inline Point operator+(const T &k) const { return Point(x + k, y + k); }
    inline Point operator-(const T &k) const { return Point(x - k, y - k); }
    inline Point operator*(const T &k) const { return Point(x * k, y * k); }
    inline Point operator/(const T &k) const { return Point(x / k, y / k); }

    inline Point &operator+=(const Point &p) {
        x += p.x, y += p.y;
        return *this;
    }
    inline Point &operator-=(const Point &p) {
        x -= p.x, y -= p.y;
        return *this;
    }
    inline Point &operator+=(const T &k) {
        x += k, y += k;
        return *this;
    }
    inline Point &operator-=(const T &k) {
        x -= k, y -= k;
        return *this;
    }
    inline Point &operator*=(const T &k) {
        x *= k, y *= k;
        return *this;
    }
    inline Point &operator/=(const T &k) {
        x /= k, y /= k;
        return *this;
    }

    inline bool operator==(const Point &p) const {
        return eq(x, p.x) and eq(y, p.y);
    }
    inline bool operator<(const Point &p) const {
        return eq(x, p.x) ? y < p.y : x < p.x;
    }
    inline bool operator>(const Point &p) const {
```

```

    return eq(x, p.x) ? y > p.y : x > p.x;
}
inline bool operator<=(const Point &p) const {
    return *this == p or *this < p;
}
inline bool operator>=(const Point &p) const {
    return *this == p or *this > p;
}

friend ostream &operator<<(ostream &os, const Point &p) {
    return os << p.x << ' ' << p.y;
}
friend istream &operator>>(istream &is, Point &p) { return is >> p.x >> p.y;
}

template <typename U>
void rotate(U rad) {
    tie(x, y) =
        make_pair(x * cos(rad) - y * sin(rad), x * sin(rad) + y * cos(rad));
}
template <typename U>
Point<U> rotated(U rad) const {
    return Point<U>(x * cos(rad) - y * sin(rad), x * sin(rad) + y * cos(rad));
}
inline T dot(const Point &p) const { return x * p.x + y * p.y; }
inline T cross(const Point &p) const { return x * p.y - y * p.x; }
inline T cross(const Point &a, const Point &b) const {
    return (a - *this).cross(b - *this);
}
inline T dist2() const { return x * x + y * y; }
inline double dist() const { return hypot(x, y); }
inline double angle() const { return atan2(y, x); }
inline double norm() const { return sqrt(dot(*this)); }
inline Point rot90() const { return Point(-y, x); }
inline Point to(const Point &p) const { return p - *this; }
};

template <typename T>
struct Vector {
    T x = 0, y = 0;

    Vector(const Point<T> &A, const Point<T> &B) : x(B.x - A.x), y(B.y - A.y) {}

    T length() const { return hypot(x, y); }
};

template <typename T>
struct Line {
    T a, b, c;

    Line(T av, T bv, T cv) : a(av), b(bv), c(cv) {}

    Line(const Point<T> &P, const Point<T> &Q)
        : a(P.y - Q.y), b(Q.x - P.x), c(P.x * Q.y - Q.x * P.y) {}
};

```

## 4.20 Polygon

```

template <typename T>
class Polygon {
private:
    vector<Point<T>> vs;
    int n;

public:
    // 0 parâmetro deve conter os n vértices do polígono
    Polygon(const vector<Point<T>>& ps) : vs(ps), n(vs.size()) {
        vs.push_back(vs.front());
    }

private:
    T D(const Point<T>& P, const Point<T>& Q, const Point<T>& R) const {
        return (P.x * Q.y + P.y * R.x + Q.x * R.y) -
            (R.x * Q.y + R.y * P.x + Q.x * P.y);
    }

public:
    bool convex() const {
        // Um polígono deve ter, no mínimo, 3 vértices
        if (n < 3) return false;

        int P = 0, N = 0, Z = 0;

        for (int i = 0; i < n; ++i) {
            auto d = D(vs[i], vs[(i + 1) % n], vs[(i + 2) % n]);
            d ? (d > 0 ? ++P : ++N) : ++Z;
        }

        return P == n or N == n;
    }

private:
    double distance(const Point<T>& P, const Point<T>& Q) {
        return hypot(P.x - Q.x, P.y - Q.y);
    }

public:
    double perimeter() const {
        auto p = 0.0;

        for (int i = 0; i < n; ++i) p += distance(vs[i], vs[i + 1]);

        return p;
    }

    double area() const {
        auto a = 0.0;

        for (int i = 0; i < n; ++i) {
            a += vs[i].x * vs[i + 1].y;
            a -= vs[i + 1].x * vs[i].y;
        }

        return 0.5 * fabs(a);
    }
}

```

```
private:
    // Ângulo APB, em radianos
    double angle(const Point<T>& P, const Point<T>& A, const Point<T>& B) {
        auto ux = P.x - A.x;
        auto uy = P.y - A.y;

        auto vx = P.x - B.x;
        auto vy = P.y - B.y;

        auto num = ux * vx + uy * vy;
        auto den = hypot(ux, uy) * hypot(vx, vy);

        // Caso especial: se den == 0, algum dos vetores é degenerado: os
        // dois pontos são iguais. Neste caso, o ângulo não está definido

        return acos(num / den);
    }

    bool equals(double x, double y) {
        static const double EPS{1e-6};
        return fabs(x - y) < EPS;
    }

public:
    bool contains(const Point<T>& P) const {
        if (n < 3) return false;

        auto sum = 0.0;

        for (int i = 0; i < n - 1; ++i) {
            auto d = D(P, vs[i], vs[i + 1]);
            auto a = angle(P, vs[i], vs[i + 1]);
            sum += d > 0 ? a : (d < 0 ? -a : 0);
        }

        static const double PI = acos(-1.0);
        return equals(fabs(sum), 2 * PI);
    }

private:
    // Interseção entre a reta AB e o segmento de reta PQ
    Point<T> intersection(const Point<T>& P, const Point<T>& Q, const Point<T>&
        A,
                        const Point<T>& B) {
        auto a = B.y - A.y;
        auto b = A.x - B.x;
        auto c = B.x * A.y - A.x * B.y;
        auto u = fabs(a * P.x + b * P.y + c);
        auto v = fabs(a * Q.x + b * Q.y + c);

        // Média ponderada pelas distâncias de P e Q até a reta AB
        return {(P.x * v + Q.x * u) / (u + v), (P.y * v + Q.y * u) / (u + v)};
    }

public:
    // Corta o polígono com a reta r que passa por A e B
    Polygon cut_polygon(const Point<T>& A, const Point<T>& B) const {
        vector<Point<T>> points;
```

```
        const double EPS{1e-6};

        for (int i = 0; i < n; ++i) {
            auto d1 = D(A, B, vs[i]);
            auto d2 = D(A, B, vs[i + 1]);

            // Vértice à esquerda da reta
            if (d1 > -EPS) points.push_back(vs[i]);

            // A aresta cruza a reta
            if (d1 * d2 < -EPS)
                points.push_back(intersection(vs[i], vs[i + 1], A, B));
        }

        return Polygon(points);
    }

    double circumradius() const {
        auto s = distance(vs[0], vs[1]);
        const double PI{acos(-1.0)};

        return (s / 2.0) * (1.0 / sin(PI / n));
    }

    double apothem() const {
        auto s = distance(vs[0], vs[1]);
        const double PI{acos(-1.0)};

        return (s / 2.0) * (1.0 / tan(PI / n));
    }
};
```

## 4.21 Polinominoes

Geometric figure made by equal squares, connected between themselves in a way that at least one side of each square coincide with a side of another square.

Watch out: the number of polynominoes increases fastly (size 12 has 63.600 figures)

```
// We consider the rotations
// as distinct (0, 10, 10+9, 10+9+8...)
vi pos = {0, 10, 19, 27, 34, 40, 45, 49, 52, 54, 55};
```

```
const int MAXP = 10;
```

```
struct Poly {
    ii v[MAXP];
    int64_t id;
    int n;

    Poly() {
        n = 1;
        v[0] = {0, 0};
        normalize();
    }

    Poly(vii &vp) {
        n = vp.size();
        for (int i = 0; i < n; i++) v[i] = vp[i];
        normalize();
    }
};
```

```

}

ii &operator[] (int i) { return v[i]; }

bool add(int a, int b) {
    for (int i = 0; i < n; i++) {
        auto [f, s] = v[i];
        if (f == a and s == b) return false;
    }

    v[n++] = ii{a, b};
    normalize();
    return true;
}

void normalize() {
    int mx = 100, my = 100;
    for (int i = 0; i < n; i++) {
        auto [f, s] = v[i];
        mx = min(mx, f), my = min(my, s);
    }

    id = 0;
    for (int i = 0; i < n; i++) {
        auto &[f, s] = v[i];
        f -= mx, s -= my;
        id |= (1LL << (pos[f] + s));
    }
}

bool operator<(Poly oth) { return id < oth.id; }
};

vector<Poly> poly[MAXP + 1];

void buildPoly(int mxN) {
    for (int i = 0; i <= mxN; i++) poly[i].clear();

    Poly init;
    queue<Poly> q;
    unordered_set<int64_t> used;
    q.push(init);
    used.insert(init.id);
    while (not q.empty()) {
        Poly u = q.front();
        q.pop();
        poly[u.n].emplace_back(u);

        if (u.n == mxN) continue;

        for (int i = 0; i < u.n; i++) {
            for (auto [dx, dy] : dir4) {
                Poly to = u;
                auto [f, s] = to[i];
                bool ok = to.add(f + dx, s + dy);

                if (ok and not used.count(to.id)) {
                    q.push(to);
                }
            }
        }
    }
}

```

```
        used.insert(to.id);
    }
}
}
```

## 4.22 Rectangle

```

template <typename T>
struct Rectangle {
    Point<T> P, Q;
    T b, h;

    Rectangle(const Point<T>& p, const Point<T>& q) : P(p), Q(q) {
        b = max(P.x, Q.x) - min(P.x, Q.x);
        h = max(P.y, Q.y) - min(P.y, Q.y);
    }

    Rectangle(const T& base, const T& height)
        : P(0, 0), Q(base, height), b(base), h(height) {}

    Rectangle intersection(const Rectangle& r) const {
        using interval = pair<T, T>;

        auto I = interval(min(P.x, Q.x), max(P.x, Q.x));
        auto U = interval(min(r.P.x, r.Q.x), max(r.P.x, r.Q.x));

        auto a = max(I.first, U.first);
        auto b = min(I.second, U.second);

        if (b < a) return {{-1, -1}, {-1, -1}};

        I = interval(min(P.y, Q.y), max(P.y, Q.y));
        U = interval(min(r.P.y, r.Q.y), max(r.P.y, r.Q.y));

        auto c = max(I.first, U.first);
        auto d = min(I.second, U.second);

        if (d < c) return {{-1, -1}, {-1, -1}};

        auto inter = Rectangle(Point(a, c), Point(b, d));

        return inter;
    }
};

```

### 4.23 Segment Structure

```
template <typename T>
class Segment {
public:
    Point<T> A, B;

    // Shamos Hoey
    // Segment(const Point<T>& P, const Point<T>& Q)
```

```

//      : a(P.y - Q.y), b(Q.x - P.x), c(P.x*Q.y - Q.x*P.y), A(P), B(Q) {
//      sweep_x = -1; }

// bool operator<(const Segment& line) const
// {
//      return (-a*sweep_x - c)*line.b < (-line.a*sweep_x -line.c)*b;
// }
//
// static T sweep_x;

// Verifica se o ponto P da reta r que contém A e B pertence ao segmento
bool contains(const Point<T>& P) const {
    return equals(A.x, B.x) ? min(A.y, B.y) <= P.y and P.y <= max(A.y, B.y)
        : min(A.x, B.x) <= P.x and P.x <= max(A.x, B.x);
}

// Esta abordagem não exige que P esteja sobre a reta AB
bool contains2(const Point<T>& P) const {
    double dAB = dist(A, B), dAP = dist(A, P), dPB = dist(P, B);

    return equals(dAP + dPB, dAB);
}

bool intersect(const Segment<T>& s) const {
    auto d1 = D(A, B, s.A);
    auto d2 = D(A, B, s.B);

    if ((equals(d1, 0) && contains(s.A)) || (equals(d2, 0) && contains(s.B)))
        return true;

    auto d3 = D(s.A, s.B, A);
    auto d4 = D(s.A, s.B, B);

    if ((equals(d3, 0) && s.contains(A)) || (equals(d4, 0) && s.contains(B)))
        return true;

    // The original check is (d1 * d2 < 0) and (d3 * d4 < 0)
    // Thus, we want to avoid overflow
    bool fst = (d1 < 0 and d2 > 0) or (d1 > 0 and d2 < 0);
    bool snd = (d3 < 0 and d4 > 0) or (d3 > 0 and d4 < 0);

    return fst and snd;
}

// Ponto mais próximo de P no segmento AB
Point<T> closest(const Point<T>& P) {
    Line<T> r(A, B);
    auto Q = r.closest(P);

    if (this->contains(Q)) return Q;

    auto distA = P.distanceTo(A);
    auto distB = P.distanceTo(B);

    if (distA <= distB)
        return A;
    else
        return B;
}

```

```

}
};

```

## 4.24 Segment Intersection Exists

```

template <typename T>
T Segment<T>::sweep_x;

template <typename T>
bool shamos_hoeys(const vector<Segment<T>>& segments) {
    struct Event {
        Point<T> P;
        size_t i;

        bool operator<(const Event& e) const { return P < e.P; }
    };

    vector<Event> events;

    for (size_t i = 0; i < segments.size(); ++i) {
        events.push_back({segments[i].A, i});
        events.push_back({segments[i].B, i});
    }

    sort(events.begin(), events.end());
    set<Segment<T>> sl;

    for (const auto& e : events) {
        auto s = segments[e.i];
        Segment<T>::sweep_x = e.P.x;

        if (e.P == s.A) {
            sl.insert(s);

            auto it = sl.find(s);

            if (it != sl.begin()) {
                auto L = *prev(it);

                if (s.intersect(L)) return true;
            }

            if (next(it) != sl.end()) {
                auto U = *next(it);

                if (s.intersect(U)) return true;
            }
        } else {
            auto it = sl.find(s);

            if (it != sl.begin() and it != sl.end()) {
                auto L = *prev(it);
                auto U = *next(it);

                if (L.intersect(U)) return true;
            }

            sl.erase(it);
        }
    }
}

```

```

    }
}

return false;
}

4.25 Sweep Line

struct Segment {
    double a, b, c;
    Point A, B;
    size_t idx;

    Segment(const Point& P, const Point& Q, size_t i)
        : a(P.y - Q.y),
          b(Q.x - P.x),
          c(P.x * Q.y - Q.x * P.y),
          A(P),
          B(Q),
          idx(i) {}

    bool operator<(const Segment& s) const {
        return (-a * sweep_x - c) * s.b < (-s.a * sweep_x - s.c) * b;
    }

    optional<Point> intersection(const Segment& s) const {
        auto det = a * s.b - b * s.a;

        if (not equals(det, 0.0)) // Concorrentes
        {
            auto x = (-c * s.b + s.c * b) / det;
            auto y = (-s.c * a + c * s.a) / det;

            if (min(A.x, B.x) <= x and x <= max(A.x, B.x) and
                min(s.A.x, s.B.x) <= x and x <= max(s.A.x, s.B.x)) {
                return Point{x, y};
            }
        }

        return {};
    }

    static double sweep_x;
};

double Segment::sweep_x;

struct Event {
    enum Type { OPEN, INTERSECTION, CLOSE };

    Point P;
    Type type;
    size_t i;

    bool operator<(const Event& e) const {
        if (P != e.P) return e.P < P;

        if (type != e.type) return type > e.type;

```

```

        return i > e.i;
    }
};

void add_neighbor_intersections(const Segment& s, const set<Segment>& sl,
                                set<Point>& ans,
                                priority_queue<Event>& events) {
    // TODO: garantir que a busca identifique unicamente o elemento s,
    // através do ajuste fino da variável Segment::sweep_x
    auto it = sl.find(s);

    if (it != sl.begin()) {
        auto L = *prev(it);
        auto P = s.intersection(L);

        if (P and ans.count(P.value()) == 0) {
            events.push(Event{P.value(), Event::INTERSECTION, s.idx});
            ans.insert(P.value());
        }
    }

    if (next(it) != sl.end()) {
        auto U = *next(it);
        auto P = s.intersection(U);

        if (P and ans.count(P.value()) == 0) {
            events.push(Event{P.value(), Event::INTERSECTION, s.idx});
            ans.insert(P.value());
        }
    }
}

set<Point> bentley_ottman(vector<Segment>& segments) {
    set<Point> ans;
    priority_queue<Event> events;

    for (size_t i = 0; i < segments.size(); ++i) {
        events.push(Event{segments[i].A, Event::OPEN, i});
        events.push(Event{segments[i].B, Event::CLOSE, i});
    }

    set<Segment> sl;

    while (not events.empty()) {
        auto e = events.top();
        events.pop();

        Segment::sweep_x = e.P.x;

        switch (e.type) {
            case Event::OPEN: {
                auto s = segments[e.i];
                sl.insert(s);

                add_neighbor_intersections(s, sl, ans, events);
            } break;

```

```

case Event::CLOSE: {
    auto s = segments[e.i];
    auto it = sl.find(s); // TODO: aqui também

    if (it != sl.begin() and it != sl.end()) {
        auto L = *prev(it);
        auto U = *next(it);
        auto P = L.intersection(U);

        if (P and ans.count(P.value()) == 0)
            events.push(Event{P.value(), Event::INTERSECTION, L.idx});
    }

    sl.erase(it);
} break;

default:
    auto r = segments[e.i];
    auto p = sl.equal_range(r);

    vector<Segment> range(p.first, p.second);

    // Remove os segmentos que se interceptam
    sl.erase(p.first, p.second);

    // Reinsere os segmentos
    Segment::sweep_x += 0.1;

    sl.insert(range.begin(), range.end());

    // Procura interseções com os novos vizinhos
    for (const auto& s : range)
        add_neighbor_intersections(s, sl, ans, events);
}

return ans;
}

```

## 4.26 Triangle

```

template <typename T>
struct Triangle {
    Point<T> A, B, C;

    // Definição do método area()

    // circulo inscrito no triangulo
    double circumradius() const {
        auto a = dist(B, C);
        auto b = dist(A, C);
        auto c = dist(A, B);

        return (a * b * c) / (4 * area());
    }

    Point<T> circumcenter() const {
        auto D = 2 * (A.x * (B.y - C.y) + B.x * (C.y - A.y) + C.x * (A.y - B.y));

```

```

        auto A2 = A.x * A.x + A.y * A.y;
        auto B2 = B.x * B.x + B.y * B.y;
        auto C2 = C.x * C.x + C.y * C.y;

        auto x = (A2 * (B.y - C.y) + B2 * (C.y - A.y) + C2 * (A.y - B.y)) / D;
        auto y = (A2 * (C.x - B.x) + B2 * (A.x - C.x) + C2 * (B.x - A.x)) / D;

        return {x, y};
    }

    // ortocentro do triangulo
    Point<T> orthocenter() const {
        Line<T> r(A, B), s(A, C);

        Line<T> u{r.b, -r.a, -(C.x * r.b - C.y * r.a)};
        Line<T> v{s.b, -s.a, -(B.x * s.b - B.y * s.a)};

        auto det = u.a * v.b - u.b * v.a;
        auto x = (-u.c * v.b + v.c * u.b) / det;
        auto y = (-v.c * u.a + u.c * v.a) / det;

        return {x, y};
    }
};

```

## 5 Graphs

### 5.1 Articulation Points

```

int dfs_num[MAX], dfs_low[MAX];
vi adj[MAX];

int dfs_articulation_points(int u, int p, int& next, set<int>& points) {
    int children = 0;
    dfs_low[u] = dfs_num[u] = next++;

    for (auto v : adj[u])
        if (not dfs_num[v]) {
            ++children;

            dfs_articulation_points(v, u, next, points);

            if (dfs_low[v] >= dfs_num[u]) points.insert(u);

            dfs_low[u] = min(dfs_low[u], dfs_low[v]);
        } else if (v != p)
            dfs_low[u] = min(dfs_low[u], dfs_num[v]);

    return children;
}

set<int> articulation_points(int N) {
    memset(dfs_num, 0, (N + 1) * sizeof(int));
    memset(dfs_low, 0, (N + 1) * sizeof(int));

    set<int> points;

```

```

for (int u = 1, next = 1; u <= N; ++u)
    if (not dfs_num[u]) {
        auto children = dfs_articulation_points(u, u, next, points);

        if (children == 1) points.erase(u);
    }

return points;
}

```

## 5.2 Bellman Ford

Time:  $O(V \cdot E)$ . Returns the shortest path from  $s$  to all other nodes.

```

using edge = tuple<int, int, int>;

pair<vi, vi> bellman_ford(int s, int N, const vector<edge>& edges) {
    vi dist(N + 1, oo), pred(N + 1, oo);

    dist[s] = 0;
    pred[s] = s;

    for (int i = 1; i <= N - 1; i++)
        for (auto [u, v, w] : edges)
            if (dist[u] < oo and dist[v] > dist[u] + w) {
                dist[v] = dist[u] + w;
                pred[v] = u;
            }

    return {dist, pred};
}

```

## 5.3 BFS 0/1

Time:  $O(V + E)$ .

```

vii adj[MAX];

vi bfs_01(int s, int N) {
    vi dist(N + 1, oo);
    dist[s] = 0;

    deque<int> q;
    q.emplace_back(s);

    while (not q.empty()) {
        auto u = q.front();
        q.pop_front();

        for (auto [v, w] : adj[u])
            if (dist[v] > dist[u] + w) {
                dist[v] = dist[u] + w;
                w == 0 ? q.emplace_front(v) : q.emplace_back(v);
            }
    }

    return dist;
}

```

## 5.4 Binary Lifting

Time:  $O(N \cdot \log_2 K)$

```

const int MAXN = 2e5, MAXLOG2 = 60;
int bl[MAXN][MAXLOG2 + 1];

int jump(int u, ll k) {
    for (int i = 0; i <= MAXLOG2; i++)
        if (k & (1LL << i)) u = bl[u][i];

    return u;
}

void build(int N) {
    for (int i = 1; i <= MAXLOG2; i++)
        for (int j = 0; j < N; j++) bl[j][i] = bl[bl[j][i - 1]][i - 1];
}

```

## 5.5 Bridges

```

int dfs_num[MAX], dfs_low[MAX];
vi adj[MAX];

void dfs_bridge(int u, int p, int& next, vii& bridges) {
    dfs_low[u] = dfs_num[u] = next++;

    for (auto v : adj[u])
        if (not dfs_num[v]) {
            dfs_bridge(v, u, next, bridges);

            if (dfs_low[v] > dfs_num[u]) bridges.emplace_back(u, v);

            dfs_low[u] = min(dfs_low[u], dfs_low[v]);
        } else if (v != p)
            dfs_low[u] = min(dfs_low[u], dfs_num[v]);
}

vii bridges(int N) {
    memset(dfs_num, 0, (N + 1) * sizeof(int));
    memset(dfs_low, 0, (N + 1) * sizeof(int));

    vii bridges;

    for (int u = 1, next = 1; u <= N; ++u)
        if (not dfs_num[u]) dfs_bridge(u, u, next, bridges);

    return bridges;
}

```

## 5.6 Negative Cycle Bellman Ford

Time:  $O(V \cdot E)$ . Detects whether there is a negative cycle in the graph using Bellman Ford.

```

using edge = tuple<int, int, int>;

bool has_negative_cycle(int s, int N, const vector<edge>& edges) {
    vi dist(N + 1, oo);

```



```

dist[s] = 0;

for (int i = 1; i <= N - 1; i++)
    for (auto [u, v, w] : edges)
        if (dist[u] < oo and dist[v] > dist[u] + w) dist[v] = dist[u] + w;

for (auto [u, v, w] : edges)
    if (dist[u] < oo and dist[v] > dist[u] + w) return true;

return false;
}

```

## 5.7 Negative Cycle Floyd Warshall

Time:  $O(n^3)$ . Detects whether there is a negative cycle in the graph using Floyd Warshall.

```

int dist[MAX][MAX];
vii adj[MAX];

bool has_negative_cycle(int N) {
    for (int u = 1; u <= N; ++u)
        for (int v = 1; v <= N; ++v) dist[u][v] = u == v ? 0 : oo;

    for (int u = 1; u <= N; ++u)
        for (auto [v, w] : adj[u]) dist[u][v] = w;

    for (int k = 1; k <= N; ++k)
        for (int u = 1; u <= N; ++u)
            for (int v = 1; v <= N; ++v)
                if (dist[u][k] < oo and dist[k][v] < oo)
                    dist[u][v] = min(dist[u][v], dist[u][k] + dist[k][v]);

    for (int i = 1; i <= N; ++i)
        if (dist[i][i] < 0) return true;

    return false;
}

```

## 5.8 Dijkstra

```

pair<vl, vl> Graph::dijkstra(ll src) {
    vl pd(this->N, LLONG_MAX), ds(this->N, LLONG_MAX);
    pd[src] = src;
    ds[src] = 0;

    set<pll> st;
    st.emplace(0, src);

    while (!st.empty()) {
        ll u = st.begin()->snd;
        ll wu = st.begin()->fst;
        st.erase(st.begin());

        if (wu != ds[u]) continue;
        for (auto& [v, w] : adj[u]) {
            if (ds[v] > ds[u] + w) {

```

```

                ds[v] = ds[u] + w;
                pd[v] = u;
                st.emplace(ds[v], v);
            }
        }
    }

    return {ds, pd};
}

```

## 5.9 Dinic

```

#include <bits/stdc++.h>
using namespace std;

using ll = long long;
struct FlowEdge {
    int v, u;
    ll cap, flow = 0;
    FlowEdge(int v, int u, ll cap) : v(v), u(u), cap(cap) {}
};

struct Dinic {
    const ll flow_inf = 1e18;
    vector<FlowEdge> edges;
    vector<vi> adj;
    int n, m = 0;
    int s, t;
    vi level, ptr;
    queue<int> q;

    Dinic(int n, int s, int t) : n(n), s(s), t(t) {
        adj.resize(n);
        level.resize(n);
        ptr.resize(n);
    }

    void add_edge(int v, int u, ll cap) {
        // constroi a aresta e a aresta reversa
        edges.emplace_back(v, u, cap);
        edges.emplace_back(u, v, 0);
        adj[v].push_back(m);
        adj[u].push_back(m + 1);
        m += 2;
    }

    // BFS para construir a arvore
    bool bfs() {
        fill(level.begin(), level.end(), -1);
        level[s] = 0;
        q.push(s);
        while (!q.empty()) {
            int v = q.front();
            q.pop();
            for (int id : adj[v]) {
                if (edges[id].cap - edges[id].flow < 1) continue;
                if (level[edges[id].u] != -1) continue;
                level[edges[id].u] = level[v] + 1;
                q.push(edges[id].u);
            }
        }
    }
};

```

```

    }
}
// se o T não é alcançavel então não existe caminho
return level[t] != -1;
}

// DFS para encontrar um caminho aumentante na arvore
ll dfs(int v, ll pushed) {
    if (pushed == 0) return 0;
    if (v == t) return pushed;
    for (int& cid = ptr[v]; cid < (int)adj[v].size(); cid++) {
        int id = adj[v][cid];
        int u = edges[id].u;
        if (level[v] + 1 != level[u] || edges[id].cap - edges[id].flow < 1)
            continue;
        ll tr = dfs(u, min(pushed, edges[id].cap - edges[id].flow));
        if (tr == 0) continue;
        edges[id].flow += tr;
        edges[id ^ 1].flow -= tr;
        return tr;
    }
    return 0;
}

ll f = 0;
ll flow() {
    // ll f = 0;
    while (true) {
        if (!bfs()) break;
        fill(ptr.begin(), ptr.end(), 0);
        while (ll pushed = dfs(s, flow_inf)) {
            f += pushed;
        }
    }
    return f;
}

// Se rodarmos o bfs denovo podemos encontrar as arestas que estão no corte
// e também os vertices que estão em cada lado.
vii mincut() {
    vii cut;
    bfs();
    for (auto& e : edges) {
        if (e.flow == e.cap && level[e.v] != -1 && level[e.u] == -1 &&
            e.cap > 0) {
            cut.emplace_back(e.v, e.u);
        }
    }
    return cut;
}
};

```

## 5.10 Floyd Warshall

```

vii adj[MAX];

pair<vector<vi>, vector<vi>> floyd_warshall(int N) {
    vector<vi> dist(N + 1, vi(N + 1, oo));
    vector<vi> pred(N + 1, vi(N + 1, oo));

```

```

    for (int u = 1; u <= N; ++u) {
        dist[u][u] = 0;
        pred[u][u] = u;
    }

    for (int u = 1; u <= N; ++u)
        for (auto [v, w] : adj[u]) {
            dist[u][v] = w;
            pred[u][v] = u;
        }

    for (int k = 1; k <= N; ++k) {
        for (int u = 1; u <= N; ++u) {
            for (int v = 1; v <= N; ++v) {
                if (dist[u][k] < oo and dist[k][v] < oo and
                    dist[u][v] > dist[u][k] + dist[k][v]) {
                    dist[u][v] = dist[u][k] + dist[k][v];
                    pred[u][v] = pred[k][v];
                }
            }
        }
    }

    return {dist, pred};
}

```

## 5.11 Graph

```

class Graph {
private:
    ll N;
    bool undirected;
    vector<vll> adj;

public:
    Graph(ll N, bool is_undirected = true) {
        this->N = N;
        adj.resize(N);
        undirected = is_undirected;
    }

    void add(ll u, ll v, ll w) {
        adj[u].emplace_back(v, w);
        if (undirected) adj[v].emplace_back(u, w);
    }
};

```

## 5.12 TopSort - Kahn

Works only on Directed Acyclic Graphs (DAGs). For each edge (u,v), u comes before v in the ordering. If the task A is a prerequisite for task B, then A comes before B in the ordering. Time:  $O(E \cdot \log(v))$

```

unordered_set<int> in[MAX], out[MAX];

vi topological_sort(int N) {
    vi o;
    queue<int> q;

    for (int u = 1; u <= N; ++u)

```

```

    if (in[u].empty()) q.push(u);

    while (not q.empty()) {
        auto u = q.front();
        q.pop();

        o.emplace_back(u);

        for (auto v : out[u]) {
            in[v].erase(u);

            if (in[v].empty()) q.push(v);
        }
    }

    return (int)o.size() == N ? o : vi{};
}

```

### 5.13 Kosaraju

Time:  $O(V + E)$ . Returns a vector of vectors indicating the directed strongly connected nodes.

```

vi adj[MAX], rev[MAX];
bitset<MAX> visited;

void dfs(int u, vi& order) {
    if (visited[u]) return;

    visited[u] = true;

    for (auto v : adj[u]) dfs(v, order);

    order.emplace_back(u);
}

vi dfs_order(int N) {
    vi order;

    for (int u = 1; u <= N; ++u) dfs(u, order);

    return order;
}

void dfs_cc(int u, vi& cc) {
    if (visited[u]) return;

    visited[u] = true;
    cc.emplace_back(u);

    for (auto v : rev[u]) dfs_cc(v, cc);
}

vector<vi> kosaraju(int N) {
    auto order = dfs_order(N);
    reverse(order.begin(), order.end());

    for (int u = 1; u <= N; ++u)
        for (auto v : adj[u]) rev[v].emplace_back(u);
}

```

```

vector<vi> cs;
visited.reset();

for (auto u : order) {
    if (visited[u]) continue;

    cs.emplace_back(vi());
    dfs_cc(u, cs.back());
}

return cs;
}

```

### 5.14 Kruskal

Time:  $O(e \cdot \log(v))$

```

using edge = tuple<int, int, int>;

int kruskal(int N, vector<edge>& es) {
    sort(es.begin(), es.end());

    int cost = 0;
    UnionFind udfs(N);

    for (auto [w, u, v] : es) {
        if (not udfs.same_set(u, v)) {
            cost += w;
            udfs.union_set(u, v);
        }
    }

    return cost;
}

```

### 5.15 Minimax

A MST minimizes the maximum weight between the edges in any spanning tree. Time:  $O(e \cdot \log(v))$

```

vii adj[MAX];

int minimax(int u, int N) {
    set<int> C;
    C.insert(u);

    priority_queue<ii, vii, greater<ii>> pq;

    for (auto [v, w] : adj[u]) pq.push(ii(w, v));

    int minmax = -oo;

    while ((int)C.size() < N) {
        int v, w;

        do {
            w = pq.top().first, v = pq.top().second;

```

```

    pq.pop();
} while (C.count(v));

minmax = max(minmax, w);
C.insert(v);

for (auto [s, p] : adj[v]) pq.push(ii(p, s));
}

return minmax;
}

```

## 5.16 MSF

Minimum Spanning Forest - a forest of trees of length  $k$  that connects all vertices in a graph with minimum total weight. Time:  $O(e \cdot \log(v))$

```

using edge = tuple<int, int, int>;

int msf(int k, int N, vector<edge>& es) {
    sort(es.begin(), es.end());

    int cost = 0, cc = N;
    UnionFind udfs(N);

    for (auto [w, u, v] : es) {
        if (not udfs.same_set(u, v)) {
            cost += w;
            udfs.union_set(u, v);

            if (--cc == k) return cost;
        }
    }

    return cost;
}

```

## 5.17 Minimum Spanning Graph (MSG)

Given some obligatory edges  $es$ , find a minimum spanning graph that contains them. Time:  $O(e \cdot \log(v))$

```

using edge = tuple<int, int, int>;

const int MAX{100010};

vector<ii> adj[MAX];

int msg(int N, const vector<edge>& es) {
    set<int> C;
    priority_queue<ii, vii, greater<ii>> pq;
    int cost = 0;

    for (auto [u, v, w] : es) {
        cost += w;

        C.insert(u);
        C.insert(v);
    }
}

```

```

for (auto [r, s] : adj[u]) pq.push(ii(s, r));

for (auto [r, s] : adj[v]) pq.push(ii(s, r));
}

while ((int)C.size() < N) {
    int v, w;

    do {
        w = pq.top().first, v = pq.top().second;
        pq.pop();
    } while (C.count(v));

    cost += w;
    C.insert(v);

    for (auto [s, p] : adj[v]) pq.push(ii(p, s));
}

return cost;
}

```

## 5.18 Prim

A node  $u$  is chosen to start a connected component. Time:  $O(e \cdot \log(v))$

```

const int MAX{100010};

vector<ii> adj[MAX];

int prim(int u, int N) {
    set<int> C;
    C.insert(u);

    priority_queue<ii, vector<ii>, greater<ii>> pq;

    for (auto [v, w] : adj[u]) pq.push(ii(w, v));

    int mst = 0;

    while ((int)C.size() < N) {
        int v, w;

        do {
            w = pq.top().first, v = pq.top().second;
            pq.pop();
        } while (C.count(v));

        mst += w;
        C.insert(v);

        for (auto [s, p] : adj[v]) pq.push(ii(p, s));
    }

    return mst;
}

```

## 5.19 Retrieve Path 2d

```
vll Graph::retrieve_path_2d(ll src, ll trg, const vector<vl>& pred) {
    vll p;

    do {
        p.emplace_back(pred[src][trg], trg);
        trg = pred[src][trg];
    } while (trg != src);

    reverse(all(p));

    return p;
}
```

## 5.20 Retrieve Path

```
vll Graph::retrieve_path(ll src, ll trg, const vl& pred) {
    vll p;

    do {
        p.emplace_back(pred[trg], trg);
        trg = pred[trg];
    } while (trg != src);

    reverse(all(p));

    return p;
}
```

## 5.21 Second Best MST

Time:  $O(v \cdot e)$

```
using edge = tuple<int, int, int>;

pair<int, vi> kruskal(int N, vector<edge>& es, int blocked = -1) {
    vi mst;
    UnionFind udfs(N);
    int cost = 0;

    for (int i = 0; i < (int)es.size(); ++i) {
        auto [w, u, v] = es[i];

        if (i != blocked and not udfs.same_set(u, v)) {
            cost += w;
            udfs.union_set(u, v);
            mst.emplace_back(i);
        }
    }

    return {(int)mst.size() == N - 1 ? cost : oo, mst};
}

int second_best(int N, vector<edge>& es) {
    sort(es.begin(), es.end());

    auto [_, mst] = kruskal(N, es);
    int best = oo;
```

```
    for (auto blocked : mst) {
        auto [cost, __] = kruskal(N, es, blocked);
        best = min(best, cost);
    }

    return best;
}
```

## 5.22 TopSort - Tarjan

Works only on Directed Acyclic Graphs (DAGs). For each edge (u,v), u comes before v in the ordering. If the task A is a prerequisite for task B, then A comes before B in the ordering. Time:  $O(V + E)$

```
enum State { NOT_FOUND, FOUND, PROCESSED };

vi adj[MAX];

bool dfs(int u, vi& o, vi& state) {
    if (state[u] == PROCESSED) return true;

    if (state[u] == FOUND) return false;

    state[u] = FOUND;

    for (auto v : adj[u])
        if (not dfs(v, o, state)) return false;

    state[u] = PROCESSED;
    o.emplace_back(u);

    return true;
}

vi topological_sort(int N) {
    vi o, state(N + 1, NOT_FOUND);

    for (int u = 1; u <= N; ++u)
        if (state[u] == NOT_FOUND and not dfs(u, o, state)) return {};

    reverse(o.begin(), o.end());

    return o;
}
```

# 6 Math

## 6.1 Binomial

```
ll binom(ll n, ll k) {
    if (k > n) return 0;
    vll dp(k + 1, 0);
    dp[0] = 1;
    for (ll i = 1; i <= n; i++)
        for (ll j = k; j > 0; j--) dp[j] = dp[j] + dp[j - 1];
```

```
    return dp[k];
}
```

## 6.2 Count Divisors Range

```
vl divisors(MAX, 0);
void count_divisors_range() {
    for (ll i = 1; i <= MAX; i++) {
        for (ll j = 1; j * i <= MAX; j++) divisors[i * j]++;
    }
}
```

## 6.3 Count Divisors

```
ll count_divisors(ll num) {
    ll count = 1;
    for (int i = 2; (ll)i * i <= num; i++) {
        if (num % i == 0) {
            int e = 0;
            do {
                e++;
                num /= i;
            } while (num % i == 0);
            count *= e + 1;
        }
    }
    if (num > 1) {
        count *= 2;
    }
    return count;
}
```

## 6.4 Factorization With Sieve

```
map<ll, ll> factorization_with_sieve(ll n, const vl& primes) {
    map<ll, ll> fact;

    for (ll d : primes) {
        if (d * d > n) break;

        ll k = 0;
        while (n % d == 0) {
            k++;
            n /= d;
        }

        if (k) fact[d] = k;
    }

    if (n > 1) fact[n] = 1;
    return fact;
}
```

## 6.5 Factorization

```
map<ll, ll> factorization(ll n) {
    map<ll, ll> ans;
```

```
    for (ll i = 2; i * i <= n; i++) {
        ll count = 0;
        for (; n % i == 0; count++, n /= i)
            ;
        if (count) ans[i] = count;
    }
    if (n > 1) ans[n]++;
    return ans;
}
```

## 6.6 Fast Doubling - Fibonacci

The Doubling Method can be seen as an improvement to the matrix exponentiation method to find the  $N$ -th Fibonacci number.

Time:  $O(\log N)$ .

```
template <typename T>
class FastDoubling {
public:
    vector<T> sts;
    T a, b, c, d;
    int mod;

    FastDoubling(int mod = 1e9 + 7) : sts(2), mod(mod) {}

    T fib(T x) {
        fill(all(sts), 0);
        a = 0, b = 0, c = 0, d = 0;
        fast_doubling(x, sts);
        return sts[0];
    }

    void fast_doubling(T n, vector<T>& res) {
        if (n == 0) {
            res[0] = 0;
            res[1] = 1;
            return;
        }
        fast_doubling(n >> 1, res);

        a = res[0];
        b = res[1];
        c = (b << 1) - a;

        if (c < 0) c += mod;

        c = (a * c) % mod;
        d = (a * a + b * b) % mod;
        if (n & 1) {
            res[0] = d;
            res[1] = c + d;
        } else {
            res[0] = c;
            res[1] = d;
        }
    }
};
```

## 6.7 Fast Exp Iterative

```
11 fast_exp_it(11 a, 11 n, 11 mod = LLONG_MAX) {
    a %= mod;
    11 res = 1;

    while (n) {
        if (n & 1) (res *= a) %= mod;

        (a *= a) %= mod;
        n >>= 1;
    }

    return res;
}
```

## 6.8 Fast Exp

```
11 fast_exp(11 a, 11 n, 11 mod = LLONG_MAX) {
    if (n == 0) return 1;
    if (n == 1) return a;

    11 x = fast_exp(a, n / 2, mod) % mod;

    return ((x * x) % mod * (n & 1 ? a : 111)) % mod;
}
```

## 6.9 Fast Fourier Transform (FFT)

Time:  $O(N \cdot \log N)$

```
using cd = complex<double>;
const double PI = acos(-1);

void fft(vector<cd>& a, bool invert) {
    int n = a.size();

    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1) j ^= bit;
        j ^= bit;

        if (i < j) swap(a[i], a[j]);
    }

    for (int len = 2; len <= n; len <<= 1) {
        double ang = 2 * PI / len * (invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for (int i = 0; i < n; i += len) {
            cd w(1);
            for (int j = 0; j < len / 2; j++) {
                cd u = a[i + j], v = a[i + j + len / 2] * w;
                a[i + j] = u + v;
                a[i + j + len / 2] = u - v;
                w *= wlen;
            }
        }
    }
}
```

```
if (invert) {
    for (cd& x : a) x /= n;
}

void fft_2d(vector<vector<cd>>& V, bool invert) {
    for (int i = 0; i < V.size(); i++) fft(V[i], invert);
    for (int i = 0; i < V.front().size(); i++) {
        vector<cd> col(V.size());
        for (int k = 0; k < V.size(); k++) col[k] = V[k][i];
        fft(col, invert);
        for (int k = 0; k < V.size(); k++) V[k][i] = col[k];
    }
}
```

## 6.10 GCD

The Euclidean algorithm allows to find the greatest common divisor of two numbers  $a$  and  $b$  in  $O(\log \cdot \min(a, b))$ .

```
11 gcd(11 a, 11 b) { return b ? gcd(b, a % b) : a; }
```

## 6.11 Integer Mod

```
const 11 INF = 1e18;
const 11 mod = 998244353;
template <11 MOD = mod>

struct Modular {
    11 value;
    static const 11 MOD_value = MOD;

    Modular(11 v = 0) {
        value = v % MOD;
        if (value < 0) value += MOD;
    }
    Modular(11 a, 11 b) : value(0) {
        *this += a;
        *this /= b;
    }

    Modular& operator+=(Modular const& b) {
        value += b.value;
        if (value >= MOD) value -= MOD;
        return *this;
    }
    Modular& operator-=(Modular const& b) {
        value -= b.value;
        if (value < 0) value += MOD;
        return *this;
    }
    Modular& operator*=(Modular const& b) {
        value = (11)value * b.value % MOD;
        return *this;
    }
}
```

```

friend Modular mexp(Modular a, ll e) {
    Modular res = 1;
    while (e) {
        if (e & 1) res *= a;
        a *= a;
        e >>= 1;
    }
    return res;
}

friend Modular inverse(Modular a) { return mexp(a, MOD - 2); }

Modular& operator/=(Modular const& b) { return *this *= inverse(b); }
friend Modular operator+(Modular a, Modular const b) { return a += b; }
Modular operator++(int) { return this->value = (this->value + 1) % MOD; }
Modular operator++() { return this->value = (this->value + 1) % MOD; }
friend Modular operator-(Modular a, Modular const b) { return a -= b; }
friend Modular operator-(Modular const a) { return 0 - a; }
Modular operator--(int) {
    return this->value = (this->value - 1 + MOD) % MOD;
}

Modular operator--() { return this->value = (this->value - 1 + MOD) % MOD; }
friend Modular operator*(Modular a, Modular const b) { return a *= b; }
friend Modular operator/(Modular a, Modular const b) { return a /= b; }
friend std::ostream& operator<<(std::ostream& os, Modular const& a) {
    return os << a.value;
}

friend bool operator==(Modular const& a, Modular const& b) {
    return a.value == b.value;
}

friend bool operator!=(Modular const& a, Modular const& b) {
    return a.value != b.value;
}
};

```

## 6.12 Is prime

$O(\sqrt{N})$

```

bool isprime(ll n) {
    if (n < 2) return false;
    if (n == 2) return true;
    if (n % 2 == 0) return false;
    for (ll i = 3; i * i <= n; i += 2)
        if (n % i == 0) return false;
    return true;
}

```

## 6.13 LCM

Calculating the least common multiple (commonly denoted LCM) can be reduced to calculating the GCD with the following simple formula:  $\text{lcm}(a, b) = (a \cdot b) / \text{gcd}(a, b)$

Thus, LCM can be calculated using the Euclidean algorithm with the same time complexity:

```

ll lcm(ll a, ll b) { return a / gcd(a, b) * b; }

```

## 6.14 Euler phi $\varphi(n)$

Computes the number of positive integers less than  $n$  that are co-primes with  $n$ , in  $O(\sqrt{N})$ .

```

ll phi(ll n) {
    if (n == 1) return 1;

    auto fs = factorization(n);
    auto res = n;

    for (auto [p, k] : fs) {
        res /= p;
        res *= (p - 1);
    }

    return res;
}

```

## 6.15 Sieve

```

vl sieve(ll N) {
    bitset<MAX + 1> sieve;
    vl ps{2, 3};
    sieve.set();

    for (ll i = 5, step = 2; i <= N; i += step, step = 6 - step) {
        if (sieve[i]) {
            ps.push_back(i);

            for (ll j = i * i; j <= N; j += 2 * i) sieve[j] = false;
        }
    }
    return ps;
}

```

## 6.16 Sum Divisors

```

ll sum_divisors(ll num) {
    ll result = 1;

    for (int i = 2; (ll)i * i <= num; i++) {
        if (num % i == 0) {
            int e = 0;
            do {
                e++;
                num /= i;
            } while (num % i == 0);

            ll sum = 0, pow = 1;
            do {
                sum += pow;
                pow *= i;
            } while (e-- > 0);
            result *= sum;
        }
    }
    if (num > 1) {

```



```

    result *= (1 + num);
}
return result;
}

```

## 6.17 Sum of difference

Function to calculate sum of absolute difference of all pairs in array:  $\frac{1}{2} \sum_{i=1}^N \sum_{j=1}^N |A_i - A_j|$

```

11 sum_of_difference(v1& arr, 11 n) {
    sort(all(arr));

    11 sum = 0;
    for (11 i = 0; i < n; i++) {
        sum += i * arr[i] - (n - 1 - i) * arr[i];
    }

    return sum;
}

```

## 7 Problems

### 7.1 Kth Digit String (CSES)

Time:  $O(\log_{10} K)$ .

Space:  $O(1)$ .

```

11 kth_digit_string(11 k) {
    if (k < 10) return k;

    11 c = 180, i = 2, u = 10, r = 0, ans = -1, m;
    for (k -= 9; k > c; i++, u *= 10) {
        k -= c;
        c /= i;
        c *= 10 * (i + 1);
    }

    if ((m = k % i))
        r++;
    else
        m = i;

    11 tmp = (k / i) + r + u - 1;
    for (m = i + 1 - m; m--; tmp /= 10) ans = tmp % 10;

    return ans;
}

```

### 7.2 Longest Common Substring (LONGCS - SPOJ)

Time:  $N = \sum_{i=1}^k |S_i|$ ;  $O(N \cdot \log N)$

```

int lcs_ks_strings(vector<string>& sts, int k) {
    vector<int> fml;
    string t;
    for (int i = 0; i < k; i++) {
        t += sts[i];
    }
}

```

```

    for (int j = 0; j < sts[i].size(); j++) fml.push_back(i);
}

suffix_array sf(t);
sf.lcp.insert(sf.lcp.begin(), 0);

int l = 0, r = 0, cnt = 0, lcs = 0, n = sf.sa.size();
vector<int> fr(k + 1);
multiset<int> mst;
while (l < n) {
    while (r < n and cnt < k) {
        mst.insert(sf.lcp[r]);
        if (!fr[fml[sf.sa[r]]]++) cnt++;
        r++;
    }
    mst.erase(mst.find(sf.lcp[l]));
    if (mst.size() and cnt == k) lcs = max(lcs, *mst.begin());
    fr[fml[sf.sa[l]]]--;
    if (!fr[fml[sf.sa[l]]]) cnt--;
    l++;
}

return lcs;
}

```

### 7.3 Substring Order II (CSES)

Time:  $O(M)$

$M = 2 \cdot N - 1$

$N = |S|$

```

// ALLOWS REPETITIONS
string kth_smallest_substring(const string& s, 11 k) {
    /* uses /strings/suffix-automaton.cpp
    add 'cnt' and 'nmb' to state struct with (0, -1);
    => for new states 'not cloned': cnt = 1

    create 'order' vector to iterate by length in decreasing
    vector<pair<int, int>>: {len, id}
    => for each new state add to 'order' vector

    to do not allow repetitions:
    => remove: kth+=s.size, sort(order) for(1, p : order)
    => add: st[clone].cnt = 1 (sa_extend)
    */
    string ans;
    k += s.size();
    SuffixAutomaton sa(s);

    sort(all(order), greater<pair<int, int>>());
    // count and mark how many times a substring of a state occurs
    for (auto& [l, p] : order) sa.st[sa.st[p].link].cnt += sa.st[p].cnt;

    auto dfs = [&](auto&& self, int u) {
        if (sa.st[u].nmb != -1) return;

        sa.st[u].nmb = sa.st[u].cnt;
        for (int i = 0; i < 26; ++i) {

```

```

        if (sa.st[u].next[i]) {
            self(self, sa.st[u].next[i]);
            sa.st[u].cnt += sa.st[sa.st[u].next[i]].cnt;
        }
    }
};
dfs(dfs, 0);

int u = 0;
while (sa.st[u].nmb < k) {
    k -= sa.st[u].nmb;
    for (int i = 0; i < 26; i++) {
        if (sa.st[u].next[i]) {
            int v = sa.st[u].next[i];
            if (sa.st[v].cnt < k)
                k -= sa.st[v].cnt;
            else {
                ans.push_back(i + 'a');
                u = v;
                break;
            }
        }
    }
}

return ans;
}

```

## 8 Strings

### 8.1 Aho-Corasick

The Aho-Corasick algorithm allows us to quickly search for multiple patterns in a text. The set of pattern strings is also called a *dictionary*. We will denote the total length of its constituent strings by  $m$  and the size of the alphabet by  $k$ .

build:  $O(m \cdot k)$

occurrences:  $O(|s| + ans)$

```

const int K = 26;
struct Vertex {
    char pch;
    int next[K];
    bool check = false;
    int p = -1, lnk = -1, out = -1, ps = -1, d = 0;

    Vertex(int p = -1, char ch = '$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
    }
};

class AhoCorasick {
public:
    int sz = 0; // number of strings added
    vector<Vertex> t;

    AhoCorasick() : t(1) {}
}

```

```

void add_string(string const& s) {
    int v = 0, ds = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (t[v].next[c] == -1) {
            t[v].next[c] = t.size();
            t.emplace_back(v, ch);
        }
        v = t[v].next[c];
        t[v].d += ds;
    }
    t[v].check = true;
    t[v].ps = sz++;
}

void build() {
    queue<int> qs;
    qs.push(0);
    while (qs.size()) {
        auto u = qs.front();
        qs.pop();

        if (!t[u].p || t[u].p == -1)
            t[u].lnk = 0;
        else {
            int k = t[t[u].p].lnk;
            int c = t[u].pch - 'a';
            while (t[k].next[c] == -1 && k) k = t[k].lnk;
            int ts = t[k].next[c];
            if (ts == -1)
                t[u].lnk = 0;
            else
                t[u].lnk = ts;
        }

        if (t[t[u].lnk].check)
            t[u].out = t[u].lnk;
        else
            t[u].out = t[t[u].lnk].out;

        for (auto v : t[u].next)
            if (v != -1) qs.push(v);
    }
}

void occurrences(string const& s, vector<vector<int>>& res) {
    // to just "count" replace 'res' vector with an int
    res.resize(sz);
    for (int i = 0, v = 0; i < s.size(); i++) {
        int c = s[i] - 'a';
        while (t[v].next[c] == -1 && v) v = t[v].lnk;
        int ts = t[v].next[c];
        if (ts == -1)
            continue;
        else
            v = t[v].next[c];

        int k = v;
    }
}

```

```

    while (t[k].out != -1) {
        k = t[k].out;
        res[t[k].ps].emplace_back(i - t[k].d + 1);
    }
    if (t[v].check) res[t[v].ps].emplace_back(i - t[v].d + 1);
}
}
};

```

## 8.2 Edit Distance

Returns the minimum number of operations (insert, delete, replace) to transform string  $a$  into string  $b$ .  
Time:  $O(M * N)$

```

int min_value(int x, int y, int z) { return min(min(x, y), z); }

int edit_distance(string str1, string str2) {
    int n = (int)str1.size(), m = (int)str2.size();
    int dp[m + 1][n + 1];

    for (int i = 0; i <= m; i++)
        for (int j = 0; j <= n; j++)
            if (i == 0)
                dp[i][j] = j;
            else if (j == 0)
                dp[i][j] = i;
            else if (str1[i - 1] == str2[j - 1])
                dp[i][j] = dp[i - 1][j - 1];
            else
                dp[i][j] = 1 + min_value(dp[i][j - 1], dp[i - 1][j], dp[i - 1][j - 1]);

    return dp[m][n];
}

```

## 8.3 LCP with Suffix Array

For a given string  $s$  we want to compute the longest common prefix (LCP) of two arbitrary suffixes with position  $i$  and  $j$ . In fact, let the request be to compute the LCP of the suffixes  $p[i]$  and  $p[j]$ . Then the answer to this query will be  $\min(lcp[i], lcp[i + 1], \dots, lcp[j - 1])$ . Thus the problem is reduced to the RMQ.  
Time:  $O(N)$ .

```

vector<int> lcp_suffix_array(string const& s, vector<int> const& p) {
    int n = s.size();
    vector<int> rank(n, 0);
    for (int i = 0; i < n; i++) rank[p[i]] = i;

    int k = 0;
    vector<int> lcp(n - 1, 0);
    for (int i = 0; i < n; i++) {
        if (rank[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = p[rank[i] + 1];
        while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
        lcp[rank[i]] = k;
    }
}

```

```

    if (k) k--;
}
return lcp;
}

```

## 8.4 Manacher

Given string  $s$  with length  $n$ . Find all the pairs  $(i, j)$  such that substring  $s[i \dots j]$  is a palindrome. String  $t$  is a palindrome when  $t = t_{rev}$  ( $t_{rev}$  is a reversed string for  $t$ ).

Time:  $O(N)$

```

vi manacher(string s) {
    string t;
    for (auto c : s) t += string("#") + c;
    t = t + '#';

    int n = t.size();
    t = "$" + t + "^";

    vi p(n + 2);
    int l = 1, r = 1;
    for (int i = 1; i <= n; i++) {
        p[i] = max(0, min(r - i, p[l + (r - i)]));
        while (t[i - p[i]] == t[i + p[i]]) p[i]++;
        if (i + p[i] > r) {
            l = i - p[i], r = i + p[i];
        }
        p[i]--;
    }

    return vi(begin(p) + 1, end(p) - 1);
}

```

## 8.5 Rabin Karp

```

vector<int> rabin_karp(string const& s, string const& t) {
    const int p = 31;
    const int m = 1e9 + 9;
    int S = s.size(), T = t.size();

    vector<long long> p_pow(max(S, T));
    p_pow[0] = 1;
    for (int i = 1; i < (int)p_pow.size(); i++) p_pow[i] = (p_pow[i - 1] * p) % m;

    vector<long long> h(T + 1, 0);
    for (int i = 0; i < T; i++)
        h[i + 1] = (h[i] + (t[i] - 'a' + 1) * p_pow[i]) % m;
    long long h_s = 0;
    for (int i = 0; i < S; i++) h_s = (h_s + (s[i] - 'a' + 1) * p_pow[i]) % m;

    vector<int> occurrences;
    for (int i = 0; i + S - 1 < T; i++) {
        long long cur_h = (h[i + S] + m - h[i]) % m;
        if (cur_h == h_s * p_pow[i] % m) occurrences.push_back(i);
    }
}

```

```

    return occurrences;
}

```

## 8.6 Suffix Array Optimized - $O(n)$

Suffix Array: sa  
Rank for LCP: rnk  
LCP: lcp  
Time:  $O(N)$ .

```

// @brunomaletta
struct suffix_array {
    string s;
    int n;
    vector<int> sa, cnt, rnk, lcp;
    rmq<int> RMQ; // /data-structures/rmq.cpp

    bool cmp(int a1, int b1, int a2, int b2, int a3 = 0, int b3 = 0) {
        return a1 != b1 ? a1 < b1 : (a2 != b2 ? a2 < b2 : a3 < b3);
    }

    template <typename T>
    void radix(int* fr, int* to, T* r, int N, int k) {
        cnt = vector<int>(k + 1, 0);
        for (int i = 0; i < N; i++) cnt[r[fr[i]]]++;
        for (int i = 1; i <= k; i++) cnt[i] += cnt[i - 1];
        for (int i = N - 1; i >= 0; i--) to[--cnt[r[fr[i]]]] = fr[i];
    }

    void rec(vector<int>& v, int k) {
        auto &tmp = rnk, &m0 = lcp;
        int N = v.size() - 3, sz = (N + 2) / 3, sz2 = sz + N / 3;
        vector<int> R(sz2 + 3);
        for (int i = 1, j = 0; j < sz2; i += i % 3) R[j++] = i;

        radix(&R[0], &tmp[0], &v[0] + 2, sz2, k);
        radix(&tmp[0], &R[0], &v[0] + 1, sz2, k);
        radix(&R[0], &tmp[0], &v[0] + 0, sz2, k);

        int dif = 0;
        int l0 = -1, l1 = -1, l2 = -1;
        for (int i = 0; i < sz2; i++) {
            if (v[tmp[i]] != l0 or v[tmp[i] + 1] != l1 or v[tmp[i] + 2] != l2)
                l0 = v[tmp[i]], l1 = v[tmp[i] + 1], l2 = v[tmp[i] + 2], dif++;
            if (tmp[i] % 3 == 1)
                R[tmp[i] / 3] = dif;
            else
                R[tmp[i] / 3 + sz] = dif;
        }

        if (dif < sz2) {
            rec(R, dif);
            for (int i = 0; i < sz2; i++) R[sa[i]] = i + 1;
        } else
            for (int i = 0; i < sz2; i++) sa[R[i] - 1] = i;

        for (int i = 0, j = 0; j < sz2; i++)
            if (sa[i] < sz) tmp[j++] = 3 * sa[i];
    }
}

```

```

radix(&tmp[0], &m0[0], &v[0], sz, k);
for (int i = 0; i < sz2; i++)
    sa[i] = sa[i] < sz ? 3 * sa[i] + 1 : 3 * (sa[i] - sz) + 2;

int at = sz2 + sz - 1, p = sz - 1, p2 = sz2 - 1;
while (p >= 0 and p2 >= 0) {
    if ((sa[p2] % 3 == 1 and
        cmp(v[m0[p]], v[sa[p2]], R[m0[p] / 3], R[sa[p2] / 3 + sz])) or
        (sa[p2] % 3 == 2 and
        cmp(v[m0[p]], v[sa[p2]], v[m0[p] + 1], v[sa[p2] + 1],
            R[m0[p] / 3 + sz], R[sa[p2] / 3 + 1])))
        sa[at--] = sa[p2--];
    else
        sa[at--] = m0[p--];
}
while (p >= 0) sa[at--] = m0[p--];
if (N % 3 == 1)
    for (int i = 0; i < N; i++) sa[i] = sa[i + 1];
}

suffix_array(const string& s_)
: s(s_), n(s.size()), sa(n + 3), cnt(n + 1), rnk(n), lcp(n - 1) {
    vector<int> v(n + 3);
    for (int i = 0; i < n; i++) v[i] = i;
    radix(&v[0], &rnk[0], &s[0], n, 256);
    int dif = 1;
    for (int i = 0; i < n; i++)
        v[rnk[i]] = dif += (i and s[rnk[i]] != s[rnk[i] - 1]);
    if (n >= 2) rec(v, dif);
    sa.resize(n);

    for (int i = 0; i < n; i++) rnk[sa[i]] = i;
    for (int i = 0, k = 0; i < n; i++, k -= !!k) {
        if (rnk[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = sa[rnk[i] + 1];
        while (i + k < n and j + k < n and s[i + k] == s[j + k]) k++;
        lcp[rnk[i]] = k;
    }
    RMQ = rmq<int>(lcp);
}

int query(int i, int j) {
    if (i == j) return n - i;
    i = rnk[i], j = rnk[j];
    return RMQ.query(min(i, j), max(i, j) - 1);
}
};

```

## 8.7 Suffix Array

Let  $s$  be a string of length  $n$ . The  $i$ -th suffix of  $s$  is the substring  $s[i \dots n - 1]$ .

A suffix array will contain integers that represent the starting indexes of the all the suffixes of a given string, after the aforementioned suffixes are sorted.

Time:  $O(N \log N)$ .

```

vector<int> sort_cyclic_shifts(string const& s) {
    int n = s.size();
    const int alphabet = 128;

    vector<int> p(n), c(n), cnt(max(alphabet, n), 0);
    for (int i = 0; i < n; i++) cnt[s[i]]++;
    for (int i = 1; i < alphabet; i++) cnt[i] += cnt[i - 1];
    for (int i = 0; i < n; i++) p[--cnt[s[i]]] = i;
    c[p[0]] = 0;
    int classes = 1;
    for (int i = 1; i < n; i++) {
        if (s[p[i]] != s[p[i - 1]]) classes++;
        c[p[i]] = classes - 1;
    }

    vector<int> pn(n), cn(n);
    for (int h = 0; (1 << h) < n; ++h) {
        for (int i = 0; i < n; i++) {
            pn[i] = p[i] - (1 << h);
            if (pn[i] < 0) pn[i] += n;
        }
        fill(cnt.begin(), cnt.begin() + classes, 0);
        for (int i = 0; i < n; i++) cnt[c[pn[i]]]++;
        for (int i = 1; i < classes; i++) cnt[i] += cnt[i - 1];
        for (int i = n - 1; i >= 0; i--) p[--cnt[c[pn[i]]]] = pn[i];
        cn[p[0]] = 0;
        classes = 1;
        for (int i = 1; i < n; i++) {
            pair<int, int> cur = {c[p[i]], c[(p[i] + (1 << h)) % n]};
            pair<int, int> prev = {c[p[i - 1]], c[(p[i - 1] + (1 << h)) % n]};
            if (cur != prev) ++classes;
            cn[p[i]] = classes - 1;
        }
        c.swap(cn);
    }

    return p;
}

vector<int> suffix_array(string s) {
    s += "$";
    vector<int> p = sort_cyclic_shifts(s);
    p.erase(p.begin());
    return p;
}

```

## 8.8 Suffix Automaton

```

class SuffixAutomaton {
public:
    struct state {
        int len, link;
        array<int, 26> next;
    };

    vector<state> st;
    int sz = 0, last;

```

```

    SuffixAutomaton(const string& s) : st(s.size() << 1) {
        sa_init();
        for (auto v : s) sa_extend((int)(v - 'a'));
    }

    void sa_init() {
        st[0].len = 0;
        st[0].link = -1;
        sz++;
        last = 0;
    }

    void sa_extend(int c) {
        int cur = sz++;
        st[cur].len = st[last].len + 1;
        int p = last;
        while (p != -1 && !st[p].next[c]) {
            st[p].next[c] = cur;
            p = st[p].link;
        }
        if (p == -1)
            st[cur].link = 0;
        else {
            int q = st[p].next[c];
            if (st[p].len + 1 == st[q].len)
                st[cur].link = q;
            else {
                int clone = sz++;
                st[clone].len = st[p].len + 1;
                st[clone].link = st[q].link;
                st[clone].next = st[q].next;
                while (p != -1 && st[p].next[c] == q) {
                    st[p].next[c] = clone;
                    p = st[p].link;
                }
                st[q].link = st[cur].link = clone;
            }
        }
        last = cur;
    }

    // longest common substring O(N)
    int lcs(const string& T) {
        int v = 0, l = 0, best = 0;
        for (int i = 0; i < T.size(); i++) {
            while (v && !st[v].next[T[i] - 'a']) {
                v = st[v].link;
                l = st[v].len;
            }
            if (st[v].next[T[i] - 'a']) {
                v = st[v].next[T[i] - 'a'];
                l++;
            }
            best = max(best, l);
        }
        return best;
    }
}

```

```
};
```

## 8.9 Suffix Tree (CP Algo - freopen)

Build:  $O(N)$

Memory:  $O(N \cdot k)$

$k$  = alphabet length

```
const int aph = 27; // add $ to final of string
const int N = 2e5 + 31;
class SuffixTree {
public:
    string a;
    vector<array<int, aph>> t;
    vector<int> l, r, p, s, dst;
    int tv, tp, ts, la, b;

    SuffixTree(const string& str, char bs = 'a') : a(str), t(N), l(N),
        r(N, str.size() - 1), p(N), s(N), dst(N), b(bs) {
        build();
    }

    void ukkadd(int c) {
        suff:;
        if (r[tv] < tp) {
            if (t[tv][c] == -1) {
                t[tv][c] = ts; l[ts] = la;
                p[ts++] = tv; tv = s[ts]; tp = r[ts] + 1; goto suff;
            }
            tv = t[ts][c]; tp = l[ts];
        }
        if (tp == -1 || c == a[tp] - b) tp++; else {
            l[ts + 1] = la; p[ts + 1] = ts;
            l[ts] = l[ts]; r[ts] = tp - 1; p[ts] = p[ts];
            t[ts][c] = ts + 1; t[ts][a[tp] - b] = tv; l[ts] = tp;
            p[ts] = ts; t[p[ts]][a[l[ts]] - b] = ts; ts += 2;
            tv = s[p[ts - 2]]; tp = l[ts - 2];
            while (tp <= r[ts - 2]) {
                tv = t[ts][a[tp] - b];
                tp += r[ts] - l[ts] + 1;
            }
            if (tp == r[ts - 2] + 1) s[ts - 2] = tv; else s[ts - 2] = ts;
            tp = r[ts] - (tp - r[ts - 2]) + 2; goto suff;
        }
    }

    void build() {
        ts = 2; tv = 0; tp = 0;
        s[0] = 1; l[0] = -1; r[0] = -1; l[1] = -1; r[1] = -1;
        for (auto& arr : t) { arr.fill(-1); } t[1].fill(0);
        for (la = 0; la < (int)a.size(); ++la) ukkadd(a[la] - b);
    }
};
```

## 8.10 Z Function

Suppose we are given a string  $s$  of length  $n$ . The Z-function for this string is an array of length  $n$  where the  $i$ -th element is equal to the greatest number of characters starting from the position  $i$  that coincide with the

first characters of  $s$ .

Time:  $O(N)$

```
vector<int> z_function(string s) {
    int n = s.size();
    vector<int> z(n);
    int l = 0, r = 0;
    for (int i = 1; i < n; i++) {
        if (i < r) {
            z[i] = min(r - i, z[i - l]);
        }
        while (i + z[i] < n && s[z[i]] == s[i + z[i]]) {
            z[i]++;
        }
        if (i + z[i] > r) {
            l = i;
            r = i + z[i];
        }
    }
    return z;
}
```

## 9 Trees

### 9.1 LCA Binary Lifting (CP Algo)

The algorithm described will need  $O(N \cdot \log N)$  for preprocessing the tree, and then  $O(\log N)$  for each LCA query.

```
ll n, l;
vector<ll> adj[MAX];

ll timer;
vector<ll> tin, tout;
vector<vector<ll>> up;

void dfs(ll v, ll p) {
    tin[v] = ++timer;
    up[v][0] = p;
    for (ll i = 1; i <= l; ++i) up[v][i] = up[up[v][i - 1]][i - 1];

    for (ll u : adj[v]) {
        if (u != p) dfs(u, v);
    }

    tout[v] = ++timer;
}

bool is_ancestor(ll u, ll v) { return tin[u] <= tin[v] && tout[u] >= tout[v]; }

ll lca(ll u, ll v) {
    if (is_ancestor(u, v)) return u;
    if (is_ancestor(v, u)) return v;
    for (ll i = l; i >= 0; --i) {
        if (!is_ancestor(up[u][i], v)) u = up[u][i];
    }
}
```

```

    return up[u][0];
}

void preprocess(ll root) {
    tin.resize(n);
    tout.resize(n);
    timer = 0;
    l = ceil(log2(n));
    up.assign(n, vector<ll>(l + 1));
    dfs(root, root);
}

```

## 9.2 LCA SegTree (CP Algo)

The algorithm can answer each query in  $O(\log N)$  with preprocessing in  $O(N)$  time.

```

struct LCA {
    vector<ll> height, euler, first, segtree;
    vector<bool> visited;
    ll n;

    LCA(vector<vector<ll>>& adj, ll root = 0) {
        n = adj.size();
        height.resize(n);
        first.resize(n);
        euler.reserve(n * 2);
        visited.assign(n, false);
        dfs(adj, root);
        ll m = euler.size();
        segtree.resize(m * 4);
        build(1, 0, m - 1);
    }

    void dfs(vector<vector<ll>>& adj, ll node, ll h = 0) {
        visited[node] = true;
        height[node] = h;
        first[node] = euler.size();
        euler.push_back(node);
        for (auto to : adj[node]) {
            if (!visited[to]) {
                dfs(adj, to, h + 1);
                euler.push_back(node);
            }
        }
    }

    void build(ll node, ll b, ll e) {
        if (b == e) {
            segtree[node] = euler[b];
        } else {
            ll mid = (b + e) / 2;
            build(node << 1, b, mid);
            build(node << 1 | 1, mid + 1, e);
            ll l = segtree[node << 1], r = segtree[node << 1 | 1];
            segtree[node] = (height[l] < height[r]) ? l : r;
        }
    }
}

```

```

ll query(ll node, ll b, ll e, ll L, ll R) {
    if (b > R || e < L) return -1;
    if (b >= L && e <= R) return segtree[node];
    ll mid = (b + e) >> 1;

    ll left = query(node << 1, b, mid, L, R);
    ll right = query(node << 1 | 1, mid + 1, e, L, R);
    if (left == -1) return right;
    if (right == -1) return left;
    return height[left] < height[right] ? left : right;
}

ll lca(ll u, ll v) {
    ll left = first[u], right = first[v];
    if (left > right) swap(left, right);
    return query(1, 0, euler.size() - 1, left, right);
}
};

```

## 9.3 LCA Sparse Table

The algorithm described will need  $O(N)$  for preprocessing, and then  $O(1)$  for each LCA query.

**0 indexed!**

```

typedef vector<vl> vl2d;
#define all(a) a.begin(), a.end()
#define len(x) (int)x.size()

template <typename T>
struct SparseTable {
    vector<T> v;
    ll n;
    static const ll b = 30;
    vl mask, t;

    ll op(ll x, ll y) { return v[x] < v[y] ? x : y; }
    ll msb(ll x) { return __builtin_clz(1) - __builtin_clz(x); }
    SparseTable() {}
    SparseTable(const vector<T>& v_) : v(v_), n(v.size()), mask(n), t(n) {
        for (ll i = 0, at = 0; i < n; mask[i++] = at |= 1) {
            at = (at << 1) & ((1 << b) - 1);
            while (at and op(i, i - msb(at & -at)) == i) at ^= at & -at;
        }
        for (ll i = 0; i < n / b; i++)
            t[i] = b * i + b - 1 - msb(mask[b * i + b - 1]);
        for (ll j = 1; (1 << j) <= n / b; j++)
            for (ll i = 0; i + (1 << j) <= n / b; i++)
                t[n / b * j + i] =
                    op(t[n / b * (j - 1) + i], t[n / b * (j - 1) + i + (1 << (j - 1))]);
    }

    ll small(ll r, ll sz = b) { return r - msb(mask[r] & ((1 << sz) - 1)); }
    T query(ll l, ll r) {
        if (r - l + 1 <= b) return small(r, r - l + 1);
        ll ans = op(small(l + b - 1), small(r));
        ll x = l / b + 1, y = r / b - 1;
        if (x <= y) {
            ll j = msb(y - x + 1);
            ans = op(ans, op(t[n / b * j + x], t[n / b * j + y - (1 << j) + 1]));
        }
    }
}

```

```

    }
    return ans;
}
};

struct LCA {
    SparseTable<ll> st;
    ll n;
    vl v, pos, dep;

    LCA(const vl2d& g, ll root) : n(len(g)), pos(n) {
        dfs(root, 0, -1, g);
        st = SparseTable<ll>(vector<ll>(all(dep)));
    }

    void dfs(ll i, ll d, ll p, const vl2d& g) {
        v.emplace_back(len(dep)) = i, pos[i] = len(dep), dep.emplace_back(d);
        for (auto j : g[i])
            if (j != p) {
                dfs(j, d + 1, i, g);
                v.emplace_back(len(dep)) = i, dep.emplace_back(d);
            }
    }

    ll lca(ll a, ll b) {
        ll l = min(pos[a], pos[b]);
        ll r = max(pos[a], pos[b]);
        return v[st.query(l, r)];
    }

    ll dist(ll a, ll b) {
        return dep[pos[a]] + dep[pos[b]] - 2 * dep[pos[lca(a, b)]];
    }
};

```

## 9.4 Tree Flatten

```

vll tree_flatten(ll root) {
    vl pre;
    pre.reserve(N);

    vll flat(N);
    ll timer = -1;
    auto dfs = [&](auto&& self, ll u, ll p) -> void {
        timer++;
        pre.push_back(u);
        for (auto [v, w] : adj[u])
            if (v != p) {
                self(self, v, u);
            }
        flat[u].second = timer;
    };
    dfs(dfs, root, -1);
    for (ll i = 0; i < (ll)N; i++) flat[pre[i]].first = i;
    return flat;
}

```

## 9.5 Tree Isomorph

Checks whether two tree are isomorph. The function *thash()* returns the hash of the tree (using centroids as special vertices). Two trees are isomorph if their hash are the same.

```

map<vector<int>, int> mhash;

struct tree {
    int n;
    vector<vector<int>> g;
    vector<int> sz, cs;

    tree(int n_) : n(n_), g(n_), sz(n_) {}

    void dfs_centroid(int v, int p) {
        sz[v] = 1;
        bool cent = true;
        for (int u : g[v])
            if (u != p) {
                dfs_centroid(u, v), sz[v] += sz[u];
                if (sz[u] > n / 2) cent = false;
            }
        if (cent and n - sz[v] <= n / 2) cs.push_back(v);
    }

    int fhash(int v, int p) {
        vector<int> h;
        for (int u : g[v])
            if (u != p) h.push_back(fhash(u, v));
        sort(h.begin(), h.end());
        if (!mhash.count(h)) mhash[h] = mhash.size();
        return mhash[h];
    }

    ll thash() {
        cs.clear();
        dfs_centroid(0, -1);
        if (cs.size() == 1) return fhash(cs[0], -1);
        ll h1 = fhash(cs[0], cs[1]), h2 = fhash(cs[1], cs[0]);
        return (min(h1, h2) << 30) + max(h1, h2);
    }

    void add(int a, int b) {
        g[a].emplace_back(b);
        g[b].emplace_back(a);
    }
};

```

## 10 Settings and macros

### 10.1 macro.cpp

```

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>

using namespace __gnu_pbds;
#define ordered_set tree<int, null_type, less<int>, rb_tree_tag,
    tree_order_statistics_node_update>

```



```
using namespace std;

#ifdef DEBUG
#include "../settings-and-macros/debug.cpp"
#else
#define dbg(...)
#endif

typedef long long ll;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;
typedef vector<int> vi;
typedef vector<ll> vl;
typedef vector<pii> vii;
typedef vector<pll> vll;

#define fst first
#define snd second
#define all(x) x.begin(), x.end()
#define len(vt) (int)vt.size()
#define vin(vt) for (auto &e : vt) cin >> e
#define LSOne(S) ((S) & -(S))
#define MSOne(S) (1ull << (63 - __builtin_clzll(S)))
#define fastio ios_base::sync_with_stdio(0); \
               cin.tie(0); \
               cout.tie(0)

const vii dir4 {{1,0},{-1,0},{0,1},{0,-1}};

auto solve() { }

int main() {
    fastio;

    ll t = 1;
    //cin >> t;

    while (t--) solve();

    return 0;
}
```

## 10.2 short-macro.cpp

```
#include <bits/stdc++.h>

using namespace std;

#ifdef DEBUG
#include "../settings-and-macros/debug.cpp"
#else
#define dbg(...)
#endif

typedef long long ll;
typedef pair<int, int> ii;

#define all(x) x.begin(), x.end()
```

```
#define vin(vt) for (auto &e : vt) cin >> e

auto solve() { }

int main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);

    ll t = 1;
    //cin >> t;

    while (t--) solve();

    return 0;
}
```

## 11 Theoretical guide

### 11.1 Modular Multiplicative Inverse

A modular multiplicative inverse of an integer  $a$  is an integer  $x$  such that  $a \cdot x$  is congruent to 1 modular some modulus  $m$ . To write it in a formal way:

$$a \cdot x \equiv 1 \pmod{m}.$$

Euler's theorem, which states that the following congruence is true if  $a$  and  $m$  are co-primes:

$$a^{\phi(m)} \equiv 1 \pmod{m}$$

Multiply both sides of the above equations by  $a^{-1}$ , and we get:

- For an arbitrary (but coprime) modulus  $m$ :  $a^{\phi(m)-1} \equiv a^{-1} \pmod{m}$
- For a prime modulus  $m$ :  $a^{m-2} \equiv a^{-1} \pmod{m}$

From these results, we can easily find the modular inverse using the binary exponentiation algorithm, which works in  $O(\log m)$  time.

### 11.2 Pick's Theorem

Pick's Theorem expresses the area of a polygon, all whose vertices are lattice (integers) points in a coordinate plane, in terms of the number of lattice points inside the polygon and the number of lattice points on the sides (boundaries) of the polygon.

$$A = I + \frac{B}{2} - 1$$

- A: area of the polygon
- I: points inside the polygon
- B: points on the sides (boundaries)

It is possible to easily calculate the number of points on the sides of a side AB.

Consider  $x = (x_1 - x_2)$  and  $y = (y_1 - y_2)$ . If  $x = 0$  or  $y = 0$ , the answer is 1D and trivial (i.e.  $x + 1$  or  $y + 1$ ). Otherwise, the answer is  $\gcd(a, b) + 1$ .

### 11.3 Side on which a point lies

The problem is the following: given a line and a point in the plane, how to determine on which side of the line the point lies?

Let your line be given by  $ax + by + c = 0$ . The point you want to check is  $(x_1, y_1)$ . If  $ax_1 + by_1 + c > 0$ , its orientation is *left*. Otherwise, it's *right* (zero means the coordinates are on the line).

## 11.4 Triangle Formulas

### 11.4.1 Area of a Triangle

The area  $A$  of a triangle can be calculated using the base and height:

$$A = \frac{1}{2} \times \text{base} \times \text{height}$$

This formula is commonly used when the base and height of the triangle are known.

### 11.4.2 Area using Heron's Formula

When dealing with a triangle where only the side lengths are known, such as a scalene triangle (where all sides have different lengths), Heron's formula is useful. It allows the area to be calculated without needing to know the height:

$$A = \sqrt{s(s-a)(s-b)(s-c)}$$

where  $s$  is the semi-perimeter, calculated as:

$$s = \frac{a+b+c}{2}$$

This formula can be applied to any triangle, whether scalene, isosceles, or equilateral, as long as the side lengths  $a$ ,  $b$ , and  $c$  are known.

### 11.4.3 Perimeter of a Triangle

The perimeter  $P$  of a triangle is simply the sum of the lengths of its sides:

$$P = a + b + c$$

This formula is valid for all types of triangles.

### 11.4.4 Pythagorean Theorem (Right Triangle)

In a right-angled triangle, the Pythagorean theorem expresses the relationship between the sides:

$$c^2 = a^2 + b^2$$

where  $c$  is the hypotenuse, and  $a$  and  $b$  are the legs. This formula applies only to right triangles.

### 11.4.5 Height of a Triangle

The height  $h$  of a triangle can be determined if the area  $A$  and base are known:

$$h = \frac{2A}{\text{base}}$$

This formula is particularly useful when you need to find the height, given the area and base of any triangle.

## 11.5 Trigonometry Formulas

$$\sin(\alpha + \beta) = \sin \alpha * \cos \beta + \sin \beta * \cos \alpha$$

$$\sin(\alpha - \beta) = \sin \alpha * \cos \beta - \sin \beta * \cos \alpha$$


$$\cos(\alpha + \beta) = \cos \alpha * \cos \beta - \sin \alpha * \sin \beta$$

$$\cos(\alpha - \beta) = \cos \alpha * \cos \beta + \sin \alpha * \sin \beta$$

$$\sin(2 * \alpha) = 2 * \sin \alpha * \cos \alpha$$

$$\cos(2 * \alpha) = \cos^2 \alpha - \sin^2 \alpha = 2 * \cos^2 \alpha - 1 = 1 - 2 * \sin^2 \alpha$$

## 11.6 Unit Circle



## 11.7 String Matching with FFT

We are given two strings, a text  $T$  and a pattern  $P$ , consisting of lowercase letters. We have to compute all the occurrences of the pattern in the text.

We create a polynomial for each string ( $T[i]$  and  $P[i]$  are numbers between 0 and 25 corresponding to the 26 letters of the alphabet):

$$A(x) = a_0x^0 + a_1x^1 + \dots + a_{n-1}x^{n-1}, \quad n = |T|$$

with

$$a_i = \cos(\alpha_i) + i \sin(\alpha_i), \quad \alpha_i = \frac{2\pi T[i]}{26}$$

And

$$B(x) = b_0x^0 + b_1x^1 + \dots + b_{m-1}x^{m-1}, \quad m = |P|$$

with

$$b_i = \cos(\beta_i) - i \sin(\beta_i), \quad \beta_i = \frac{2\pi P[m-i-1]}{26}$$

Notice that with the expression  $P[m-i-1]$  explicitly reverses the pattern.

The  $(m-1+i)$ th coefficients of the product of the two polynomials  $C(x) = A(x) \cdot B(x)$  will tell us, if the pattern appears in the text at position  $i$ .

If there isn't a match, then at least a character is different, which leads that one of the products  $a_{i+1} \cdot b_{m-1-j}$  is not equal to 1, which leads to the coefficient  $c_{m-1+i} \neq m$ .

11.7.1 Wildcards

This is an extension of the previous problem. This time we allow that the pattern contains the wildcard character \*, which can match every possible letter. We create the exact same polynomials, except that we set  $b_i = 0$  if  $P[m - i - 1] = *$ . If  $x$  is the number of wildcards in  $P$ , then we will have a match of  $P$  in  $T$  at index  $i$  if  $c_{m-1+i} = m - x$ .

11.8 Number of Different Substrings

sum\_{i=0}^{n-1} (n - p[i]) - sum\_{i=0}^{n-2} lcp[i] = (n^2 + n) / 2 - sum\_{i=0}^{n-2} lcp[i]

11.9 Exponent With Module

If  $a$  and  $m$  are coprime, then

a^n ≡ a^{n mod ϕ(m)} mod m

Generally, if  $n \geq \log_2 m$ , then

a^n ≡ a^{ϕ(m) + [n mod ϕ(m)]} mod m

11.10 Line Equations

11.10.1 Reduced Equation

- $m$ : Slope of the line, calculated as

m = (y2 - y1) / (x2 - x1)

where  $(x_1, y_1)$  and  $(x_2, y_2)$  are two distinct points on the line.

- $b$ : y-intercept, the point where the line crosses the y-axis.
- Easier comparisons between lines.
- Cannot represent vertical lines.

11.10.2 General Equation

Ax + By + C = 0

- $A, B$ : Coefficients that define the line’s orientation.
- $C$ : Constant term that affects the line’s position.
- Able to represent any line.

11.11 Laws of Trigonometry for Triangles

11.11.1 Law of Sines

The Law of Sines relates the ratios of the sides of a triangle to the sines of their opposite angles. It is useful for solving any type of triangle (acute, obtuse, or right). The formula is given by:

a / sin(α) = b / sin(β) = c / sin(γ)

where: -  $a, b$ , and  $c$  are the lengths of the sides of the triangle, -  $\alpha, \beta$ , and  $\gamma$  are the angles opposite these sides, respectively. This formula is particularly helpful in the following cases: - When you know two angles and one side (AAS or ASA case). - When you know two sides and one non-included angle (SSA case).

11.11.2 Law of Cosines

The Law of Cosines relates the lengths of the sides of a triangle to the cosine of one of its angles. This law is useful for solving any type of triangle, especially when you are dealing with non-right triangles. The formula is given by:

c^2 = a^2 + b^2 - 2ab · cos(γ)

where: -  $a, b$ , and  $c$  are the lengths of the sides of the triangle, -  $\gamma$  is the angle opposite side  $c$ . The Law of Cosines is particularly useful when: - You know two sides and the included angle (SAS case). - You know all three sides and want to find an angle (SSS case).

11.12 Triangle Inequality

The Triangle Inequality states that if  $a, b$ , and  $c$  are real numbers, they will be the measures of the sides of a triangle if, and only if,

a ≤ b + c, b ≤ a + c, c ≤ a + b.

Obs: Equal is valid only if a degenerate triangle is accepted.

11.12.1 Finding a third side

If you have two sides  $a$  and  $b$ , the third side  $c$  must satisfy:

|a - b| < c < a + b

11.13 Common Geometric Shape Formulas

11.13.1 Area of a Trapezium

The area  $A$  of a trapezium (trapezoid) can be calculated using the lengths of the two parallel sides  $a$  and  $b$ , and the height  $h$ :

A = 1/2 × (a + b) × h

11.13.2 Area of a Regular Hexagon

The area  $A$  of a regular hexagon can be calculated using the length of one side  $s$ :

A = (3√3 / 2) × s^2

This formula is valid for a regular hexagon, where all six sides are equal.

11.13.3 Area of a Parallelogram

The area  $A$  of a parallelogram is calculated by multiplying the base  $b$  by the height  $h$  (the perpendicular distance between the bases):

A = b × h

11.13.4 Area of a Rhombus

The area  $A$  of a rhombus (Losango in portuguese) can be calculated using the lengths of its diagonals  $d_1$  and  $d_2$ :

A = 1/2 × d1 × d2

11.13.5 Area of an Ellipse

The area  $A$  of an ellipse is given by the formula:

A = π × a × b

where  $a$  and  $b$  are the lengths of the semi-major and semi-minor axes, respectively.

### 11.13.6 Area of a Regular Pentagon

The area  $A$  of a regular pentagon with side length  $s$  is given by:

$$A = \frac{1}{4} \times \sqrt{5(5 + 2\sqrt{5})} \times s^2$$

This formula is specific to regular pentagons, where all sides and angles are equal.

## 11.14 Notable Series

1. Sum of the first  $n$  naturals:

$$S_n = \sum_{i=1}^n i = 1 + 2 + 3 + \cdots + n = \frac{n(n+1)}{2}$$

2. Sum of the squares of the first  $n$  naturals:

$$S_n = \sum_{i=1}^n i^2 = 1^2 + 2^2 + 3^2 + \cdots + n^2 = \frac{n(n+1)(2n+1)}{6}$$

3. Sum of the cubes of the first natural  $n$ :

$$S_n = \sum_{i=1}^n i^3 = 1^3 + 2^3 + 3^3 + \cdots + n^3 = \left[ \frac{n(n+1)}{2} \right]^2$$

4. Sum of the first  $n$  odd numbers:

$$S_n = \sum_{i=1}^n 2i - 1 = 1 + 3 + 5 + \cdots + (2n - 1) = n^2$$