



Notebook - Competitive Programming

Anões do TLE

Contents		
1 Data structures	2	
1.1 Union Find Disjoint Set (UFDS)	2	
2 Dynamic programming	2	
2.1 Kadane	2	
2.2 Longest Increasing Subsequence (LIS)	2	
3 Geometry	2	
3.1 Convex Hull	2	
3.2 Point To Segment	3	
4 Graphs	3	
4.1 Articulation Points	3	
4.2 Bellman Ford	3	
4.3 BFS 0/1	3	
4.4 Bridges	4	
4.5 Negative Cycle Bellman Ford	4	
4.6 Negative Cycle Floyd Warshall	4	
4.7 Dijkstra	4	
4.8 Floyd Warshall	5	
4.9 Graph	5	
4.10 Retrieve Path 2d	5	
4.11 Retrieve Path	5	
5 Math	5	
5.1 Binomial	5	
5.2 Count Divisors	5	
5.3 Factorization With Sieve	6	
5.4 Factorization	6	
5.5 Fast Exp Iterative	6	
5.6 Fast Exp	6	
5.7 GCD	6	
5.8 Integer Mod	6	
5.9 Is prime	7	
5.10 LCM	7	
5.11 Euler phi $\varphi(n)$	7	
5.12 Sieve	7	
5.13 Sum Divisors	7	
5.14 Sum of difference	8	
6 Problems	8	
6.1 Kth Digit String (CSES)	8	
7 Strings	8	
7.1 Manacher	8	
8 Trees	8	
8.1 LCA Binary Lifting (CP Algo)	8	
8.2 LCA SegTree (CP Algo)	9	
8.3 LCA Sparse Table	9	
8.4 Tree Isomorph	10	
9 Settings and macros	10	
9.1 macro.cpp	10	
9.2 short-macro.cpp	11	

1 Data structures

1.1 Union Find Disjoint Set (UFDS)

Uncomment the lines to recover which element belong to each set.

Time: $\approx O(1)$ for everything.

```
class UFDS {
public:
    vi ps, size;
    // vector<unordered_set<int>> sts;

    UFDS(int N) : size(N + 1, 1), ps(N + 1), sts(N) {
        iota(ps.begin(), ps.end(), 0);
        // for (int i = 0; i < N; i++) sts[i].insert(i);
    }

    int find_set(int x) { return x == ps[x] ? x : (ps[x] = find_set(ps[x])); }

    bool same_set(int x, int y) { return find_set(x) == find_set(y); }

    void union_set(int x, int y) {
        if (same_set(x, y)) return;

        int px = find_set(x);
        int py = find_set(y);

        if (size[px] < size[py]) swap(px, py);

        ps[py] = px;
        size[px] += size[py];
        // sts[px].merge(sts[py]);
    }
};
```

2 Dynamic programming

2.1 Kadane

```
int kadane(const vi& xs) {
    vi s(xs.size());
    s[0] = xs[0];

    for (size_t i = 1; i < xs.size(); ++i) s[i] = max(xs[i], s[i - 1] + xs[i]);

    return *max_element(all(s));
}
```

2.2 Longest Increasing Subsequence (LIS)

Time: $O(N \cdot \log N)$.

```
int lis(vi const& a) {
    int n = a.size();
    const int INF = 1e9;
    vi d(n + 1, INF);
    d[0] = -INF;
```

```
    for (int i = 0; i < n; i++) {
        int l = upper_bound(d.begin(), d.end(), a[i]) - d.begin();
        if (d[l - 1] < a[i] && a[i] < d[l]) d[l] = a[i];
    }

    int ans = 0;
    for (int l = 0; l <= n; l++) {
        if (d[l] < INF) ans = l;
    }

    return ans;
}
```

3 Geometry

3.1 Convex Hull

Given a set of points find the smallest convex polygon that contains all the given points.

Time: $O(N \cdot \log N)$

By default it removes the collinear points, set the boolean to true if you don't want that

```
struct pt {
    double x, y;
};

int orientation(pt a, pt b, pt c) {
    double v = a.x * (b.y - c.y) + b.x * (c.y - a.y) + c.x * (a.y - b.y);
    if (v < 0) return -1; // clockwise
    if (v > 0) return +1; // counter-clockwise
    return 0;
}

bool cw(pt a, pt b, pt c, bool include_collinear) {
    int o = orientation(a, b, c);
    return o < 0 || (include_collinear && o == 0);
}

bool collinear(pt a, pt b, pt c) { return orientation(a, b, c) == 0; }

void convex_hull(vector<pt>& a, bool include_collinear = false) {
    pt p0 = *min_element(a.begin(), a.end(), [](pt a, pt b) {
        return make_pair(a.y, a.x) < make_pair(b.y, b.x);
    });
    sort(a.begin(), a.end(), [&p0](const pt& a, const pt& b) {
        int o = orientation(p0, a, b);
        if (o == 0)
            return (p0.x - a.x) * (p0.x - a.x) + (p0.y - a.y) * (p0.y - a.y) <
                (p0.x - b.x) * (p0.x - b.x) + (p0.y - b.y) * (p0.y - b.y);
        return o < 0;
    });
    if (include_collinear) {
        int i = (int)a.size() - 1;
        while (i >= 0 && collinear(p0, a[i], a.back())) i--;
        reverse(a.begin() + i + 1, a.end());
    }

    vector<pt> st;
```

```

for (int i = 0; i < (int)a.size(); i++) {
    while (st.size() > 1 &&
           !cw(st[st.size() - 2], st.back(), a[i], include_collinear))
        st.pop_back();
    st.push_back(a[i]);
}

a = st;
}

```

3.2 Point To Segment

```
typedef pair<double, double> pdb;
```

```

double pt2segment(pdb A, pdb B, pdb E) {
    pdb AB = {B.fst - A.fst, B.snd - A.snd};
    pdb BE = {E.fst - B.fst, E.snd - B.snd};
    pdb AE = {E.fst - A.fst, E.snd - A.snd};

    double AB_BE = AB.fst * BE.fst + AB.snd * BE.snd;
    double AB_AE = AB.fst * AE.fst + AB.snd * AE.snd;

    double ans;
    if (AB_BE > 0) {
        double y = E.snd - B.snd;
        double x = E.fst - B.fst;
        ans = hypot(x, y);
    } else if (AB_AE < 0) {
        double y = E.snd - A.snd;
        double x = E.fst - A.fst;
        ans = hypot(x, y);
    } else {
        auto [x1, y1] = AB;
        auto [x2, y2] = AE;
        double mod = hypot(x1, y1);
        ans = abs(x1 * y2 - y1 * x2) / mod;
    }

    return ans;
}

```

4 Graphs

4.1 Articulation Points

```

int dfs_num[MAX], dfs_low[MAX];
vi adj[MAX];

```

```

int dfs_articulation_points(int u, int p, int& next, set<int>& points) {
    int children = 0;
    dfs_low[u] = dfs_num[u] = next++;

    for (auto v : adj[u])
        if (not dfs_num[v]) {
            ++children;

```

```

        dfs_articulation_points(v, u, next, points);

        if (dfs_low[v] >= dfs_num[u]) points.insert(u);

        dfs_low[u] = min(dfs_low[u], dfs_low[v]);
    } else if (v != p)
        dfs_low[u] = min(dfs_low[u], dfs_num[v]);

    return children;
}

set<int> articulation_points(int N) {
    memset(dfs_num, 0, (N + 1) * sizeof(int));
    memset(dfs_low, 0, (N + 1) * sizeof(int));

    set<int> points;

    for (int u = 1, next = 1; u <= N; ++u)
        if (not dfs_num[u]) {
            auto children = dfs_articulation_points(u, u, next, points);

            if (children == 1) points.erase(u);
        }

    return points;
}

```

4.2 Bellman Ford

Time: $O(V \cdot E)$. Returns the shortest path from s to all other nodes.

```
using edge = tuple<int, int, int>;
```

```

pair<vi, vi> bellman_ford(int s, int N, const vector<edge>& edges) {
    vi dist(N + 1, oo), pred(N + 1, oo);

    dist[s] = 0;
    pred[s] = s;

    for (int i = 1; i <= N - 1; i++)
        for (auto [u, v, w] : edges)
            if (dist[u] < oo and dist[v] > dist[u] + w) {
                dist[v] = dist[u] + w;
                pred[v] = u;
            }

    return {dist, pred};
}

```

4.3 BFS 0/1

Time: $O(V + E)$.

```
vii adj[MAX];
```

```

vi bfs_01(int s, int N) {
    vi dist(N + 1, oo);
    dist[s] = 0;

```

```

deque<int> q;
q.emplace_back(s);

while (not q.empty()) {
    auto u = q.front();
    q.pop_front();

    for (auto [v, w] : adj[u])
        if (dist[v] > dist[u] + w) {
            dist[v] = dist[u] + w;
            w == 0 ? q.emplace_front(v) : q.emplace_back(v);
        }
}

return dist;
}

```

4.4 Bridges

```

int dfs_num[MAX], dfs_low[MAX];
vi adj[MAX];

void dfs_bridge(int u, int p, int& next, vii& bridges) {
    dfs_low[u] = dfs_num[u] = next++;

    for (auto v : adj[u])
        if (not dfs_num[v]) {
            dfs_bridge(v, u, next, bridges);

            if (dfs_low[v] > dfs_num[u]) bridges.emplace_back(u, v);

            dfs_low[u] = min(dfs_low[u], dfs_low[v]);
        } else if (v != p)
            dfs_low[u] = min(dfs_low[u], dfs_num[v]);
}

vii bridges(int N) {
    memset(dfs_num, 0, (N + 1) * sizeof(int));
    memset(dfs_low, 0, (N + 1) * sizeof(int));

    vii bridges;

    for (int u = 1, next = 1; u <= N; ++u)
        if (not dfs_num[u]) dfs_bridge(u, u, next, bridges);

    return bridges;
}

```

4.5 Negative Cycle Bellman Ford

Time: $O(V \cdot E)$. Detects whether there is a negative cycle in the graph using Bellman Ford.

```

using edge = tuple<int, int, int>;

bool has_negative_cycle(int s, int N, const vector<edge>& edges) {
    vi dist(N + 1, oo);

```

```

    dist[s] = 0;

    for (int i = 1; i <= N - 1; i++)
        for (auto [u, v, w] : edges)
            if (dist[u] < oo and dist[v] > dist[u] + w) dist[v] = dist[u] + w;

    for (auto [u, v, w] : edges)
        if (dist[u] < oo and dist[v] > dist[u] + w) return true;

    return false;
}

```

4.6 Negative Cycle Floyd Warshall

Time: $O(n^3)$. Detects whether there is a negative cycle in the graph using Floyd Warshall.

```

int dist[MAX][MAX];
vii adj[MAX];

bool has_negative_cycle(int N) {
    for (int u = 1; u <= N; ++u)
        for (int v = 1; v <= N; ++v) dist[u][v] = u == v ? 0 : oo;

    for (int u = 1; u <= N; ++u)
        for (auto [v, w] : adj[u]) dist[u][v] = w;

    for (int k = 1; k <= N; ++k)
        for (int u = 1; u <= N; ++u)
            for (int v = 1; v <= N; ++v)
                if (dist[u][k] < oo and dist[k][v] < oo)
                    dist[u][v] = min(dist[u][v], dist[u][k] + dist[k][v]);

    for (int i = 1; i <= N; ++i)
        if (dist[i][i] < 0) return true;

    return false;
}

```

4.7 Dijkstra

```

pair<vl, vl> Graph::dijkstra(ll src) {
    vl pd(this->N, LLONG_MAX), ds(this->N, LLONG_MAX);
    pd[src] = src;
    ds[src] = 0;

    set<pll> st;
    st.emplace(0, src);

    while (!st.empty()) {
        ll u = st.begin()->snd;
        ll wu = st.begin()->fst;
        st.erase(st.begin());

        if (wu != ds[u]) continue;
        for (auto& [v, w] : adj[u]) {
            if (ds[v] > ds[u] + w) {

```

```

        ds[v] = ds[u] + w;
        pd[v] = u;
        st.emplace(ds[v], v);
    }
}

return {ds, pd};
}

```

4.8 Floyd Warshall

```

vii adj[MAX];

pair<vector<vi>, vector<vi>> floyd_warshall(int N) {
    vector<vi> dist(N + 1, vi(N + 1, oo));
    vector<vi> pred(N + 1, vi(N + 1, oo));

    for (int u = 1; u <= N; ++u) {
        dist[u][u] = 0;
        pred[u][u] = u;
    }

    for (int u = 1; u <= N; ++u)
        for (auto [v, w] : adj[u]) {
            dist[u][v] = w;
            pred[u][v] = u;
        }

    for (int k = 1; k <= N; ++k) {
        for (int u = 1; u <= N; ++u) {
            for (int v = 1; v <= N; ++v) {
                if (dist[u][k] < oo and dist[k][v] < oo and
                    dist[u][v] > dist[u][k] + dist[k][v]) {
                    dist[u][v] = dist[u][k] + dist[k][v];
                    pred[u][v] = pred[k][v];
                }
            }
        }
    }

    return {dist, pred};
}

```

4.9 Graph

```

class Graph {
private:
    ll N;
    bool undirected;
    vector<vll> adj;

public:
    Graph(ll N, bool is_undirected = true) {
        this->N = N;
        adj.resize(N);
        undirected = is_undirected;
    }
}

```

```

void add(ll u, ll v, ll w) {
    adj[u].emplace_back(v, w);
    if (undirected) adj[v].emplace_back(u, w);
}
};

```

4.10 Retrieve Path 2d

```

vll Graph::retrieve_path_2d(ll src, ll trg, const vector<vl>& pred) {
    vll p;

    do {
        p.emplace_back(pred[src][trg], trg);
        trg = pred[src][trg];
    } while (trg != src);

    reverse(all(p));

    return p;
}

```

4.11 Retrieve Path

```

vll Graph::retrieve_path(ll src, ll trg, const vl& pred) {
    vll p;

    do {
        p.emplace_back(pred[trg], trg);
        trg = pred[trg];
    } while (trg != src);

    reverse(all(p));

    return p;
}

```

5 Math

5.1 Binomial

```

ll binom(ll n, ll k) {
    if (k > n) return 0;
    vll dp(k + 1, 0);
    dp[0] = 1;
    for (ll i = 1; i <= n; i++)
        for (ll j = k; j > 0; j--) dp[j] = dp[j] + dp[j - 1];
    return dp[k];
}

```

5.2 Count Divisors

```

ll count_divisors(ll num) {
    ll count = 1;
    for (int i = 2; (ll)i * i <= num; i++) {
        if (num % i == 0) {
            int e = 0;
            do {

```

```

        e++;
        num /= i;
    } while (num % i == 0);
    count *= e + 1;
}
}
if (num > 1) {
    count *= 2;
}
return count;
}

```

5.3 Factorization With Sieve

```

map<ll, ll> factorization_with_sieve(ll n, const vl& primes) {
    map<ll, ll> fact;

```

```

    for (ll d : primes) {
        if (d * d > n) break;

        ll k = 0;
        while (n % d == 0) {
            k++;
            n /= d;
        }

        if (k) fact[d] = k;
    }

```

```

    if (n > 1) fact[n] = 1;
    return fact;
}

```

5.4 Factorization

```

map<ll, ll> factorization(ll n) {
    map<ll, ll> ans;
    for (ll i = 2; i * i <= n; i++) {
        ll count = 0;
        for (; n % i == 0; count++, n /= i)
            ;
        if (count) ans[i] = count;
    }
    if (n > 1) ans[n]++;
    return ans;
}

```

5.5 Fast Exp Iterative

```

long long fast_exp_it(long long a, int n) {
    long long res = 1, base = a;

    while (n) {
        if (n & 1) res *= base;

        base *= base;
        n >>= 1;
    }

```

```

    }

    return res;
}

```

5.6 Fast Exp

```

long long fast_exp(long long a, int n) {
    if (n == 1) return a;

    auto x = fast_exp(a, n / 2);

    return x * x * (n % 2 ? a : 1);
}

```

5.7 GCD

The Euclidean algorithm allows to find the greatest common divisor of two numbers a and b in $O(\log \cdot \min(a, b))$.

```

ll gcd(ll a, ll b) { return b ? gcd(b, a % b) : a; }

```

5.8 Integer Mod

```

const ll INF = 1e18;
const ll mod = 998244353;
template <ll MOD = mod>

```

```

struct Modular {
    ll value;
    static const ll MOD_value = MOD;

```

```

    Modular(ll v = 0) {
        value = v % MOD;
        if (value < 0) value += MOD;
    }
    Modular(ll a, ll b) : value(0) {
        *this += a;
        *this /= b;
    }

```

```

    Modular& operator+=(Modular const& b) {
        value += b.value;
        if (value >= MOD) value -= MOD;
        return *this;
    }

```

```

    Modular& operator-=(Modular const& b) {
        value -= b.value;
        if (value < 0) value += MOD;
        return *this;
    }

```

```

    Modular& operator*=(Modular const& b) {
        value = (ll)value * b.value % MOD;
        return *this;
    }

```

```

    friend Modular mexp(Modular a, ll e) {

```

```

Modular res = 1;
while (e) {
    if (e & 1) res *= a;
    a *= a;
    e >>= 1;
}
return res;
}

friend Modular inverse(Modular a) { return mexp(a, MOD - 2); }

Modular& operator/=(Modular const& b) { return *this *= inverse(b); }
friend Modular operator+(Modular a, Modular const b) { return a += b; }
Modular operator++(int) { return this->value = (this->value + 1) % MOD; }
Modular operator++() { return this->value = (this->value + 1) % MOD; }
friend Modular operator-(Modular a, Modular const b) { return a -= b; }
friend Modular operator--(Modular const a) { return 0 - a; }
Modular operator--(int) {
    return this->value = (this->value - 1 + MOD) % MOD;
}

Modular operator--() { return this->value = (this->value - 1 + MOD) % MOD; }
friend Modular operator*(Modular a, Modular const b) { return a *= b; }
friend Modular operator/(Modular a, Modular const b) { return a /= b; }
friend std::ostream& operator<<(std::ostream& os, Modular const& a) {
    return os << a.value;
}
}

friend bool operator==(Modular const& a, Modular const& b) {
    return a.value == b.value;
}
}

friend bool operator!=(Modular const& a, Modular const& b) {
    return a.value != b.value;
}
}

};

```

5.9 Is prime

$O(\sqrt{N})$

```

bool isprime(ll n) {
    if (n < 2) return false;
    if (n == 2) return true;
    if (n % 2 == 0) return false;
    for (ll i = 3; i * i < n; i += 2)
        if (n % i == 0) return false;
    return true;
}

```

5.10 LCM

Calculating the least common multiple (commonly denoted LCM) can be reduced to calculating the GCD with the following simple formula: $\text{lcm}(a, b) = (a \cdot b) / \text{gcd}(a, b)$. Thus, LCM can be calculated using the Euclidean algorithm with the same time complexity:

```

ll lcm(ll a, ll b) { return a / gcd(a, b) * b; }

```

5.11 Euler phi $\varphi(n)$

Computes the number of positive integers less than n that are coprimes with n , in $O(\sqrt{N})$.

```

ll phi(ll n) {
    if (n == 1) return 1;

    auto fs = factorization(n);
    auto res = n;

    for (auto [p, k] : fs) {
        res /= p;
        res *= (p - 1);
    }

    return res;
}

```

5.12 Sieve

```

v1 sieve(ll N) {
    bitset<MAX + 1> sieve;
    v1 ps{2, 3};
    sieve.set();

    for (ll i = 5, step = 2; i <= N; i += step, step = 6 - step) {
        if (sieve[i]) {
            ps.push_back(i);

            for (ll j = i * i; j <= N; j += 2 * i) sieve[j] = false;
        }
    }
    return ps;
}

```

5.13 Sum Divisors

```

ll sum_divisors(ll num) {
    ll result = 1;

    for (int i = 2; (ll)i * i <= num; i++) {
        if (num % i == 0) {
            int e = 0;
            do {
                e++;
                num /= i;
            } while (num % i == 0);

            ll sum = 0, pow = 1;
            do {
                sum += pow;
                pow *= i;
            } while (e-- > 0);
            result *= sum;
        }
    }

    if (num > 1) {
        result *= (1 + num);
    }
    return result;
}

```

5.14 Sum of difference

Function to calculate sum of absolute difference of all pairs in array: $\frac{1}{2} \sum_{i=1}^N \sum_{j=1}^N |A_i - A_j|$

```
11 sum_of_diference(vl& arr, ll n) {
    sort(all(arr));

    ll sum = 0;
    for (ll i = 0; i < n; i++) {
        sum += i * arr[i] - (n - 1 - i) * arr[i];
    }

    return sum;
}
```

6 Problems

6.1 Kth Digit String (CSES)

Time: $O(\log_{10} K)$.

Space: $O(1)$.

```
11 kth_digit_string(ll k) {
    if (k < 10) return k;

    ll c = 180, i = 2, u = 10, r = 0, ans = -1, m;
    for (k -= 9; k > c; i++, u *= 10) {
        k -= c;
        c /= i;
        c *= 10 * (i + 1);
    }

    if ((m = k % i))
        r++;
    else
        m = i;

    ll tmp = (k / i) + r + u - 1;
    for (m = i + 1 - m; m--; tmp /= 10) ans = tmp % 10;

    return ans;
}
```

7 Strings

7.1 Manacher

Given string s with length n . Find all the pairs (i, j) such that substring $s[i \dots j]$ is a palindrome. String t is a palindrome when $t = t_{rev}$ (t_{rev} is a reversed string for t).

Time: $O(N)$

```
vi manacher(string s) {
    string t;
    for (auto c : s) t += string("#") + c;
    t = t + '?#?';
```

```
int n = t.size();
t = "$" + t + "^";

vi p(n + 2);
int l = 1, r = 1;
for (int i = 1; i <= n; i++) {
    p[i] = max(0, min(r - i, p[l + (r - i)]));
    while (t[i - p[i]] == t[i + p[i]]) p[i]++;
    if (i + p[i] > r) {
        l = i - p[i], r = i + p[i];
    }
    p[i]--;
}

return vi(begin(p) + 1, end(p) - 1);
}
```

8 Trees

8.1 LCA Binary Lifting (CP Algo)

The algorithm described will need $O(N \cdot \log N)$ for preprocessing the tree, and then $O(\log N)$ for each LCA query.

```
11 n, l;
vector<ll> adj[MAX];
```

```
11 timer;
vector<ll> tin, tout;
vector<vector<ll>> up;
```

```
void dfs(ll v, ll p) {
    tin[v] = ++timer;
    up[v][0] = p;
    for (ll i = 1; i <= l; ++i) up[v][i] = up[up[v][i - 1]][i - 1];

    for (ll u : adj[v]) {
        if (u != p) dfs(u, v);
    }
}
```

```
    tout[v] = ++timer;
}
```

```
bool is_ancestor(ll u, ll v) { return tin[u] <= tin[v] && tout[u] >= tout[v];
}
```

```
11 lca(ll u, ll v) {
    if (is_ancestor(u, v)) return u;
    if (is_ancestor(v, u)) return v;
    for (ll i = l; i >= 0; --i) {
        if (!is_ancestor(up[u][i], v)) u = up[u][i];
    }
    return up[u][0];
}
```

```
void preprocess(ll root) {
    tin.resize(n);
```



```

tout.resize(n);
timer = 0;
l = ceil(log2(n));
up.assign(n, vector<ll>(l + 1));
dfs(root, root);
}

```

8.2 LCA SegTree (CP Algo)

The algorithm can answer each query in $O(\log N)$ with preprocessing in $O(N)$ time.

```

struct LCA {
    vector<ll> height, euler, first, segtree;
    vector<bool> visited;
    ll n;

    LCA(vector<vector<ll>>& adj, ll root = 0) {
        n = adj.size();
        height.resize(n);
        first.resize(n);
        euler.reserve(n * 2);
        visited.assign(n, false);
        dfs(adj, root);
        ll m = euler.size();
        segtree.resize(m * 4);
        build(1, 0, m - 1);
    }

    void dfs(vector<vector<ll>>& adj, ll node, ll h = 0) {
        visited[node] = true;
        height[node] = h;
        first[node] = euler.size();
        euler.push_back(node);
        for (auto to : adj[node]) {
            if (!visited[to]) {
                dfs(adj, to, h + 1);
                euler.push_back(node);
            }
        }
    }

    void build(ll node, ll b, ll e) {
        if (b == e) {
            segtree[node] = euler[b];
        } else {
            ll mid = (b + e) / 2;
            build(node << 1, b, mid);
            build(node << 1 | 1, mid + 1, e);
            ll l = segtree[node << 1], r = segtree[node << 1 | 1];
            segtree[node] = (height[l] < height[r]) ? l : r;
        }
    }

    ll query(ll node, ll b, ll e, ll L, ll R) {
        if (b > R || e < L) return -1;
        if (b >= L && e <= R) return segtree[node];
        ll mid = (b + e) >> 1;

```

```

        ll left = query(node << 1, b, mid, L, R);
        ll right = query(node << 1 | 1, mid + 1, e, L, R);
        if (left == -1) return right;
        if (right == -1) return left;
        return height[left] < height[right] ? left : right;
    }

    ll lca(ll u, ll v) {
        ll left = first[u], right = first[v];
        if (left > right) swap(left, right);
        return query(1, 0, euler.size() - 1, left, right);
    }
};

```

8.3 LCA Sparse Table

The algorithm described will need $O(N)$ for preprocessing, and then $O(1)$ for each LCA query.

0 indexed!

```

typedef vector<vl> vl2d;
#define all(a) a.begin(), a.end()
#define len(x) (int)x.size()

template <typename T>
struct SparseTable {
    vector<T> v;
    ll n;
    static const ll b = 30;
    vl mask, t;

    ll op(ll x, ll y) { return v[x] < v[y] ? x : y; }
    ll msb(ll x) { return __builtin_clz(1) - __builtin_clz(x); }
    SparseTable() {}
    SparseTable(const vector<T>& v_) : v(v_), n(v.size()), mask(n), t(n) {
        for (ll i = 0, at = 0; i < n; mask[i++] = at |= 1) {
            at = (at << 1) & ((1 << b) - 1);
            while (at and op(i, i - msb(at & -at)) == i) at ^= at & -at;
        }
        for (ll i = 0; i < n / b; i++)
            t[i] = b * i + b - 1 - msb(mask[b * i + b - 1]);
        for (ll j = 1; (1 << j) <= n / b; j++)
            for (ll i = 0; i + (1 << j) <= n / b; i++)
                t[n / b * j + i] =
                    op(t[n / b * (j - 1) + i], t[n / b * (j - 1) + i + (1 << (j - 1))]);
    }

    ll small(ll r, ll sz = b) { return r - msb(mask[r] & ((1 << sz) - 1)); }
    T query(ll l, ll r) {
        if (r - l + 1 <= b) return small(r, r - l + 1);
        ll ans = op(small(l + b - 1), small(r));
        ll x = l / b + 1, y = r / b - 1;
        if (x <= y) {
            ll j = msb(y - x + 1);
            ans = op(ans, op(t[n / b * j + x], t[n / b * j + y - (1 << j) + 1]));
        }
        return ans;
    }
};

```

```

struct LCA {
    SparseTable<ll> st;
    ll n;
    vl v, pos, dep;

    LCA(const vl2d& g, ll root) : n(len(g)), pos(n) {
        dfs(root, 0, -1, g);
        st = SparseTable<ll>(vector<ll>(all(dep)));
    }

    void dfs(ll i, ll d, ll p, const vl2d& g) {
        v.emplace_back(len(dep)) = i, pos[i] = len(dep), dep.emplace_back(d);
        for (auto j : g[i])
            if (j != p) {
                dfs(j, d + 1, i, g);
                v.emplace_back(len(dep)) = i, dep.emplace_back(d);
            }
    }

    ll lca(ll a, ll b) {
        ll l = min(pos[a], pos[b]);
        ll r = max(pos[a], pos[b]);
        return v[st.query(l, r)];
    }

    ll dist(ll a, ll b) {
        return dep[pos[a]] + dep[pos[b]] - 2 * dep[pos[lca(a, b)]];
    }
};

```

8.4 Tree Isomorph

Checks whether two tree are isomorph. The function *thash()* returns the hash of the tree (using centroids as special vertices). Two trees are isomorph if their hash are the same.

```
map<vector<int>, int> mhash;
```

```

struct tree {
    int n;
    vector<vector<int>> g;
    vector<int> sz, cs;

    tree(int n_) : n(n_), g(n_), sz(n_) {}

    void dfs_centroid(int v, int p) {
        sz[v] = 1;
        bool cent = true;
        for (int u : g[v])
            if (u != p) {
                dfs_centroid(u, v), sz[v] += sz[u];
                if (sz[u] > n / 2) cent = false;
            }
        if (cent and n - sz[v] <= n / 2) cs.push_back(v);
    }

    int fhash(int v, int p) {
        vector<int> h;
        for (int u : g[v])
            if (u != p) h.push_back(fhash(u, v));
        sort(h.begin(), h.end());
    }
};

```

```

    if (!mhash.count(h)) mhash[h] = mhash.size();
    return mhash[h];
}

ll thash() {
    cs.clear();
    dfs_centroid(0, -1);
    if (cs.size() == 1) return fhash(cs[0], -1);
    ll h1 = fhash(cs[0], cs[1]), h2 = fhash(cs[1], cs[0]);
    return (min(h1, h2) << 30) + max(h1, h2);
}

void add(int a, int b) {
    g[a].emplace_back(b);
    g[b].emplace_back(a);
}
};

```

9 Settings and macros

9.1 macro.cpp

```

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>

using namespace __gnu_pbds;
#define ordered_set tree<int, null_type, less<int>, rb_tree_tag,
    tree_order_statistics_node_update>

using namespace std;

typedef long long ll;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;
typedef vector<int> vi;
typedef vector<ll> vl;
typedef vector<pii> vii;
typedef vector<pll> vll;

#define fst first
#define snd second
#define all(x) x.begin(), x.end()
#define vin(vt) for (auto &e : vt) cin >> e
#define LSONe(S) ((S) & -(S))
#define MSOne(S) (1ull << (63 - __builtin_clzll(S)))
#define fastio ios_base::sync_with_stdio(0); \
    cin.tie(0); \
    cout.tie(0)

const vii dir4 {{1,0},{-1,0},{0,1},{0,-1}};

auto solve() { }

int main() {
    fastio;

    ll t = 1;
}

```

```

    //cin >> t;

    while (t--) solve();

    return 0;
}

```

9.2 short-macro.cpp

```

#include <bits/stdc++.h>

using namespace std;

typedef long long ll;
typedef pair<int, int> ii;

#define all(x) x.begin(), x.end()

```

```

#define vin(vt) for (auto &e : vt) cin >> e

auto solve() { }

int main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);

    ll t = 1;
    //cin >> t;

    while (t--) solve();

    return 0;
}

```